

Grayhill Incorporated

EZCom-LP
900 MHz Digital Radio

FCC ID#: NMAEZCOMLPP

MPE Calculation

Portable OCU Unit

TITLE: Grayhill MPE CALCULATION				W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com	
PROJECT: GRAYHILL EZ-COM LP CERTIFICATION					
DRAWN BY: JOHN LOFGREN SR. ENGR.	DATE: March 10, 2003	SIZE: A	DRAWING NUMBER: GRAYHILL-MPE-V1.0 EZ-COM LP		REVISION: 0.1
CHECKED BY: BRIAN PETTED VP ENG	DATE: March 10, 2003				
APPROVED BY: BRIAN PETTED VP ENG	DATE: March 10, 2003				
FILENAME, FILES AFFECTED: Portable OCU unit MPE Calculations.doc		SCALE: NOT TO SCALE	SHEET: 1 OF 4		

TABLE OF CONTENTS

1.0	SCOPE.....	3
2.0	REVISION CONTROL	3
3.0	APPLICABLE DOCUMENTS	3
4.0	MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS	4

TITLE:	GRAYHILL MPE CALCULATION	 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT:	GRAYHILL EZ -COM LPM CERTIFICATION		
FILENAME, FILES AFFECTED:	Portable OCU unit MPE Calculations	REVISION: 0.1	PAGE: 2 OF 4

1.0 SCOPE

This report demonstrates the Maximum Permissible Exposure (MPE) Calculation required for an Intentional Radiator equipment authorization.

2.0 REVISION CONTROL

DATE	CHANGES	REVISION
03/10/03	ORIGINAL RELEASE	0.0
03/19/03	ADD CALCULATIONS FOR MOBILE UNITS, CHANGE PRESENTATION FORMAT	0.1

3.0 APPLICABLE DOCUMENTS

[1] "Code of Federal Regulations Title 47, Volume 1, Sec. 1.1310 Radiofrequency radiation exposure limits" **47CFR1.1310**, Revised as of October 1, 2001, Page 297-298.

[2] "Code of Federal Regulations Title 47, Volume 1, Sec. 2.1091 Radiofrequency radiation exposure evaluation: mobile devices." **47CFR2.1091**, Revised as of October 1, 2001, Page 588-589.

[3] "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", Supplement C, OET Bulletin 65, Edition 97-01

TITLE: GRAYHILL MPE CALCULATION	 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com	
PROJECT: GRAYHILL EZ -COM LPM CERTIFICATION			
FILENAME, FILES AFFECTED: Portable OCU unit MPE Calculations	REVISION: 0.1	PAGE: 3 OF 4	

4.0 MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS

Calculation 1

Portable unit with 0 dBi helical antenna and 10 cm separation.

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 27.0 (dBm)

Maximum peak output power at antenna input terminal: 501.19 (mW)

Antenna gain(typical): 0.0 (dBi)

Maximum antenna gain: 1.00 (numeric)

Prediction distance: 10 (cm)

Prediction frequency: 915 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 0.61 (mW/cm²)

Power density at prediction frequency: 0.40 (mW/cm²)

Maximum allowable antenna gain: 1.85 (dBi)

Margin of Compliance at 10cm = 1.83 dB

TITLE:	GRAYHILL MPE CALCULATION	 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT:	GRAYHILL EZ -COM LPM CERTIFICATION		
FILENAME, FILES AFFECTED:	Portable OCU unit MPE Calculations	REVISION: 0.1	PAGE: 4 OF 4