

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Report No.: RFBEMI-WTW-P25060631

FCC ID: NOIKBN428B

Product: Electronic Display Device

Brand: Rakuten kobo

Model No.: N428B

Received Date: 2025/6/30

Test Date: 2025/7/10 ~ 2025/7/24

Issued Date: 2025/9/18

Applicant: NETRONIX, INC.

Address: No. 945, Boai St., Jubei City, Hsin-Chu, 30265, Taiwan

Factory: (1) NETRONIX, INC.
(2) NTX Electronics YANGZHOU CO., LTD.

Address: (1) No. 945, Boai St., Jubei City, Hsin-Chu, 30265, Taiwan
(2) No. 8, Wuzhou West Road, Economic and technological Development Zone, Yangzhou, Jiangsu Province, 225009, China


Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / 723255 / TW2022

Designation Number:

Approved by:  , **Date:** 2025/9/18
May Chen / Manager

This test report consists of 54 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by: Vito Lung / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	8
3.3 Channel List	9
3.4 Test Mode Applicability and Tested Channel Detail	10
3.5 Duty Cycle of Test Signal	11
3.6 Test Program Used and Operation Descriptions	12
3.7 Connection Diagram of EUT and Peripheral Devices	12
3.8 Configuration of Peripheral Devices and Cable Connections	13
4 Test Instruments	14
4.1 RF Output Power	14
4.2 Power Spectral Density	14
4.3 6 dB Bandwidth	14
4.4 Conducted Out of Band Emissions	14
4.5 AC Power Conducted Emissions	15
4.6 Unwanted Emissions below 1 GHz	15
4.7 Unwanted Emissions above 1 GHz	16
5 Limits of Test Items.....	17
5.1 RF Output Power	17
5.2 Power Spectral Density	17
5.3 6 dB Bandwidth	17
5.4 Conducted Out of Band Emissions	17
5.5 AC Power Conducted Emissions	17
5.6 Unwanted Emissions below 1 GHz	17
5.7 Unwanted Emissions above 1 GHz	18
6 Test Arrangements	19
6.1 RF Output Power	19
6.1.1 Test Setup	19
6.1.2 Test Procedure	19
6.2 Power Spectral Density	19
6.2.1 Test Setup	19
6.2.2 Test Procedure	19
6.3 6 dB Bandwidth	20
6.3.1 Test Setup	20
6.3.2 Test Procedure	20
6.4 Conducted Out of Band Emissions	20
6.4.1 Test Setup	20
6.4.2 Test Procedure	20
6.5 AC Power Conducted Emissions	21
6.5.1 Test Setup	21
6.5.2 Test Procedure	21
6.6 Unwanted Emissions below 1 GHz	22
6.6.1 Test Setup	22
6.6.2 Test Procedure	23
6.7 Unwanted Emissions above 1 GHz	24
6.7.1 Test Setup	24
6.7.2 Test Procedure	24
7 Test Results of Test Item	25

7.1	RF Output Power.....	25
7.2	Power Spectral Density	27
7.3	6 dB Bandwidth	29
7.4	Conducted Out of Band Emissions	31
7.5	AC Power Conducted Emissions	34
7.6	Unwanted Emissions below 1 GHz	36
7.7	Unwanted Emissions above 1 GHz.....	38
8	Pictures of Test Arrangements	53
9	Information of the Testing Laboratories	54

Release Control Record

Issue No.	Description	Date Issued
RFBEMI-WTW-P25060631	Original release.	2025/9/18

1 Certificate

Product: Electronic Display Device

Brand: Rakuten kobo

Test Model: N428B

Sample Status: Engineering sample

Applicant: NETRONIX, INC.

Test Date: 2025/7/10 ~ 2025/7/24

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement ANSI C63.10-2013

procedure: KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -5.82 dB at 0.76328 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -9.6 dB at 30.05 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.1 dB at 2390.00 MHz and 2483.50 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.1 dB
Power Spectral Density	-	1.3 dB
6 dB Bandwidth	-	1050.00 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.6 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.1 dB
	30 MHz ~ 1 GHz	5.1 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	5.1 dB
	18 GHz ~ 40 GHz	5.3 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Electronic Display Device
Brand	Rakuten kobo
Test Model	N428B
Status of EUT	Engineering sample
Power Supply Rating	3.87 Vdc from battery 5 Vdc from USB interface
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 72.2 Mbps
Operating Frequency	2.412 GHz ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11
Output Power	142.233 mW (21.53 dBm)

Note:

1. The EUT model is listed as below.

No.	Model	Color	Different
1	N428B	Black	EUT has two colors: only the color is different, the circuit design is the same.
2		White	

2. The EUT must be supplied with a battery as the following table:

Item	Brand	Model	Specification
Battery	DESAY BATTERY TECHNOLOGY CO., LTD.	K24072300-2410878	Power Rating:3.87 Vdc, 8.91Wh, 2300mAh

3. The EUT uses following accessories.

Item	Brand	Model	Supplier Model	Color	Specification	Material	TID number
1st source USB Cable	Yih Fone	SH-0846	YF-USB2-A-C-1M(K)	Black	Shielded, 1.0M	TPE	12574
	Yih Fone	SH-0837	YF-USB2-A-C-1M-WH(K)	White	Shielded, 1.0M	TPE	12575
2nd source USB Cable	LUXSHARE-ICT	LB93US005-1H	---	Black	Shielded, 1.0M	TPE	---
	LUXSHARE-ICT	LB93US006-1H	---	White	Shielded, 1.0M	TPE	---

4. The EUT will be supported with the following eMMC and DRAM source.

Source	Item	Brand	Model
Main Source	1st source eMMC	PHISON	PTE7A0YJ-32GE
	1st source DRAM	MICRON	MT53D512M16D1DS-046 WT:D
2nd Source	2nd source eMMC	MK FOUNDER	MKEMF032GT1E-C
	1st source DRAM	MICRON	MT53D512M16D1DS-046 WT:D
3rd Source	3rd source eMMC	FORESEE	FEMDNN032G-C9A55
	2nd source DRAM	KINGSTON	D0811PM2FDGUK

5. There are Bluetooth and WLAN (2.4 GHz & 5 GHz) technology used for the EUT.

6. Simultaneously transmission combination.

Combination	Technology	
1	WLAN (2.4 GHz)	Bluetooth
2	WLAN (5 GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

7. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Brand	Model	Antenna Net Gain(dBi)	Frequency range (GHz)	Antenna Type	Connector Type
INPAQ	ACM3-3216-P1-CC-S	3.91	2.4~2.5	Chip	none
		3.41	5.15~5.85		

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a SISO function:

2.4 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX

3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	8	2447 MHz
2	2417 MHz	9	2452 MHz
3	2422 MHz	10	2457 MHz
4	2427 MHz	11	2462 MHz
5	2432 MHz		
6	2437 MHz		
7	2442 MHz		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. For Radiated, pre-scan Power from AC Adapter via USB Cable / Laptop via USB Cable / Battery and find the worst case as a representative test condition. 2. For AC conduction, pre-scan Power from AC Adapter via USB Cable / Laptop via USB Cable and find the worst case as a representative test condition. 3. EUT can be used in the following ways: X-axis / Y-axis / Z-axis. Pre-scan these ways and find the worst case as a representative test condition. 4. The USB Cable has the following models: SH-0846 / LB93US005-1H. Pre-scan these models of USB Cables and find the worst case as a representative test condition. 5. The eMMC has the following models: PTE7A0YJ-32GE / MKEMF032GT1E-C / FEMDNN032GC9A55. Pre-scan these models of eMMC and find the worst case as a representative test condition. 6. The DRAM has the following models: MT53D512M16D1DS-046 WT:D / D0811PM2FDGUK. Pre-scan these models of DRAM and find the worst case as a representative test condition. 7. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. For Radiated Worst Condition: Laptop via USB Cable 2. For AC conduction Worst Condition: AC Adapter via USB Cable 3. X-axis/ Y-axis/ Z-axis Worst Condition: Z-axis 4. USB Cable Worst Condition: LB93US005-1H 5. eMMC Worst Condition: PTE7A0YJ-32GE 6. DRAM Worst Condition: MT53D512M16D1DS-046 WT:D

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power / Power Spectral Density	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	1, 6, 11	BPSK	MCS0
6 dB Bandwidth / Conducted Out of Band Emissions	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	1, 6, 11	BPSK	MCS0
AC Power Conducted Emissions	802.11b	1	DBPSK	1Mb/s
Unwanted Emissions below 1 GHz	802.11b	1	DBPSK	1Mb/s
Unwanted Emissions above 1 GHz	802.11b	1, 6, 11	DBPSK	1Mb/s
	802.11g	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	1, 6, 11	BPSK	MCS0


Note: Both USB cables from the same brand are identical to each other except for exterior color and model names.

3.5 Duty Cycle of Test Signal


802.11b: Duty cycle = 16.58 ms / 16.61 ms x 100% = 99.8%

802.11g: Duty cycle = 2.757 ms / 2.8 ms x 100% = 98.5%

802.11n (HT20): Duty cycle = 2.56 ms / 2.604 ms x 100% = 98.3%



802.11b



802.11g




802.11n (HT20)

3.6 Test Program Used and Operation Descriptions


Controlling software (HyperTerminal paste wifitesttool 20250310.txt command) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices

For Unwanted Emissions test:



For AC Power Conducted Emission test:



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Laptop	DELL	E5520	8Y4DMQ1	N/A	Provided by Lab
B	Adapter	LENOVO	ADLX45YLC3D	N/A	N/A	Provided by Lab
C	Adapter	ASUS	EXA1205UA	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB Cable	1	1	YES	0	Supplied by applicant
2	DC Cable	1	1.7	NO	0	Provided by Lab
3	AC Cable	1	0.9	NO	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-20	00800A1K01A-20-02	2025/5/23	2026/5/22
Pulse Power Sensor Anritsu	MA2411B	1726434	2025/6/3	2026/6/2
RF Power Meter Anritsu	ML2495A	1529002	2025/6/3	2026/6/2

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2025/7/21

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030A	MY55330160	2025/1/16	2026/1/15
Software	ADT_RF Test Software V8	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2025/7/21

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance Telegartner	50 ohm	3	2024/11/1	2025/10/31
EMI Test Receiver R&S	ESCS 30	100375	2025/5/21	2026/5/20
Fixed Attenuator STI	STI02-2200-10	005	2025/2/17	2026/2/16
LISN R&S	ESH3-Z5	835239/001	2025/3/27	2026/3/26
		848773/004	2024/10/7	2025/10/6
RF Coaxial Cable JYEBAO	5D-FB	COCCAB-001	2025/2/17	2026/2/16
Software BVADT	BVADT_Conc_V7.3.7.4	N/A	N/A	N/A

Notes:

1. The test was performed in Conduction 1
2. Tested Date: 2025/7/23

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-0842	2024/10/8	2025/10/7
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2025/3/25	2026/3/24
Fixed Attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	2025/3/29	2026/3/28
Loop Antenna TESEQ	HLA 6121	63620	2024/10/17	2025/10/16
Preamplifier EMCI	EMC330N	980538	2025/3/29	2026/3/28
	EMC001340	980142	2025/2/17	2026/2/16
PXA Signal Analyzer Keysight	N9030B	MY57141948	2025/5/20	2026/5/19
RF Coaxial Cable PEWC	8D	966-5-1	2025/3/29	2026/3/28
		966-5-2	2025/3/29	2026/3/28
		966-5-3	2025/3/29	2026/3/28
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.
2. Tested Date: 2025/7/22

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2025/3/25	2026/3/24
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1819	2024/11/10	2025/11/9
	BBHA 9170	9170-739	2024/11/10	2025/11/9
Preamplifier EMCI	EMC12630SE	980509	2025/1/18	2026/1/17
	EMC184045SE	980387	2024/8/8	2025/8/7
PXA Signal Analyzer Keysight	N9030B	MY57141948	2025/5/20	2026/5/19
RF Coaxial Cable EMCI	EMC102-KM-KM-1200	160924	2025/1/24	2026/1/23
	EMC102-KM-KM-4000	200214	2025/1/24	2026/1/23
	EMC104-SM-SM-1500	180503	2025/3/8	2026/3/7
	EMC104-SM-SM-2000	180501	2025/3/8	2026/3/7
	EMC104-SM-SM-6000	180506	2025/3/8	2026/3/7
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.
2. Tested Date: 2025/7/10 ~ 2025/7/24

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:


A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: 3 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3.87 Vdc	Environmental Conditions:	23°C, 62% RH	Tested By:	Dolly Chung
--------------	----------	---------------------------	--------------	------------	-------------

For Peak Power

802.11b

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	27.416	14.38	30	Pass
6	2437	26.915	14.30	30	Pass
11	2462	26.669	14.26	30	Pass

Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	139.316	21.44	30	Pass
6	2437	133.66	21.26	30	Pass
11	2462	141.906	21.52	30	Pass

Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	134.896	21.30	30	Pass
6	2437	138.038	21.40	30	Pass
11	2462	142.233	21.53	30	Pass

Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

For Average Power

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	15.74	11.97
6	2437	15.453	11.89
11	2462	15.346	11.86

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	14.125	11.50
6	2437	13.836	11.41
11	2462	13.397	11.27

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	13.274	11.23
6	2437	13.397	11.27
11	2462	12.972	11.13

7.2 Power Spectral Density

Input Power:	3.87 Vdc	Environmental Conditions:	23°C, 62% RH	Tested By:	Dolly Chung
--------------	----------	---------------------------	--------------	------------	-------------

802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-9.98	8	Pass
6	2437	-10.02	8	Pass
11	2462	-9.55	8	Pass

Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-11.63	8	Pass
6	2437	-11.73	8	Pass
11	2462	-12.22	8	Pass


Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2412	-12.79	8	Pass
6	2437	-12.58	8	Pass
11	2462	-12.67	8	Pass

Note: The antenna gain is 3.91 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	3.87 Vdc	Environmental Conditions:	23°C, 62% RH	Tested By:	Dolly Chung
--------------	----------	---------------------------	--------------	------------	-------------

802.11b

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	8.11	0.5	Pass
6	2437	8.06	0.5	Pass
11	2462	8.09	0.5	Pass





802.11g

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.33	0.5	Pass
6	2437	15.16	0.5	Pass
11	2462	15.49	0.5	Pass

802.11n (HT20)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.12	0.5	Pass
6	2437	15.35	0.5	Pass
11	2462	15.72	0.5	Pass


Spectrum Plot of Minimum Value



7.4 Conducted Out of Band Emissions

Input Power:	3.87 Vdc	Environmental Conditions:	23°C, 62% RH	Tested By:	Dolly Chung
--------------	----------	---------------------------	--------------	------------	-------------

802.11b



802.11g



802.11n (HT20)




7.5 AC Power Conducted Emissions

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68% RH
Tested By	Roy Mai		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	9.97	34.92	22.47	44.89	32.44	64.98	54.98	-20.09	-22.54
2	0.21250	9.99	32.27	14.54	42.26	24.53	63.11	53.11	-20.85	-28.58
3	0.32578	9.99	18.60	-5.66	28.59	4.33	59.56	49.56	-30.97	-45.23
4	0.41563	9.99	17.74	-4.39	27.73	5.60	57.54	47.54	-29.81	-41.94
5	0.51719	10.00	21.66	-2.48	31.66	7.52	56.00	46.00	-24.34	-38.48
6	0.67734	10.01	15.01	-6.69	25.02	3.32	56.00	46.00	-30.98	-42.68

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	22 °C, 68% RH
Tested By	Roy Mai		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.01	19.06	-1.97	29.07	8.04	65.79	55.79	-36.72	-47.75
2	0.19687	10.02	29.27	-3.26	39.29	6.76	63.74	53.74	-24.45	-46.98
3	0.31016	10.01	11.40	-9.60	21.41	0.41	59.97	49.97	-38.56	-49.56
4	0.76328	10.03	30.22	30.15	40.25	40.18	56.00	46.00	-15.75	-5.82
5	1.64844	10.08	8.24	-10.79	18.32	-0.71	56.00	46.00	-37.68	-46.71
6	27.45703	10.87	26.24	25.32	37.11	36.19	60.00	50.00	-22.89	-13.81

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	8 °C, 52% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	150.01	33.3 QP	43.5	-10.2	3.00 H	360	45.7	-12.4
2	226.72	23.4 QP	46.0	-22.6	1.00 H	252	38.6	-15.2
3	329.22	22.2 QP	46.0	-23.8	1.00 H	272	33.0	-10.8
4	497.88	28.9 QP	46.0	-17.1	1.00 H	294	35.7	-6.8
5	632.52	27.9 QP	46.0	-18.1	2.00 H	1	31.7	-3.8
6	869.83	31.1 QP	46.0	-14.9	3.00 H	40	31.4	-0.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	8 °C, 52% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.05	30.4 QP	40.0	-9.6	2.00 V	360	44.0	-13.6
2	149.99	22.1 QP	43.5	-21.4	2.00 V	360	34.5	-12.4
3	328.27	21.2 QP	46.0	-24.8	3.00 V	171	32.0	-10.8
4	449.99	27.6 QP	46.0	-18.4	1.50 V	1	35.2	-7.6
5	600.02	27.6 QP	46.0	-18.4	1.00 V	232	31.9	-4.3
6	851.66	30.1 QP	46.0	-15.9	2.00 V	360	30.8	-0.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.0 PK	74.0	-15.0	1.40 H	43	62.1	-3.1
2	2390.00	51.4 AV	54.0	-2.6	1.40 H	43	54.5	-3.1
3	*2412.00	110.0 PK			1.40 H	43	113.2	-3.2
4	*2412.00	107.9 AV			1.40 H	43	111.1	-3.2
5	4824.00	51.8 PK	74.0	-22.2	1.10 H	54	49.8	2.0
6	4824.00	50.5 AV	54.0	-3.5	1.10 H	54	48.5	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	1.22 V	58	62.4	-3.1
2	2390.00	51.5 AV	54.0	-2.5	1.22 V	58	54.6	-3.1
3	*2412.00	110.5 PK			1.22 V	58	113.7	-3.2
4	*2412.00	108.3 AV			1.22 V	58	111.5	-3.2
5	4824.00	50.3 PK	74.0	-23.7	1.01 V	340	48.3	2.0
6	4824.00	49.5 AV	54.0	-4.5	1.01 V	340	47.5	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.7 PK	74.0	-18.3	1.46 H	48	58.8	-3.1
2	2390.00	44.8 AV	54.0	-9.2	1.46 H	48	47.9	-3.1
3	*2437.00	110.1 PK			1.46 H	48	113.4	-3.3
4	*2437.00	107.9 AV			1.46 H	48	111.2	-3.3
5	2483.50	54.5 PK	74.0	-19.5	1.46 H	48	57.6	-3.1
6	2483.50	44.0 AV	54.0	-10.0	1.46 H	48	47.1	-3.1
7	4874.00	55.3 PK	74.0	-18.7	1.02 H	54	53.3	2.0
8	4874.00	53.7 AV	54.0	-0.3	1.02 H	54	51.7	2.0
9	7311.00	49.9 PK	74.0	-24.1	1.28 H	111	42.4	7.5
10	7311.00	37.4 AV	54.0	-16.6	1.28 H	111	29.9	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.2 PK	74.0	-18.8	1.57 V	65	58.3	-3.1
2	2390.00	43.6 AV	54.0	-10.4	1.57 V	65	46.7	-3.1
3	*2437.00	110.4 PK			1.57 V	65	113.7	-3.3
4	*2437.00	108.7 AV			1.57 V	65	112.0	-3.3
5	2483.50	55.6 PK	74.0	-18.4	1.57 V	65	58.7	-3.1
6	2483.50	42.3 AV	54.0	-11.7	1.57 V	65	45.4	-3.1
7	4874.00	52.8 PK	74.0	-21.2	1.03 V	338	50.8	2.0
8	4874.00	51.6 AV	54.0	-2.4	1.03 V	338	49.6	2.0
9	7311.00	50.3 PK	74.0	-23.7	1.26 V	102	42.8	7.5
10	7311.00	37.6 AV	54.0	-16.4	1.26 V	102	30.1	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.0 PK			1.00 H	44	113.1	-3.1
2	*2462.00	107.8 AV			1.00 H	44	110.9	-3.1
3	2483.50	58.5 PK	74.0	-15.5	1.00 H	44	61.6	-3.1
4	2483.50	50.8 AV	54.0	-3.2	1.00 H	44	53.9	-3.1
5	4924.00	52.3 PK	74.0	-21.7	1.03 H	56	50.2	2.1
6	4924.00	51.2 AV	54.0	-2.8	1.03 H	56	49.1	2.1
7	7386.00	40.9 PK	74.0	-33.1	2.02 H	58	33.4	7.5
8	7386.00	32.6 AV	54.0	-21.4	2.02 H	58	25.1	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.4 PK			1.36 V	57	112.5	-3.1
2	*2462.00	107.6 AV			1.36 V	57	110.7	-3.1
3	2483.50	58.6 PK	74.0	-15.4	1.36 V	57	61.7	-3.1
4	2483.50	51.2 AV	54.0	-2.8	1.36 V	57	54.3	-3.1
5	4924.00	52.0 PK	74.0	-22.0	1.00 V	337	49.9	2.1
6	4924.00	51.0 AV	54.0	-3.0	1.00 V	337	48.9	2.1
7	7386.00	41.1 PK	74.0	-32.9	2.02 V	66	33.6	7.5
8	7386.00	32.7 AV	54.0	-21.3	2.02 V	66	25.2	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.1 PK	74.0	-2.9	1.38 H	44	74.2	-3.1
2	2390.00	53.9 AV	54.0	-0.1	1.38 H	44	57.0	-3.1
3	*2412.00	109.5 PK			1.38 H	44	112.7	-3.2
4	*2412.00	99.4 AV			1.38 H	44	102.6	-3.2
5	4824.00	48.3 PK	74.0	-25.7	2.33 H	360	46.3	2.0
6	4824.00	34.8 AV	54.0	-19.2	2.33 H	360	32.8	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.2 PK	74.0	-2.8	1.24 V	54	74.3	-3.1
2	2390.00	53.8 AV	54.0	-0.2	1.24 V	54	56.9	-3.1
3	*2412.00	109.8 PK			1.24 V	54	113.0	-3.2
4	*2412.00	99.5 AV			1.24 V	54	102.7	-3.2
5	4824.00	48.1 PK	74.0	-25.9	2.39 V	360	46.1	2.0
6	4824.00	34.5 AV	54.0	-19.5	2.39 V	360	32.5	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	67.1 PK	74.0	-6.9	1.42 H	48	70.2	-3.1
2	2390.00	52.5 AV	54.0	-1.5	1.42 H	48	55.6	-3.1
3	*2437.00	114.5 PK			1.42 H	48	117.8	-3.3
4	*2437.00	104.4 AV			1.42 H	48	107.7	-3.3
5	2483.50	71.2 PK	74.0	-2.8	1.42 H	48	74.3	-3.1
6	2483.50	53.8 AV	54.0	-0.2	1.42 H	48	56.9	-3.1
7	4874.00	55.0 PK	74.0	-19.0	3.26 H	301	53.0	2.0
8	4874.00	42.4 AV	54.0	-11.6	3.26 H	301	40.4	2.0
9	7311.00	48.6 PK	74.0	-25.4	2.24 H	353	41.1	7.5
10	7311.00	35.9 AV	54.0	-18.1	2.24 H	353	28.4	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.3 PK	74.0	-7.7	1.55 V	67	69.4	-3.1
2	2390.00	51.7 AV	54.0	-2.3	1.55 V	67	54.8	-3.1
3	*2437.00	114.4 PK			1.55 V	67	117.7	-3.3
4	*2437.00	104.5 AV			1.55 V	67	107.8	-3.3
5	2483.50	68.5 PK	74.0	-5.5	1.55 V	67	71.6	-3.1
6	2483.50	53.3 AV	54.0	-0.7	1.55 V	67	56.4	-3.1
7	4874.00	54.8 PK	74.0	-19.2	3.23 V	316	52.8	2.0
8	4874.00	42.5 AV	54.0	-11.5	3.23 V	316	40.5	2.0
9	7311.00	48.1 PK	74.0	-25.9	2.30 V	360	40.6	7.5
10	7311.00	35.6 AV	54.0	-18.4	2.30 V	360	28.1	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.4 PK			1.00 H	41	113.5	-3.1
2	*2462.00	100.7 AV			1.00 H	41	103.8	-3.1
3	2483.50	73.4 PK	74.0	-0.6	1.00 H	41	76.5	-3.1
4	2483.50	53.2 AV	54.0	-0.8	1.00 H	41	56.3	-3.1
5	4924.00	48.5 PK	74.0	-25.5	2.92 H	0	46.4	2.1
6	4924.00	34.6 AV	54.0	-19.4	2.92 H	0	32.5	2.1
7	7386.00	50.3 PK	74.0	-23.7	1.54 H	325	42.8	7.5
8	7386.00	37.5 AV	54.0	-16.5	1.54 H	325	30.0	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	35.4 PK	74.0	-38.6	1.75 V	95	41.3	-5.9
2	1608.00	26.3 AV	54.0	-27.7	1.75 V	95	32.2	-5.9
3	#3216.00	38.6 PK			1.56 V	92	40.2	-1.6
4	#3216.00	27.9 AV			1.56 V	92	29.5	-1.6
5	4824.00	41.5 PK	74.0	-32.5	1.69 V	129	39.5	2.0
6	4824.00	32.7 AV	54.0	-21.3	1.69 V	129	30.7	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band, the limit was restricted at the Conducted Out of Band Emissions.

RF Mode	802.11n (HT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.3 PK	74.0	-2.7	1.47 H	44	74.4	-3.1
2	2390.00	53.6 AV	54.0	-0.4	1.47 H	44	56.7	-3.1
3	*2412.00	107.8 PK			1.47 H	44	111.0	-3.2
4	*2412.00	97.4 AV			1.47 H	44	100.6	-3.2
5	4824.00	44.0 PK	74.0	-30.0	1.22 H	318	42.0	2.0
6	4824.00	30.6 AV	54.0	-23.4	1.22 H	318	28.6	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.1 PK	74.0	-2.9	1.24 V	54	74.2	-3.1
2	2390.00	53.3 AV	54.0	-0.7	1.24 V	54	56.4	-3.1
3	*2412.00	108.6 PK			1.24 V	54	111.8	-3.2
4	*2412.00	97.9 AV			1.24 V	54	101.1	-3.2
5	4824.00	44.3 PK	74.0	-29.7	1.18 V	326	42.3	2.0
6	4824.00	30.7 AV	54.0	-23.3	1.18 V	326	28.7	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.6 PK	74.0	-2.4	1.43 H	46	74.7	-3.1
2	2390.00	50.1 AV	54.0	-3.9	1.43 H	46	53.2	-3.1
3	*2437.00	114.9 PK			1.43 H	46	118.2	-3.3
4	*2437.00	103.6 AV			1.43 H	46	106.9	-3.3
5	2483.50	68.5 PK	74.0	-5.5	1.43 H	46	71.6	-3.1
6	2483.50	51.2 AV	54.0	-2.8	1.43 H	46	54.3	-3.1
7	4874.00	45.3 PK	74.0	-28.7	2.11 H	349	43.3	2.0
8	4874.00	33.9 AV	54.0	-20.1	2.11 H	349	31.9	2.0
9	7311.00	39.3 PK	74.0	-34.7	1.57 H	28	31.8	7.5
10	7311.00	30.0 AV	54.0	-24.0	1.57 H	28	22.5	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.5 PK	74.0	-7.5	1.56 V	64	69.6	-3.1
2	2390.00	50.3 AV	54.0	-3.7	1.56 V	64	53.4	-3.1
3	*2437.00	113.6 PK			1.56 V	64	116.9	-3.3
4	*2437.00	103.8 AV			1.56 V	64	107.1	-3.3
5	2483.50	67.4 PK	74.0	-6.6	1.56 V	64	70.5	-3.1
6	2483.50	51.2 AV	54.0	-2.8	1.56 V	64	54.3	-3.1
7	4874.00	47.8 PK	74.0	-26.2	2.82 V	358	45.8	2.0
8	4874.00	35.1 AV	54.0	-18.9	2.82 V	358	33.1	2.0
9	7311.00	39.0 PK	74.0	-35.0	1.55 V	13	31.5	7.5
10	7311.00	29.6 AV	54.0	-24.4	1.55 V	13	22.1	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11n (HT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power (System)	120 Vac, 60 Hz	Environmental Conditions	23 °C, 76% RH
Tested By	Roy Mai		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.3 PK			1.00 H	44	112.4	-3.1
2	*2462.00	99.6 AV			1.00 H	44	102.7	-3.1
3	2483.50	71.5 PK	74.0	-2.5	1.00 H	44	74.6	-3.1
4	2483.50	53.9 AV	54.0	-0.1	1.00 H	44	57.0	-3.1
5	4924.00	44.3 PK	74.0	-29.7	1.23 H	315	42.2	2.1
6	4924.00	31.1 AV	54.0	-22.9	1.23 H	315	29.0	2.1
7	7386.00	39.3 PK	74.0	-34.7	1.59 H	2	31.8	7.5
8	7386.00	30.0 AV	54.0	-24.0	1.59 H	2	22.5	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	108.8 PK			1.39 V	57	111.9	-3.1
2	*2462.00	98.9 AV			1.39 V	57	102.0	-3.1
3	2483.50	70.7 PK	74.0	-3.3	1.39 V	57	73.8	-3.1
4	2483.50	53.0 AV	54.0	-1.0	1.39 V	57	56.1	-3.1
5	4924.00	44.0 PK	74.0	-30.0	1.23 V	303	41.9	2.1
6	4924.00	30.7 AV	54.0	-23.3	1.23 V	303	28.6	2.1
7	7386.00	39.0 PK	74.0	-35.0	1.59 V	25	31.5	7.5
8	7386.00	29.4 AV	54.0	-24.6	1.59 V	25	21.9	7.5


Remarks:


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

Plot of Band Edge


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--

802.11b Channel 1




802.11b Channel 11


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11g Channel 1




802.11g Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11n (HT20) Channel 1




802.11n (HT20) Channel 11




Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---