

# FCC TEST REPORT(15.247)

**REPORT NO.:** RF140828E03

**MODEL NO.:** D5001, D3001, D3003

**FCC ID:** NQ8D5001

**RECEIVED:** Aug. 28, 2014

**TESTED:** Sep. 10 to 23, 2014

**ISSUED:** Oct. 03, 2014

**APPLICANT:** Pace Micro Technology plc

**ADDRESS:** Saltaire, Shipley, West Yorkshire, BD18 3LF,  
UK

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS :** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,  
R.O.C.

**TEST LOCATION (1):** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,  
R.O.C.

**TEST LOCATION (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,  
R.O.C.

This report should not be used by the client to claim  
product certification, approval, or endorsement by TAF  
or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

## Table of Contents

|                                                                |    |
|----------------------------------------------------------------|----|
| RELEASE CONTROL RECORD .....                                   | 4  |
| 1. CERTIFICATION.....                                          | 5  |
| 2. SUMMARY OF TEST RESULTS .....                               | 6  |
| 2.1 MEASUREMENT UNCERTAINTY .....                              | 7  |
| 3. GENERAL INFORMATION .....                                   | 8  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                           | 8  |
| 3.2 DESCRIPTION OF TEST MODES .....                            | 12 |
| 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....   | 13 |
| 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....              | 16 |
| 3.4 DUTY CYCLE OF TEST SIGNAL .....                            | 17 |
| 3.5 DESCRIPTION OF SUPPORT UNITS .....                         | 18 |
| 3.6 CONFIGURATION OF SYSTEM UNDER TEST.....                    | 19 |
| 4. TEST TYPES AND RESULTS .....                                | 20 |
| 4.1 CONDUCTED EMISSION MEASUREMENT.....                        | 20 |
| 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....           | 20 |
| 4.1.2 TEST INSTRUMENTS.....                                    | 20 |
| 4.1.3 TEST PROCEDURES .....                                    | 21 |
| 4.1.4 DEVIATION FROM TEST STANDARD.....                        | 21 |
| 4.1.5 TEST SETUP.....                                          | 21 |
| 4.1.6 EUT OPERATING CONDITIONS .....                           | 22 |
| 4.1.7 TEST RESULTS .....                                       | 23 |
| 4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....           | 25 |
| 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT ... | 25 |
| 4.2.2 TEST INSTRUMENTS.....                                    | 26 |
| 4.2.3 TEST PROCEDURES .....                                    | 27 |
| 4.2.4 DEVIATION FROM TEST STANDARD.....                        | 27 |
| 4.2.5 TEST SETUP.....                                          | 28 |
| 4.2.6 EUT OPERATING CONDITIONS .....                           | 28 |
| 4.2.7 TEST RESULTS .....                                       | 29 |
| 4.3 6dB BANDWIDTH MEASUREMENT .....                            | 42 |
| 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....                | 42 |
| 4.3.2 TEST INSTRUMENTS.....                                    | 42 |
| 4.3.3 TEST PROCEDURE.....                                      | 42 |
| 4.3.4 DEVIATION FROM TEST STANDARD.....                        | 42 |
| 4.3.5 TEST SETUP.....                                          | 42 |
| 4.3.6 EUT OPERATING CONDITIONS .....                           | 42 |
| 4.3.7 TEST RESULTS (MODE 1) .....                              | 43 |
| 4.3.8 TEST RESULTS (MODE 2) .....                              | 45 |



A D T

|       |                                                                                             |    |
|-------|---------------------------------------------------------------------------------------------|----|
| 4.4   | CONDUCTED OUTPUT POWER MEASUREMENT .....                                                    | 46 |
| 4.4.1 | LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....                                          | 46 |
| 4.4.2 | TEST INSTRUMENTS .....                                                                      | 46 |
| 4.4.3 | TEST PROCEDURES .....                                                                       | 46 |
| 4.4.4 | DEVIATION FROM TEST STANDARD .....                                                          | 47 |
| 4.4.5 | TEST SETUP .....                                                                            | 47 |
| 4.4.6 | EUT OPERATING CONDITIONS .....                                                              | 47 |
| 4.4.7 | TEST RESULTS(MODE 1) .....                                                                  | 48 |
| 4.4.8 | TEST RESULTS(MODE 2) .....                                                                  | 49 |
| 4.5   | POWER SPECTRAL DENSITY MEASUREMENT .....                                                    | 50 |
| 4.5.1 | LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....                                          | 50 |
| 4.5.2 | TEST INSTRUMENTS .....                                                                      | 50 |
| 4.5.3 | TEST PROCEDURE .....                                                                        | 50 |
| 4.5.4 | DEVIATION FROM TEST STANDARD .....                                                          | 50 |
| 4.5.5 | TEST SETUP .....                                                                            | 50 |
| 4.5.6 | EUT OPERATING CONDITION .....                                                               | 50 |
| 4.5.7 | TEST RESULTS(MODE 1) .....                                                                  | 51 |
| 4.5.8 | TEST RESULTS(MODE 2) .....                                                                  | 54 |
| 4.6   | CONDUCTED OUT-BAND EMISSION MEASUREMENT .....                                               | 56 |
| 4.6.1 | LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT .....                                     | 56 |
| 4.6.2 | TEST INSTRUMENTS .....                                                                      | 56 |
| 4.6.3 | TEST PROCEDURE .....                                                                        | 56 |
| 4.6.4 | DEVIATION FROM TEST STANDARD .....                                                          | 57 |
| 4.6.5 | TEST SETUP .....                                                                            | 57 |
| 4.6.6 | EUT OPERATING CONDITION .....                                                               | 57 |
| 4.6.7 | TEST RESULTS(MODE 1) .....                                                                  | 57 |
| 4.6.8 | TEST RESULTS(MODE 2) .....                                                                  | 70 |
| 5.    | PHOTOGRAPHS OF THE TEST CONFIGURATION .....                                                 | 77 |
| 6.    | INFORMATION ON THE TESTING LABORATORIES .....                                               | 78 |
| 7.    | APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING<br>CHANGES TO THE EUT BY THE LAB ..... | 79 |



A D T

## RELEASE CONTROL RECORD

| ISSUE NO.   | REASON FOR CHANGE | DATE ISSUED   |
|-------------|-------------------|---------------|
| RF140828E03 | Original release  | Oct. 03, 2014 |

## 1. CERTIFICATION

**PRODUCT:** DOCSIS 3.0 Wireless Gateway Router with MOCA 2.0  
**BRAND NAME:** Pace  
**MODEL NO.:** D5001, D3001, D3003  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**APPLICANT:** Pace Micro Technology plc  
**TESTED:** Sep. 10 to 23, 2014  
**STANDARDS:** **FCC Part 15, Subpart C (Section 15.247)**  
ANSI C63.10-2009

The above equipment (Model: D5001) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Midoli Peng, Date: Oct. 03, 2014  
( Midoli Peng, Specialist )

Approved by : May Chen, Date: Oct. 03, 2014  
( May Chen, Manager )

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) |                             |        |                                                                                 |
|-----------------------------------------------------------|-----------------------------|--------|---------------------------------------------------------------------------------|
| STANDARD SECTION                                          | TEST TYPE                   | RESULT | REMARK                                                                          |
| 15.207                                                    | AC Power Conducted Emission | PASS   | Meet the requirement of limit. Minimum passing margin is -17.40dB at 0.54063MHz |
| 15.247(d)<br>15.209                                       | Radiated Emissions          | PASS   | Meet the requirement of limit. Minimum passing margin is -0.2dB at 2381.00MHz   |
| 15.247(d)                                                 | Band Edge Measurement       | PASS   | Meet the requirement of limit.                                                  |
| 15.247(a)(2)                                              | 6dB bandwidth               | PASS   | Meet the requirement of limit.                                                  |
| 15.247(b)                                                 | Conducted Output power      | PASS   | Meet the requirement of limit.                                                  |
| 15.247(e)                                                 | Power Spectral Density      | PASS   | Meet the requirement of limit.                                                  |
| 15.203                                                    | Antenna Requirement         | PASS   | Antenna connector is i-pex(MHF) not a standard connector.                       |

**NOTE:** 1. The EUT was operating in 2400 ~ 2483.5MHz, 5.15~5.25GHz, and 5.725~5.850GHz frequencies band. This report was recorded the RF parameters including 2400 ~ 2483.5MHz. For the 5.15~5.25GHz and 5.725~5.850GHz RF parameters was recorded in another test report.

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| Measurement                       | Value   |
|-----------------------------------|---------|
| Conducted emissions               | 2.86 dB |
| Radiated emissions (30MHz-1GHz)   | 5.37 dB |
| Radiated emissions (1GHz -6GHz)   | 3.65 dB |
| Radiated emissions (6GHz -18GHz)  | 3.88 dB |
| Radiated emissions (18GHz -40GHz) | 4.11 dB |

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                              |                                                                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT</b>               | DOCSIS 3.0 Wireless Gateway Router with MOCA 2.0                                                                                         |
| <b>MODEL NO.</b>             | D5001, D3001, D3003                                                                                                                      |
| <b>POWER SUPPLY</b>          | DC 12V from internal power supply                                                                                                        |
| <b>MODULATION TYPE</b>       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM<br>256QAM for OFDM in 11ac mode only                                     |
| <b>MODULATION TECHNOLOGY</b> | DSSS, OFDM                                                                                                                               |
| <b>TRANSFER RATE</b>         | 802.11b: up to 11Mbps<br>802.11a / g: up to 54Mbps<br>802.11n: up to 450Mbps<br>802.11ac: up to 1300Mbps                                 |
| <b>OPERATING FREQUENCY</b>   | <b>For 15.407</b><br>5.18 ~ 5.24GHz, 5.745 ~ 5.825GHz                                                                                    |
|                              | <b>For 15.247</b><br>2.412 ~ 2.462GHz                                                                                                    |
| <b>NUMBER OF CHANNEL</b>     | <b>For 15.407</b><br>9 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)<br>4 for 802.11n (HT40), 802.11ac (VHT40)<br>2 for 802.11ac (VHT80) |
|                              | <b>For 15.247</b><br>11 for 802.11b, 802.11g, 802.11n (HT20)<br>7 for 802.11n (HT40)                                                     |
| <b>MAXIMUM OUTPUT POWER</b>  | Please see NOTE                                                                                                                          |
| <b>ANTENNA TYPE</b>          | Please see NOTE                                                                                                                          |
| <b>DATA CABLE</b>            | NA                                                                                                                                       |
| <b>I/O PORTS</b>             | Refer to user's manual                                                                                                                   |
| <b>ASSOCIATED DEVICES</b>    | NA                                                                                                                                       |

### Note:

1. The EUT has three model names which are identical to each other in all aspects except for the following table:

| Model Name      | D5001                         | D3001                         | D3003                         | Remark                                       |
|-----------------|-------------------------------|-------------------------------|-------------------------------|----------------------------------------------|
| DSxUS           | 24x8                          | 16x4                          | 16x4                          | Remove BCM3184 wide band tuner for E469&E470 |
| Wifi function   | 2.4G / 5G 11n & ac concurrent | 2.4G / 5G 11n & ac concurrent | 2.4G / 5G 11n & ac concurrent | -                                            |
| With Moca       | Yes                           | Yes                           | NA                            | Remove BCM6803 for E470                      |
| Wide band tuner | BCM3184                       | NA                            | NA                            | Remove BCM3184 wide band tuner for E469&E470 |
| MoCA Chip       | BCM6803KFSBG+ BCM3451KMLG     | BCM6803KFSBG+ BCM3451KMLG     | NA                            | Remove BCM6803 for E470                      |

In general, these 3 models share the same main board PCB but with different component mounting. Two WiFi boards, enclosures, antennas, PSU are all the same without any changing.

From the above models, model: **D5001** was selected as representative model for the test and its data was recorded in this report.

2. The maximum output power(mW) table as below table:

| 2.4GHz                 |         |                  |                  |                  |
|------------------------|---------|------------------|------------------|------------------|
| Test Mode              | 802.11b | 802.11g          | 802.11n (HT20)   | 802.11n (HT40)   |
| 3TX / CDD Mode         | 808.083 | 986.932          | 995.844          | 254.792          |
| 3TX / Beamforming Mode | NA      | NA               | 531.12           | 254.792          |
| 5GHz                   |         |                  |                  |                  |
| Test Mode              | 802.11a | 802.11ac (VHT20) | 802.11ac (VHT40) | 802.11ac (VHT80) |
| 3TX / CDD Mode         | 678.435 | 704.784          | 630.307          | 171.995          |
| 3TX / Beamforming Mode | NA      | 398.179          | 359.682          | 171.995          |

3. The EUT must be supplied with an internal power supply:

| Brand   | Model No.  | Spec.                                                                                  |
|---------|------------|----------------------------------------------------------------------------------------|
| AMPOWER | E12B001.00 | AC I/P: 100~240V, 50/60Hz, 1.3A<br>AC Input cable: 1.8m, unshielded<br>DC O/P: 12V, 4A |

4. There are six antennas provided to this EUT, please refer to the following table:

| Antenna No. | Transmitter Circuit | Brand      | Model            | Gain (dBi)<br>(Include cable loss) | Frequency range<br>(GHz to GHz) | Antenna Type | Connector Type | Cable Length (mm) |
|-------------|---------------------|------------|------------------|------------------------------------|---------------------------------|--------------|----------------|-------------------|
| LB1         | 2                   | Galtronics | 02102073-05762B1 | 2.84                               | 2.4~2.4835                      | Dipole       | i-pex(MHF)     | 310               |
| LB2         | 0                   | Galtronics | 02102073-05762C1 | 3.8                                | 2.4~2.4835                      | PCB          | i-pex(MHF)     | 161               |
| LB3         | 1                   | Galtronics | 02102073-05762A1 | 4.87                               | 2.4~2.4835                      | PCB          | i-pex(MHF)     | 66                |
| HB1         | 0                   | Galtronics | 02102142-05762B2 | 5.50<br>5.27                       | 5.15~5.35<br>5.47~5.85          | Dipole       | i-pex(MHF)     | 130               |
| HB2         | 2                   | Galtronics | 02102142-05762B1 | 4.75<br>5.68                       | 5.15~5.35<br>5.47~5.85          | Dipole       | i-pex(MHF)     | 80                |
| HB3         | 1                   | Galtronics | 02102142-05762B3 | 4.03<br>5.74                       | 5.15~5.35<br>5.47~5.85          | Dipole       | i-pex(MHF)     | 170               |

5. The EUT incorporates a MIMO function.

| MODULATION MODE                           | DATA RATE (MCS) | TX & RX CONFIGURATION                                 |     |
|-------------------------------------------|-----------------|-------------------------------------------------------|-----|
| 802.11a                                   | 6 ~ 54Mbps      | 1TX<br>2TX CDD<br>3TX CDD                             | 3RX |
| 802.11b                                   | 1 ~ 11Mbps      | 1TX<br>2TX CDD<br>3TX CDD                             | 3RX |
| 802.11g                                   | 6 ~ 54Mbps      | 1TX<br>2TX CDD<br>3TX CDD                             | 3RX |
| 802.11n (HT20)<br>&<br>802.11n (HT40)     | MCS 0~7         | 1TX<br>2TX CDD / beamforming<br>3TX CDD / beamforming | 3RX |
|                                           | MCS 8~15        | 2TX beamforming<br>3TX CDD / beamforming              | 3RX |
|                                           | MCS 16~23       | 3TX / beamforming                                     | 3RX |
| 802.11ac (VHT20)                          | MCS0~8 Nss= 1   | 1TX<br>2Tx CDD / beamforming<br>3TX CDD / beamforming | 3RX |
|                                           | MCS0~8 Nss= 2   | 2TX beamforming<br>3TX CDD / beamforming              | 3RX |
|                                           | MCS0~9 Nss= 3   | 3TX / beamforming                                     | 3RX |
| 802.11ac (VHT40)<br>&<br>802.11ac (VHT80) | MCS0~9 Nss= 1   | 1TX<br>2Tx CDD / beamforming<br>3TX CDD / beamforming | 3RX |
|                                           | MCS0~9 Nss= 2   | 2TX CDD / beamforming<br>3TX CDD / beamforming        | 3RX |
|                                           | MCS0~9 Nss= 3   | 3TX / beamforming                                     | 3RX |

Note: The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and 802.11ac mode for 20MHz (40MHz), therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)



A D T

6. The emission of the simultaneous operation (2.4GHz & 5GHz) has been evaluated and no non-compliance was found.
7. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

#### Operated in 2400 ~ 2483.5MHz band:

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |         |         |      |    | DESCRIPTION            |
|--------------------------|---------------|---------|---------|------|----|------------------------|
|                          | PLC           | RE < 1G | RE ≥ 1G | APCM | OB |                        |
| 1                        | √             | √       | √       | √    | √  | 3TX / CDD Mode         |
| 2                        | -             | -       | -       | √    | √  | 3TX / Beamforming Mode |

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz  
**RE ≥ 1G**: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement  
**OB**: Conducted Out-Band Emission Measurement

#### **POWER LINE CONDUCTED EMISSION TEST:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE           | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) | EUT<br>CONFIGURE<br>MODE |
|----------------|----------------------|-------------------|--------------------------|--------------------|---------------------|--------------------------|
| 802.11n (HT20) | 1 to 11              | 6                 | OFDM                     | BPSK               | 6.5                 | 1                        |

#### **RADIATED EMISSION TEST (BELOW 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE           | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA RATE<br>(Mbps) | EUT<br>CONFIGURE<br>MODE |
|----------------|----------------------|-------------------|--------------------------|--------------------|---------------------|--------------------------|
| 802.11n (HT20) | 1 to 11              | 6                 | OFDM                     | BPSK               | 6.5                 | 1                        |

### RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | EUT CONFIGURE MODE |
|----------------|-------------------|----------------|-----------------------|-----------------|------------------|--------------------|
| 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1                | 1                  |
| 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6                | 1                  |
| 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | 1                  |
| 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | 1                  |

### ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | EUT CONFIGURE MODE |
|----------------|-------------------|----------------|-----------------------|-----------------|------------------|--------------------|
| 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1                | 1                  |
| 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6                | 1                  |
| 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | 1, 2               |
| 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | 1, 2               |

### CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | EUT CONFIGURE MODE |
|----------------|-------------------|----------------|-----------------------|-----------------|------------------|--------------------|
| 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1                | 1                  |
| 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6                | 1                  |
| 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | 1, 2               |
| 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | 1, 2               |

**A D T****TEST CONDITION:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER (SYSTEM) | TESTED BY    |
|---------------|--------------------------|----------------------|--------------|
| PLC           | 30deg. C, 70%RH          | 120Vac, 60Hz         | Mike Hsieh   |
| RE<1G         | 23deg. C, 68%RH          | 120Vac, 60Hz         | Robert Cheng |
| RE≥1G         | 25deg. C, 67%RH          | 120Vac, 60Hz         | Andy Ho      |
| APCM          | 25deg. C, 60%RH          | 120Vac, 60Hz         | James Chan   |
| OB            | 25deg. C, 60%RH          | 120Vac, 60Hz         | James Chan   |

### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r02**

**662911 D01 Multiple Transmitter Output v02r01**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

### 3.4 DUTY CYCLE OF TEST SIGNAL

If duty cycle of test signal is  $\geq 98\%$ , duty factor is not required.

If duty cycle of test signal is  $< 98\%$ , duty factor shall be considered.


**802.11b**: Duty cycle = 12.42 ms/12.48 ms = 0.995

**802.11g**: Duty cycle = 2.063 ms/2.083 ms = 0.990


**802.11n (HT20)**: Duty cycle = 0.975 ms/0.993 ms = 0.982

**802.11n (HT40)**: Duty cycle = 0.49 ms/0.51 ms = 0.961, Duty factor =  $10 \cdot \log(1/0.961) = 0.17$


**802.11b**




**802.11g**



**802.11n (HT20)**



**802.11n (HT40)**





A D T

### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| No. | Product                                       | Brand | Model No. | Serial No.    | FCC ID  | Remark          |
|-----|-----------------------------------------------|-------|-----------|---------------|---------|-----------------|
| A   | NOTEBOOK COMPUTER                             | DELL  | E5430     | 7YV4VY1       | FCC DoC | Provided by Lab |
| B   | iPod shuffle<br>(For other test items)        | Apple | MC749TA/A | CC4DN25WDFDM  | NA      | Provided by Lab |
|     | iPod shuffle<br>(For conducted emission test) | Apple | MD778TA/A | CC4JMCXF4T1   | NA      | Provided by Lab |
| C   | iPod shuffle<br>(For other test items)        | Apple | MC749TA/A | CC4DMFKUDFDM  | NA      | Provided by Lab |
|     | iPod shuffle<br>(For conducted emission test) | Apple | MD778TA/A | CC4JMH7LF4T1  | NA      | Provided by Lab |
| D   | HUB                                           | ZyXEL | ES-116P   | S060H02000215 | FCC DoC | Provided by Lab |

**NOTE:**

1. All power cords of the above support units are non-shielded (1.8 m).

| No. | Cable   | Qty. | Length (m) | Shielded<br>(Yes/ No) | Cores<br>(Number) | Remark             |
|-----|---------|------|------------|-----------------------|-------------------|--------------------|
| 1.  | RJ-45   | 3    | 10         | No                    | 0                 | Provided by Lab    |
| 2.  | Coaxial | 1    | 10         | Yes                   | 0                 | Provided by Lab    |
| 3.  | AC      | 1    | 1.8        | No                    | 0                 | Supplied by client |
| 4.  | USB     | 1    | 0.1        | Yes                   | 0                 | Provided by Lab    |
| 5.  | USB     | 1    | 0.1        | Yes                   | 0                 | Provided by Lab    |
| 6.  | RJ-45   | 1    | 10         | No                    | 0                 | Provided by Lab    |

### 3.6 CONFIGURATION OF SYSTEM UNDER TEST



## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15-0.5                    | 66 to 56                     | 56 to 46 |
| 0.5-5                       | 56                           | 46       |
| 5-30                        | 60                           | 50       |

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

#### 4.1.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER                                                     | MODEL NO.                   | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|--------------------------------------------------------------------------------|-----------------------------|------------|-----------------|------------------|
| Test Receiver<br>ROHDE & SCHWARZ                                               | ESCS 30                     | 100375     | Apr. 29, 2014   | Apr. 28, 2015    |
| Line-Impedance<br>Stabilization Network<br>(for EUT)<br>SCHWARZBECK            | NSLK8127                    | 8127-522   | Sep. 12, 2013   | Sep. 11, 2014    |
| Line-Impedance<br>Stabilization Network<br>(for Peripheral)<br>ROHDE & SCHWARZ | ENV216                      | 100071     | Nov. 13, 2013   | Nov. 12, 2014    |
| RF Cable<br>(JYEBAO)                                                           | 5DFB                        | COCCAB-001 | Mar. 10, 2014   | Mar. 09, 2015    |
| 50 ohms Terminator                                                             | N/A                         | EMC-03     | Sep. 24, 2013   | Sep. 23, 2014    |
| 50 ohms Terminator                                                             | N/A                         | EMC-02     | Oct. 01, 2013   | Sep. 30, 2014    |
| Software<br>ADT                                                                | BV<br>ADT_Cond_V7.3.7.<br>3 | NA         | NA              | NA               |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Sep. 10, 2014

### 4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


#### NOTE:

- The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.1.5 TEST SETUP



**Note:** 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

1. Placed the EUT on testing table.
2. Prepared computer system (support unit A) to act as communication partner.
3. The communication partner ran test program "Mtool.exe[2.0.1.1]" to enable EUT under transmission/receiving condition continuously.


#### 4.1.7 TEST RESULTS

| PHASE | Line (L) | DETECTOR FUNCTION | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

|    | Freq.    | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
| No |          | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    | [MHz]    | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.17734  | 0.07   | 44.62         | 36.34 | 44.69          | 36.41 | 64.61     | 54.61 | -19.92 | -18.20 |
| 2  | 0.24375  | 0.07   | 38.68         | 31.59 | 38.75          | 31.66 | 61.97     | 51.97 | -23.21 | -20.30 |
| 3  | 0.35313  | 0.09   | 40.50         | 27.37 | 40.59          | 27.46 | 58.89     | 48.89 | -18.30 | -21.43 |
| 4  | 0.54063  | 0.10   | 37.26         | 26.88 | 37.36          | 26.98 | 56.00     | 46.00 | -18.64 | -19.02 |
| 5  | 14.16797 | 0.57   | 30.12         | 24.24 | 30.69          | 24.81 | 60.00     | 50.00 | -29.31 | -25.19 |
| 6  | 29.92969 | 1.00   | 33.12         | 28.08 | 34.12          | 29.08 | 60.00     | 50.00 | -25.88 | -20.92 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| PHASE | Neutral (N) | DETECTOR FUNCTION | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17734        | 0.07                    | 43.55                      | 34.06 | 43.62                       | 34.13 | 64.61              | 54.61 | -20.99         | -20.48 |
| 2  | 0.25938        | 0.08                    | 39.36                      | 23.26 | 39.44                       | 23.34 | 61.45              | 51.45 | -22.02         | -28.12 |
| 3  | 0.35313        | 0.09                    | 41.36                      | 27.81 | 41.45                       | 27.90 | 58.89              | 48.89 | -17.44         | -20.99 |
| 4  | 0.54063        | 0.10                    | 38.50                      | 28.09 | 38.60                       | 28.19 | 56.00              | 46.00 | -17.40         | -17.81 |
| 5  | 14.92578       | 0.58                    | 33.07                      | 26.64 | 33.65                       | 27.22 | 60.00              | 50.00 | -26.35         | -22.78 |
| 6  | 29.72266       | 0.98                    | 35.13                      | 30.25 | 36.11                       | 31.23 | 60.00              | 50.00 | -23.89         | -18.77 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



## 4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009-0.490       | 2400/F(kHz)                       | 300                           |
| 0.490-1.705       | 24000/F(kHz)                      | 30                            |
| 1.705-30.0        | 30                                | 30                            |
| 30-88             | 100                               | 3                             |
| 88-216            | 150                               | 3                             |
| 216-960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.



A D T

#### 4.2.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER              | MODEL NO.                | SERIAL NO.                          | CALIBRATED DATE | CALIBRATED UNTIL |
|-----------------------------------------|--------------------------|-------------------------------------|-----------------|------------------|
| MXE EMI Receiver<br>Agilent             | N9038A                   | MY51210105                          | July 21, 2014   | July 20, 2015    |
| Pre-Amplifier<br>Mini-Circuits          | ZFL-1000VH2<br>B         | AMP-ZFL-03                          | Nov. 13, 2013   | Nov. 12, 2014    |
| Trilog Broadband Antenna<br>SCHWARZBECK | VULB 9168                | 9168-360                            | Feb. 26, 2014   | Feb. 25, 2015    |
| RF Cable                                | NA                       | CHGCAB_001                          | Oct. 05, 2013   | Oct. 04, 2014    |
| Spectrum Analyzer<br>R&S                | FSV40                    | 100964                              | July 05, 2014   | July 04, 2015    |
| Horn_Antenna<br>AISI                    | AIH.8018                 | 0000320091110                       | Nov. 18, 2013   | Nov. 17, 2014    |
| Pre-Amplifier<br>Agilent                | 8449B                    | 3008A02578                          | June 24, 2014   | June 23, 2015    |
| RF Cable                                | NA                       | RF104-201<br>RF104-203<br>RF104-204 | Dec. 12, 2013   | Dec. 11, 2014    |
| Pre-Amplifier<br>SPACEK LABS            | SLKKa-48-6               | 9K16                                | Nov. 13, 2013   | Nov. 12, 2014    |
| Horn_Antenna<br>SCHWARZBECK             | BBHA 9170                | 9170-424                            | Oct. 08, 2013   | Oct. 07, 2014    |
| Software                                | ADT_Radiated<br>_V8.7.07 | NA                                  | NA              | NA               |
| Antenna Tower & Turn Table<br>CT        | NA                       | NA                                  | NA              | NA               |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Tested Date: Sep. 18 to 19, 2014

### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

### 4.2.4 DEVIATION FROM TEST STANDARD


No deviation

## 4.2.5 TEST SETUP

### <Frequency Range below 1GHz>



### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

## 4.2.7 TEST RESULTS

### BELOW 1GHz WORST-CASE DATA

#### 802.11n (HT20)

|                 |              |                      |                 |
|-----------------|--------------|----------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 108.81         | 28.8 QP                       | 43.5              | -14.7          | 2.00 H                   | 87                         | 45.28                  | -16.45                         |
| 2                                                   | 125.01         | 31.2 QP                       | 43.5              | -12.4          | 2.00 H                   | 274                        | 46.07                  | -14.92                         |
| 3                                                   | 250.00         | 32.9 QP                       | 46.0              | -13.2          | 1.00 H                   | 299                        | 47.17                  | -14.32                         |
| 4                                                   | 500.01         | 34.5 QP                       | 46.0              | -11.6          | 1.50 H                   | 243                        | 41.81                  | -7.36                          |
| 5                                                   | 625.00         | 40.0 QP                       | 46.0              | -6.0           | 1.00 H                   | 252                        | 44.45                  | -4.41                          |
| 6                                                   | 651.96         | 34.0 QP                       | 46.0              | -12.0          | 1.00 H                   | 216                        | 38.06                  | -4.08                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 37.57          | 34.8 QP                       | 40.0              | -5.2           | 1.00 V                   | 131                        | 48.83                  | -14.00                         |
| 2                                                   | 98.48          | 25.9 QP                       | 43.5              | -17.6          | 1.50 V                   | 312                        | 44.10                  | -18.20                         |
| 3                                                   | 380.51         | 35.3 QP                       | 46.0              | -10.7          | 1.00 V                   | 350                        | 45.39                  | -10.09                         |
| 4                                                   | 390.70         | 31.7 QP                       | 46.0              | -14.3          | 1.00 V                   | 100                        | 41.56                  | -9.90                          |
| 5                                                   | 500.01         | 34.1 QP                       | 46.0              | -11.9          | 1.00 V                   | 243                        | 41.46                  | -7.36                          |
| 6                                                   | 628.64         | 34.3 QP                       | 46.0              | -11.8          | 1.00 V                   | 286                        | 38.61                  | -4.36                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



A D T

## ABOVE 1GHz DATA

## 802.11b

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2412.00       | 114.9 PK                      |                   |                | 1.41 H                   | 247                        | 117.27                 | -2.37                          |
| 2                                                   | *2412.00       | 111.9 AV                      |                   |                | 1.41 H                   | 247                        | 114.27                 | -2.37                          |
| 3                                                   | 2491.00        | 59.3 PK                       | 74.0              | -14.7          | 1.36 H                   | 244                        | 61.31                  | -2.01                          |
| 4                                                   | 2491.00        | 53.5 AV                       | 54.0              | -0.5           | 1.36 H                   | 244                        | 55.51                  | -2.01                          |
| 5                                                   | 4824.00        | 47.7 PK                       | 74.0              | -26.3          | 1.09 H                   | 273                        | 41.99                  | 5.71                           |
| 6                                                   | 4824.00        | 39.8 AV                       | 54.0              | -14.2          | 1.09 H                   | 273                        | 34.09                  | 5.71                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2412.00       | 113.5 PK                      |                   |                | 1.10 V                   | 270                        | 115.87                 | -2.37                          |
| 2                                                   | *2412.00       | 111.1 AV                      |                   |                | 1.10 V                   | 270                        | 113.47                 | -2.37                          |
| 3                                                   | 2491.00        | 55.3 PK                       | 74.0              | -18.7          | 1.79 V                   | 203                        | 57.31                  | -2.01                          |
| 4                                                   | 2491.00        | 49.2 AV                       | 54.0              | -4.8           | 1.79 V                   | 203                        | 51.21                  | -2.01                          |
| 5                                                   | 4824.00        | 49.2 PK                       | 74.0              | -24.8          | 1.02 V                   | 263                        | 43.49                  | 5.71                           |
| 6                                                   | 4824.00        | 43.3 AV                       | 54.0              | -10.7          | 1.02 V                   | 263                        | 37.59                  | 5.71                           |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2355.00        | 56.5 PK                       | 74.0              | -17.5          | 1.23 H                   | 138                        | 59.13                  | -2.63                          |
| 2                                                   | 2355.00        | 49.5 AV                       | 54.0              | -4.5           | 1.23 H                   | 138                        | 52.13                  | -2.63                          |
| 3                                                   | *2437.00       | 118.7 PK                      |                   |                | 1.42 H                   | 244                        | 120.95                 | -2.25                          |
| 4                                                   | *2437.00       | 115.8 AV                      |                   |                | 1.42 H                   | 244                        | 118.05                 | -2.25                          |
| 5                                                   | 4874.00        | 48.1 PK                       | 74.0              | -25.9          | 1.12 H                   | 279                        | 42.20                  | 5.90                           |
| 6                                                   | 4874.00        | 40.3 AV                       | 54.0              | -13.7          | 1.12 H                   | 279                        | 34.40                  | 5.90                           |
| 7                                                   | 7311.00        | 57.9 PK                       | 74.0              | -16.1          | 1.16 H                   | 62                         | 44.73                  | 13.17                          |
| 8                                                   | 7311.00        | 52.0 AV                       | 54.0              | -2.0           | 1.16 H                   | 62                         | 38.83                  | 13.17                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2355.00        | 56.2 PK                       | 74.0              | -17.8          | 1.15 V                   | 270                        | 58.83                  | -2.63                          |
| 2                                                   | 2355.00        | 49.4 AV                       | 54.0              | -4.6           | 1.15 V                   | 270                        | 52.03                  | -2.63                          |
| 3                                                   | *2437.00       | 115.0 PK                      |                   |                | 1.37 V                   | 274                        | 117.25                 | -2.25                          |
| 4                                                   | *2437.00       | 112.0 AV                      |                   |                | 1.37 V                   | 274                        | 114.25                 | -2.25                          |
| 5                                                   | 4874.00        | 49.2 PK                       | 74.0              | -24.8          | 1.00 V                   | 259                        | 43.30                  | 5.90                           |
| 6                                                   | 4874.00        | 43.0 AV                       | 54.0              | -11.0          | 1.00 V                   | 259                        | 37.10                  | 5.90                           |
| 7                                                   | 7311.00        | 59.3 PK                       | 74.0              | -14.7          | 1.05 V                   | 267                        | 46.13                  | 13.17                          |
| 8                                                   | 7311.00        | 53.5 AV                       | 54.0              | -0.5           | 1.05 V                   | 267                        | 40.33                  | 13.17                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2381.00        | 59.6 PK                       | 74.0              | -14.4          | 1.23 H                   | 136                        | 62.10                  | -2.50                          |
| 2   | 2381.00        | 53.8 AV                       | 54.0              | -0.2           | 1.23 H                   | 136                        | 56.30                  | -2.50                          |
| 3   | *2462.00       | 115.5 PK                      |                   |                | 1.16 H                   | 90                         | 117.64                 | -2.14                          |
| 4   | *2462.00       | 112.6 AV                      |                   |                | 1.16 H                   | 90                         | 114.74                 | -2.14                          |
| 5   | 4924.00        | 47.0 PK                       | 74.0              | -27.0          | 1.22 H                   | 106                        | 40.89                  | 6.11                           |
| 6   | 4924.00        | 38.1 AV                       | 54.0              | -15.9          | 1.22 H                   | 106                        | 31.99                  | 6.11                           |
| 7   | 7386.00        | 54.4 PK                       | 74.0              | -19.6          | 1.12 H                   | 66                         | 41.22                  | 13.18                          |
| 8   | 7386.00        | 48.5 AV                       | 54.0              | -5.5           | 1.12 H                   | 66                         | 35.32                  | 13.18                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2381.00        | 56.5 PK                       | 74.0              | -17.5          | 1.00 V                   | 274                        | 59.00                  | -2.50                          |
| 2   | 2381.00        | 51.9 AV                       | 54.0              | -2.1           | 1.00 V                   | 274                        | 54.40                  | -2.50                          |
| 3   | *2462.00       | 110.8 PK                      |                   |                | 1.34 V                   | 88                         | 112.94                 | -2.14                          |
| 4   | *2462.00       | 108.3 AV                      |                   |                | 1.34 V                   | 88                         | 110.44                 | -2.14                          |
| 5   | 4924.00        | 48.9 PK                       | 74.0              | -25.1          | 1.02 V                   | 271                        | 42.79                  | 6.11                           |
| 6   | 4924.00        | 42.8 AV                       | 54.0              | -11.2          | 1.02 V                   | 271                        | 36.69                  | 6.11                           |
| 7   | 7386.00        | 55.9 PK                       | 74.0              | -18.1          | 1.07 V                   | 268                        | 42.72                  | 13.18                          |
| 8   | 7386.00        | 50.2 AV                       | 54.0              | -3.8           | 1.07 V                   | 268                        | 37.02                  | 13.18                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

# 802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 73.7 PK                       | 74.0              | -0.3           | 1.42 H                   | 243                        | 76.17                  | -2.47                          |
| 2                                                   | 2390.00        | 52.2 AV                       | 54.0              | -1.8           | 1.42 H                   | 243                        | 54.67                  | -2.47                          |
| 3                                                   | *2412.00       | 115.7 PK                      |                   |                | 1.42 H                   | 243                        | 118.07                 | -2.37                          |
| 4                                                   | *2412.00       | 105.4 AV                      |                   |                | 1.42 H                   | 243                        | 107.77                 | -2.37                          |
| 5                                                   | 2485.60        | 60.7 PK                       | 74.0              | -13.3          | 1.16 H                   | 145                        | 62.72                  | -2.02                          |
| 6                                                   | 2485.60        | 50.1 AV                       | 54.0              | -3.9           | 1.16 H                   | 145                        | 52.12                  | -2.02                          |
| 7                                                   | 4824.00        | 46.9 PK                       | 74.0              | -27.1          | 1.17 H                   | 90                         | 41.19                  | 5.71                           |
| 8                                                   | 4824.00        | 38.1 AV                       | 54.0              | -15.9          | 1.17 H                   | 90                         | 32.39                  | 5.71                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.5 PK                       | 74.0              | -6.5           | 1.30 V                   | 90                         | 69.97                  | -2.47                          |
| 2                                                   | 2390.00        | 47.9 AV                       | 54.0              | -6.1           | 1.30 V                   | 90                         | 50.37                  | -2.47                          |
| 3                                                   | *2412.00       | 111.0 PK                      |                   |                | 1.30 V                   | 90                         | 113.37                 | -2.37                          |
| 4                                                   | *2412.00       | 101.1 AV                      |                   |                | 1.30 V                   | 90                         | 103.47                 | -2.37                          |
| 5                                                   | 2485.60        | 56.5 PK                       | 74.0              | -17.5          | 1.18 V                   | 270                        | 58.52                  | -2.02                          |
| 6                                                   | 2485.60        | 49.6 AV                       | 54.0              | -4.4           | 1.18 V                   | 270                        | 51.62                  | -2.02                          |
| 7                                                   | 4824.00        | 47.1 PK                       | 74.0              | -26.9          | 1.03 V                   | 277                        | 41.39                  | 5.71                           |
| 8                                                   | 4824.00        | 38.8 AV                       | 54.0              | -15.2          | 1.03 V                   | 277                        | 33.09                  | 5.71                           |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2388.10        | 59.7 PK                       | 74.0              | -14.3          | 1.39 H                   | 242                        | 62.18                  | -2.48                          |
| 2   | 2388.10        | 43.8 AV                       | 54.0              | -10.2          | 1.39 H                   | 242                        | 46.28                  | -2.48                          |
| 3   | *2437.00       | 120.8 PK                      |                   |                | 1.39 H                   | 242                        | 123.05                 | -2.25                          |
| 4   | *2437.00       | 111.4 AV                      |                   |                | 1.39 H                   | 242                        | 113.65                 | -2.25                          |
| 5   | 2484.50        | 67.2 PK                       | 74.0              | -6.8           | 1.39 H                   | 242                        | 69.22                  | -2.02                          |
| 6   | 2484.50        | 50.3 AV                       | 54.0              | -3.7           | 1.39 H                   | 242                        | 52.32                  | -2.02                          |
| 7   | 4874.00        | 47.1 PK                       | 74.0              | -26.9          | 1.21 H                   | 88                         | 41.20                  | 5.90                           |
| 8   | 4874.00        | 38.1 AV                       | 54.0              | -15.9          | 1.21 H                   | 88                         | 32.20                  | 5.90                           |
| 9   | 7311.00        | 60.4 PK                       | 74.0              | -13.6          | 1.11 H                   | 74                         | 47.23                  | 13.17                          |
| 10  | 7311.00        | 48.5 AV                       | 54.0              | -5.5           | 1.11 H                   | 74                         | 35.33                  | 13.17                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2388.10        | 58.4 PK                       | 74.0              | -15.6          | 1.26 V                   | 76                         | 60.88                  | -2.48                          |
| 2   | 2388.10        | 42.1 AV                       | 54.0              | -11.9          | 1.26 V                   | 76                         | 44.58                  | -2.48                          |
| 3   | *2437.00       | 116.2 PK                      |                   |                | 1.26 V                   | 76                         | 118.45                 | -2.25                          |
| 4   | *2437.00       | 107.1 AV                      |                   |                | 1.26 V                   | 76                         | 109.35                 | -2.25                          |
| 5   | 2484.50        | 56.5 PK                       | 74.0              | -17.5          | 1.15 V                   | 274                        | 58.52                  | -2.02                          |
| 6   | 2484.50        | 49.8 AV                       | 54.0              | -4.2           | 1.15 V                   | 274                        | 51.82                  | -2.02                          |
| 7   | 4874.00        | 47.0 PK                       | 74.0              | -27.0          | 1.01 V                   | 263                        | 41.10                  | 5.90                           |
| 8   | 4874.00        | 38.6 AV                       | 54.0              | -15.4          | 1.01 V                   | 263                        | 32.70                  | 5.90                           |
| 9   | 7311.00        | 60.5 PK                       | 74.0              | -13.5          | 1.07 V                   | 240                        | 47.33                  | 13.17                          |
| 10  | 7311.00        | 48.6 AV                       | 54.0              | -5.4           | 1.07 V                   | 240                        | 35.43                  | 13.17                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2385.20        | 59.8 PK                       | 74.0              | -14.2          | 1.18 H                   | 151                        | 62.29                  | -2.49                          |
| 2                                                   | 2385.20        | 49.0 AV                       | 54.0              | -5.0           | 1.18 H                   | 151                        | 51.49                  | -2.49                          |
| 3                                                   | *2462.00       | 116.8 PK                      |                   |                | 1.35 H                   | 243                        | 118.94                 | -2.14                          |
| 4                                                   | *2462.00       | 107.0 AV                      |                   |                | 1.35 H                   | 243                        | 109.14                 | -2.14                          |
| 5                                                   | 2483.50        | 73.2 PK                       | 74.0              | -0.8           | 1.35 H                   | 243                        | 75.23                  | -2.03                          |
| 6                                                   | 2483.50        | 51.6 AV                       | 54.0              | -2.4           | 1.35 H                   | 243                        | 53.63                  | -2.03                          |
| 7                                                   | 4924.00        | 47.2 PK                       | 74.0              | -26.8          | 1.21 H                   | 97                         | 41.09                  | 6.11                           |
| 8                                                   | 4924.00        | 37.9 AV                       | 54.0              | -16.1          | 1.21 H                   | 97                         | 31.79                  | 6.11                           |
| 9                                                   | 7386.00        | 58.1 PK                       | 74.0              | -15.9          | 1.12 H                   | 86                         | 44.92                  | 13.18                          |
| 10                                                  | 7386.00        | 46.9 AV                       | 54.0              | -7.1           | 1.12 H                   | 86                         | 33.72                  | 13.18                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2385.20        | 56.8 PK                       | 74.0              | -17.2          | 1.16 V                   | 285                        | 59.29                  | -2.49                          |
| 2                                                   | 2385.20        | 49.8 AV                       | 54.0              | -4.2           | 1.16 V                   | 285                        | 52.29                  | -2.49                          |
| 3                                                   | *2462.00       | 112.2 PK                      |                   |                | 1.31 V                   | 70                         | 114.34                 | -2.14                          |
| 4                                                   | *2462.00       | 102.7 AV                      |                   |                | 1.31 V                   | 70                         | 104.84                 | -2.14                          |
| 5                                                   | 2483.50        | 67.6 PK                       | 74.0              | -6.4           | 1.31 V                   | 70                         | 69.63                  | -2.03                          |
| 6                                                   | 2483.50        | 47.9 AV                       | 54.0              | -6.1           | 1.31 V                   | 70                         | 49.93                  | -2.03                          |
| 7                                                   | 4924.00        | 46.3 PK                       | 74.0              | -27.7          | 1.06 V                   | 259                        | 40.19                  | 6.11                           |
| 8                                                   | 4924.00        | 38.1 AV                       | 54.0              | -15.9          | 1.06 V                   | 259                        | 31.99                  | 6.11                           |
| 9                                                   | 7386.00        | 58.2 PK                       | 74.0              | -15.8          | 1.13 V                   | 225                        | 45.02                  | 13.18                          |
| 10                                                  | 7386.00        | 47.1 AV                       | 54.0              | -6.9           | 1.13 V                   | 225                        | 33.92                  | 13.18                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

## 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 73.2 PK                       | 74.0              | -0.8           | 1.44 H                   | 156                        | 75.67                  | -2.47                          |
| 2                                                   | 2390.00        | 52.5 AV                       | 54.0              | -1.5           | 1.44 H                   | 156                        | 54.97                  | -2.47                          |
| 3                                                   | *2412.00       | 116.0 PK                      |                   |                | 1.44 H                   | 156                        | 118.37                 | -2.37                          |
| 4                                                   | *2412.00       | 104.8 AV                      |                   |                | 1.44 H                   | 156                        | 107.17                 | -2.37                          |
| 5                                                   | 2483.70        | 64.4 PK                       | 74.0              | -9.6           | 1.19 H                   | 162                        | 66.43                  | -2.03                          |
| 6                                                   | 2483.70        | 50.0 AV                       | 54.0              | -4.0           | 1.19 H                   | 162                        | 52.03                  | -2.03                          |
| 7                                                   | 4824.00        | 46.6 PK                       | 74.0              | -27.4          | 1.18 H                   | 91                         | 40.89                  | 5.71                           |
| 8                                                   | 4824.00        | 37.9 AV                       | 54.0              | -16.1          | 1.18 H                   | 91                         | 32.19                  | 5.71                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.9 PK                       | 74.0              | -6.1           | 1.26 V                   | 85                         | 70.37                  | -2.47                          |
| 2                                                   | 2390.00        | 48.1 AV                       | 54.0              | -5.9           | 1.26 V                   | 85                         | 50.57                  | -2.47                          |
| 3                                                   | *2412.00       | 111.4 PK                      |                   |                | 1.33 V                   | 60                         | 113.77                 | -2.37                          |
| 4                                                   | *2412.00       | 100.4 AV                      |                   |                | 1.33 V                   | 60                         | 102.77                 | -2.37                          |
| 5                                                   | 2483.70        | 56.8 PK                       | 74.0              | -17.2          | 1.14 V                   | 300                        | 58.83                  | -2.03                          |
| 6                                                   | 2483.70        | 48.7 AV                       | 54.0              | -5.3           | 1.14 V                   | 300                        | 50.73                  | -2.03                          |
| 7                                                   | 4824.00        | 47.6 PK                       | 74.0              | -26.4          | 1.08 V                   | 291                        | 41.89                  | 5.71                           |
| 8                                                   | 4824.00        | 39.1 AV                       | 54.0              | -14.9          | 1.08 V                   | 291                        | 33.39                  | 5.71                           |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 64.0 PK                       | 74.0              | -10.0          | 1.23 H                   | 159                        | 66.47                  | -2.47                          |
| 2   | 2390.00        | 48.1 AV                       | 54.0              | -5.9           | 1.23 H                   | 159                        | 50.57                  | -2.47                          |
| 3   | *2437.00       | 121.0 PK                      |                   |                | 1.23 H                   | 159                        | 123.25                 | -2.25                          |
| 4   | *2437.00       | 111.1 AV                      |                   |                | 1.23 H                   | 159                        | 113.35                 | -2.25                          |
| 5   | 2483.50        | 65.3 PK                       | 74.0              | -8.7           | 1.23 H                   | 159                        | 67.33                  | -2.03                          |
| 6   | 2483.50        | 49.1 AV                       | 54.0              | -4.9           | 1.23 H                   | 159                        | 51.13                  | -2.03                          |
| 7   | 4874.00        | 46.1 PK                       | 74.0              | -27.9          | 1.23 H                   | 85                         | 40.20                  | 5.90                           |
| 8   | 4874.00        | 37.5 AV                       | 54.0              | -16.5          | 1.23 H                   | 85                         | 31.60                  | 5.90                           |
| 9   | 7311.00        | 53.8 PK                       | 74.0              | -20.2          | 1.14 H                   | 70                         | 40.63                  | 13.17                          |
| 10  | 7311.00        | 48.0 AV                       | 54.0              | -6.0           | 1.14 H                   | 70                         | 34.83                  | 13.17                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 56.4 PK                       | 74.0              | -17.6          | 1.37 V                   | 50                         | 58.87                  | -2.47                          |
| 2   | 2390.00        | 46.4 AV                       | 54.0              | -7.6           | 1.37 V                   | 50                         | 48.87                  | -2.47                          |
| 3   | *2437.00       | 116.4 PK                      |                   |                | 1.37 V                   | 50                         | 118.65                 | -2.25                          |
| 4   | *2437.00       | 106.7 AV                      |                   |                | 1.37 V                   | 50                         | 108.95                 | -2.25                          |
| 5   | 2483.50        | 60.0 PK                       | 74.0              | -14.0          | 1.37 V                   | 50                         | 62.03                  | -2.03                          |
| 6   | 2483.50        | 44.7 AV                       | 54.0              | -9.3           | 1.37 V                   | 50                         | 46.73                  | -2.03                          |
| 7   | 4874.00        | 47.0 PK                       | 74.0              | -27.0          | 1.04 V                   | 299                        | 41.10                  | 5.90                           |
| 8   | 4874.00        | 38.8 AV                       | 54.0              | -15.2          | 1.04 V                   | 299                        | 32.90                  | 5.90                           |
| 9   | 7311.00        | 53.6 PK                       | 74.0              | -20.4          | 1.04 V                   | 263                        | 40.43                  | 13.17                          |
| 10  | 7311.00        | 47.9 AV                       | 54.0              | -6.1           | 1.04 V                   | 263                        | 34.73                  | 13.17                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2462.00       | 116.4 PK                      |                   |                | 1.69 H                   | 171                        | 118.54                 | -2.14                          |
| 2   | *2462.00       | 105.9 AV                      |                   |                | 1.69 H                   | 171                        | 108.04                 | -2.14                          |
| 3   | 2485.20        | 73.4 PK                       | 74.0              | -0.6           | 1.69 H                   | 171                        | 75.42                  | -2.02                          |
| 4   | 2485.20        | 51.9 AV                       | 54.0              | -2.1           | 1.69 H                   | 171                        | 53.92                  | -2.02                          |
| 5   | 4924.00        | 45.9 PK                       | 74.0              | -28.1          | 1.19 H                   | 72                         | 39.79                  | 6.11                           |
| 6   | 4924.00        | 37.5 AV                       | 54.0              | -16.5          | 1.19 H                   | 72                         | 31.39                  | 6.11                           |
| 7   | 7386.00        | 53.6 PK                       | 74.0              | -20.4          | 1.14 H                   | 80                         | 40.42                  | 13.18                          |
| 8   | 7386.00        | 47.7 AV                       | 54.0              | -6.3           | 1.14 H                   | 80                         | 34.52                  | 13.18                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2462.00       | 111.8 PK                      |                   |                | 1.36 V                   | 35                         | 113.94                 | -2.14                          |
| 2   | *2462.00       | 101.5 AV                      |                   |                | 1.36 V                   | 35                         | 103.64                 | -2.14                          |
| 3   | 2485.20        | 67.8 PK                       | 74.0              | -6.2           | 1.36 V                   | 35                         | 69.82                  | -2.02                          |
| 4   | 2485.20        | 48.2 AV                       | 54.0              | -5.8           | 1.36 V                   | 35                         | 50.22                  | -2.02                          |
| 5   | 4924.00        | 45.6 PK                       | 74.0              | -28.4          | 1.06 V                   | 304                        | 39.49                  | 6.11                           |
| 6   | 4924.00        | 37.7 AV                       | 54.0              | -16.3          | 1.06 V                   | 304                        | 31.59                  | 6.11                           |
| 7   | 7386.00        | 53.7 PK                       | 74.0              | -20.3          | 1.04 V                   | 247                        | 40.52                  | 13.18                          |
| 8   | 7386.00        | 47.6 AV                       | 54.0              | -6.4           | 1.04 V                   | 247                        | 34.42                  | 13.18                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

## 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 72.4 PK                       | 74.0              | -1.6           | 1.23 H                   | 144                        | 74.87                  | -2.47                          |
| 2                                                   | 2390.00        | 53.5 AV                       | 54.0              | -0.5           | 1.23 H                   | 144                        | 55.97                  | -2.47                          |
| 3                                                   | *2422.00       | 111.3 PK                      |                   |                | 1.23 H                   | 144                        | 113.62                 | -2.32                          |
| 4                                                   | *2422.00       | 100.9 AV                      |                   |                | 1.23 H                   | 144                        | 103.22                 | -2.32                          |
| 5                                                   | 4844.00        | 46.3 PK                       | 74.0              | -27.7          | 1.16 H                   | 82                         | 40.52                  | 5.78                           |
| 6                                                   | 4844.00        | 37.7 AV                       | 54.0              | -16.3          | 1.16 H                   | 82                         | 31.92                  | 5.78                           |
| 7                                                   | 7266.00        | 53.2 PK                       | 74.0              | -20.8          | 1.20 H                   | 72                         | 40.00                  | 13.20                          |
| 8                                                   | 7266.00        | 47.3 AV                       | 54.0              | -6.7           | 1.20 H                   | 72                         | 34.10                  | 13.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.7 PK                       | 74.0              | -6.3           | 1.42 V                   | 30                         | 70.17                  | -2.47                          |
| 2                                                   | 2390.00        | 48.3 AV                       | 54.0              | -5.7           | 1.42 V                   | 30                         | 50.77                  | -2.47                          |
| 3                                                   | *2422.00       | 106.7 PK                      |                   |                | 1.42 V                   | 30                         | 109.02                 | -2.32                          |
| 4                                                   | *2422.00       | 96.5 AV                       |                   |                | 1.42 V                   | 30                         | 98.82                  | -2.32                          |
| 5                                                   | 4844.00        | 47.1 PK                       | 74.0              | -26.9          | 1.01 V                   | 312                        | 41.32                  | 5.78                           |
| 6                                                   | 4844.00        | 38.9 AV                       | 54.0              | -15.1          | 1.01 V                   | 312                        | 33.12                  | 5.78                           |
| 7                                                   | 7266.00        | 53.4 PK                       | 74.0              | -20.6          | 1.07 V                   | 260                        | 40.20                  | 13.20                          |
| 8                                                   | 7266.00        | 47.8 AV                       | 54.0              | -6.2           | 1.07 V                   | 260                        | 34.60                  | 13.20                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 62.2 PK                       | 74.0              | -11.8          | 1.20 H                   | 152                        | 64.67                  | -2.47                          |
| 2                                                   | 2390.00        | 46.8 AV                       | 54.0              | -7.2           | 1.20 H                   | 152                        | 49.27                  | -2.47                          |
| 3                                                   | *2437.00       | 113.7 PK                      |                   |                | 1.20 H                   | 152                        | 115.95                 | -2.25                          |
| 4                                                   | *2437.00       | 103.1 AV                      |                   |                | 1.20 H                   | 152                        | 105.35                 | -2.25                          |
| 5                                                   | 2485.40        | 73.2 PK                       | 74.0              | -0.8           | 1.20 H                   | 152                        | 75.22                  | -2.02                          |
| 6                                                   | 2485.40        | 51.2 AV                       | 54.0              | -2.8           | 1.20 H                   | 152                        | 53.22                  | -2.02                          |
| 7                                                   | 4874.00        | 46.0 PK                       | 74.0              | -28.0          | 1.22 H                   | 67                         | 40.10                  | 5.90                           |
| 8                                                   | 4874.00        | 37.5 AV                       | 54.0              | -16.5          | 1.22 H                   | 67                         | 31.60                  | 5.90                           |
| 9                                                   | 7311.00        | 53.6 PK                       | 74.0              | -20.4          | 1.09 H                   | 66                         | 40.43                  | 13.17                          |
| 10                                                  | 7311.00        | 47.5 AV                       | 54.0              | -6.5           | 1.09 H                   | 66                         | 34.33                  | 13.17                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2390.00        | 61.2 PK                       | 74.0              | -12.8          | 1.36 V                   | 25                         | 63.67                  | -2.47                          |
| 2                                                 | 2390.00        | 44.3 AV                       | 54.0              | -9.7           | 1.36 V                   | 25                         | 46.77                  | -2.47                          |
| 3                                                 | *2437.00       | 109.1 PK                      |                   |                | 1.36 V                   | 25                         | 111.35                 | -2.25                          |
| 4                                                 | *2437.00       | 98.7 AV                       |                   |                | 1.36 V                   | 25                         | 100.95                 | -2.25                          |
| 5                                                 | 2485.40        | 68.0 PK                       | 74.0              | -6.0           | 1.36 V                   | 25                         | 70.02                  | -2.02                          |
| 6                                                 | 2485.40        | 48.7 AV                       | 54.0              | -5.3           | 1.36 V                   | 25                         | 50.72                  | -2.02                          |
| 7                                                 | 4874.00        | 46.8 PK                       | 74.0              | -27.2          | 1.03 V                   | 327                        | 40.90                  | 5.90                           |
| 8                                                 | 4874.00        | 38.8 AV                       | 54.0              | -15.2          | 1.03 V                   | 327                        | 32.90                  | 5.90                           |
| 9                                                 | 7311.00        | 53.5 PK                       | 74.0              | -20.5          | 1.10 V                   | 276                        | 40.33                  | 13.17                          |
| 10                                                | 7311.00        | 47.6 AV                       | 54.0              | -6.4           | 1.10 V                   | 276                        | 34.43                  | 13.17                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



A D T

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 110.8 PK                      |                   |                | 1.20 H                   | 145                        | 112.98                 | -2.18                          |
| 2                                                   | *2452.00       | 100.4 AV                      |                   |                | 1.20 H                   | 145                        | 102.58                 | -2.18                          |
| 3                                                   | 2485.80        | 70.0 PK                       | 74.0              | -4.0           | 1.20 H                   | 145                        | 72.02                  | -2.02                          |
| 4                                                   | 2485.80        | 53.6 AV                       | 54.0              | -0.4           | 1.20 H                   | 145                        | 55.62                  | -2.02                          |
| 5                                                   | 4904.00        | 46.3 PK                       | 74.0              | -27.7          | 1.19 H                   | 73                         | 40.28                  | 6.02                           |
| 6                                                   | 4904.00        | 37.6 AV                       | 54.0              | -16.4          | 1.19 H                   | 73                         | 31.58                  | 6.02                           |
| 7                                                   | 7356.00        | 54.1 PK                       | 74.0              | -19.9          | 1.05 H                   | 69                         | 40.92                  | 13.18                          |
| 8                                                   | 7356.00        | 47.9 AV                       | 54.0              | -6.1           | 1.05 H                   | 69                         | 34.72                  | 13.18                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 106.2 PK                      |                   |                | 1.41 V                   | 23                         | 108.38                 | -2.18                          |
| 2                                                   | *2452.00       | 96.1 AV                       |                   |                | 1.41 V                   | 23                         | 98.28                  | -2.18                          |
| 3                                                   | 2485.80        | 68.0 PK                       | 74.0              | -6.0           | 1.41 V                   | 23                         | 70.02                  | -2.02                          |
| 4                                                   | 2485.80        | 48.5 AV                       | 54.0              | -5.5           | 1.41 V                   | 23                         | 50.52                  | -2.02                          |
| 5                                                   | 4904.00        | 47.0 PK                       | 74.0              | -27.0          | 1.06 V                   | 336                        | 40.98                  | 6.02                           |
| 6                                                   | 4904.00        | 38.9 AV                       | 54.0              | -15.1          | 1.06 V                   | 336                        | 32.88                  | 6.02                           |
| 7                                                   | 7356.00        | 54.3 PK                       | 74.0              | -19.7          | 1.08 V                   | 268                        | 41.12                  | 13.18                          |
| 8                                                   | 7356.00        | 47.9 AV                       | 54.0              | -6.1           | 1.08 V                   | 268                        | 34.72                  | 13.18                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|----------------------------|-----------|------------|-----------------|------------------|
| SPECTRUM ANALYZER R&S      | FSV 40    | 100964     | July 05, 2014   | July 04, 2015    |

#### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 23, 2014


#### 4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.3.7 TEST RESULTS (MODE 1)

#### 802.11b

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412                    | 8.60                | 9.04    | 9.06    | 0.5                 | PASS        |
| 6       | 2437                    | 9.07                | 8.61    | 9.08    | 0.5                 | PASS        |
| 11      | 2462                    | 8.14                | 8.58    | 8.61    | 0.5                 | PASS        |

#### 802.11g

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412                    | 16.39               | 16.40   | 16.43   | 0.5                 | PASS        |
| 6       | 2437                    | 16.39               | 16.40   | 15.51   | 0.5                 | PASS        |
| 11      | 2462                    | 16.41               | 16.40   | 16.42   | 0.5                 | PASS        |

#### 802.11n (HT20)


| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412                    | 17.64               | 17.68   | 17.67   | 0.5                 | PASS        |
| 6       | 2437                    | 17.70               | 17.65   | 16.24   | 0.5                 | PASS        |
| 11      | 2462                    | 17.74               | 17.66   | 17.65   | 0.5                 | PASS        |

#### 802.11n (HT40)


| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 3       | 2422                    | 36.47               | 36.42   | 36.44   | 0.5                 | PASS        |
| 6       | 2437                    | 36.33               | 36.48   | 36.43   | 0.5                 | PASS        |
| 9       | 2452                    | 36.52               | 36.05   | 36.16   | 0.5                 | PASS        |

# SPECTRUM PLOT OF WORST VALUE


## 802.11b / Chain(0) : CH11




## 802.11g / Chain(2) : CH6



## 802.11n (HT20) / Chain(2) : CH6



## 802.11n (HT40) / Chain(1) : CH9




### 4.3.8 TEST RESULTS (MODE 2)

#### 802.11n (HT20)

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412                    | 17.64               | 17.68   | 17.67   | 0.5                 | PASS        |
| 6       | 2437                    | 17.62               | 17.65   | 17.59   | 0.5                 | PASS        |
| 11      | 2462                    | 17.74               | 17.66   | 17.65   | 0.5                 | PASS        |

#### 802.11n (HT40)

| CHANNEL | CHANNEL FREQUENCY (MHz) | 6dB BANDWIDTH (MHz) |         |         | MINIMUM LIMIT (MHz) | PASS / FAIL |
|---------|-------------------------|---------------------|---------|---------|---------------------|-------------|
|         |                         | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 3       | 2422                    | 36.47               | 36.42   | 36.44   | 0.5                 | PASS        |
| 6       | 2437                    | 36.33               | 36.48   | 36.43   | 0.5                 | PASS        |
| 9       | 2452                    | 36.52               | 36.05   | 36.16   | 0.5                 | PASS        |



## 4.4 CONDUCTED OUTPUT POWER MEASUREMENT

### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|----------------------------|-----------|------------|-----------------|------------------|
| Power meter<br>Anritsu     | ML2495A   | 1014008    | Apr. 30, 2014   | Apr. 29, 2015    |
| Power sensor<br>Anritsu    | MA2411B   | 0917122    | Apr. 30, 2014   | Apr. 29, 2015    |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 23, 2014


### 4.4.3 TEST PROCEDURES

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the average power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

#### 4.4.7 TEST RESULTS(MODE 1)

##### 802.11b

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 1       | 2412            | 20.98               | 20.86   | 20.81   | 367.717          | 25.66             | 30          | PASS        |
| 6       | 2437            | 24.29               | 24.32   | 24.30   | 808.083          | 29.07             | 30          | PASS        |
| 11      | 2462            | 20.26               | 20.20   | 20.38   | 320.027          | 25.05             | 30          | PASS        |

##### 802.11g

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 1       | 2412            | 20.40               | 20.27   | 20.46   | 327.235          | 25.15             | 30          | PASS        |
| 6       | 2437            | 25.20               | 25.30   | 25.01   | 986.932          | 29.94             | 30          | PASS        |
| 11      | 2462            | 20.38               | 20.43   | 20.37   | 328.445          | 25.16             | 30          | PASS        |

##### 802.11n (HT20)

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 1       | 2412            | 19.10               | 19.03   | 19.39   | 248.162          | 23.95             | 30          | PASS        |
| 6       | 2437            | 25.10               | 25.26   | 25.27   | 995.844          | 29.98             | 30          | PASS        |
| 11      | 2462            | 19.00               | 19.13   | 19.30   | 246.393          | 23.92             | 30          | PASS        |

##### 802.11n (HT40)

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 3       | 2422            | 18.51               | 18.58   | 18.61   | 215.680          | 23.34             | 30          | PASS        |
| 6       | 2437            | 19.21               | 19.27   | 19.39   | 254.792          | 24.06             | 30          | PASS        |
| 9       | 2452            | 16.16               | 16.18   | 16.45   | 126.957          | 21.04             | 30          | PASS        |

#### 4.4.8 TEST RESULTS(MODE 2)

##### 802.11n (HT20)

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 1       | 2412            | 19.10               | 19.03   | 19.39   | 248.162          | 23.95             | 27.35       | PASS        |
| 6       | 2437            | 22.37               | 22.55   | 22.52   | 531.12           | 27.25             | 27.35       | PASS        |
| 11      | 2462            | 19.00               | 19.13   | 19.30   | 246.393          | 23.92             | 27.35       | PASS        |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$  , so the power limit shall be reduced to  $30-(8.65-6) = 27.35\text{dBm}$ .

##### 802.11n (HT40)

| CHANNEL | FREQUENCY (MHz) | AVERAGE POWER (dBm) |         |         | TOTAL POWER (mW) | TOTAL POWER (dBm) | LIMIT (dBm) | PASS / FAIL |
|---------|-----------------|---------------------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                  |                   |             |             |
| 3       | 2422            | 18.51               | 18.58   | 18.61   | 215.68           | 23.34             | 27.35       | PASS        |
| 6       | 2437            | 19.21               | 19.27   | 19.39   | 254.792          | 24.06             | 27.35       | PASS        |
| 9       | 2452            | 16.16               | 16.18   | 16.45   | 126.957          | 21.04             | 27.35       | PASS        |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$  , so the power limit shall be reduced to  $30-(8.65-6) = 27.35\text{dBm}$ .

## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|----------------------------|-----------|------------|-----------------|------------------|
| SPECTRUM ANALYZER R&S      | FSV 40    | 100964     | July 05, 2014   | July 04, 2015    |

#### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 23, 2014


### 4.5.3 TEST PROCEDURE

1. Set the RBW = 10 kHz, VBW =30 kHz, Detector = power averaging (RMS).
2. Ensure that the number of measurement points in the sweep  $\geq 2 \times$  span/RBW
3. Sweep time = auto couple.
4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
5. Use the peak marker function to determine the maximum amplitude level.

### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.5.5 TEST SETUP



### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

## 4.5.7 TEST RESULTS(MODE 1)

### 802.11b

| TX CHAIN | CHANNEL | FREQUENCY (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-----------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412            | -7.00     | 4.77            | -2.23           | 5.35        | PASS       |
|          | 6       | 2437            | -4.57     | 4.77            | 0.20            | 5.35        | PASS       |
|          | 11      | 2462            | -5.68     | 4.77            | -0.91           | 5.35        | PASS       |
| 1        | 1       | 2412            | -6.48     | 4.77            | -1.71           | 5.35        | PASS       |
|          | 6       | 2437            | -3.23     | 4.77            | 1.54            | 5.35        | PASS       |
|          | 11      | 2462            | -5.92     | 4.77            | -1.15           | 5.35        | PASS       |
| 2        | 1       | 2412            | -7.09     | 4.77            | -2.32           | 5.35        | PASS       |
|          | 6       | 2437            | -4.46     | 4.77            | 0.31            | 5.35        | PASS       |
|          | 11      | 2462            | -6.15     | 4.77            | -1.38           | 5.35        | PASS       |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .

### 802.11g

| TX CHAIN | CHANNEL | FREQUENCY (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-----------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412            | -8.53     | 4.77            | -3.76           | 5.35        | PASS       |
|          | 6       | 2437            | -3.79     | 4.77            | 0.98            | 5.35        | PASS       |
|          | 11      | 2462            | -8.33     | 4.77            | -3.56           | 5.35        | PASS       |
| 1        | 1       | 2412            | -8.77     | 4.77            | -4.00           | 5.35        | PASS       |
|          | 6       | 2437            | -3.02     | 4.77            | 1.75            | 5.35        | PASS       |
|          | 11      | 2462            | -8.03     | 4.77            | -3.26           | 5.35        | PASS       |
| 2        | 1       | 2412            | -9.30     | 4.77            | -4.53           | 5.35        | PASS       |
|          | 6       | 2437            | -6.29     | 4.77            | -1.52           | 5.35        | PASS       |
|          | 11      | 2462            | -9.19     | 4.77            | -4.42           | 5.35        | PASS       |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .

### 802.11n (HT20)

| TX CHAIN | CHANNEL | FREQUENCY (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-----------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412            | -10.71    | 4.77            | -5.94           | 5.35        | PASS       |
|          | 6       | 2437            | -4.49     | 4.77            | 0.28            | 5.35        | PASS       |
|          | 11      | 2462            | -10.37    | 4.77            | -5.60           | 5.35        | PASS       |
| 1        | 1       | 2412            | -11.29    | 4.77            | -6.52           | 5.35        | PASS       |
|          | 6       | 2437            | -4.12     | 4.77            | 0.65            | 5.35        | PASS       |
|          | 11      | 2462            | -11.02    | 4.77            | -6.25           | 5.35        | PASS       |
| 2        | 1       | 2412            | -11.92    | 4.77            | -7.15           | 5.35        | PASS       |
|          | 6       | 2437            | -6.03     | 4.77            | -1.26           | 5.35        | PASS       |
|          | 11      | 2462            | -11.54    | 4.77            | -6.77           | 5.35        | PASS       |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .


### 802.11n (HT40)

| TX CHAIN | CHANNEL | FREQ. (MHz) | PSD W/O DUTY FACTOR (dBm) | 10 log (N=3) dB | DUTY FACTOR (dB) | TOTAL PSD WITH DUTY FACTOR (dBm) | LIMIT (dBm) | PASS /FAIL |
|----------|---------|-------------|---------------------------|-----------------|------------------|----------------------------------|-------------|------------|
| 0        | 1       | 2412        | -12.46                    | 4.77            | 0.17             | -7.52                            | 5.35        | PASS       |
|          | 6       | 2437        | -12.84                    | 4.77            | 0.17             | -7.90                            | 5.35        | PASS       |
|          | 11      | 2462        | -15.65                    | 4.77            | 0.17             | -10.71                           | 5.35        | PASS       |
| 1        | 1       | 2412        | -13.16                    | 4.77            | 0.17             | -8.22                            | 5.35        | PASS       |
|          | 6       | 2437        | -12.48                    | 4.77            | 0.17             | -7.54                            | 5.35        | PASS       |
|          | 11      | 2462        | -15.40                    | 4.77            | 0.17             | -10.46                           | 5.35        | PASS       |
| 2        | 1       | 2412        | -14.51                    | 4.77            | 0.17             | -9.57                            | 5.35        | PASS       |
|          | 6       | 2437        | -13.32                    | 4.77            | 0.17             | -8.38                            | 5.35        | PASS       |
|          | 11      | 2462        | -16.17                    | 4.77            | 0.17             | -11.23                           | 5.35        | PASS       |


**NOTE:** 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .  
2. Refer to section 3.4 for duty cycle spectrum plot.

## SPECTRUM PLOT OF WORST VALUE


### 802.11b / Chain(1) : CH6




### 802.11g / Chain(1) : CH6



### 802.11n (HT20) / Chain(1) : CH6



### 802.11n (HT40) / Chain(0) : CH3



## 4.5.8 TEST RESULTS(MODE 2)

### 802.11n (HT20)

| TX CHAIN | CHANNEL | FREQUENCY (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-----------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412            | -10.71    | 4.77            | -5.94           | 5.35        | PASS       |
|          | 6       | 2437            | -9.51     | 4.77            | -4.74           | 5.35        | PASS       |
|          | 11      | 2462            | -10.37    | 4.77            | -5.60           | 5.35        | PASS       |
| 1        | 1       | 2412            | -11.29    | 4.77            | -6.52           | 5.35        | PASS       |
|          | 6       | 2437            | -8.72     | 4.77            | -3.95           | 5.35        | PASS       |
|          | 11      | 2462            | -11.02    | 4.77            | -6.25           | 5.35        | PASS       |
| 2        | 1       | 2412            | -11.92    | 4.77            | -7.15           | 5.35        | PASS       |
|          | 6       | 2437            | -9.71     | 4.77            | -4.94           | 5.35        | PASS       |
|          | 11      | 2462            | -11.54    | 4.77            | -6.77           | 5.35        | PASS       |

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .

### 802.11n (HT40)

| TX CHAIN | CHANNEL | FREQ. (MHz) | PSD W/O DUTY FACTOR (dBm) | 10 log (N=3) dB | DUTY FACTOR (dB) | TOTAL PSD WITH DUTY FACTOR (dBm) | LIMIT (dBm) | PASS /FAIL |
|----------|---------|-------------|---------------------------|-----------------|------------------|----------------------------------|-------------|------------|
| 0        | 1       | 2412        | -12.46                    | 4.77            | 0.17             | -7.52                            | 5.35        | PASS       |
|          | 6       | 2437        | -12.84                    | 4.77            | 0.17             | -7.90                            | 5.35        | PASS       |
|          | 11      | 2462        | -15.65                    | 4.77            | 0.17             | -10.71                           | 5.35        | PASS       |
| 1        | 1       | 2412        | -13.16                    | 4.77            | 0.17             | -8.22                            | 5.35        | PASS       |
|          | 6       | 2437        | -12.48                    | 4.77            | 0.17             | -7.54                            | 5.35        | PASS       |
|          | 11      | 2462        | -15.40                    | 4.77            | 0.17             | -10.46                           | 5.35        | PASS       |
| 2        | 1       | 2412        | -14.51                    | 4.77            | 0.17             | -9.57                            | 5.35        | PASS       |
|          | 6       | 2437        | -13.32                    | 4.77            | 0.17             | -8.38                            | 5.35        | PASS       |
|          | 11      | 2462        | -16.17                    | 4.77            | 0.17             | -11.23                           | 5.35        | PASS       |



**NOTE:** 1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 8.65\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8-(8.65-6) = 5.35\text{dBm}$ .

2. Refer to section 3.4 for duty cycle spectrum plot.

# SPECTRUM PLOT OF WORST VALUE

802.11n (HT20) / Chain(1) : CH6

802.11n (HT40) / Chain(0) : CH3



## 4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|----------------------------|-----------|------------|-----------------|------------------|
| SPECTRUM ANALYZER R&S      | FSV 40    | 100964     | July 05, 2014   | July 04, 2015    |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Sep. 23, 2014

### 4.6.3 TEST PROCEDURE

#### Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


#### Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

#### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.6.5 TEST SETUP



#### 4.6.6 EUT OPERATING CONDITION


Same as Item 4.3.6

#### 4.6.7 TEST RESULTS(MODE 1)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.


802.11b

### Maximum REF




### Chain 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




# Chain 1



## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




## Chain 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge






A D T

802.11g




**Chain 0**


**CH 1**




**CH 6**




**CH 11**



**CH 1 Band edge**




**CH 11 Band edge**




## Chain 1


### CH 1




### CH 6




### CH 11



### CH 1 Band edge



### CH 11 Band edge







A D T

## Chain 2



## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




802.11n(HT20)

### Maximum REF




### Chain 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




## Chain 1


### CH 1




### CH 6




### CH 11



### CH 1 Band edge



### CH 11 Band edge







A D T

## Chain 2


### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




802.11n(HT40)

### Maximum REF




### Chain 0


#### CH 3




#### CH 6




#### CH 9



#### CH 3 Band edge




#### CH 9 Band edge




## Chain 1



### CH 3




### CH 6




### CH 9



### CH 3 Band edge




### CH 9 Band edge




## Chain 2


### CH 1




### CH 6




### CH 11



### CH 1 Band edge



### CH 11 Band edge






A D T

#### 4.6.8 TEST RESULTS(MODE 2)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.


802.11n(HT20)

### Maximum REF




### Chain 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




## Chain 1


### CH 1




### CH 6




### CH 11



### CH 1 Band edge



### CH 11 Band edge







A D T

## Chain 2


### CH 1




### CH 6




### CH 11




### CH 1 Band edge




### CH 11 Band edge



Maximum REF



## CH 3



Ref 31 dBm Alt 20 dB

Offset 21 dB

RBW 100 kHz  
VBW 300 kHz  
SMT 2.5 s

[[1]] MP VIEW

Marker 1 [T1] 1.43 dB  
2.44505 GHz

Marker 2 [T1] -36.88 dB  
1.04657 GHz

Marker 3 [T1] -32.37 dB  
16.93409 GHz

D1 5.31 dBm

D2 -24.79 dBm

Start 30 MHz 2.457 GHz/ Stop 25 GHz

ADT

[illegible]

Ref 31 dBm Offset 21 dB

Center 2 528 GHz Span 200 MHz

F71 MP VIEW

Marker 1 [T1] 218 dBm 243440 GHz






Marker 2 [T1] -38.81 dBm 248350 GHz

Marker 3 [T1] -36.52 dBm 249520 GHz

Marker 4 [T1] -40.15 dBm 250000 GHz




A D T


**Chain 1****CH 3****CH 6****CH 9****CH 3 Band edge****CH 9 Band edge**

## Chain 2


### CH 1




### CH 6




### CH 11



### CH 1 Band edge



### CH 11 Band edge





A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF/Telecom Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab:**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.



A D T

## **7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No modifications were made to the EUT by the lab during the test.

--- END ---