

**Label with static, pre-printed text only
(STA-L000xxx)**



**Label with example variable data.
Not for manufacture.**



Notes:

- Barcodes shown are example, dummy barcodes for illustration only.
- The barcodes MUST have a minimum x-dimension of 5 mils (0.125mm). This can only be achieved by using a 600dpi printer.
- The barcodes must be as wide as possible across the width of the label, while still including enough quiet zone to the left and right of the barcode to ensure an accurate scan.
- Centre all the barcodes, as shown, and ensure the quiet zones extend out to the margins, as shown. The barcodes plus left and right quiet zones must be at least 26mm across.
- Colons (:) and hyphens (-) are to be used only in human-readable serial numbers. Do not include these in the barcoded serial numbers.
- The barcodes are made up of a printed white "background", so the black label material forms the black bars of the barcodes.
- The QR Code to be printed white - no need to reverse print.
- The label system (label, ink and printing) shall be UL certified to UL 969.

Blank Label Part	STA-L000320	Ribbon	STA-CDNP001			E297-PX051AEI-Product-Label			Rev	
									A	
Additional Notes				Model	PX051AEI	Drafted By	Nick Tonge	Sheet 1 of 1		
See also: Serialisation specification for E297 PX051AEI (latest issue) Label Position Instructions 700-534044x First issue				Model Part No	E2973428200	Date	5 February 2016			
				Additional Graphics (if required)		Approved by		Signature	Date	
				DC Symbol.bmp		Tech Pubs	M Heron			
						Project Team	Jon Naylor			
		Approvals	Rob Turner							