



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20180300012E-02  
**Applicant:** Netvox Technology Co., Ltd.  
**Address of Applicant:** No. 21-1, Sec. 1 Chung Hua West Road, Tainan, Taiwan, R.O.C.  
**Manufacturer:** Netvox Technology Co., Ltd. (Xiamen)  
**Address of Manufacturer:** No.2, Xin Feng 2 Road, Xiamen Torch Hi-Tech Industrial Development Zone, Xiamen City, China  
**Factory:** N/A  
**Address of Factory:** N/A  
**Equipment Under Test (EUT):**  
**Product:** Wireless Temperature And Humidity Sensor  
**Model No.:** R711  
**Brand Name:** Netvox  
**FCC ID:** NRH-LR-R711  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Test:** 2018-03-08 to 2018-03-14  
**Date of Issue:** 2018-03-14  
**Test Result :** PASS\*

**Tested By:**

(Aaron Ma)

**Reviewed By:**

(Owen Zhou)

**Approved By:**

(Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 2 Version

### Revision History Of Report

| Report No.           | Version | Description    | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20180300012E-02 | Rev.01  | Initial report | 2018-03-14 |

### 3 Contents

|                                              | Page |
|----------------------------------------------|------|
| 1 COVER PAGE.....                            | 1    |
| 2 VERSION .....                              | 2    |
| 3 CONTENTS .....                             | 3    |
| 4 GENERAL INFORMATION.....                   | 4    |
| 4.1 CLIENT INFORMATION.....                  | 4    |
| 4.2 GENERAL DESCRIPTION OF EUT .....         | 4    |
| 5 SAR EVALUATION .....                       | 5    |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT ..... | 5    |
| 5.1.1 <i>Standard Requirement</i> .....      | 5    |
| 5.1.2 <i>Limits</i> .....                    | 5    |
| 5.1.3 <i>EUT RF Exposure</i> .....           | 5    |

## 4 General Information

### 4.1 Client Information

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| Applicant:               | Netvox Technology Co., Ltd.                                                                 |
| Address of Applicant:    | No. 21-1, Sec. 1 Chung Hua West Road, Tainan, Taiwan, R.O.C.                                |
| Manufacturer:            | Netvox Technology Co., Ltd. (Xiamen)                                                        |
| Address of Manufacturer: | No.2, Xin Feng 2 Road, Xiamen Torch Hi-Tech Industrial Development Zone, Xiamen City, China |

### 4.2 General Description of EUT

|                       |                                              |
|-----------------------|----------------------------------------------|
| Name:                 | Wireless Temperature And Humidity Sensor     |
| Model No.:            | R711                                         |
| Trade Mark :          | Netvox                                       |
| Hardware Version:     | V1.0                                         |
| Software Version:     | V1.0                                         |
| Frequency Range:      | 902MHZ ~ 928MHz                              |
| Modulation Type:      | FSK                                          |
| Number of Channels:   | 80 (declared by the client)                  |
| Sample Type:          | Portable production                          |
| Test Software of EUT: | Netvox LoRa FCC Test (manufacturer declare ) |
| Antenna Type:         | Integral antenna                             |
| Antenna Gain:         | 0dBi                                         |
| Power Supply:         | 2 x AAA battery, DC3V                        |

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right.$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 5.1.3 EUT RF Exposure

$$e_{\text{irp}} = p_t \times g_t = (E \times d)^2 / 30$$

where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m,  $10^{((\text{dB}\mu\text{V/m})/20)/10^6}$ ,

$d$  = measurement distance in meters (m)---3m,

$$\text{So } p_t = (E \times d)^2 / 30 / g_t$$

The worst case (refer to report CQASZ20180300012E-01) is below:

For Wireless Module:

Field strength = 94.04dB $\mu$ V/m @3m

Ant. gain 0dBi; so Ant numeric gain=1.0

$$\text{So } p_t = \{ [10^{(94.04/20)} / 10^6 \times 3]^2 / 30 / 1.0 \} \times 1000 \text{mW} = 0.761 \text{mW}$$

$$\text{So } (0.761 \text{mW} / 5 \text{mm}) \times \sqrt{0.9275 \text{GHz}} = 0.146,$$

$$0.147 < 3.0 \text{ for 1-g SAR}$$

So the SAR report is not required.