

USER'S GUIDE

- THE TEXT OF THIS INSTRUCTIONS WILL BE PRINTED ON THE SURFACE OF THE INDIVIDUAL BOX AT THE TIME OF MASS PRODUCTION.

1. PRODUCT SPECIFICATION

MODEL NO.	VOLTAGE(V)	FREQUENCY(Hz)	POWER(W)	CURRENT(A)	LIFE(Hrs)
EQR1235AP	120	60	35	0.5	10,000

2. USER'S GUIDE

- ELECTRONIC BALLAST
- INSTANT ON, FLICKER-FREE AND LIGHT WEIGHT
- RELIABLE OPERATING TEMPERATURE RANGE : -10°C TO 40°C

1)CAUTION

- ①NOT FOR USE WITH DIMMERS.
- ②NOT FOR USE WITH TOTALLY ENCLOSED RECESSED FIXTURES.
- ③RISK OF ELECTRIC SHOCK - USE ONLY IN DRY LOCATIONS.
- ④THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXIT FIXTURES OR EMERGENCY EXIT LIGHTS.
- ⑤NOT FOR USE WHERE EXPOSED TO THE WEATHER.

2) NOTE

- ①This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.
- ②Do not touch the lamp as soon as turn off because it is very hot.