



**FCC CFR47 PART 15 SUBPART C
CERTIFICATION
TEST REPORT**

FOR

PCMCIA RFID READER CARD

MODEL NUMBER: MPR6000

FCC ID: NTTWJMPR6XXX

REPORT NUMBER: 04U2954-3

ISSUE DATE: NOVEMBER 22, 2004

Prepared for
**WJ COMUNICATIONS
401 RIVER OAKS PARKWAY
SAN JOSE, CA 95134**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**

NVLAP[®]
LAB CODE:200065-0

Revision History

<u>Rev.</u>	<u>Revisions</u>	<u>Revised By</u>
-------------	------------------	-------------------

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY.....	6
4.1. MEASURING INSTRUMENT CALIBRATION.....	6
4.2. MEASUREMENT UNCERTAINTY.....	6
5. EQUIPMENT UNDER TEST.....	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS.....	7
5.4. SOFTWARE AND FIRMWARE	7
5.5. WORST-CASE CONFIGURATION AND MODE.....	8
5.6. DESCRIPTION OF TEST SETUP	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. LIMITS AND RESULTS	12
7.1. ANTENNA PORT CHANNEL TESTS FOR CLASS 0 MODULATION.....	12
7.1.1. 20 dB BANDWIDTH	12
7.1.2. HOPPING FREQUENCY SEPARATION.....	16
7.1.3. NUMBER OF HOPPING CHANNELS.....	18
7.1.4. AVERAGE TIME OF OCCUPANCY	20
7.1.5. PEAK OUTPUT POWER	24
7.1.6. MAXIMUM PERMISSIBLE EXPOSURE.....	28
7.1.7. CONDUCTED SPURIOUS EMISSIONS.....	31
7.2. ANTENNA PORT CHANNEL TESTS FOR CLASS 1 MODULATION.....	40
7.2.1. 20 dB BANDWIDTH	40
7.2.2. HOPPING FREQUENCY SEPARATION.....	44
7.2.3. NUMBER OF HOPPING CHANNELS.....	46
7.2.4. AVERAGE TIME OF OCCUPANCY	48
7.2.5. PEAK OUTPUT POWER	52
7.2.6. MAXIMUM PERMISSIBLE EXPOSURE.....	56
7.2.7. CONDUCTED SPURIOUS EMISSIONS.....	59
7.3. RADIATED EMISSIONS.....	68
7.3.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	68
7.3.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 3 dBi MONOPOLE ANTENNA AND CLASS 0 MODULATION	71

7.3.3. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 9.2dBi CIRCULARLY POLARIZED ANTENNA AND CLASS 0 MODULATION.....	72
7.3.4. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 3 dBi MONOPOLE ANTENNA AND CLASS 1 MODULATION.....	73
7.3.5. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 9.2dBi CIRCULARLY POLARIZED ANTENNA AND CLASS 1 MODULATION.....	74
1. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz.....	75
7.4. <i>POWERLINE CONDUCTED EMISSIONS</i>	83
8. SETUP PHOTOS	87

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: WJ COMMUNICATIONS
401 RIVER OAKS PARKWAY
SAN JOSE, CA 95134

EUT DESCRIPTION: PCMCIA RFID READER CARD

MODEL: MPR6000

SERIAL NUMBER: 50143040039

DATE TESTED: NOVEMBER 10 - 12, 2004

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



YAN ZHENG
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

Tested By:



HITESH H. SOLANKI
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a PCMCIA RFID Reader card with the external antennas. The antennas are the circularly polarized antenna with gain of 9.2 dBi and the monopole antenna with gain of 3 dBi.

The WJ RFID reader card is capable of producing two types of modulation that are standards in the RFID tag industry, Class 0 and Class 1. Passive RF ID tags are manufactured to respond to either Class 0 or Class 1 reader interrogation.

The radio module is manufactured by WJ Communications.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

CLASS 0

Channel	Frequency (MHz)	Power (dBm)	Power (mW)
Low	903	26.77	475.3
Middle	914	26.62	459.2
High	927	26.51	447.7

CLASS 1

Channel	Frequency (MHz)	Power (dBm)	Power (mW)
Low	903	26.75	473.2
Middle	914	26.60	457.1
High	927	26.49	445.7

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes 2 different antennas; a circularly polarized antenna with gain of 9.2 dBi and a monopole antenna with gain of 3 dBi.

5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was MPR version 2.0.

5.5. WORST-CASE CONFIGURATION AND MODE

For antenna conducted emissions, both Class 0 and Class 1 modulations were investigated. Worst case emissions are reported.

There are four different test configurations for spurious and harmonic radiated emissions tests:

Class 0 modulation with Class 0 tag on the test table

Class 0 modulation with Class 1 tag on the test table

Class 1 modulation with Class 1 tag on the test table

Class 1 modulation with Class 0 tag on the test table

The Class 0 tag is a matrix type tag.

The Class 1 tag is an Alien Technologies type tag.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
LAPTOP	IBM	390E	AF - 1B8BD	N/A
AC/DC ADAPTER	IBM	N/A	02K6555	N/A

I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	2	AC	Un-shielded	0.5 m	N/A
2	DC	1	DC	Un-shielded	1m	N/A

TEST SETUP

The EUT is a PCMCIA card. It is inserted into the support Laptop and is operated by using the test software, which is capable of exercising the EUT on different channels as well as in hopping mode.

SETUP DIAGRAM FOR TESTS

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
LISN, 10 kHz ~ 30 MHz	FCC	50/250-25-2	4/23/1900	10/13/2005
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	10/13/05
EMI Test Receiver	R & S	ESHS 20	827129/006	7/17/05
EMI Receiver, 9 kHz ~ 2.9 GHz	HP	8542E	3942A00286	11/21/04
RF Filter Section	HP	85420E	3705A00256	11/21/04
30MHz---- 2Ghz	Sunol Sciences	JB1 Antenna	A121003	12/22/04
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	2238	2/4/05
Amplifier 1-26GHz	MITEQ	NSP2600-SP	924342	4/25/05
Spectrum Analyzer 20 Hz ~ 44 GHz	Agilent	E4446A	US42070220	4/1/05
1.5 GHz High Pass Filter	Micro-Tronics	HPM13193	2	N/A

7. LIMITS AND RESULTS

7.1. ANTENNA PORT CHANNEL TESTS FOR CLASS 0 MODULATION

7.1.1. 20 dB BANDWIDTH

LIMIT

None: for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 1% to 3% of the 20 dB bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled.


RESULTS

No non-compliance noted:

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
Low	903	251
Middle	914	248
High	927	255

20 dB BANDWIDTH





7.1.2. HOPPING FREQUENCY SEPARATION

LIMIT

§15.247 (a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 10 kHz and the VBW is set to 30 kHz. The sweep time is coupled.

RESULTS

No non-compliance noted:

The hopping frequency separation is 500KHz.

HOPPING FREQUENCY SEPARATION

7.1.3. NUMBER OF HOPPING CHANNELS

LIMIT

§15.247 (a) (1) (i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to 1 % of the span. The analyzer is set to Max Hold.

RESULTS

No non-compliance noted:

50 Channels observed.

NUMBER OF HOPPING CHANNELS

7.1.4. AVERAGE TIME OF OCCUPANCY

LIMIT

§15.247 (a) (1) (i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 20 second scan, to enable resolution of each occurrence.


RESULTS

No non-compliance noted:


The system has 50 hopping frequencies. There are 7 pulses within the 20-second period. The on time for each pulse is $58.17\text{ms} - 2 \times 3\text{ms} = 52.17\text{ms}$.


Therefore, the average time of occupancy in the specified 20-second period is:

$$(58.17\text{ms} - 2 \times 3\text{ms}) \times 7 = 365.19\text{ms} = 0.365\text{s}$$

PULSE WIDTH

OFF TIME WITHIN THE PULSE



NUMBER OF PULSES IN 20 SECOND OBSERVATION PERIOD

7.1.5. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (2) For frequency hopping systems operating in the 902-928 MHz band , employing at least 50 hopping channels: 1 watt; and
employing less than 50 hopping channels, but at least 25 hopping channels: 0.25 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The maximum antenna gain is 9.2 dBi (worst case), therefore the limit is 26.8 dBm.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer and the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

No non-compliance noted:

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	903	26.77	26.8	-0.03
Middle	914	26.62	26.8	-0.18
High	927	26.51	26.8	-0.29

OUTPUT POWER





7.1.6. MAXIMUM PERMISSIBLE EXPOSURE

LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm²

Substituting the logarithmic form of power and gain using:

$$P \text{ (mW)} = 10^{(P \text{ (dBm)} / 10)} \text{ and}$$

$$G \text{ (numeric)} = 10^{(G \text{ (dBi)} / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S} \quad \text{Equation (1)}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm²

Equation (1) and the measured peak power is used to calculate the MPE distance.

LIMITS

From §1.1310 Table 1 (B), $S = 1.0 \text{ mW/cm}^2$

RESULTS

No non-compliance noted:

Power Density Limit (mW/cm²)	Output Power (dBm)	Antenna Gain (dBi)	MPE Distance (cm)
1.0	26.77	9.20	17.73

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

7.1.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.


The spectrum from 30 MHz to 10 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL





SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



7.2. ANTENNA PORT CHANNEL TESTS FOR CLASS 1 MODULATION

7.2.1. 20 dB BANDWIDTH

LIMIT

None: for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 1% to 3% of the 20 dB bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled.


RESULTS

No non-compliance noted:

Channel	Frequency (MHz)	20 dB Bandwidth (kHz)
Low	903	299
Middle	914	294
High	927	294

20 dB BANDWIDTH





7.2.2. HOPPING FREQUENCY SEPARATION

LIMIT

§15.247 (a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 10 kHz and the VBW is set to 30 kHz. The sweep time is coupled.

RESULTS

No non-compliance noted:

The hopping frequency separation is 500KHz.

HOPPING FREQUENCY SEPARATION

7.2.3. NUMBER OF HOPPING CHANNELS

LIMIT

§15.247 (a) (1) (i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to 1 % of the span. The analyzer is set to Max Hold.

RESULTS

No non-compliance noted:

50 Channels observed.

NUMBER OF HOPPING CHANNELS

7.2.4. AVERAGE TIME OF OCCUPANCY

LIMIT

§15.247 (a) (1) (i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 20 second scan, to enable resolution of each occurrence.


RESULTS


No non-compliance noted:


The system has 50 hopping frequencies. There are 8 pulses within the 20-second period. The on time for each pulse is $52 \text{ ms} - 2 \times 3.167 \text{ ms} = 45.67 \text{ ms}$.

Therefore, the average time of occupancy in the specified 20-second period is:

$$(52 \text{ ms} - 2 \times 3.167 \text{ ms}) \times 8 = 365.32 \text{ ms} = 0.365 \text{ s}$$

PULSE WIDTH

OFF TIME WITHIN A PULSE

NUMBER OF PULSES IN 20 SECOND OBSERVATION PERIOD

7.2.5. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (2) For frequency hopping systems operating in the 902-928 MHz band , employing at least 50 hopping channels: 1 watt; and
employing less than 50 hopping channels, but at least 25 hopping channels: 0.25 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The maximum antenna gain is 9.2 dBi (worst case), therefore the limit is 26.8 dBm.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer and the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

No non-compliance noted:

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	903	26.75	26.8	-0.05
Middle	914	26.60	26.8	-0.20
High	927	26.49	26.8	-0.31

OUTPUT POWER





7.2.6. MAXIMUM PERMISSIBLE EXPOSURE

LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm²

Substituting the logarithmic form of power and gain using:

$$P \text{ (mW)} = 10^{(P \text{ (dBm)} / 10)} \text{ and}$$

$$G \text{ (numeric)} = 10^{(G \text{ (dBi)} / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S} \quad \text{Equation (1)}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm²

Equation (1) and the measured peak power is used to calculate the MPE distance.

LIMITS

From §1.1310 Table 1 (B), $S = 1.0 \text{ mW/cm}^2$

RESULTS

No non-compliance noted:

Power Density Limit (mW/cm²)	Output Power (dBm)	Antenna Gain (dBi)	MPE Distance (cm)
1.0	26.75	9.20	17.69

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

7.2.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.


The spectrum from 30 MHz to 10 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL





SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



7.3. RADIATED EMISSIONS

7.3.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each 5 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

7.3.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 3 dBi MONOPOLE ANTENNA AND CLASS 0 MODULATION

HARMONICS AND SPURIOUS EMISSIONS

11/10/04 High Frequency Measurement
Compliance Certification Services, Morgan Hill Open Field Site

Test Engr: HITESH H SOLANKI
Project #: 04U2954-1
Company: WJ COMMUNICATIONS
EUT Descrip.: PCMCIA RFID CARD READER
EUT M/N: MPR60xx
Test Target: FCC CLASS B
Mode Oper: TX CONTINUOUSLY, TAG : ALIEN (CLASS 1), READER MODE : CLASS 0, ANTENNA : MAXRAD OMNI (3 dBi) (WORST CASE)

Test Equipment:

EMCO Horn 1-18GHz
T73; S/N: 6717 @3m

Pre-amplifier 1-26GHz
T34 HP 8449B

Pre-amplifier 26-40GHz

Horn > 18GHz

Hi Frequency Cables
2 foot cable
3 foot cable
4 foot cable
12 foot cable
4_Hitesh
12_Hitesh

HPF
Reject Filter

Peak Measurements
RBW=VBW=1MHz

Average Measurements
RBW=1MHz ; VBW=10Hz

f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Filtr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
LOW CHANNEL															
1.805	3.0	49.1	41.3	26.4	2.4	-37.1	0.0	0.0	40.9	33.1	74	54	-33.1	-20.9	V
2.708	3.0	42.4	31.4	29.2	3.0	-35.9	0.0	0.0	38.7	27.7	74	54	-35.3	-26.3	V
MIDDLE CHANNEL															
1.829	3.0	51.3	42.0	26.5	2.4	-37.0	0.0	0.0	43.2	33.9	74	54	-30.8	-20.1	V
2.744	3.0	44.5	30.6	29.4	3.1	-35.9	0.0	0.0	41.0	27.1	74	54	-33.0	-26.9	V
HIGH CHANNEL															
1.854	3.0	45.3	36.8	26.6	2.4	-37.0	0.0	0.0	37.3	28.8	74	54	-36.7	-25.2	V
2.781	3.0	42.1	31.0	29.5	3.1	-35.9	0.0	0.0	38.8	27.7	74	54	-35.2	-26.3	V
LOW CHANNEL															
1.805	3.0	50.6	40.2	26.4	2.4	-37.1	0.0	0.0	42.4	32.0	74	54	-31.6	-22.0	H
2.708	3.0	44.7	31.9	29.2	3.0	-35.9	0.0	0.0	41.0	28.2	74	54	-33.0	-25.8	H
MIDDLE CHANNEL															
1.829	3.0	51.0	44.7	26.5	2.4	-37.0	0.0	0.0	42.9	36.6	74	54	-31.1	-17.4	H
2.744	3.0	38.9	29.9	29.4	3.1	-35.9	0.0	0.0	35.4	26.4	74	54	-38.6	-27.6	H
HIGH CHANNEL															
1.854	3.0	46.9	40.2	26.6	2.4	-37.0	0.0	0.0	38.9	32.2	74	54	-35.1	-21.8	H
2.781	3.0	42.3	31.5	29.5	3.1	-35.9	0.0	0.0	39.0	28.2	74	54	-35.0	-25.8	H
Legend:															
f	Measurement Frequency		Amp	Preamp Gain		Avg Lim	Average Field Strength Limit								
Dist	Distance to Antenna		D Corr	Distance Correct to 3 meters		Pk Lim	Peak Field Strength Limit								
Read	Analyzer Reading		Avg	Average Field Strength @ 3 m		Avg Mar	Margin vs. Average Limit								
AF	Antenna Factor		Peak	Calculated Peak Field Strength		Pk Mar	Margin vs. Peak Limit								
CL	Cable Loss		HPF	High Pass Filter											

7.3.3. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 9.2dBi CIRCULARLY POLARIZED ANTENNA AND CLASS 0 MODULATION

HARMONICS AND SPURIOUS EMISSIONS

11/10/04

High Frequency Measurement

Compliance Certification Services, Morgan Hill Open Field Site

Test Engr:

HITESH H SOLANKI

Project #:

04U2954-1

Company:

WJ COMMUNICATIONS

EUT Descrip.:

PCMCIA RFID CARD READER

EUT M/N:

MPR60xx

Test Target:

FCC CLASS B

Mode Oper:

TX CONTINUOUSLY, TAG : SMALL MATRIX (CLASS 0), READER MODE : CLASS 0, ANTENNA : MAXRAD PANEL (7dBd/ 9.2 dBi GAIN) (WORST CASE)

Test Equipment:

EMCO Horn 1-18GHz

Pre-amplifier 1-26GHz

Pre-amplifier 26-40GHz

Horn > 18GHz

T73; S/N: 6717 @3m

T34 HP 8449B

Hi Frequency Cables

2 foot cable

3 foot cable

4 foot cable

12 foot cable

4_Hitesh

12_Hitesh

HPF

Reject Filter

Peak Measurements

RBW=VBW=1MHz

Average Measurements

RBW=1MHz ; VBW=10Hz

f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
LOW CHANNEL															
1.805	3.0	47.7	39.8	26.4	2.4	-37.1	0.0	0.0	39.5	31.6	74	54	-34.5	-22.4	V
2.708	3.0	43.2	28.9	29.2	3.0	-35.9	0.0	0.0	39.5	25.2	74	54	-34.5	-28.8	V
MIDDLE CHANNEL															
1.829	3.0	46.0	40.0	26.5	2.4	-37.0	0.0	0.0	37.9	31.9	74	54	-36.1	-22.1	V
2.744	3.0	39.0	31.2	29.4	3.1	-35.9	0.0	0.0	35.5	27.7	74	54	-38.5	-26.3	V
HIGH CHANNEL															
1.854	3.0	50.2	45.6	26.6	2.4	-37.0	0.0	0.0	42.2	37.6	74	54	-31.8	-16.4	V
2.781	3.0	44.6	31.2	29.5	3.1	-35.9	0.0	0.0	41.3	27.9	74	54	-32.7	-26.1	V
LOW CHANNEL															
1.805	3.0	50.0	43.4	26.4	2.4	-37.1	0.0	0.0	41.8	35.2	74	54	-32.2	-18.8	H
2.708	3.0	43.2	30.1	29.2	3.0	-35.9	0.0	0.0	39.5	26.4	74	54	-34.5	-27.6	H
MIDDLE CHANNEL															
1.829	3.0	43.4	36.5	26.5	2.4	-37.0	0.0	0.0	35.3	28.4	74	54	-38.7	-25.6	H
2.744	3.0	44.0	31.2	29.4	3.1	-35.9	0.0	0.0	40.5	27.7	74	54	-33.5	-26.3	H
HIGH CHANNEL															
1.854	3.0	56.7	52.3	26.6	2.4	-37.0	0.0	0.0	48.7	44.3	74	54	-25.3	-9.7	H
2.781	3.0	44.3	31.1	29.5	3.1	-35.9	0.0	0.0	41.0	27.8	74	54	-33.0	-26.2	H

f

Measurement Frequency

Dist

Distance to Antenna

Read

7.3.4. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 3 dBi MONOPOLE ANTENNA AND CLASS 1 MODULATION

HARMONICS AND SPURIOUS EMISSIONS

[illegible]

7.3.5. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ WITH 9.2dBi CIRCULARLY POLARIZED ANTENNA AND CLASS 1 MODULATION

HARMONICS AND SPURIOUS EMISSIONS

[illegible]


1. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz**SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)**

HORIZONTAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 20 File#: 04U2954-1.EMI Date: 11-19-2004 Time: 11:47:35



(Auxiliary ATC)

Trace: 19

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL
Test Operator: : HITESH H. SOLANKI
Project #: : 04U2954-1
Company: : WJ COMMUNICATION
EUT: : PCMCIA RFID READER CARD
Model No: : MPR60XX
Configuration: : EUT W/ EXT. CARD & 9.2dBi ANTENNA
Target of Test: : FCC CLASS B
Mode of Operation: Tx ON MIDDLE CHANNEL

HORIZONTAL DATA

	Freq	Remark	Read Level	Level	Factor	Limit Line	Over Limit
	MHz		dBuV	dBuV/m	dB	dBuV/m	dB
1	30.970	Peak	40.27	36.05	-4.22	40.00	-3.95
2	218.180	Peak	47.34	33.84	-13.50	46.00	-12.16
3	276.380	Peak	52.70	41.88	-10.83	46.00	-4.13
4	459.710	Peak	49.61	42.03	-7.58	46.00	-3.97
5	688.630	Peak	50.06	45.99	-4.07	46.00	-0.01
6 *	917.550	Peak	94.21	93.86	-0.35	46.00	47.86


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)

VERTICAL PLOT (30 MHz – 882 MHz)



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 25 File#: 04U2954-1.EMI Date: 11-19-2004 Time: 12:31:51



(Auxiliary ATC)

Trace: 24

Ref Trace:

Condition: FCC CLASS-B VERTICAL
Test Operator: : HITESH H. SOLANKI
Project #: : 04U2954-1
Company: : WJ COMMUNICATION
EUT: : PCMCIA RFID READER CARD
Model No: : MPR60XX
Configuration: : EUT W/ EXT. CARD & 9.2 dBi ANTENNA
Target of Test: : FCC CLASS B
Mode of Operation: Tx ON MIDDLE CHANNEL

VERTICAL DATA(30 MHz – 882 MHz)


	Freq	Remark	Read Level	Level	Factor	Limit Line	Over Limit
	MHz		dBuV	dBuV/m	dB	dBuV/m	dB
1	31.704	Peak	43.99	38.99	-5.00	40.00	-1.01
2	847.920	Peak	46.00	44.41	-1.59	46.00	-1.59
3	868.368	Peak	45.98	44.53	-1.44	46.00	-1.47

VERTICAL PLOT (882 MHz – 948 MHz)



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 38 File#: 04U2954-1.EMI Date: 11-19-2004 Time: 15:40:15



(Auxiliary ATC)

Trace: 26

Ref Trace:

Condition: FCC CLASS-B VERTICAL
Test Operator: : HITESH H. SOLANKI
Project #: : 04U2954-1
Company: : WJ COMMUNICATION
EUT: : PCMCIA RFID READER CARD
Model No: : MPR60XX
Configuration: : EUT W/ EXT. CARD & 9.2 dBi ANTENNA
Target of Test: : FCC CLASS B
Mode of Operation: Tx ON MIDDLE CHANNEL

VERTICAL DATA(882 MHz – 948 MHz)


	Freq	Remark	Read Level	Level	Factor	Limit Line	Over Limit
	MHz		dBuV	dBuV/m	dB	dBuV/m	dB
1 *	914.736	Peak	108.22	107.85	-0.37	46.00	61.85

VERTICAL PLOT (948 MHz – 1000 MHz)



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 29 File#: 04U2954-1.EMI Date: 11-19-2004 Time: 12:36:15



(Auxiliary ATC)

Trace: 28

Ref Trace:

Condition: FCC CLASS-B VERTICAL
Test Operator: : HITESH H. SOLANKI
Project #: : 04U2954-1
Company: : WJ COMMUNICATION
EUT: : PCMCIA RFID READER CARD
Model No: : MPR60xx
Configuration: : EUT W/ EXT. CARD & 9.2 dBi ANTENNA
Target of Test: : FCC CLASS B
Mode of Operation: Tx ON MIDDLE CHANNEL

VERTICAL DATA(948 MHz – 1000 MHz)

	Freq	Remark	Read	Level	Factor	Limit	Over
			Level			Line	Limit
	MHz		dBuV	dBuV/m	dB	dBuV/m	dB
1	950.236	Peak	44.80	44.85	0.05	46.00	-1.15
2	956.892	Peak	44.72	44.91	0.18	46.00	-1.09
3	977.224	Peak	45.18	45.69	0.51	54.00	-8.31

7.4. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


Line conducted data is recorded for both NEUTRAL and HOT lines.


RESULTS

No non-compliance noted:

6 WORST EMISSIONS


CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	FCC B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.15	55.88	--	--	0.00	66.00	56.00	-10.12	-0.12	L1
0.57	40.48	--	--	0.00	56.00	46.00	-15.52	-5.52	L1
19.84	42.38	--	--	0.00	60.00	50.00	-17.62	-7.62	L1
0.15	55.62	--	--	0.00	65.94	55.94	-10.32	-0.32	L2
0.57	40.48	--	--	0.00	56.00	46.00	-15.52	-5.52	L2
19.84	44.80	--	--	0.00	60.00	50.00	-15.20	-5.20	L2
6 Worst Data									

LINE 1 RESULTS


LINE 2 RESULTS

8. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SETUP




RADIATED BACK PHOTO (9.2 dBi ANTENNA)



RADIATED FRONT PHOTO, (MONOPOLE 3 dBi ANTENNA)



RADIATED BACK PHOTO, (MONOPOLE 3 dBi ANTENNA)



POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP

LINE CONDUCTED FRONT PHOTO



LINE CONDUCTED BACK PHOTO



END OF REPORT