EXHIBIT 1 – MAXIMUM PERMISSIBLE EXPOSURE	
PRODUCT NAME	Brady Print Server
PRODUCT MODEL NUMBER	BNCBTWIFI
FCC ID	NUC-BNCBTWIFI
IC ID	3287A-BNCBTWIFI
MANUFACTURER	Brady World Wide Inc
TEST REPORT NUMBER	BNCBTWIFI-MPE
TEST REPORT DATE	10th May 2011
TEST REPORT VERSION	0.03
ISSUED TO	**Brady World Wide Inc** 6555 W Good Hope Road, Milwaukee, WI 53223 Phone: 1-414-228-5940 e-mail: jeff_mueller@bradycorp.com and **Brady Corporation Asia Pacific Pte Ltd.** 1 Kaki Bukit Crescent, Singapore - 416236 Phone: +65 6477 7261
ISSUED BY	**TARANG** Wipro Technologies, SJP2, Survey#70,77,78/8A, Dodda Kanelli, Sarjapur road, Bangalore-560 035. Karnataka. India. Tel: +91-80-30292929 Fax: +91-80-30298200 Email: tarang.planet@wipro.com Web: www.wipro.com

REVISION HISTORY

S. No	Version	Date	Change History	Remarks
1	0.01	26th Apr 2011	Initial version for internal review	
2	0.02	3rd May 2011	Updated the "Issued To" field in Page 1	
3	0.03	10th May 2011	Updated the "Issued To" field in Page 1 to include Brady Corporation Asia Pacific Pte Ltd	

This report must not be reproduced, except in full, without prior written permission from Tarang lab.

1 MAXIMUM PERMISSIBLE EXPOSURE RESULTS

1.1 RESULTS FOR 802.11b BAND

Frequency (MHz)	Min.User Distance (cm)	Gain (dBi)	Numeric Gain	Conducted Power (mW)	Power Density (mW/cm2)	Limit (mW/cm^2)	Result
2412	20	0.5	1.122	18.28	0.004080	5	Pass
2437	20	0.5	1.122	16.03	0.003578	5	Pass
2462	20	0.5	1.122	15.84	0.003535	5	Pass

1.2 RESULTS FOR 802.11g BAND

Frequency (MHz)	Min.User Distance (cm)	Gain (dBi)	Numeric Gain	Conducted Power (mW)	Power Density (mW/cm2)	Limit (mW/cm^2)	Result
2412	20	0.5	1.122	0.3830	0.000085	5	Pass
2437	20	0.5	1.122	0.8165	0.000182	5	Pass
2462	20	0.5	1.122	0.2090	0.000047	5	Pass

1.3 RESULTS FOR 802.11n BAND

Frequency (MHz)	Min.User Distance (cm)	Gain (dBi)	Numeric Gain	Conducted Power (mW)	Power Density (mW/cm2)	Limit (mW/cm^2)	Result
2412	20	0.5	1.122	0.334	0.000075	5	Pass
2437	20	0.5	1.122	0.265	0.000059	5	Pass
2462	20	0.5	1.122	0.211	0.000047	5	Pass

Tarang
Wipro Technologies, SJP2, Survey#70,77,78/8A, Dodda Kanelli, Sarjapur road, Bangalore-560 035. Karnataka. India.
Tel: +91-80-30298772 Fax: 91-80-28440054 E-mail: tarang.planet@wipro.com

This report must not be reproduced, except in full, without prior written permission from Tarang lab.

1.4 RESULTS FOR BLUETOOTH BAND

Frequency (MHz)	Min.User Distance (cm)	Gain (dBi)	Numeric Gain	Conducted Power (mW)	Power Density (mW/cm2)	Limit (mW/cm^2)	Result
2.402	20	0.5	1.122	5.866	0.001309	5	Pass
2.412	20	0.5	1.122	5.642	0.001259	5	Pass
2.422	20	0.5	1.122	5.527	0.001234	5	Pass
2.432	20	0.5	1.122	5.445	0.001215	5	Pass
2.442	20	0.5	1.122	4.818	0.001075	5	Pass
2.452	20	0.5	1.122	4.924	0.001099	5	Pass
2.462	20	0.5	1.122	4.628	0.001033	5	Pass
2.472	20	0.5	1.122	4.826	0.001077	5	Pass
2.480	20	0.5	1.122	3.928	0.000877	5	Pass

Pd (mW/cm^2) = (30*P*G)/ (377*d^2); Gain (numeric) = 10^ (dBi/10)
Pd =Power density (mW/cm^2)
P = Peak RF output power (mW)
G = EUT Antenna Numeric gain
d= Separation between radiator and human body (cm)

This report must not be reproduced, except in full, without prior written permission from Tarang lab.