

# Spectrum Brands, Inc. dba Kwikset **MPE REPORT**

**SCOPE OF WORK**

MPE CALCULATION – KWIKSET 942 / WEISER GED1850

**REPORT NUMBER**

104650309LAX-003

**ISSUE DATE**

5-May-2021

**PAGES**

9

**DOCUMENT CONTROL NUMBER**

Non-Specific Radio Report Shell Rev. December 2017  
© 2017 INTERTEK



## MPE REPORT

(FULL COMPLIANCE)

**Report Number:** 104650309LAX-003

**Project Number:** G104650309

**Report Issue Date:** May 5, 2021

**Model(s) Tested:** Kwikset 942 / Weiser GED1850

**Standards: FCC Part 1 Subpart I, April 2021**

Procedures Implementing the National Environmental Policy Act of 1969  
*§1.1307 Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.*

**ISED RSS-102 Issue 5, March 19, 2015**

Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus  
(All Frequency Bands)

Tested by:

Intertek

25791 Commercentre Drive

Lake Forest, CA 92630

USA

Client:


Spectrum Brands, Inc. dba Kwikset

19701 DaVinci

Foothill Ranch, CA 92610

USA

Report prepared by



Grace Lin

EMC Staff Engineer

Report reviewed by



Uri Spector

EMC Team Leader

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*

Table of Contents

|                                                                       |          |
|-----------------------------------------------------------------------|----------|
| <i>Spectrum Brands, Inc. dba Kwikset.....</i>                         | <i>1</i> |
| <i>1 Introduction and Conclusion .....</i>                            | <i>4</i> |
| <i>2 Evaluation Summary .....</i>                                     | <i>4</i> |
| <i>3 Client Information.....</i>                                      | <i>5</i> |
| <i>4 Description of Equipment Under Test and Variant Models .....</i> | <i>5</i> |
| <i>5 Power Density Calculation .....</i>                              | <i>6</i> |
| <i>6 ISED RSS-102 Issue 5 §2.5.2 Exemption .....</i>                  | <i>8</i> |
| <i>7 Revision History .....</i>                                       | <i>9</i> |

## 1 Introduction and Conclusion

This evaluation report covers for a mobile device subject to routine environmental evaluation for RF exposure. A mobile device is defined as a transmitting device designed to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

The evaluation indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining sections are the verbatim text from the actual evaluation during the investigation. These sections include the evaluation name, the specified Method, and Results. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product evaluated **complies** with the requirements of the standard(s) indicated. The results obtained in this report pertain only to the item(s) evaluated. Intertek does not make any claims of compliance for samples or variants which were not evaluated.

## 2 Evaluation Summary

| Section | Test full name                                                   | Result    |
|---------|------------------------------------------------------------------|-----------|
| 3       | Client Information                                               | -         |
| 4       | Description of Equipment Under Evaluation and Variant Models     | -         |
| 5       | System Setup and Method                                          | -         |
| 6       | Power Density Calculation<br>(FCC §1.1310; ISED RSS-102 Issue 5) | Compliant |
| 7       | Revision History                                                 | -         |

### 3 Client Information

This EUT was evaluated at the request of:

**Client:** Spectrum Brands, Inc. dba Kwikset  
19701 DaVinci  
Foothill Ranch, CA 92610  
USA

**Contact:** Johanis Hashim  
**Telephone:** 949 672-4179  
**Email:** Johanis.hashim@spectrumbrands.com

### 4 Description of Equipment Under Test and Variant Models

**Manufacturer:** Spectrum Brands, Inc. dba Kwikset  
19701 DaVinci  
Foothill Ranch, CA 92610  
USA

#### Description of Equipment Under Test (provided by client)

The equipment under test is a wireless deadbolt with integrated Bluetooth Low Energy (BLE) transceiver.

| Equipment Under Test Power Configuration |               |                 |                  |
|------------------------------------------|---------------|-----------------|------------------|
| Rated Voltage                            | Rated Current | Rated Frequency | Number of Phases |
| 6 Vdc                                    | -             | -               | -                |

#### Variant Models:

The following variant models have been identified by the manufacturer as being electrically identical models, depopulated models, or with reasonable similarity to the model(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

- Kwikset 942 is identical to Weiser GED1850. Different model name is for different market.

## 5 Power Density Calculation

### 5.1 Requirement(s)

#### FCC §1.1310 Radiofrequency radiation exposure limits

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic field.

**Table 1 – Limits for Maximum Permissible Exposure (MPE)**

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposure</b>         |                               |                               |                                     |                          |
| 0.3-3.0                                                        | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30                                                         | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300                                                         | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                                      |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                                  |                               |                               | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30                                                        | 842/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                                      |                               |                               | f/1500                              | 30                       |
| 1,500-100,000                                                  |                               |                               | 1.0                                 | 30                       |

F = frequency in MHz

\* = Plane-wave equivalent power density

#### ISED RSS-102 Issue 5

Table 2 below sets forth limits for the RF field strength.

**Table 2 – RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

| Frequency range (MHz) | Electric field strength (V/m rms) | Magnetic field strength (A/m rms)        | Power Density (W/m <sup>2</sup> ) | Reference Period (minutes) |
|-----------------------|-----------------------------------|------------------------------------------|-----------------------------------|----------------------------|
| 0.003-10              | 83                                | 90                                       | -                                 | Instantaneous*             |
| 0.1-10                | -                                 | 0.73/ f                                  | -                                 | 6**                        |
| 1.1-10                | 87/ f <sup>0.5</sup>              | -                                        | -                                 | 6**                        |
| 10-20                 | 27.46                             | 0.0728                                   | -2                                | 6                          |
| 20-48                 | 58.07/ f <sup>0.25</sup>          | 0.1540/ f <sup>0.25</sup>                | 8.944/ f <sup>0.5</sup>           | 6                          |
| 48-300                | 22.06                             | 0.05852                                  | 1.291                             | 6                          |
| 300-6000              | 3.142 f <sup>0.3417</sup>         | 0.008335 f <sup>0.3417</sup>             | 0.02619 f <sup>0.6834</sup>       | 6                          |
| 6000-15000            | 61.4                              | 0.163                                    | 10                                | 6                          |
| 15000-150000          | 61.4                              | 0.163                                    | 10                                | 616000/ f <sup>1.2</sup>   |
| 150000-300000         | 0.158 f <sup>0.5</sup>            | 4.21 x 10 <sup>-4</sup> f <sup>0.5</sup> | 6.67 x 10 <sup>-5</sup> f         | 616000/f <sup>1.2</sup>    |

Note: f is frequency in MHz. \*Based on nerve stimulation (NS)

\*\*Based on specific absorption rate (SAR)

## 5.2 Method

An MPE evaluation was performed in order to show that the device was compliant with FCC §2.1091 and ISSED RSS-102. The maximum power density was calculated for each transmitter at a separation distance of 20 cm. The calculation was performed using the maximum gain from the internal and external antennas declared by the manufacturer.

The maximum permissible exposure (MPE) is predicted by using the following equation:

$$S = PG/4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

## 5.3 Calculation:

For P = 0.312<sup>a)</sup> mW, G = 2.62 dBi (1.8621), R = 20 cm,

$$S = [(0.312) * (1.8621)] / (4 * \pi * 20^2) = 0.0001 \text{ mW/cm}^2 = 0.001 \text{ W/m}^2$$

a): Data was taken from Intertek test report number: 104650309LAX-001

## 5.4 Results:

The sample tested was found to Comply. The calculated maximum power density at 20 cm distance is less than the limits for general population / uncontrolled exposure.

## 6 ISED RSS-102 Issue 5 §2.5.2 Exemption

### 6.1 Requirement(s)

Exemption Limits:  $1.31 \times 10^{-2} f^{-0.6834}$  W (300 MHz  $\leq$  f < 6 GHz), f is in MHz.

### 6.2 Calculation

| Channel Frequency (MHz)                                               | Peak Power <sup>a)</sup> (dBm cond.) | Ant. Gain (dBi) | Peak Power (dBm eirp) | Peak Power (mW eirp) | RSS-102 Exemption Limit (W) | Results   |
|-----------------------------------------------------------------------|--------------------------------------|-----------------|-----------------------|----------------------|-----------------------------|-----------|
| 2402                                                                  | -5.06                                | 2.62            | -2.44                 | 0.57                 | 2.68                        | Compliant |
| 2440                                                                  | -5.93                                | 2.62            | -3.31                 | 0.47                 | 2.71                        | Compliant |
| 2480                                                                  | -6.40                                | 2.62            | -3.78                 | 0.42                 | 2.74                        | Compliant |
| a): Date was taken from Intertek test report number: 104650309LAX-001 |                                      |                 |                       |                      |                             |           |

### 6.3 Results:

The sample tested was found to Comply. The power (e.i.r.p.) is much lower than the exemption limit, RF exposure evaluation is exempted.

**7 Revision History**

| Revision Level | Date       | Report Number    | Prepared<br>By | Reviewed<br>By | Notes          |
|----------------|------------|------------------|----------------|----------------|----------------|
| 0              | 05/05/2021 | 104650309LAX-003 | GL             | US             | Original Issue |