

4

3

1

NOTES: UNLESS OTHERWISE SPECIFIED

I. FCC ID LABEL FOR THE HALO 3 SELECT PRODUCTS.

A. IC: 3022A-HAL3S
WHERE IC --- INDUSTRY CANADA
WHERE 3022A-HAL3S --- INDUSTRY CANADA NUMBER

B. FCC ID: NUL-HAL3S
WHERE NUL --- FIRST THREE CHARACTERS OF GRANTEE CODE
WHERE --- REMAINING NUMBERS/CHARACTERS FCC ID

C. MODEL: HAL3S
WHERE HAL3S --- INTERNAL HHI FCC MODEL NUMBER.

D. LABEL COLOR: BLACK.

E. LABEL MATERIAL:
REFER TO 695-00006-001 FOR LABEL SPECIFICATION.

F. FONT: FIT ON LABEL, WHITE.

G. LABEL LOCATION: REFER TO DRAWING 5053535.

H. ALL DIMENSIONS ARE IN INCHES.

REV	DESCRIPTION	DATE	DRAFTER	ENGINEER	APPROVED
I	PRODUCTION RELEASE PER EO14087-64	06/06/24	L. LIN	T. NGUYEN	BEN. R

MODEL: 9800
FCC ID: NUL-HAL3S

HVIN: HAL3
IC: 3022A-HAL3S

1.38

.20

P/N	DESCRIPTION
5054037	LABEL, FCC, HALO 3

KWIKSET

Spectrum Brands

Hardware & Home Improvement

THIS DOCUMENT IS THE PROPERTY OF SPECTRUM BRANDS, INC AND/OR ITS AFFILIATES. THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO SPECTRUM BRANDS. NEITHER THIS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIZED PERSON, COPIED, OR PUBLISHED WITHOUT SPECTRUM BRANDS' PRIOR WRITTEN CONSENT.

DRAFTER
L. LIN
02/23/23

CHECKED
B. QUACH
02/23/23

ENGINEER
T. NGUYEN
02/23/23

APPROVED
JA. LIN
02/23/23

DATE
02/23/23

DATE
02/23/23

DATE
02/23/23

DATE
02/23/23

SPECTRUM BRANDS, INC HARDWARE AND HOME IMPROVEMENT
19701 DA VINCI, LAKE FOREST, CA 92610

TITLE
LABEL, FCC, HALO 3

SIZE
B

DO NOT SCALE
DRAWING

DWG NO
5054036

RELEASE STATE
Production

SCALE
4 / 1

REV
1

ITER
0

SHEET
1 OF 1

THIRD ANGLE PROJECTION



WS Packaging Group, Inc.[®]

Leaders in Printing and Packaging Worldwide

PRODUCTION SPECIFICATION SHEET

Item Code: R2WPET-PERM-50KRAF-104

Old FAL: 0097-0H52-0002

Total Construction Caliper: 6 mils +/- 10%

FACESHEET: A white topcoated polyester featuring excellent tear strength, heat resistance, dimensional stability, opacity, and chemical resistance. Excellent thermal transfer printability with some resin enhanced wax and most resin based ribbons.

Caliper: 2 mil +/- 10%

ADHESIVE: A high performance permanent adhesive with balanced adhesion to a wide variety of substrates, including low surface energy plastics, engineering grade plastics, bare, coated, or painted metals, including powder coat and enamel paints. It features medium tack and excellent chemical and UV resistance for outdoor industrial applications.

Minimum Application Temperature: +50° F

Service Temperature Range: - 40°F - + 302° F

LINER: A 50# bleached super-calendered paper kraft liner for roll to roll label applications.

Caliper: 3.2 mil +/- 10%

UL and c-UL Recognized.

Shelf Life:

One year when stored at 72°F at 50% RH

All original documents remain on file at WS Packaging Group, Algoma, Wisconsin.

19701 DaVinci
Lake Forest, CA 92610
(T) 949.672.4452

NUL-HAL3S FCC ID Label Location

