

4

3

1

REV	DESCRIPTION	DATE	DRAFTER	ENGINEER	APPROVED
1	PRODUCTION RELEASE PER EO14923-03	10/11/24	P. BECKMAN	J. DAVIS	JA. LIN

NOTES: UNLESS OTHERWISE SPECIFIED

I. FCC ID LABEL FOR THE SBD 10-BUTTON VHC LOCK

A. IC: 3022A-450126HCT
WHERE IC --- INDUSTRY CANADA
WHERE 3022A-450126VHC --- INDUSTRY CANADA NUMBER

B. FCC ID: NUL450126HCT
WHERE NUL --- FIRST THREE CHARACTERS OF GRANTEE CODE
WHERE --- REMAINING NUMBERS/CHARACTERS FCC ID

C. MODEL: 450126VHC
WHERE 450126VHC --- INTERNAL HHI FCC MODEL NUMBER.

D. HVIN: GED1800
WHERE HVIN --- HARDWARE VERSION IDENTIFICATION NUMBER
WHERE GED 1800 --- WEISER MODEL NUMBER


E. LABEL COLOR: BLACK.

F. LABEL MATERIAL:
REFER TO 695-00006-001 FOR LABEL SPECIFICATION

G. FONT: FIT ON LABEL, WHITE.

H. LABEL LOCATION: REFER TO DRAWING 5052244.

1. ALL DIMENSIONS ARE IN INCHES.



Technical drawing of a rectangular label. The label has a width of 1.38 and a height of .20. The text on the label is as follows:

MODEL: 450126VHC	HVIN: GED1800
FCC ID: NUL450126HCT	IC: 3022A-450126HCT

D

D

C

C

B

B

A

A

4

3

2

1

KWIKSET Spectrum Brands Hardware & Home Improvement	THIS DOCUMENT IS THE PROPERTY OF SPECTRUM BRANDS, INC AND/OR ITS AFFILIATES. THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO SPECTRUM BRANDS. NEITHER THIS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIZED PERSON, COPIED, OR PUBLISHED WITHOUT SPECTRUM BRANDS' PRIOR WRITTEN CONSENT.	APPROVED	DATE	SIZE	DO NOT SCALE DRAWING	DWG NO			
		JA. LIN	10/1124	B			5056082		
		THIRD ANGLE PROJECTION		RELEASE STATE			REV		ITER
				Preliminary			A		I
		SCALE		4 / 1		SHEET		1 OF 1	



WS Packaging Group, Inc.[®]

Leaders in Printing and Packaging Worldwide

PRODUCTION SPECIFICATION SHEET

Item Code: R2WPET-PERM-50KRAF-104

Old FAL: 0097-0H52-0002

Total Construction Caliper: 6 mils +/- 10%

FACESHEET: A white topcoated polyester featuring excellent tear strength, heat resistance, dimensional stability, opacity, and chemical resistance. Excellent thermal transfer printability with some resin enhanced wax and most resin based ribbons.

Caliper: 2 mil +/- 10%

ADHESIVE: A high performance permanent adhesive with balanced adhesion to a wide variety of substrates, including low surface energy plastics, engineering grade plastics, bare, coated, or painted metals, including powder coat and enamel paints. It features medium tack and excellent chemical and UV resistance for outdoor industrial applications.

Minimum Application Temperature: +50° F

Service Temperature Range: - 40°F - + 302° F

LINER: A 50# bleached super-calendered paper kraft liner for roll to roll label applications.

Caliper: 3.2 mil +/- 10%

UL and c-UL Recognized.

Shelf Life:

One year when stored at 72°F at 50% RH

All original documents remain on file at WS Packaging Group, Algoma, Wisconsin.



FCC ID: NUL450126HCT
IC:3022A-450126HCT

View of the EUT with no Plastic
Cover and Label Location
HVIN: GED1800