



**FCC CFR47 PART 15 SUBPART C
CERTIFICATION**

TEST REPORT

FOR

802.11 B/G WIRELESS LAN CARD

MODEL NUMBER: TMW1059

FCC ID: NUSTMW1059

REPORT NUMBER: 04I2702-1

ISSUE DATE: MAY 05, 2004

Prepared for

**TOKO INCORPORATED
18, OAZA GOMIGAYA, TSURUGASHIMA-SHI,
SAITAMA-KEN 350-2281
JAPAN**

Prepared by

**COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
3. TEST METHODOLOGY	5
4. FACILITIES AND ACCREDITATION	5
5. CALIBRATION AND UNCERTAINTY.....	6
5.1. MEASURING INSTRUMENT CALIBRATION.....	6
5.2. MEASUREMENT UNCERTAINTY.....	6
5.3. TEST AND MEASUREMENT EQUIPMENT.....	7
6. SETUP OF EQUIPMENT UNDER TEST.....	8
7. APPLICABLE LIMITS AND TEST RESULTS	10
7.1. 6 dB BANDWIDTH.....	10
7.2. 99% BANDWIDTH.....	17
7.3. PEAK OUTPUT POWER.....	24
7.4. AVERAGE POWER.....	32
7.5. PEAK POWER SPECTRAL DENSITY	33
7.6. CONDUCTED SPURIOUS EMISSIONS.....	40
7.7. RADIATED EMISSIONS.....	53
7.7.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	53
7.7.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ	56
7.7.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz.....	74
7.8. POWERLINE CONDUCTED EMISSIONS	75
8. SETUP PHOTOS.....	79

1. TEST RESULT CERTIFICATION

COMPANY NAME: TOKO INCORPORATED
18, OAZA GOMIGAYA, TSURUGASHIMA-SHI,
SAITAMA-KEN 350-2281
JAPAN

EUT DESCRIPTION: 802.11B/G WIRELESS LAN CARD

MODEL: TMW1059

DATE TESTED: MAY 03-04, 2004


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Approved & Released For CCS By:

Tested By:



MICHAEL HECKROTTE
ENGINEERING MANAGER
COMPLIANCE CERTIFICATION SERVICES



CHIN PANG
EMC TECHNICIAN
COMPLIANCE CERTIFICATION SERVICES

2. EUT DESCRIPTION

The EUT is an 802.11b/g Wireless LAN Card in a PCMCIA form factor, operating in the 2400-2483.5MHz Band.

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	21.19	131.52
2412 - 2462	802.11g	22.83	191.87

The radio utilizes an inverted “ F “ type antenna with a maximum peak gain of 2.14 dBi.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4/2001, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.



No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

5. CALIBRATION AND UNCERTAINTY

5.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5.3. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
Quasi-Peak Adaptor	HP	85650A	2811A01155	5/24/2005
SA Display Section 2	HP	85662A	38496	5/24/2005
SA RF Section, 1.5 GHz	HP	85680B	38496	2/22/2005
Preamplifier, 1300MHz	HP	8447D	38405	8/18/2004
Site B Antenna, Bilog	Chase	2944A06589	38217	3/8/2005
LISN, 10 kHz ~ 30 MHz	FCC	50/250-25-2	38419	10/13/2004
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	38273	10/13/2004
EMI Test Receiver	R & S	ESHS 20	38273	7/17/2004
Line Filter	Lindgren	LMF-3489	38185	CNR
Spectrum Analyzer	Agilent	E4446A	US42070220	1/13/2005
Preamplifier, 1 ~ 26 GHz	Miteq	NSP10023988	38365	4/25/2005
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	38467	2/4/2005
2.7GHz HP Filter	MicroTronic	HPM13194	38387	CNR
2.4-2.5GHz Rejector Filter	MicroTronic	BRM50702	1	CNR
4.6GHz HP Filter	Mircrowave	HP4570-9SS	3	CNR

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	IBM	ThinkPad	NA	DoC
AC Adapter	IBM	Made in China	NA	DoC


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US115	UNSHIELDED	1m	3 Prong
2	DC	1	DC	UNSHIELDED	2m	Ferrite on DC output end

TEST SETUP

The EUT is installed in a host laptop computer via a cardbus-to-PCI adapter / extension board during the tests. Test software is used to exercise the radio card.

SETUP DIAGRAM FOR TESTS



7. APPLICABLE LIMITS AND TEST RESULTS

7.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS


No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	11170	500	10670
Middle	2437	11250	500	10750
High	2462	11330	500	10830

802.11g Mode


Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	16330	500	15830
Middle	2437	16250	500	15750
High	2462	16170	500	15670









6 DB BANDWIDTH (802.11g MODE)







7.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

No non-compliance noted:


802.11b Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	14.9657
Middle	2437	14.9987
High	2462	14.9938


802.11g Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.363
Middle	2437	16.3873
High	2462	16.3443


99% BANDWIDTH (802.11b MODE)









99% BANDWIDTH (802.11g MODE)







7.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The maximum antenna gain is 2.14 dBi, therefore the limit is 30Bm.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	20.26	30	-9.74
Middle	2437	21.19	30	-8.81
High	2462	21.01	30	-8.99


802.11g Mode

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	22.51	30	-7.49
Middle	2437	22.83	30	-7.17
High	2462	22.76	30	-7.24


OUTPUT POWER (802.11b MODE)









OUTPUT POWER (802.11g MODE)







7.4. AVERAGE POWER

AVERAGE POWER LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

802.11b Mode

Channel	Frequency (MHz)	Average Power (dBm)
Low	2412	17.43
Middle	2437	17.94
High	2462	17.74

802.11g Mode

Channel	Frequency (MHz)	Average Power (dBm)
Low	2412	15.20
Middle	2437	15.06
High	2462	15.91

7.5. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-1.53	8	-9.53
Middle	2437	-4.98	8	-12.98
High	2462	-2.31	8	-10.31


802.11g Mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-8.97	8	-16.97
Middle	2437	-8.88	8	-16.88
High	2462	-8.95	8	-16.95


PEAK POWER SPECTRAL DENSITY (802.11b MODE)









PEAK POWER SPECTRAL DENSITY (802.11g MODE)







7.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS

No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL (802.11b MODE)










SPURIOUS EMISSIONS, HIGH CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, LOW CHANNEL (802.11g MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11g MODE)





SPURIOUS EMISSIONS, HIGH CHANNEL (802.11g MODE)





7.7. RADIATED EMISSIONS

7.7.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


RESULTS

No non-compliance noted:


7.7.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ


RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)







HARMONICS AND SPURIOUS EMISSIONS (b MODE)


05/03/04 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site															
Test Engr:Chin Pang Project #:04I2702-1 Company:TOKO, Inc EUT Descr:802.11g/b Wireless LAN Card EUT M/N:TMW 1059 (FCC ID: NUSTMW 1059) Test Target:FCC 15.247 Mode Oper:TX, 11b															
Test Equipment:															
EMCO Horn 1-18GHz TS9; S/N: 3245 @3m		Spectrum Analyzer Agilent E4446A Analyzer		Pre-amplifier 1-26GHz T63 Miteq 646456		Pre-amplifier 26-40GHz		Horn >18GHz							
Hi Frequency Cables ☐ (2 ft) ☒ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)															
Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth															
Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth															
f GHz	Dist feet	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	HPF	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes
11b, Transmitting at Low Ch															
4.824	9.8	49.5	36.4	33.1	2.9	-35.3	0.0	1.0	51.1	38.0	74.0	54.0	-22.9	-16.0	V
7.238	9.8	50.0	39.6	35.9	3.7	-34.6	0.0	1.0	55.9	45.5	74.0	54.0	-18.1	-8.5	V
4.824	9.8	47.5	34.0	33.1	2.9	-35.3	0.0	1.0	49.1	35.6	74.0	54.0	-24.9	-18.4	H
7.238	9.8	53.8	44.1	35.9	3.7	-34.6	0.0	1.0	59.7	50.0	74.0	54.0	-14.3	-4.0	H
9.648	9.8	42.0	33.0	37.9	4.3	-33.3	0.0	1.0	51.8	42.8	74.0	54.0	-22.2	-11.2	H
11b, Transmitting at Mid Ch															
4.847	9.8	47.0	35.6	33.1	2.9	-35.3	0.0	1.0	48.7	37.3	74.0	54.0	-25.3	-16.7	V
7.311	9.8	52.5	43.0	36.0	3.7	-34.6	0.0	1.0	58.6	49.1	74.0	54.0	-15.4	-4.9	V
9.748	9.8	43.0	32.0	37.8	4.3	-33.4	0.0	1.0	52.7	41.7	74.0	54.0	-21.3	-12.3	V
4.847	9.8	46.0	34.2	33.1	2.9	-35.3	0.0	1.0	47.7	35.9	74.0	54.0	-26.3	-18.1	H
7.311	9.8	51.7	42.2	36.0	3.7	-34.6	0.0	1.0	57.8	48.3	74.0	54.0	-16.2	-5.7	H
9.748	9.8	40.0	31.9	37.8	4.3	-33.4	0.0	1.0	49.7	41.6	74.0	54.0	-24.3	-12.4	H
11b, Transmitting at High Ch															
4.923	9.8	51.0	38.0	33.1	3.0	-35.3	0.0	1.0	52.8	39.8	74.0	54.0	-21.2	-14.2	V
7.384	9.8	52.3	41.8	36.1	3.7	-34.5	0.0	1.0	58.5	48.0	74.0	54.0	-15.5	-6.0	V
4.923	9.8	47.0	35.0	33.1	3.0	-35.3	0.0	1.0	48.8	36.8	74.0	54.0	-25.2	-17.2	H
7.384	9.8	50.0	40.0	36.1	3.7	-34.5	0.0	1.0	56.2	46.2	74.0	54.0	-17.8	-7.8	H
NO OTHER SPURIOUS EMISSIONS DETECTED ABOVE THE SYSTEM NOISE FLOOR IN THE RESTRICTED BAND -20dB TO THE LIMIT															
f	Measurement Frequency			Amp	Preamp Gain			Avg Lim	Average Field Strength Limit						
Dist	Distance to Antenna			D Corr	Distance Correct to 3 meters			Pk Lim	Peak Field Strength Limit						
Read	Analyzer Reading			Avg	Average Field Strength @ 3 m			Avg Mar	Margin vs. Average Limit						
AF	Antenna Factor			Peak	Calculated Peak Field Strength			Pk Mar	Margin vs. Peak Limit						
CL	Cable Loss			HPF	High Pass Filter										


RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS (g MODE)

05/03/04 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site Test Engr:Chin Pang Project #:04I2702-1 Company:TOKO, Inc EUT Descip.:802.11g/b Wireless LAN Card EUT M/N:TMW 1059 (FCC ID: NUSTMW 1059) Test Target:FCC 15.247 Mode Oper:TX, 11g Test Equipment: <table border="1"><tr><td>EMCO Horn 1-18GHz T59; S/N: 3245 @3m</td><td>Spectrum Analyzer Agilent E4446A Analyzer</td><td>Pre-amplifier 1-26GHz T63 Miteq 646456</td><td>Pre-amplifier 26-40GHz</td><td>Horn > 18GHz</td></tr></table> <table border="1"><tr><td colspan="4">Hi Frequency Cables ☐ (2 ft) ☒ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)</td><td colspan="2">Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth</td><td colspan="2">Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth</td></tr></table>																	EMCO Horn 1-18GHz T59; S/N: 3245 @3m	Spectrum Analyzer Agilent E4446A Analyzer	Pre-amplifier 1-26GHz T63 Miteq 646456	Pre-amplifier 26-40GHz	Horn > 18GHz	Hi Frequency Cables ☐ (2 ft) ☒ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)				Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth		Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth	
EMCO Horn 1-18GHz T59; S/N: 3245 @3m	Spectrum Analyzer Agilent E4446A Analyzer	Pre-amplifier 1-26GHz T63 Miteq 646456	Pre-amplifier 26-40GHz	Horn > 18GHz																									
Hi Frequency Cables ☐ (2 ft) ☒ (2 ~ 3 ft) ☐ (4 ~ 6 ft) ☒ (12 ft)				Peak Measurements: 1 MHz Resolution Bandwidth 1MHz Video Bandwidth		Average Measurements: 1 MHz Resolution Bandwidth 10Hz Video Bandwidth																							
f GHz	Dist feet	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	HPF	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes														
11g, Transmitting at Low Ch Art setting 15.5dBm																													
4.824	9.8	46.0	34.5	33.1	2.9	-35.3	0.0	1.0	47.6	36.1	74.0	54.0	-26.4	-17.9	V														
7.238	9.8	50.2	38.4	35.9	3.7	-34.6	0.0	1.0	56.1	44.3	74.0	54.0	-17.9	-9.7	V														
4.824	9.8	45.0	32.4	33.1	2.9	-35.3	0.0	1.0	46.6	34.0	74.0	54.0	-27.4	-20.0	H														
7.238	9.8	54.2	42.4	35.9	3.7	-34.6	0.0	1.0	60.1	48.3	74.0	54.0	-13.9	-5.7	H														
11g, Transmitting at Mid Ch Art setting 15.5dBm																													
4.874	9.8	48.0	35.4	33.1	2.9	-35.3	0.0	1.0	49.7	37.1	74.0	54.0	-24.3	-16.9	V														
7.311	9.8	53.8	41.0	36.0	3.7	-34.6	0.0	1.0	59.9	47.1	74.0	54.0	-14.1	-6.9	V														
9.748	9.8	45.0	33.0	37.8	4.3	-33.4	0.0	1.0	54.7	42.7	74.0	54.0	-19.3	-11.3	V														
4.874	9.8	46.0	34.2	33.1	2.9	-35.3	0.0	1.0	47.7	35.9	74.0	54.0	-26.3	-18.1	H														
7.311	9.8	52.8	40.0	36.0	3.7	-34.6	0.0	1.0	58.9	46.1	74.0	54.0	-15.1	-7.9	H														
11g, Transmitting at High Ch, Art Setting 15.5dBm																													
4.924	9.8	48.3	35.0	33.1	3.0	-35.3	0.0	1.0	50.1	36.8	74.0	54.0	-23.9	-17.2	V														
7.384	9.8	55.8	41.8	36.1	3.7	-34.5	0.0	1.0	62.0	48.0	74.0	54.0	-12.0	-6.0	V														
4.924	9.8	47.0	35.0	33.1	3.0	-35.3	0.0	1.0	48.8	36.8	74.0	54.0	-25.2	-17.2	H														
7.384	9.8	56.0	42.0	36.1	3.7	-34.5	0.0	1.0	62.2	48.2	74.0	54.0	-11.8	-5.8	H														
NO OTHER SPURIOUS EMISSIONS DETECTED ABOVE THE SYSTEM NOISE FLOOR IN THE RESTRICTED BAND -20dB TO THE LIMIT																													
No other spurious emissions were detected above system noise floor.																													
f	Measurement Frequency			Amp	Preamp Gain			Avg Lim	Average Field Strength Limit																				
Dist	Distance to Antenna			D Corr	Distance Correct to 3 meters			Pk Lim	Peak Field Strength Limit																				
Read	Analyzer Reading			Avg	Average Field Strength @ 3 m			Avg Mar	Margin vs. Average Limit																				
AF	Antenna Factor			Peak	Calculated Peak Field Strength			Pk Mar	Margin vs. Peak Limit																				
CL	Cable Loss			HPF	High Pass Filter																								

7.7.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION,)

						Project #: 04I2702-1 Report #: 040504B1 Date & Time: 05/04/04 10:07 AM Test Engr: Chin Pang	
FCC, VCCI, CISPR, CE, AUSTEL, NZ UL, CSA, TUV, BSMI, DHHS, NVLAP 561F MONTEREY ROAD, SAN JOSE, CA 95037-9001 PHONE: (408) 463-0885 FAX: (408) 463-0888							
Company: TOKO, INC.							
EUT Description: 802.11b/g Wireless LAN Card							
Test Configuration : EUT/Laptop/AC Adapter							
Type of Test: FCC Class B							
Mode of Operation: TX (WORST CASE)							
<< Main Sheet							

Freq. (MHz)	Reading (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Level (dBuV/m)	Limit FCC_B	Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)	Mark (P/Q/A)
180.00	53.40	9.26	3.09	28.82	36.93	43.50	-6.57	3mV	0.00	1.00	P
72.00	53.80	6.49	1.77	29.20	32.85	40.00	-7.15	3mV	0.00	1.00	P
171.80	52.80	9.54	2.89	28.90	36.33	43.50	-7.17	3mH	0.00	1.50	P
364.50	48.10	14.70	4.57	28.71	38.66	46.00	-7.34	3mH	0.00	1.50	P
430.00	45.30	16.35	5.11	28.98	37.77	46.00	-8.23	3mV	0.00	1.50	P
80.00	51.90	7.05	1.94	29.30	31.59	40.00	-8.41	3mH	0.00	1.50	P
6 Worst Data											

7.8. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.


RESULTS

No non-compliance noted:


6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	EN B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.21	54.95	--	42.47	0.00	64.37	54.37	-9.42	-11.90	L1
0.28	45.24	--	35.84	0.00	62.40	52.40	-17.16	-16.56	L1
5.84	38.50	--	27.84	0.00	60.00	50.00	-21.50	-22.16	L1
0.21	52.18	--	41.03	0.00	64.34	54.34	-12.16	-13.31	L2
0.28	44.35	--	33.98	0.00	62.37	52.37	-18.02	-18.39	L2
6.19	40.74	--	26.19	0.00	60.00	50.00	-19.26	-23.81	L2
6 Worst Data									

LINE 1 RESULTS




LINE 2 RESULTS



8. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SETUP



RADIATED BACK PHOTO



POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP



LINE CONDUCTED BACK PHOTO



END OF REPORT