

FCC TEST REPORT

REPORT NO.: RF940512L04

MODEL NO.: CS8043, CS8044, CS8055

RECEIVED: May 12, 2005

TESTED: May 30 ~ Jun. 02, 2005

ISSUED: Jun. 17, 2005

APPLICANT: In-Tech Electronics Ltd.

ADDRESS: 207-210, 2F., Century Centre, 44-46 Hung To Road, Kwun Tong, Kowloon, Hong Kong

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 77 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



NO. 2177-01



0528
ILAC MRA

TABLE OF CONTENTS

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY.....	6
3.	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST.....	9
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	11
3.3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	13
3.3.4	DESCRIPTION OF SUPPORT UNITS.....	13
4.	TEST TYPES AND RESULTS	14
4.1	CONDUCTED EMISSION MEASUREMENT	14
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
4.1.2	TEST INSTRUMENTS	14
4.1.3	TEST PROCEDURES	15
4.1.4	DEVIATION FROM TEST STANDARD	15
4.1.5	TEST SETUP	16
4.1.6	EUT OPERATING CONDITIONS.....	17
4.1.7	TEST RESULTS	18
4.2	RADIATED EMISSION MEASUREMENT	36
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	36
4.2.2	TEST INSTRUMENTS	37
4.2.3	TEST PROCEDURES	38
4.2.4	DEVIATION FROM TEST STANDARD	38
4.2.5	TEST SETUP	39
4.2.6	EUT OPERATING CONDITIONS.....	39
4.2.7	TEST RESULTS	40
4.3	NUMBER OF HOPPING FREQUENCY USED	46
4.3.1	LIMIT OF HOPPING FREQUENCY USED	46
4.3.2	TEST INSTRUMENTS	46
4.3.3	TEST PROCEDURES	46
4.3.4	DEVIATION FROM TEST STANDARD	47
4.3.5	TEST SETUP	47
4.3.6	TEST RESULTS	47
4.4	DWELL TIME ON EACH CHANNEL	49
4.4.1	LIMIT OF DWELL TIME USED	49
4.4.2	TEST INSTRUMENTS	49
4.4.3	TEST PROCEDURES	49
4.4.4	DEVIATION FROM TEST STANDARD	49
4.4.5	TEST SETUP	50



4.4.6	TEST RESULTS	50
4.5	CHANNEL BANDWIDTH	54
4.5.1	LIMITS OF CHANNEL BANDWIDTH	54
4.5.2	TEST INSTRUMENTS	54
4.5.3	TEST PROCEDURE	54
4.5.4	DEVIATION FROM TEST STANDARD	55
4.5.5	TEST SETUP	55
4.5.6	EUT OPERATING CONDITION	55
4.5.7	TEST RESULTS	55
4.6	HOPPING CHANNEL SEPARATION	58
4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	58
4.6.2	TEST INSTRUMENTS.....	58
4.6.3	TEST PROCEDURES	58
4.6.4	DEVIATION FROM TEST STANDARD	59
4.6.5	TEST SETUP.....	59
4.6.6	TEST RESULTS	59
4.7	MAXIMUM PEAK OUTPUT POWER.....	62
4.7.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	62
4.7.2	TEST INSTRUMENTS.....	62
4.7.3	TEST PROCEDURES	62
4.7.4	DEVIATION FROM TEST STANDARD	62
4.7.5	TEST SETUP	63
4.7.6	EUT OPERATING CONDITION	63
4.7.7	TEST RESULTS	63
4.8	BAND EDGES MEASUREMENT	66
4.8.1	LIMITS OF BAND EDGES MEASUREMENT	66
4.8.2	TEST INSTRUMENTS.....	66
4.8.3	TEST PROCEDURE.....	66
4.8.4	DEVIATION FROM TEST STANDARD	66
4.8.5	EUT OPERATING CONDITION	66
4.8.6	TEST RESULTS	67
4.9	ANTENNA REQUIREMENT	70
4.9.1	STANDARD APPLICABLE	70
4.9.2	ANTENNA CONNECTED CONSTRUCTION.....	70
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	71
6.	INFORMATION ON THE TESTING LABORATORIES	77



1. CERTIFICATION

PRODUCT: BT Stereo Pendant (Refer to page 7 for more info)
MODEL NO.: CS8043 (Refer to page 7 for more info)
BRAND NAME: In-Tech
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: May 30 ~ Jun. 02, 2005
APPLICANT: In-Tech Electronics Ltd.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: CS8043, CS8044, CS8055) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Wendy Liao , **DATE:** Jun. 17, 2005
Wendy Liao

TECHNICAL
ACCEPTANCE : Gary Chang , **DATE:** Jun. 17, 2005
Responsible for RF Gary Chang

APPROVED BY : Cody Chang , **DATE:** Jun. 17, 2005
Cody Chang / Deputy Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -13.23dB at 0.502MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit
15.247(a)(1)(iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -6.70 dB at 166.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~ 1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	BT Stereo Pendant
MODEL NO.	CS8043
POWER SUPPLY	3.7Vdc from rechargeable lithium battery 5Vdc from AC adapter
MODULATION TYPE	GFSK
RADIO TECHNOLOGY	FHSS
TRANSFER RATE	723Kbps
FREQUENCY RANGE	2400 ~ 2483.5 MHz
NUMBER OF CHANNEL	79
OUTPUT POWER	1.089 mW
ANTENNA TYPE	Ceramic antenna with 1.0dBi gain
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was operated with following power adapter:

BRAND:	PI Electronics Ltd.
MODEL:	P925BW05050AB67
INPUT:	100-240Vac, 50-60Hz, 0.1A
OUTPUT:	5Vdc, 500mA
POWER LINE:	DC 1.4 m non-shielded cable without core

2. The models as below are used the same PCB, the difference are their model designation, brand name, product name and appearance due to marketing requirement.

BRAND	PRODUCT NAME	MODEL	REMARK
In-Tech	BT Stereo Pendant	CS8043	With audio out port, and pendant
In-Tech	BT Stereo Headset	CS8044	With audio out port, and headset
In-Tech	BT Stereo Audio Adaptor	CS8055	With audio in port

3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES


Since the EUT is considered a portable unit, it was pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane. Therefore only the test data of this X-plane was used for radiated test.

79 channels are provided to this EUT:


CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST


TEST MODE A



TEST MODE B



TEST MODE C



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT CONFIGURE MODE	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	√	√	NOTE 1	NOTE 2	Model no.: CS8043
B	√	√	NOTE 1	NOTE 2	Model no.: CS8044
C	√	√	NOTE 1	NOTE 2	Model no.: CS8055

Where **PLC**: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

NOTE: 1. No effect on Radiated Emission above 1GHz.

2. No effect on Conducted RF measurement.

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
B	0 to 78	0, 39, 78	FHSS	GFSK	DH5
C	0 to 78	0, 39, 78	FHSS	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, antenna ports (if EUT with antenna diversity architecture), and X, Y, Z Axis, and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	AXIS
A	0 to 78	78	FHSS	GFSK	DH5	X
B	0 to 78	78	FHSS	GFSK	DH5	X
C	0 to 78	78	FHSS	GFSK	DH5	X

**RADIATED EMISSION TEST (ABOVE 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, antenna ports (if EUT with antenna diversity architecture), and X, Y, Z Axis, and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	AXIS
0 to 78	0, 39, 78	FHSS	GFSK	DH5	X

BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 78	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5



3.3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a BT Stereo Pendant. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	25191592336	E2K24CLNS
2	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m shielded cable without core
3	1.2 m shielded cable without core

NOTE: All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 06, 2005
RF signal cable Woken	5D-FB	Cable-HyC02-01	Jan. 09, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 20, 2006
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 20, 2006
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 3.
 3. The VCCI Site Registration No. is C-2047.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:** 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.6 EUT OPERATING CONDITIONS

TEST MODE A & B:

- a. Placed the EUT on a testing table.

TEST MODE C:

- a. Connected the EUT to a notebook system and placed on a testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The notebook system sent "H" messages to its screen.
- d. The notebook system sent "H" messages to modem.
- e. The notebook system sent "H" messages to printer, and the printer printed them on paper.
- f. Steps c ~ e were repeated.


4.1.7 TEST RESULTS

CONDUCTED WORST CASE DATA:

EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 1
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.252	0.10	44.32	42.84	44.42	42.94	61.71	51.71	-17.29	-8.77
2	0.502	0.12	42.22	41.79	42.34	41.91	56.00	46.00	-13.66	-4.09
3	0.752	0.16	31.81	-	31.97	-	56.00	46.00	-24.03	-
4	4.261	0.20	25.02	-	25.22	-	56.00	46.00	-30.78	-
5	5.764	0.23	22.53	-	22.76	-	60.00	50.00	-37.24	-
6	11.047	0.32	25.77	-	26.09	-	60.00	50.00	-33.91	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 2
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.252	0.10	45.69	44.69	45.79	44.79	61.71	51.71	-15.92	-6.92
2	0.503	0.12	41.91	40.20	42.03	40.32	56.00	46.00	-13.97	-5.68
3	1.003	0.20	34.28	-	34.48	-	56.00	46.00	-21.52	-
4	3.504	0.20	27.89	-	28.09	-	56.00	46.00	-27.91	-
5	5.762	0.26	25.02	-	25.28	-	60.00	50.00	-34.72	-
6	11.246	0.42	20.43	-	20.85	-	60.00	50.00	-39.15	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 1
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.248	0.10	42.84	41.21	42.94	41.31	61.84	51.84	-18.90	-10.53
2	0.502	0.12	42.65	41.71	42.77	41.83	56.00	46.00	-13.23	-4.17
3	0.752	0.16	31.83	-	31.99	-	56.00	46.00	-24.01	-
4	1.254	0.20	31.26	-	31.46	-	56.00	46.00	-24.54	-
5	3.510	0.20	28.20	-	28.40	-	56.00	46.00	-27.60	-
6	10.980	0.32	24.63	-	24.95	-	60.00	50.00	-35.05	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 2
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.252	0.10	45.75	44.79	45.85	44.89	61.71	51.71	-15.86	-6.82
2	0.502	0.12	42.45	40.85	42.57	40.97	56.00	46.00	-13.43	-5.03
3	0.752	0.16	33.66	-	33.82	-	56.00	46.00	-22.18	-
4	1.253	0.20	32.45	-	32.65	-	56.00	46.00	-23.35	-
5	2.754	0.20	29.00	-	29.20	-	56.00	46.00	-26.80	-
6	11.020	0.42	25.89	-	26.31	-	60.00	50.00	-33.69	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 1
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.248	0.10	42.90	41.45	43.00	41.55	61.84	51.84	-18.84	-10.29
2	0.499	0.12	42.26	-	42.38	-	56.01	46.01	-13.64	-4.62
3	1.004	0.20	29.45	-	29.65	-	56.00	46.00	-26.35	-
4	3.512	0.20	28.44	-	28.64	-	56.00	46.00	-27.36	-
5	5.760	0.23	24.45	-	24.68	-	60.00	50.00	-35.32	-
6	11.030	0.32	25.18	-	25.50	-	60.00	50.00	-34.50	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	PHASE	Line 2
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.252	0.10	45.69	44.69	45.79	44.79	61.71	51.71	-15.92	-6.92
2	0.502	0.12	42.31	40.67	42.43	40.79	56.00	46.00	-13.57	-5.21
3	1.004	0.20	34.08	-	34.28	-	56.00	46.00	-21.72	-
4	1.250	0.20	32.61	-	32.81	-	56.00	46.00	-23.19	-
5	5.758	0.26	25.66	-	25.92	-	60.00	50.00	-34.08	-
6	11.506	0.43	22.40	-	22.83	-	60.00	50.00	-37.17	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 1
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.298	0.10	37.13	-	37.23	-	60.29	50.29	-23.06	-
2	0.580	0.13	37.64	26.60	37.77	26.73	56.00	46.00	-18.23	-19.27
3	1.195	0.20	30.95	-	31.15	-	56.00	46.00	-24.85	-
4	1.656	0.20	31.83	-	32.03	-	56.00	46.00	-23.97	-
5	2.074	0.20	34.89	-	35.09	-	56.00	46.00	-20.91	-
6	11.000	0.32	28.56	-	28.88	-	60.00	50.00	-31.12	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value.
5. Correction factor = Insertion loss + Cable loss.
6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 2
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.599	0.13	33.02	-	33.15	-	56.00	46.00	-22.85	-
2	0.748	0.16	32.67	-	32.83	-	56.00	46.00	-23.17	-
3	1.188	0.20	32.62	-	32.82	-	56.00	46.00	-23.18	-
4	1.582	0.20	33.36	-	33.56	-	56.00	46.00	-22.44	-
5	2.465	0.20	33.96	-	34.16	-	56.00	46.00	-21.84	-
6	10.742	0.41	27.54	-	27.95	-	60.00	50.00	-32.05	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 1
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.595	0.13	31.32	-	31.45	-	56.00	46.00	-24.55	-
2	1.633	0.20	31.30	-	31.50	-	56.00	46.00	-24.50	-
3	2.074	0.20	32.03	-	32.23	-	56.00	46.00	-23.77	-
4	3.309	0.20	27.56	-	27.76	-	56.00	46.00	-28.24	-
5	4.008	0.20	29.76	-	29.96	-	56.00	46.00	-26.04	-
6	10.840	0.32	29.32	-	29.64	-	60.00	50.00	-30.36	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 2
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.595	0.13	33.43	-	33.56	-	56.00	46.00	-22.44	-
2	0.748	0.16	32.60	-	32.76	-	56.00	46.00	-23.24	-
3	1.176	0.20	31.60	-	31.80	-	56.00	46.00	-24.20	-
4	1.605	0.20	33.61	-	33.81	-	56.00	46.00	-22.19	-
5	2.477	0.20	33.07	-	33.27	-	56.00	46.00	-22.73	-
6	2.883	0.20	31.68	-	31.88	-	56.00	46.00	-24.12	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value.
5. Correction factor = Insertion loss + Cable loss.
6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 1
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.580	0.13	35.91	26.45	36.04	26.58	56.00	46.00	-19.96	-19.42
2	0.740	0.16	32.76	-	32.92	-	56.00	46.00	-23.08	-
3	1.188	0.20	29.95	-	30.15	-	56.00	46.00	-25.85	-
4	1.641	0.20	32.53	-	32.73	-	56.00	46.00	-23.27	-
5	2.090	0.20	33.43	-	33.63	-	56.00	46.00	-22.37	-
6	2.457	0.20	30.25	-	30.45	-	56.00	46.00	-25.55	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	PHASE	Line 2
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.10	46.77	37.49	46.87	37.59	66.00	56.00	-19.13	-18.41
2	0.298	0.10	38.65	-	38.75	-	60.29	50.29	-21.54	-
3	1.184	0.20	32.54	-	32.74	-	56.00	46.00	-23.26	-
4	1.598	0.20	33.44	-	33.64	-	56.00	46.00	-22.36	-
5	2.031	0.20	33.01	-	33.21	-	56.00	46.00	-22.79	-
6	2.461	0.20	34.04	-	34.24	-	56.00	46.00	-21.76	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 1
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.244	0.10	42.55	41.52	42.65	41.62	61.97	51.97	-19.32	-10.35
2	0.494	0.12	39.19	39.30	39.31	38.42	56.10	46.10	-16.80	-7.69
3	0.982	0.20	30.57	-	30.77	-	56.00	46.00	-25.23	-
4	4.184	0.20	28.30	-	28.50	-	56.00	46.00	-27.50	-
5	7.119	0.25	24.30	-	24.55	-	60.00	50.00	-35.45	-
6	10.077	0.30	27.45	-	27.75	-	60.00	50.00	-32.25	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value.
5. Correction factor = Insertion loss + Cable loss.
6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 2
CHANNEL	Channel 0	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.246	0.10	44.28	42.60	44.38	42.70	61.88	51.88	-17.50	-9.18
2	0.491	0.12	40.07	37.96	40.19	38.08	56.15	46.15	-15.96	-8.07
3	0.979	0.20	34.38	-	34.58	-	56.00	46.00	-21.42	-
4	1.227	0.20	31.88	-	32.08	-	56.00	46.00	-23.92	-
5	2.697	0.20	28.62	-	28.82	-	56.00	46.00	-27.18	-
6	10.527	0.41	26.60	-	27.01	-	60.00	50.00	-32.99	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 1
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.244	0.10	42.59	41.67	42.69	41.77	61.97	51.97	-19.28	-10.20
2	0.490	0.11	41.83	40.17	41.94	40.28	56.17	46.17	-14.23	-5.89
3	0.978	0.20	30.61	-	30.81	-	56.00	46.00	-25.19	-
4	2.684	0.20	26.23	-	26.43	-	56.00	46.00	-29.57	-
5	7.105	0.25	23.59	-	23.84	-	60.00	50.00	-36.16	-
6	11.740	0.33	20.29	-	20.62	-	60.00	50.00	-39.38	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 2
CHANNEL	Channel 39	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.248	0.10	43.49	41.67	43.59	41.77	61.84	51.84	-18.25	-10.07
2	0.494	0.12	38.39	35.58	38.51	35.70	56.10	46.10	-17.60	-10.41
3	0.978	0.20	34.48	-	34.68	-	56.00	46.00	-21.32	-
4	1.473	0.20	30.24	-	30.44	-	56.00	46.00	-25.56	-
5	5.648	0.25	26.51	-	26.76	-	60.00	50.00	-33.24	-
6	10.793	0.42	23.82	-	24.24	-	60.00	50.00	-35.76	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 1
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.244	0.10	42.57	41.67	42.67	41.77	61.97	51.97	-19.30	-10.20
2	0.490	0.11	41.52	40.21	41.63	40.32	56.17	46.17	-14.54	-5.85
3	0.978	0.20	30.53	-	30.73	-	56.00	46.00	-25.27	-
4	4.172	0.20	27.89	-	28.09	-	56.00	46.00	-27.91	-
5	5.645	0.23	25.10	-	25.33	-	60.00	50.00	-34.67	-
6	11.250	0.32	24.94	-	25.26	-	60.00	50.00	-34.74	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	PHASE	Line 2
CHANNEL	Channel 78	6dB BANDWIDTH	9 kHz
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	22deg. C, 62%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

NO	FREQ. [MHz]	CORR. FACTOR (dB)	READING VALUE [dB (uV)]		EMISSION LEVEL [dB (uV)]		LIMIT [dB (uV)]		MARGIN (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.248	0.10	43.27	41.37	43.37	41.47	61.84	51.84	-18.47	-10.37
2	0.490	0.11	40.14	38.03	40.25	38.14	56.17	46.17	-15.92	-8.03
3	0.986	0.20	30.93	-	31.13	-	56.00	46.00	-24.87	-
4	2.688	0.20	28.88	-	29.08	-	56.00	46.00	-26.92	-
5	6.112	0.27	22.47	-	22.74	-	60.00	50.00	-37.26	-
6	10.754	0.42	26.55	-	26.97	-	60.00	50.00	-33.03	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value.
 5. Correction factor = Insertion loss + Cable loss.
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 07, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Nov. 29, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170242	Jan. 23, 2006
Preamplifier Agilent	8447D	2944A10631	Nov. 17, 2005
Preamplifier Agilent	8449B	3008A01960	Nov. 14, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Jan. 26, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219275/4	Jan. 26, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The IC Site Registration No. is IC4924-4.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 5.1.6

4.2.7 TEST RESULTS

RADIATED WORST CASE DATA:

EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 78	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa
TEST MODE	A	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	20.80 QP	40.00	-19.20	1.25 H	358	6.79	14.01
2	144.69	29.30 QP	43.50	-14.20	1.25 H	151	14.75	14.56
3	175.79	30.34 QP	43.50	-13.16	1.25 H	277	17.01	13.33
4	206.89	24.92 QP	43.50	-18.58	1.00 H	256	13.50	11.42
5	595.67	27.01 QP	46.00	-18.99	1.25 H	82	6.30	20.71
6	768.68	26.61 QP	46.00	-19.39	1.00 H	106	3.29	23.32

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	27.04 QP	40.00	-12.96	1.00 V	184	13.03	14.01
2	70.82	22.92 QP	40.00	-17.08	1.00 V	139	10.66	12.27
3	101.92	30.70 QP	43.50	-12.80	1.00 V	154	19.60	11.10
4	164.13	35.39 QP	43.50	-8.11	1.00 V	136	20.87	14.52
5	407.11	27.44 QP	46.00	-18.56	1.00 V	139	10.53	16.91
6	931.96	27.59 QP	46.00	-18.41	1.00 V	37	2.44	25.14

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT	BT Stereo Headset	MEASUREMENT DETAIL	
MODEL	CS8044	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 78	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa
TEST MODE	B	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.80	22.50 QP	40.00	-17.50	1.50 H	31	8.34	14.16
2	151.40	27.90 QP	43.50	-15.60	1.00 H	352	13.17	14.72
3	185.20	31.50 QP	43.50	-12.00	1.00 H	251	19.02	12.48
4	199.10	25.10 QP	43.50	-18.40	1.25 H	32	13.76	11.34
5	499.50	23.50 QP	46.00	-22.50	1.00 H	252	4.94	18.56
6	795.10	25.40 QP	46.00	-20.60	1.50 H	315	1.96	23.44

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.50	28.20 QP	40.00	-11.80	1.00 V	137	14.10	14.10
2	85.10	23.80 QP	40.00	-16.20	1.00 V	122	13.82	9.98
3	98.50	31.80 QP	43.50	-11.70	1.00 V	162	21.01	10.79
4	155.20	34.20 QP	43.50	-9.30	1.00 V	68	19.38	14.82
5	398.50	28.40 QP	46.00	-17.60	1.25 V	311	11.71	16.69
6	698.80	28.40 QP	46.00	-17.60	1.50 V	139	6.40	22.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	BT Stereo Audio Adapter	MEASUREMENT DETAIL	
MODEL	CS8055	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 78	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa
TEST MODE	C	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Long Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.50	22.00 QP	40.00	-18.00	1.25 H	331	7.72	14.28
2	145.50	31.20 QP	43.50	-12.30	1.25 H	136	16.62	14.58
3	176.50	33.20 QP	43.50	-10.30	1.50 H	285	19.94	13.26
4	200.50	25.50 QP	43.50	-18.00	1.25 H	335	14.22	11.28
5	601.00	28.90 QP	46.00	-17.10	1.50 H	305	8.06	20.84
6	764.10	29.50 QP	46.00	-16.50	1.25 H	22	6.20	23.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.20	28.50 QP	40.00	-11.50	1.00 V	253	14.45	14.05
2	71.50	23.80 QP	40.00	-16.20	1.00 V	152	11.71	12.09
3	102.20	31.80 QP	43.50	-11.70	1.00 V	177	20.68	11.12
4	166.00	36.80 QP	43.50	-6.70	1.00 V	122	22.47	14.33
5	405.20	29.50 QP	46.00	-16.50	1.00 V	335	12.64	16.86
6	551.00	32.80 QP	46.00	-13.20	1.25 V	251	13.31	19.49

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa	TESTED BY	Morgan

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1601.00	42.86 PK	74.00	-31.14	1.00 H	345	13.52	29.34
2	2390.00	56.57 PK	74.00	-17.43	1.00 H	20	24.70	31.87
2	2390.00	44.57 AV	54.00	-9.43	1.00 H	20	12.70	31.87
3	*2402.00	100.51 PK			1.00 H	360	68.59	31.92
3	*2402.00	70.51 AV			1.00 H	360	38.59	31.92
4	4804.00	51.28 PK	74.00	-22.72	1.20 H	174	13.51	37.77
4	4804.00	21.28 AV	54.00	-32.72	1.20 H	174	-16.49	37.77

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1601.00	43.86 PK	74.00	-30.14	1.29 V	314	14.52	29.34
2	2390.00	52.31 PK	74.00	-21.69	1.13 V	8	20.44	31.87
2	2390.00	40.31 AV	54.00	-13.69	1.13 V	8	8.44	31.87
3	*2402.00	96.25 PK			1.13 V	8	64.33	31.92
3	*2402.00	66.25 AV			1.13 V	8	34.33	31.92
4	4804.00	57.58 PK	74.00	-16.42	1.26 V	307	19.81	37.77
4	4804.00	27.58 AV	54.00	-26.42	1.26 V	307	-10.19	37.77

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 247 ms per channel. Therefore, the duty cycle be equal to: $20\log(3.125/100) = -30$ dB.
 6. Average value = peak reading $-20\log(\text{duty cycle})$.

EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa	TESTED BY	Morgan

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1627.00	42.98 PK	74.00	-31.02	1.07 H	312	13.57	29.41
2	*2441.00	100.57 PK			1.45 H	294	68.50	32.07
2	*2441.00	70.57 AV			1.45 H	294	38.50	32.07
3	4882.00	51.32 PK	74.00	-22.68	1.20 H	159	13.31	38.01
3	4882.00	21.32 AV	54.00	-32.68	1.20 H	159	-16.69	38.01

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1627.00	43.97 PK	74.00	-30.03	1.31 V	12	14.56	29.41
2	*2441.00	96.72 PK			1.15 V	16	64.65	32.07
2	*2441.00	66.72 AV			1.15 V	16	34.65	32.07
3	4882.00	58.36 PK	74.00	-15.64	1.27 V	15	20.35	38.01
3	4882.00	28.36 AV	54.00	-25.64	1.27 V	15	-9.65	38.01

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 247 ms per channel. Therefore, the duty cycle be equal to: $20\log(3.125/100) = -30$ dB.
 6. Average value = peak reading $-20\log(\text{duty cycle})$.

EUT	BT Stereo Pendant	MEASUREMENT DETAIL	
MODEL	CS8043	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	GFSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	23deg. C, 64%RH, 991hPa	TESTED BY	Morgan

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	43.88 PK	74.00	-30.12	1.01 H	257	14.40	29.48
2	*2480.00	101.01 PK			1.48 H	280	68.78	32.23
2	*2480.00	71.01 AV			1.48 H	280	38.78	32.23
3	2483.50	55.41 PK	74.00	-18.59	1.48 H	280	23.17	32.24
3	2483.50	43.41 AV	54.00	-10.59	1.48 H	280	11.17	32.24
4	4960.00	52.38 PK	74.00	-21.62	1.23 H	167	14.13	38.25
4	4960.00	22.38 AV	54.00	-31.62	1.23 H	167	-15.87	38.25

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1653.00	44.96 PK	74.00	-29.04	1.28 V	315	15.48	29.48
2	*2480.00	96.78 PK			1.16 V	325	64.55	32.23
2	*2480.00	66.78 AV			1.16 V	325	34.55	32.23
3	2483.50	51.18 PK	74.00	-22.82	1.16 V	325	18.94	32.24
3	2483.50	39.18 AV	54.00	-14.82	1.16 V	325	6.94	32.24
4	4960.00	58.62 PK	74.00	-15.38	1.24 V	125	20.37	38.25
4	4960.00	28.62 AV	54.00	-25.38	1.24 V	125	-9.63	38.25

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 247 ms per channel. Therefore, the duty cycle be equal to: $20\log(3.125/100) = -30$ dB.
 6. Average value = peak reading $-20\log(\text{duty cycle})$.



4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURES

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD



No deviation.

4.3.5 TEST SETUP



4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP





4.4.6 TEST RESULTS



MODE	NUMBER OF TRANSMISSION IN A 31.6 (79HOPPING * 0.4)	LENGTH OF TRANSMISSION TIME (msec)	RESULT (msec)	LIMIT (msec)
DH1	50 (times / 5 sec) * 6.32 = 316.00 times	0.440	139.04	400
DH3	26 (times / 5 sec) * 6.32 = 164.32 times	1.736	285.26	400
DH5	17 (times / 5 sec) * 6.32 = 107.44 times	2.996	321.89	400

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.



DH1



DH3



DH5





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, the 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS


EUT	BT Stereo Pendant	MODEL	CS8043
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Long Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.759
39	2441	0.810
78	2480	0.798


CH 0



CH 39



CH 78



4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP




4.6.6 TEST RESULTS

EUT	BT Stereo Pendant	MODEL	CS8043
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Long Chen


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.010	0.506	PASS
39	2441	1.005	0.540	PASS
78	2480	1.000	0.532	PASS

NOTE: The minimum limit is two-third of 20dB bandwidth. Test results please refer to next two pages.


CH 0



CH 39



CH 78





4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.7.3 TEST PROCEDURES

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using 1 MHz RBW and 3 MHz VBW.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS


EUT	BT Stereo Pendant	MODEL	CS8043
MODULATION TYPE	GFSK	ENVIRONMENTAL CONDITIONS	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Long Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
0	2402	1.089	0.37	30	PASS
39	2441	0.887	-0.52	30	PASS
78	2480	0.935	-0.29	30	PASS


CH 0



CH 39



CH 78



4.8 BAND EDGES MEASUREMENT

4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



4.8.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

NOTE 1:



The band edge emission plot on page 68 shows 46.49dBc between carrier maximum power and local maximum emission in restrict band (2.3882GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 100.51dBuV/m (Peak), so the maximum field strength in restrict band is $100.51 - 46.49 = 54.02$ dBuV/m, which is under 74 dBuV/m limit.



The band edge emission plot on page 68 shows 46.49dBc between carrier maximum power and local maximum emission in restrict band (2.3882GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 69.59dBuV/m (Average), so the maximum field strength in restrict band is $70.51 - 46.49 = 24.02$ dBuV/m, which is under 54 dBuV/m limit.

NOTE 2:

The band edge emission plot on page 69 shows 47.00dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 101.01dBuV/m (Peak), so the maximum field strength in restrict band is $101.01 - 47.00 = 54.01$ dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on page 69 shows 47.00dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 71.01dBuV/m (Average), so the maximum field strength in restrict band is $71.01 - 47.00 = 24.01$ dBuV/m, which is under 54 dBuV/m limit.







4.9 ANTENNA REQUIREMENT

4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Ceramic antenna without antenna connector. The maximum gain of this antenna is 1.0dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST


TEST MODE A



TEST MODE B





TEST MODE C




RADIATED EMISSION TEST


TEST MODE A



TEST MODE B



TEST MODE C



6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.