




PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.

TEL (410) 290-6652 · FAX (410) 290-6654

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 15.245 Certification

SPORTS SENSORS, INC.
P.O. Box 46198
Cincinnati, OH 45246-0198
Attn: Telemachos J. Manolatos, Vice President

Dates of Tests: January 9-10, 2003
Test Report S/N: TX.230110009.NVE
Test Site: PCTEST Lab, Columbia MD

FCC ID

NVE364

APPLICANT

SPORTS SENSORS, INC.

FCC Rule Part(s): § 15.245
Classification: Part 15 Field Disturbance Sensor (FDS)
EUT Type: SWING SPEED RADAR™
Frequency Range: 10.5 – 10.55 GHz
Trade Name: SPORTS SENSORS
Model: 364

This device has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992 with the following remarks (Note Codes): 37.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian
Vice President Engineering





PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTS SENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 1 of 15

TABLE OF CONTENTS

ATTACHMENT A:	COVER
LETTER(S)	
ATTACHMENT B: ATTESTATION STATEMENT(S)	
ATTACHMENT C: TEST REPORT	
1.1 SCOPE	3
2.1 INTRODUCTION (SITE DESCRIPTION)	4
3.1 PRODUCTION INFORMATION	5
4.1 DESCRIPTION OF TESTS (CONDUCTED & RADIATED)	6-7
5.1 ANTENNA REQUIREMENT/APPLIED MODULATION	8
6.1 FREQUENCY MEASUREMENTS (Fundamental & Harmonics)	9
7.1 FREQUENCY MEASUREMENTS (Receiver Radiated Spurious)	10
8.1 LINE-CONDUCTED EMISSIONS	11
9.1 SAMPLE CALCULATIONS	12
10.1 ACCURACY OF MEASUREMENT	13
11.1 LIST OF TEST EQUIPMENT	14
12.1 CONCLUSION	15
ATTACHMENT D: TEST PLOTS	
ATTACHMENT E: FCC ID LABEL & LOCATION	
ATTACHMENT F: TEST SETUP PHOTOGRAPHS	
ATTACHMENT G: EXTERNAL PHOTOGRAPHS	
ATTACHMENT H: INTERNAL PHOTOGRAPHS	
ATTACHMENT I: BLOCK DIAGRAM(S)	
ATTACHMENT J: SCHEMATIC DIAGRAM(S)	
ATTACHMENT K: OPERATIONAL DESCRIPTION	
ATTACHMENT L: USER'S MANUAL	

MEASUREMENT REPORT



1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

Company Name:	SPORTS SENSORS, INC.
Address:	P.O. Box 46198 Cincinnati, OH 45246-0198
Attention:	Mr. Telemachos J. Manolatos, Vice President

- FCC ID: **NVE364**
- Model: **364**
- Trade Name: **SPORTS SENSORS**
- EUT Type: **SWING SPEED RADAR™**
- Equipment Class: **Part 15 Field Disturbance Sensor (FDS)**
- Application Type: **Certification**
- Frequency Range: **10.5 – 10.55 GHz**
- FCC Rule Part(s): **§ 15.245**
- Dates of Tests: **January 9-10, 2003**
- Place of Tests: **PCTEST Lab, Columbia, MD U.S.A.**
- Test Report S/N: **TX.230110009.NVE**

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTS SENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 3 of 15

2.1 INTRODUCTION

The measurement procedure described in Section 15.249 of FCC Rules, and American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-1992) was used in determining radiated and conducted emissions emanating from **SPORTS SENSORS Inc. SWING SPEED RADAR™ FCC ID: NVE364**.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on October 19, 1992.

2.2 PCTEST Location

The map at right shows the location of the PCTEST Lab, its proximity to the FCC Lab, the Columbia vicinity area, the Baltimore-Washington International (BWI) airport, and the city of Baltimore, and the Washington, D.C. area. (see Figure 1).




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

PCTEST PT. 15.245 REPORT	PCTEST	MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 4 of 15

3.1 Product Information

3.2 Equipment Description

The Equipment Under Test (EUT) is the **SPORTS SENSORS Inc. SWING SPEED RADAR™** FCC ID: **NVE364**.

- * Tx Freq. Range(Base): **10.5 – 10.55 GHz**
- * Antenna: **Permanently Attached, Omni-Directional**
- * Power Supply: **3AA Batteries**

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTS SENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 5 of 15

4.1 Description of Tests




Figure 2. Shielded Enclosure Line-Conducted Test Facility






Figure 5. LISN Schematic Diagram

4.2 Conducted Emissions

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure. It is manufactured by Ray Proof Series 81 (see Figure 2). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m. x 1.5m. wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room (see Figure 3). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 4). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filters (100dB 14kHz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing, with an inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Solar LISN. LISN schematic diagram is shown in Figure 5. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 450kHz to 30MHz with 20 msec. sweep time. The frequency producing the maximum level was reexamined using EMI/ Field Intensity Meter and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode. The bandwidth of the receiver was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Attachment I. Each EME reported was calibrated using the HP8640B signal generator.

PCTEST PT. 15.245 REPORT	PCTEST	MEASUREMENT REPORT	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364 Page 6 of 15

4.1 Description of Tests (continued)




Figure 6. 3-Meter Test Site




Figure 7. Dimensions of Outdoor Test Site




Figure 8. Turntable and System Setup




Figure 9. Normalized Site Attenuation Curves (H&V)

4.3 Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using biconical antenna and from 200 to 1000 MHz using log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antenna (see Figure 6). The test equipment was placed on a wooden and plastic bench situated on a 1.5 x 2 meter area adjacent to the measurement area (see Figure 7). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1 MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 8). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment; powering the monitor from the floor mounted outlet box and the computer aux AC outlet if applicable, and changing the polarity of the antenna; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Attachment I. Each EME reported was calibrated using the HP8640B signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 9 according to ANSI C63.4.

PCTEST PT. 15.245 REPORT	PCTEST	MEASUREMENT REPORT	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364
			Page 7 of 15

5.1 §15.203 Antenna Requirement

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of a permanently attached antenna, or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

Unit

The Sports Sensors Inc. SWING SPEED RADAR™ unit complies with the requirement of §15.203. The antenna is a permanently attached Telescopic Omni-directional Antenna.

CONCLUSION

For the unit, there are no provisions for connection to an external antenna.

Sports Sensors Inc. SWING SPEED RADAR™ unit meets the Antenna Requirements of §15.203.

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364 Page 8 of 15

6.1 FREQUENCY MEASUREMENTS (FUNDAMENTAL & HARMONICS)

A. Transmitter Portion - Model: 364

Operating Frequency: 10.525 MHz
Distance of Measurements: 3 meters
Channel: Low

FREQ. (MHz)	Level (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (μV/m)	Margin (dB)
10,525	- 51.65	43.0	V	PEAK	82699.000	28.7
21,050	- 115.00	50.0	V	PEAK	125.893	12.0
31,575	- 118.40	57.3	V	PEAK	197.242	8.1
42,100	- 132.00	63.0	V	PEAK	79.433	16.0
52,625	- 135.00	70.0	V	PEAK	125.893	12.0

Fundamental Frequency (MHz)	Field Strength of Fundamental (millivolts/meter)	Field strength of harmonics (millivolts/meter)
2435 - 2465	500	1.6
5785 - 5815	500	1.6
10500 - 10550	2500	25.0
24075 - 24175	2500	25.0

Figure 12. Radiated limits at 3 meters

NOTES:


1. The limit at fundamental freq. is 2500 mV/m @ 3m. using average detector (RBW = 1 MHz VBW = 3Hz).
2. All emissions exceeding 20m V/m @3m. are reported.
3. All spurious emissions in the restricted bands specified in §15.205 are below the limit shown in Fig. 10.
4. Measurements are made at 20° or between +15° C to +25° C.
5. The antenna is manipulated through typical positions and length during the tests.
6. The emissions are maximized by changing polarity of the antenna.
7. The EUT is supplied with the nominal AC voltage and/or a new/fully recharged battery.
8. All channels were investigated and the worst-case are reported.

7.1 Frequency Measurements (Radiated Spurious)

7.1 Radiated Emissions

FREQ. (MHz)	Level* (dBm)	AFCL** (dB)	POL (H/V)	Height (m)	Azimuth (° angle)	F/S (μ V/m)	Margin*** (dB)
39.6	- 82.20	1.10	V	2.6	60	19.77	- 14.1
79.2	- 87.30	7.40	H	2.2	210	22.70	- 12.9
118.8	- 91.39	11.39	H	2.1	180	22.44	- 16.5
468.3	- 105.33	25.34	V	1.8	30	22.44	- 19.0
468.3	- 105.83	25.34	V	1.4	50	21.18	- 19.5
990.0	- 111.16	33.86	V	1.3	90	30.60	- 16.3

Table 1. Radiated Measurements at 3-meters.



NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The radiated limits are shown on Figure 10. Above 1 GHz the limit is 500mV/m

Figure 13. Limits at 3 meters

- * All readings are calibrated by HP8640B signal generator with accuracy traceable to the National Institute of Standards and Technology (formerly NBS).
- ** AFCL = Antenna Factor (Roberts dipole) and Cable Loss (30 ft. RG58C/U).
- *** Measurements using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used using a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

PCTEST PT. 15.245 REPORT	PCTEST	MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 10 of 15

8.1 Line-Conducted Test Data

8.2 Conducted Emissions

(See Data under PLOTS – Attachment D)

NOTES:

1. All frequencies, channels, & modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device is 250_mV from 450kHz to 30MHz.
3. Line A = Phase; Line B = Neutral
4. Deviations to the Specifications: None

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364 Page 11 of 15

9.1 Sample Calculations

$$\text{dBmV} = 20 \log_{10} (\text{mV/m})$$

$$\text{dBmV} = \text{dBm} + 107$$

9.2 Example 1:

@ 20.3 MHz

Class B limit	= 250 μV = 47.96 dB μV
Reading	= - 67.8 dBm (calibrated level)
Convert to dB μV	= - 67.8 + 107 = 39.2 dB μV
$10^{(39.2/20)}$	= 91.2 μV
Margin	= 39.2 - 47.96 = - 8.76
	= 8.8 dB below limit

9.3 Example 2:

@ 66.7 MHz

Class B limit	= 100 $\mu\text{V/m}$ = 47.96 dB $\mu\text{V/m}$
Reading	= - 76.0 dBm (calibrated level)
Convert to dB $\mu\text{V/m}$	= - 76.0 + 107 = 31.0 dB $\mu\text{V/m}$
Antenna Factor + Cable Loss	= 5.8 dB
Total	= 36.8 dB $\mu\text{V/m}$
Margin	= 36.8 - 40.0 = - 3.2
	= 3.2 dB below limit

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364 Page 12 of 15

10.1 Accuracy of Measurement

10.2 Measurement Uncertainty Calculations:

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994).

Contribution (Line Conducted)	Probability Distribution	Uncertainty (± dB)	
		9kHz-150MHz	150-30MHz
Receiver specification	Rectangular	1.5	1.5
LISN coupling specification	Rectangular	1.5	1.5
Cable and input attenuator calibration	Normal (k=2)	0.3	0.5
Mismatch: Receiver VRC $\Gamma_1 = 0.03$ LISN VRC $\Gamma_R = 0.8$ (9kHz) 0.2 (30MHz) Uncertainty limits $20\text{Log}(1 \pm \Gamma_1 \Gamma_R)$	U-Shaped	0.2	0.35
System repeatability	Std. deviation	0.2	0.05
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	1.26	1.30
Expanded uncertainty	Normal (k=2)	2.5	2.6

Calculations for 150kHz to 30MHz:

$$u_c(y) = \sqrt{\sum_{i=1}^m u_i^2(y)} = \pm \sqrt{\frac{1.5^2 + 1.5^2}{3} + \left(\frac{0.5}{2}\right)^2 + 0.35} = \pm 1.298\text{dB}$$

$$U = 2U_c(y) = \pm 2.6\text{dB}$$

Contribution (Radiated Emissions)	Probability Distribution	Uncertainties (± dB)	
		3 m	10 m
Ambient Signals		-	-
Antenna factor calibration	Normal (k=2)	± 1.0	± 1.0
Cable loss calibration	Normal (k=2)	± 0.5	± 0.5
Receiver specification	Rectangular	± 1.5	± 1.5
Antenna directivity	Rectangular	+ 0.5 / - 0	+ 0.5
Antenna factor variation with height	Rectangular	± 2.0	± 0.5
Antenna phase centre variation	Rectangular	0.0	± 0.2
Antenna factor frequency interpolation	Rectangular	± 0.25	± 0.25
Measurement distance variation	Rectangular	± 0.6	± 0.4
Site imperfections	Rectangular	± 2.0	± 2.0
Mismatch: Receiver VRC $\Gamma_1 = 0.2$ Antenna VRC $\Gamma_R = 0.67$ (Bi) 0.3 (Lp) Uncertainty limits $20\text{Log}(1 \pm \Gamma_1 \Gamma_R)$	U-Shaped	+ 1.1 - 1.25	± 0.5
System repeatability	Std. Deviation	± 0.5	± 0.5
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	+ 2.19 / - 2.21	+ 1.74 / - 1.72
Expanded uncertainty U	Normal (k=2)	+ 4.38 / - 4.42	+ 3.48 / - 3.44

Calculations for 3m biconical antenna. Coverage factor of k=2 will ensure that the level of confidence will be approximately 95%, therefore: $U=2u_c(y) = 2 \times \pm 2.19 = \pm 4.38\text{dB}$

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 13 of 15

11.1 Test Equipment

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	2/05/03	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/03	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (9kHz-1.8GHz)	06/02/03	3144A02458
Spectrum Analyzer	HP 8591A (9kHz-1.8GHz)	10/15/03	3108A02053
Spectrum Analyzer	HP 8594A (9kHz-2.9GHz)	11/02/03	3051A00187
Signal Generator	HP 8640B (500Hz-1GHz)	06/02/03	2232A19558
Signal Generator	HP 8640B (500Hz-1GHz)	06/02/03	1851A09816
Signal Generator	Rohde & Schwarz (0.1-1000MHz)	09/11/03	894215/012
Aitech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/03	0792-03271
Aitech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/03	0805-03334
Aitech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/03	0608-03241
Quasi-Peak Adapter	HP 85650A	08/09/03	2043A00301
Aitech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/03	0194-04082
RG58 Coax Test Cable	No. 167		n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Transient Limiter	HP 11947A (9kHz-200MHz)		2820A00300
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355		
Log-Spiral Antenna (3)	Aitech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set) A100		5118
Aitech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (2)	3816/2		1077, 1079
EMCO LISN	3725/2		2009
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (10-26.5GHz)		
Aitech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8591A		3034A01395
Modulation Analyzer	HP 8901A		2432A03467
NTSC Pattern Generator	Leader 408		0377433
Noise Figure Meter	HP 8970B		3106A02189
Noise Figure Meter	Aitech 7510		TE31700
Noise Generator	Aitech 7010		1473
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
B-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285
Spectrum Analyzer:	HP 8562A		
Mixers:	11517A, 11970A, 11970K, 11970U, 11970V, 11970W		
HP Adapters:	11518, 11519, 11520		

* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 	Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTS SENSORS SWING SPEED RADAR™	FCC ID: NVE364 Page 14 of 15

12.1 Conclusion

The data collected shows that the **Sports Sensors Inc. SWING SPEED RADAR™ FCC ID: NVE364** complies with Part 15 Subpart C of the FCC Rules.

No modifications were made to the device.

PCTEST PT. 15.245 REPORT		MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: TX.230110009.NVE	Test Dates: JANUARY 9-10, 2003	EUT Type: SPORTSENSORS SWING SPEED RADAR™	FCC ID: NVE364	Page 15 of 15