



REPORT No. : SZ21040365S01

RF EXPOSURE EVALUATION REPORT

APPLICANT : dormakaba EAD GmbH

PRODUCT NAME : data collection terminal

MODEL NAME : 9600-K6 BLE, 9600-K6 SBB

BRAND NAME : dormakaba

FCC ID : NVI-KT9600K6B

STANDARD(S) : FCC 47CFR Part 2(2.1091)

RECEIPT DATE : 2021-07-09

TEST DATE : 2021-08-03 to 2021-08-16

ISSUE DATE : 2021-12-20



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information.....	3
1.1 Applicant and Manufacturer Information.....	3
1.2 Equipment under Test (EUT) Description.....	3
1.3 Applied Reference Documents	4
2. Device Category and RF Exposure Limit	5
3. RF Output Power.....	6
4. RF Exposure Assessment	7
Annex A Testing Laboratory Information	8

Change History		
Version	Date	Reason for change
1.0	2021-12-20	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	dormakaba EAD GmbH
Applicant Address:	Albertistr. 3, 78056 Villingen-Schwenningen, Germany
Manufacturer:	In-Tech Electronics Ltd
Manufacturer Address:	Unit A,13/F, Wing Tai Centre,12 Hing Yip Street, Kwun Tong Kowloon, Hong Kong

1.2 Equipment under Test (EUT) Description

Product Name:	data collection terminal
Serial No.:	6#
Hardware Version:	04
Software Version:	V9
Bluetooth Version:	5.0
Frequency Bands:	Bluetooth: 2402MHz-2480MHz RFID: 13.56 MHz
Modulation Mode:	Bluetooth LE: GFSK RFID: ASK
Antenna Type:	Bluetooth LE: PCB Antenna RFID: Loop Antenna
Antenna Gain:	Bluetooth LE: 0.35dBi RFID: 0dBi

Note 1: According to the certificate holder, they declared that the models 9600-K6 BLE and 9600-K6 SBB made the following changes:

1. 9600-K6 BLE: change the LCD.
2. 9600-K6 SBB: change the LCD and add USB port inside.

The main measuring model is 9600-K6 SBB, only the results for 9600-K6 SBB were recorded in this report.



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method determination /Remark
FCC 47CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table. Note 2: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.		



2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. RF Output Power

Mode	Channel	Frequency (MHz)	Average Power (dBm)
			GFSK
Bluetooth LE	CH 00	2402	0.62
	CH 19	2440	0.39
	CH 39	2480	0.42
Tune-up Limit			1.00

Note:

1. According to KDB 447498 Section 4.3, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. The modular for RFID approach to certain low power transmitters that has low radiation, therefore the power density of RFID mode is close to zero.
3. The output power refers to report (Report No.: SZ21040365W01).

4. RF Exposure Assessment

➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
Bluetooth	2402	1.00	0.35	1.36	0.0003	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

2. MPE calculate method

$$\text{Power Density} = \text{EIRP}/4\pi R^2$$

Where: EIRP = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

➤ Simultaneous Transmission Assessment:

Multi-Band Simultaneous Transmission Consideration

Simultaneous Transmission Consideration	Position	Applicable Combination
	Hand	Bluetooth + RFID

1. This device contains transmitters that may operate simultaneously, therefore simultaneous transmission analysis is required.
2. The worst condition for Bluetooth & RFID will be calculated for transmitting simultaneously.

Formula: Result=Power density₁/ limit₁ + Power density₂/ limit₂ + Power density₃/ limit₃ ≤ 1.

Transmission Bands	Power Density/ SAR	Limit	Simultaneous Transmission Result
Bluetooth	0.0003	1	0.0003
RFID 13.56MHz	0	0.979	

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

_____ END OF REPORT _____