

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Uplink Frequency Range: 1850 - 1910 MHz Tested at 1857.5 MHz CDMA Modulation Peak Detector		

[illegible]

EUT emissions observed throughout the given frequency spectrum were recorded & evaluated. Emission levels closest to the limit are listed on this data sheet.

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Downlink Frequency Range: 1930 - 1990 MHz Tested at 1937.5 MHz CDMA Modulation Peak Detector		

[illegible]

EUT emissions observed throughout the given frequency spectrum were recorded & evaluated. Emission levels closest to the limit are listed on this data sheet.

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Uplink Frequency Range: 1850 - 1910 MHz Tested at 1857.5 MHz GSM Modulation Peak Detector		

[illegible]

EUT emissions observed throughout the given frequency spectrum were recorded & evaluated. Emission levels closest to the limit are listed on this data sheet.

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Downlink Frequency Range: 1930 - 1990 MHz Tested at 1937.5 MHz GSM Modulation Peak Detector		

[illegible]

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Uplink Frequency Range: 1850 - 1910 MHz Tested at 1857.5 MHz TDMA Modulation Peak Detector		

[illegible]

EUT emissions observed throughout the given frequency spectrum were recorded & evaluated. Emission levels closest to the limit are listed on this data sheet.

RETLIF TESTING LABORATORIES

EMISSIONS DATA SHEET

Test Method:	Spurious Radiated Emissions (ERP) 30 MHz to 20.0 GHz		
Customer:	Cellular Specialties, Inc.	Job No:	R-4023N
Test Sample:	Bidirectional Amplifier		
Model No:	610 PCS	Serial No:	n/a
Test Specification:	FCC Part 2.1053/90.209 Paragraph: n/a		
Operating Mode:	Amplifying input signal		
Technician:	T. Firkowski	Date:	12/18/02
Notes:	Downlink Frequency Range: 1930 - 1990 MHz Tested at 1937.5 MHz TDMA Modulation Peak Detector		

[illegible]