

PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0


SAR (1g): 0.869 mW/g, SAR (10g): 0.600 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0991 [824MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, standard battery

Test Date - 10/26/2000



PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0


SAR (1g): 0.899 mW/g, SAR (10g): 0.637 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0380 [836MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, standard battery

Test Date - 10/26/2000



PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0


SAR (1g): 0.829 mW/g, SAR (10g): 0.574 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0799 [848MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, standard battery

Test Date - 10/26/2000



PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0


SAR (1g): 0.776 mW/g, SAR (10g): 0.542 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0991 [824MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, extended battery

Test Date - 10/26/2000



PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0


SAR (1g): 0.694 mW/g, SAR (10g): 0.497 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0380 [836MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, extended battery

Test Date - 10/26/2000



PANASONIC FCC ID:NWJ10A002A -- TDMA Body SAR

Generic Twin Phantom; Flat Section; Probe: ET3DV5 - SN1370 -- Probe Cal Date 02/00

Med. Parameters 835 MHz Muscle: $\sigma = 0.95$ mho/m $\epsilon_r = 56.2$ $\rho = 1.00$ g/cm³; Antenna Position -- Out; Crest Factor 3.0

SAR (1g): 0.628 mW/g, SAR (10g): 0.437 mW/g

Panasonic Tri-mode Model:EBTX-210

TDMA Mode, Ch.0799 [848MHz]; Spacing = 1.2cm from flat phantom to phone, w/Holster

Conducted Power = 28.5dBm [Level: PL2]; S/N: P8.2-1, extended battery

Test Date - 10/26/2000

