# FCC PART 15C REPORT FOR CERTIFICATION
On Behalf of

Winstars Technology Limited

WiFi 6E Tri-Band AX5400 PCI-E Adapter

Model Number: WS-WN675X3

Addition Model: WL-WN675X3, WS-WN675X3M, WL-WN675X3M, PAX2235-WIFI-6E-CARD

FCC ID: NZ3-WN0006

| | |
|---|---|
| Applicant : | Winstars Technology Limited |
| Address: | 1-5F, NO.5, Taisong Industrial Zone, Dalang Calang Community, |
| | Dalang Street, Longhua District, Shenzhen, China |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 | |

| | |
|---|---|
| Report Number: | ESTE-R2312165 |
| Date of Test: | Oct. 08 ~ Dec. 22, 2023 |
| Date of Report: | Dec. 25, 2023 |

# TABLE OF CONTENTS

Description Page

TEST REPORT VERIFICATION ..... 3
1. GENERAL INFORMATION ..... 5
1.1. Description of Device (EUT) ..... 5
1.2. Antenna Information ..... 5
1.3. Information of RF Cable ..... 5
2. SUMMARY OF TEST ..... 6
2.1. Summary of test result ..... 6
2.2. Test Facilities ..... 7
2.3. Measurement uncertainty ..... 8
2.4. Assistant equipment used for test ..... 8
2.5. Block Diagram ..... 8
2.6. Test Mode ..... 9
2.7. Power Setting of Test Software ..... 10
2.8. Duty Cycle ..... 10
2.9. Channel List ..... 11
2.10. Test Equipment List ..... 12
3. 6DB BANDWIDTH ..... 14
3.1. Limit ..... 14
3.2. Test Setup ..... 14
3.3. Spectrum Analyzer Setting ..... 14
3.4. Test Procedure ..... 14
3.5. Test Result ..... 14
4. MAXIMUM PEAK OUTPUT POWER ..... 15
4.1. Limit ..... 15
4.2. Test Setup ..... 15
4.3. Spectrum Analyzer Setting ..... 15
4.4. Test Procedure ..... 15
4.5. Test Result ..... 15
5. POWER SPECTRAL DENSITY ..... 16
5.1. Limit ..... 16
5.2. Test Setup ..... 16
5.3. Spectrum Analyzer Setting ..... 16
5.4. Test Procedure ..... 16
5.5. Test Result ..... 16
6. CONDUCTED BAND EDGE ..... 17
6.1. Limit ..... 17
6.2. Test Setup ..... 17
6.3. Spectrum Analyzer Setting ..... 17
6.4. Test Procedure ..... 17
6.5. Test Result ..... 17
7. CONDUCTED SPURIOUS EMISSIONS ..... 18
7.1. Limit ..... 18
7.2. Test Setup ..... 18
7.3. Spectrum Analyzer Setting ..... 18

7.4. Test Procedure ..... 18
7.5. Test Result ..... 18
8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE ..... 19
8.1. Limit ..... 19
8.2. Test Setup ..... 20
8.3. Spectrum Analyzer Setting ..... 20
8.4. Test Procedure ..... 22
8.5. Test Result ..... 23
9. AC POWER LINE CONDUCTED EMISSIONS ..... 35
9.1. Limit ..... 35
9.2. Test Setup ..... 35
9.3. Spectrum Analyzer Setting ..... 35
9.4. Test Procedure ..... 35
9.5. Test Result ..... 36
10. ANTENNA REQUIREMENTS ..... 38
10.1. Limit ..... 38
10.2. Test Result ..... 38
11. APPENDIX ..... 39
12. TEST SETUP PHOTO ..... 119
13. EUT PHOTO ..... 121

# EST Technology Co., Ltd.

| | |
|---|---|
| **Applicant:**<br>**Address:** | Winstars Technology Limited<br>1-5F, NO.5, Taisong Industrial Zone, Dalang Community,<br>Dalang Street, Longhua District, Shenzhen, China |
| **Manufacturer:**<br>**Address:** | Winstars Technology Limited<br>1-5F, NO.5, Taisong Industrial Zone, Dalang Community,<br>Dalang Street, Longhua District, Shenzhen, China |
| **Factory:**<br>**Address:** | Winstars Technology Limited<br>1-5F, NO.5, Taisong Industrial Zone, Dalang Community,<br>Dalang Street, Longhua District, Shenzhen, China |
| **E.U.T:** | WiFi 6E Tri-Band AX5400 PCI-E Adapter |
| **Model Number:** | WS-WN675X3 |
| **Addition Model:** | WL-WN675X3, WS-WN675X3M, WL-WN675X3M,<br>PAX2235-WIFI-6E-CARD |
| **Power Supply:** | DC 5V |
| **Trade Name:** | ------ Serial No.: ------ |
| **Date of Receipt:** | Oct. 08, 2023 Date of Test: Oct. 08 ~ Dec. 22, 2023 |
| **Test Specification:** | FCC Part 15 Subpart C (15.247)<br>ANSI C63.10:2013<br>FCC KDB 558074 D01 15.247 Meas Guidance v05r02 |
| **Test Result:** | The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.<br><br>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.<br><br>**Date:** Dec. 25, 2023 |

| Prepared by: | Reviewed by: | Approved by: |
|---|---|---|
| Zephyr Zhu | | |
| Zephyr Zhu / Assistant | Seven Wang / Engineer | Iceman Hu / Manager |

**Other Aspects:**
None.

*Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested*

*This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.*

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

| | | |
|---|---|---|
| Product Name | : | WiFi 6E Tri-Band AX5400 PCI-E Adapter |
| Model Number | : | WS-WN675X3 |
| Software Version | : | 22.190.0 |
| Hardware Version | : | WS-WN675X2-PCIE |
| Operation frequency | : | 2412MHz~2462MHz<br>2422MHz~2452MHz |
| Number of channel | : | IEEE 802.11b/g/n HT20: 11 Channels<br>IEEE 802.11n HT40: 7 Channels |
| Max Output Power (PEAK) | : | 802.11b: 14.92dBm<br>802.11g: 15.82dBm<br>802.11n HT20: 16.92dBm<br>802.11ax HE20: 16.20dBm<br>802.11n HT40: 17.04dBm<br>802.11ax HE40: 15.89 dBm |
| Modulation Type | : | 802.11b mode: DSSS(CCK/QPSK/BPSK)<br>802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM)<br>802.11n mode: OFDM (BPSK/QPSK/16QAM/64QAM) |
| Sample Type | : | Prototype production |

Note: For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

## 1.2. Antenna Information

| Ant No. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|---|---|---|---|---|---|
| 1 | - | - | External | - | 1.59 |
| 2 | - | - | External | - | 1.59 |
| Directional | - | - | External | - | 4.60 |

Note:
1.The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
2.The test results of this report only apply to the sample as received.

## 1.3. Information of RF Cable

| Cable Loss(dB) | Provided by |
|---|---|
| 1.0 | Winstars Technology Limited |

Note:
1.The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.
2.The laboratory is not responsible for the accuracy of the cable loss.

# 2. SUMMARY OF TEST

## 2.1. Summary of test result

| No. | Description of Test Item | FCC Standard Section | Results |
|---|---|---|---|
| 1 | 6dB Bandwidth | 15.247(a)(2) | PASS |
| 2 | Maximum Peak Output Power | 15.247(b)(3) | PASS |
| 3 | Power Spectral Density | 15.247(e) | PASS |
| 4 | Conducted Band Edge | 15.247(d) | PASS |
| 5 | Conducted Spurious Emissions | 15.247(d) | PASS |
| 6 | Radiated Spurious Emissions and Band Edge | 15.205<br>15.209<br>15.247(d) | PASS |
| 7 | AC Power Line Conducted Emissions | 15.207 | PASS |
| 8 | Antenna Requirement | 15.203 | PASS |

Note:“N/A” denotes test is not applicable in this test report.

## 2.2. Test Facilities

| | | |
|---|---|---|
| EMC Lab | : | Accredited by CNAS, CHINA<br>Registration No.: L5288<br>This Accreditation is valid until: November 12, 2029<br><br>Recognized by FCC, USA<br>Designation Number: CN1215<br>This Recognition is valid until: January 31, 2024<br><br>Accredited by A2LA, USA<br>Registration No.: 4366.01<br>This Accreditation is valid until: January 31, 2024<br><br>Recognized by Industry Canada<br>CAB identifier No.: CN0035<br>This Recognition is valid until: January 31, 2024<br><br>Recognized by VCCI, Japan<br>Registration No.:C-14103; T-20073; R-13663;<br>R-20103; G-20097<br>Date of registration: Apr. 20, 2020<br>This Recognition is valid until: Apr. 19, 2026<br><br>Recognized by TUV Rheinland, Germany<br>Registration No.: UA 50413872 0001<br>Date of registration: July 31, 2018<br><br>Recognized by Intertek<br>Registration No.: 2011-RTL-L2-64<br>Date of registration: November 08, 2018 |
| Name of Firm | : | EST Technology Co., Ltd. |
| Site Location | : | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |

## 2.3. Measurement uncertainty

| Test Item | Uncertainty |
|---|---|
| Uncertainty for Conduction emission test | ±3.48dB |
| Uncertainty for spurious emissions test (Below 30MHz) | ±1.62 dB |
| Uncertainty for spurious emissions test (30MHz-1GHz) | ±4.60 dB(Polarize: H) |
| | ±4.68 dB(Polarize: V) |
| Uncertainty for spurious emissions test (1GHz to 25GHz) | ±4.96dB |
| Uncertainty for radio frequency | $7\times10^{-8}$ |
| Uncertainty for conducted RF Power | 1.08dB |
| Uncertainty for Power density test | 0.26dB |

Note:This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2.4. Assistant equipment used for test

| Item | Equipment | Brand | Model Name/Type No. | FCC ID | Series No. |
|---|---|---|---|---|---|
| - | - | - | - | - | - |

| Item | Shielded Type | Ferrite Core | Length | Note |
|---|---|---|---|---|
| 1 | NO | NO | 1.5m | AC Cable |

## 2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into 2.4G WIFI test mode by software before test.




(EUT: WiFi 6E Tri-Band AX5400 PCI-E Adapter)

## 2.6. Test Mode

The test mode was selected for the final test as listed below.

| Test Item | Mode | Date Rate | Test Channel |
|---|---|---|---|
| 6dB Bandwidth | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |
| Maximum Peak Output Power | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |
| Power Spectral Density | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |
| Conducted Band Edge | IEEE 802.11b | 1Mbps | Low/ High |
| | IEEE 802.11g | 6Mbps | Low/ High |
| | IEEE 802.11n HT20 | MCS0 | Low/ High |
| | IEEE 802.11n HT40 | MCS0 | Low/ High |
| | IEEE 802.11ax HE20 | MCS0 | Low/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/High |
| Conducted Spurious Emissions | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |
| Radiated Spurious Emissions(Below 1GHz) | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |
| Radiated Spurious Emissions(Above 1GHz) | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/Middle/High |
| | IEEE 802.11ax HE40 | MCS0 | Low/Middle/High |

| | | | |
|---|---|---|---|
| Radiated Band Edge | IEEE 802.11b | 1Mbps | Low/High |
| | IEEE 802.11g | 6Mbps | Low/High |
| | IEEE 802.11n HT20 | MCS0 | Low/High |
| | IEEE 802.11n HT40 | MCS0 | Low/High |
| | IEEE 802.11ax HE20 | MCS0 | Low/ High |
| | IEEE 802.11ax HE40 | MCS0 | Low/High |
| AC Power Line Conducted Emissions | IEEE 802.11b | 1Mbps | Low/Middle/High |
| | IEEE 802.11g | 6Mbps | Low/Middle/High |
| | IEEE 802.11n HT20 | MCS0 | Low/Middle/High |
| | IEEE 802.11n HT40 | MCS0 | Low/Middle/High |

Note: In radiated measurement,the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane.**

## 2.7. Power Setting of Test Software

| Software Name | DRTU | | |
|---|---|---|---|
| Frequency(MHz) | 2412 | 2437 | 2462 |
| IEEE 802.11b Setting | 7,7 | 7,7 | 7,7 |
| IEEE 802.11g Setting | 3,3 | 3,3 | 3,3 |
| IEEE 802.11n HT20 Setting | 1,1 | 1,1 | 1,1 |
| IEEE802.11ax HE20 Setting | 1,1 | 1,1 | 1,1 |
| Frequency(MHz) | 2422 | 2437 | 2452 |
| IEEE 802.11n HT40 Setting | 1,1 | 1,1 | 1,1 |
| IEEE802.11ax HE40 Setting | 1,1 | 1,1 | 1,1 |

Note: This information is provided by the applicant.

## 2.8. Duty Cycle

Refer to section 11: Appendix H

Note:

1. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle⩾98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor(consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).

## 2.9. Channel List

| IEEE 802.11b/802.11g/802.11n HT20/802.11ax HE20 | | | | | |
|---|---|---|---|---|---|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1 | 2412 | 6 | 2437 | 11 | 2462 |
| 2 | 2417 | 7 | 2442 | | |
| 3 | 2422 | 8 | 2447 | | |
| 4 | 2427 | 9 | 2452 | | |
| 5 | 2432 | 10 | 2457 | | |
| IEEE 802.11n HT40/802.11ax HE40 | | | | | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 3 | 2422 | 6 | 2437 | 9 | 2452 |
| 4 | 2427 | 7 | 2442 | | |
| 5 | 2432 | 8 | 2447 | | |

## 2.10. Test Equipment List

| For conducted emission test | | | | | | |
|---|---|---|---|---|---|---|
| Equipment | Manufacturer | Model No. | Serial No. | Calibration Body | Last Cal. | Next Cal. |
| EMI Test Receiver | Rohde & Schwarz | ESHS30 | EST-E001 | LISAI | June 12,23 | 1 Year |
| Artificial Mains Network | Rohde & Schwarz | ENV216 | EST-E002 | LISAI | June 12,23 | 1 Year |
| Pulse Limiter | Rohde & Schwarz | ESH3-Z2 | EST-E078 | LISAI | June 12,23 | 1 Year |
| Test Software | Audix | e3-6.111221a | N/A | N/A | N/A | N/A |

| For radiated emission test(9kHz-30MHz) | | | | | | |
|---|---|---|---|---|---|---|
| Equipment | Manufacturer | Model No. | Serial No. | Calibration Body | Last Cal. | Next Cal. |
| EMI Test Receiver | Rohde & Schwarz | ESR7 | EST-E047 | LISAI | June 12,23 | 1 Year |
| Active Loop Antenna | SCHWAREBECK | FMZB 1519B | EST-E054 | LISAI | June 12,23 | 1 Year |
| Test Software | Audix | e3-6.111221a | N/A | N/A | N/A | N/A |
| 9kHz-30MHz Cable | N/A | EST-001 | N/A | N/A | N/A | N/A |

| For radiated emissions test (30MHz-1000MHz) | | | | | | |
|---|---|---|---|---|---|---|
| Equipment | Manufacturer | Model No. | Serial No. | Calibration Body | Last Cal. | Next Cal. |
| EMI Test Receiver | Rohde & Schwarz | ESR7 | EST-E047 | LISAI | June 12,23 | 1 Year |
| Bilog Antenna | Teseq | CBL 6111D | EST-E034 | LISAI | June 12,23 | 1 Year |
| Test Software | Audix | e3-6.111221a | N/A | N/A | N/A | N/A |
| 30-1000MHz Cable | N/A | EST-002 | N/A | N/A | N/A | N/A |

| For radiated emission test(Above 1000MHz) | | | | | | |
|---|---|---|---|---|---|---|
| Equipment | Manufacturer | Model No. | Serial No. | Calibration Body | Last Cal. | Next Cal. |
| Horn Antenna | SCHWARZBECK | BBHA9120D | EST-E144 | LISAI | June 12,23 | 1 Year |
| Horn Antenna | Com-Power | AHA-840 | EST-E133 | LISAI | June 12,23 | 1 Year |
| Low Noise Amplifier | RF | TRLA-010180G45N | EST-E142 | LISAI | June 12,23 | 1 Year |
| Spectrum Analyzer | Rohde &Schwarz | FSV40 | EST-E069 | LISAI | June 12,23 | 1 Year |
| Test Software | Audix | e3-6.111221a | N/A | N/A | N/A | N/A |
| Above 1GHz Cable | N/A | EST-003 | N/A | N/A | N/A | N/A |

| For connect EUT antenna terminal test | | | | | | |
|---|---|---|---|---|---|---|
| Equipment | Manufacturer | Model No. | Serial No. | Calibration Body | Last Cal. | Next Cal. |
| TS 1120 | Tonscend | / | / | / | / | / |
| Test Software | Tonscend | TS1120-3 | 3.3.38 | / | / | / |
| RF Control Unit | Tonscend | JS0806-2 | EST-E134 | LISAI | June 12,23 | 1 Year |
| Signal and Spectrum Analyzer | Keysight | N9010B | EST-E141 | LISAI | June 12,23 | 1 Year |

# 3. 6DB BANDWIDTH

## 3.1. Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz,the minimum 6 dB bandwidth shall be at least 500 kHz.

## 3.2. Test Setup




## 3.3. Spectrum Analyzer Setting

6dB Bandwidth

| Spectrum Parameters | Setting |
|---|---|
| RBW | 100KHz |
| VBW | 300KHz |
| Span | 40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode) |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

99% Occupied Bandwidth

| Spectrum Parameters | Setting |
|---|---|
| RBW | 300KHz(20MHz Bandwidth mode)/1MHz(40MHz Bandwidth mode) |
| VBW | 1MHz(20MHz Bandwidth mode)/3MHz(40MHz Bandwidth mode) |
| Span | 40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode) |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

## 3.4. Test Procedure

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 3.3.
c. Set the EUT transmit continuously with maximum output power.
d. Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
e. Repeat above procedures until all modes and channels were measured.
f. Record the results in the test report.

## 3.5. Test Result

Refer to section 11: Appendix A

# 4. MAXIMUM PEAK OUTPUT POWER

## 4.1. Limit

For systems using digital modulation in 2400-2483.5MHz,the maximum peak output power is 1 Watt(30dBm).

## 4.2. Test Setup




## 4.3. Spectrum Analyzer Setting

| Spectrum Parameters | Setting |
|---|---|
| RBW | 1MHz |
| VBW | 3MHz |
| Span | 40MHz(20MHz Bandwidth mode)/80MHz(40MHz Bandwidth mode) |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

## 4.4. Test Procedure

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 4.3.
c. Set the EUT transmit continuously with maximum output power.
d. Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
e. Repeat above procedures until all modes and channels were measured.
f. Record the results in the test report.

## 4.5. Test Result

Refer to section 11: Appendix C

# 5. POWER SPECTRAL DENSITY

## 5.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

## 5.2. Test Setup

## 5.3. Spectrum Analyzer Setting

| Spectrum Parameters | Setting |
|---|---|
| RBW | 3KHz |
| VBW | 10KHz |
| Span | 30MHz(20MHz Bandwidth mode)/60MHz(40MHz Bandwidth mode) |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

## 5.4. Test Procedure

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 5.3.
c. Set the EUT transmit continuously with maximum output power.
d. Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
e. Repeat above procedures until all modes and channels were measured.
f. Record the results in the test report.

## 5.5. Test Result

Refer to section 11: Appendix D

# 6. CONDUCTED BAND EDGE

## 6.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

## 6.2. Test Setup




## 6.3. Spectrum Analyzer Setting

| Spectrum Parameters | Setting |
|---|---|
| RBW | 100KHz |
| VBW | 300KHz |
| Span | 100MHz(20MHz Bandwidth mode)/200MHz(40MHz Bandwidth mode) |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

## 6.4. Test Procedure

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 6.3.
c. Set the EUT transmit continuously with maximum output power.
d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
e. Repeat above procedures until all modes and channels were measured.
f. Record the results in the test report

## 6.5. Test Result

Refer to section 11: Appendix E & F

# 7. CONDUCTED SPURIOUS EMISSIONS

## 7.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

## 7.2. Test Setup

## 7.3. Spectrum Analyzer Setting

| Spectrum Parameters | Setting |
|---|---|
| RBW | 100KHz |
| VBW | 300KHz |
| Start frequency | 30MHz |
| Stop frequency | 26.5GHz |
| Sweep Time | Auto |
| Detector | Peak |
| Trace Mode | Max Hold |

## 7.4. Test Procedure

a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
b. Spectrum analyzer setting parameters in accordance with section 7.3.
c. Set the EUT transmit continuously with maximum output power.
d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
e. Repeat above procedures until all modes and channels were measured.
f. Record the results in the test report.

## 7.5. Test Result

Refer to section 11: Appendix E & G

# 8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

## 8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

| MHz | MHz | MHz | GHz |
|---|---|---|---|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| [1]0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2690 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | ([2]) |

15.209 Limit

| Frequency (MHz) | Field Strength(μV/m) | Distance(m) |
|---|---|---|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

(1) Emission level dBμV = 20 log Emission level μV/m.
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument,antenna and the closest point of any part of the device or system.

## 8.2. Test Setup

9kHz~30MHz




30~1000MHz




Above 1GHz




## 8.3. Spectrum Analyzer Setting

For 9KHz-150KHz

| Spectrum Parameters | Setting |
|---|---|
| RBW | 300Hz(for Peak&AVG)/CISPR 200Hz(for QP) |
| VBW | 300Hz(for Peak&AVG)/CISPR 200Hz(for QP) |
| Start frequency | 9KHz |
| Stop frequency | 150KHz |
| Sweep Time | Auto |
| Detector | PEAK/QP/AVG |
| Trace Mode | Max Hold |

For 150KHz-30MHz

| Spectrum Parameters | Setting |
|---|---|
| RBW | 9KHz |
| VBW | 9KHz |
| Start frequency | 150KHz |
| Stop frequency | 30MHz |
| Sweep Time | Auto |
| Detector | QP |
| Trace Mode | Max Hold |

For 30MHz-1GHz

| Spectrum Parameters | Setting |
|---|---|
| RBW | 120KHz |
| VBW | 300KHz |
| Start frequency | 30MHz |
| Stop frequency | 1GHz |
| Sweep Time | Auto |
| Detector | QP |
| Trace Mode | Max Hold |

For Above 1GHz

| Spectrum Parameters | Setting | |
|---|---|---|
| RBW | 1MHz | |
| VBW | PEAK Measurement | AVG Measurement |
| | 3MHz | Duty cycle≥98%,VBW=10Hz |
| | | Duty cycle＜98%,VBW≥1/T |
| Start frequency | 1GHz | |
| Stop frequency | 25GHz | |
| Sweep Time | Auto | |
| Detector | PEAK | |
| Trace Mode | Max Hold | |

Note :T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

## 8.4. Test Procedure

a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
c. Set the EUT transmit continuously with maximum output power.
d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
f. Spectrum analyzer setting parameters in accordance with section 8.3.
g. Repeat above procedures until all channels were measured.
h. Record the results in the test report.

Note:

1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2412MHz/2422MHz/2437MHz/2452MHz/2462MHz are fundamental frequency,which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.
3. IEEE 802.11b, IEEE 802.11g, IEEE 802. 11nH20, IEEE 802. 11nH40 all have been tested, only worst case 802.11n HT20 is recorded.

## 8.5. Test Result

### Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 73 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (78)




Site no. : 1# 966 Chamber Data no. : 73
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:21.7°C.Humi:58%;Press:101.1KPa
Engineer : DCY
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : TX Mode

| | Freq. (MHz) | ANT Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 102.75 | 10.70 | 1.43 | 12.13 | 24.26 | 43.50 | 19.24 | QP |
| 2 | 204.60 | 8.60 | 2.08 | 19.47 | 30.15 | 43.50 | 13.35 | QP |
| 3 | 269.59 | 13.80 | 2.44 | 6.81 | 23.05 | 46.00 | 22.95 | QP |
| 4 | 381.14 | 16.16 | 2.98 | 12.17 | 31.31 | 46.00 | 14.69 | QP |
| 5 | 401.51 | 15.60 | 3.07 | 10.10 | 28.77 | 46.00 | 17.23 | QP |
| 6 | 647.89 | 21.88 | 4.01 | 3.16 | 29.05 | 46.00 | 16.95 | QP |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no. : 1# 966 Chamber Data no. : 74
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : FCC PART 15 C(3M)
Env. / Ins. : Temp:21.7°C.Humi:58%;Press:101.1KPa
Engineer : DCY
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : TX Mode

| | Freq. (MHz) | ANT Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 43.58 | 11.80 | 0.88 | 19.09 | 31.77 | 40.00 | 8.23 | QP |
| 2 | 98.87 | 10.20 | 1.40 | 15.65 | 27.25 | 43.50 | 16.25 | QP |
| 3 | 130.88 | 11.80 | 1.63 | 12.36 | 25.79 | 43.50 | 17.71 | QP |
| 4 | 167.74 | 10.50 | 1.86 | 14.13 | 26.49 | 43.50 | 17.01 | QP |
| 5 | 196.84 | 8.50 | 2.03 | 13.89 | 24.42 | 43.50 | 19.08 | QP |
| 6 | 254.07 | 13.74 | 2.34 | 7.75 | 23.83 | 46.00 | 22.17 | QP |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test,only the worst case was reported.

# Radiated Emissions Above 1G

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 77 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 77
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2422MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4844.00 | 32.47 | 5.24 | 44.45 | 53.16 | 46.42 | 74.00 | 27.58 | Peak |
| 2 | 7266.00 | 36.21 | 6.69 | 44.07 | 46.68 | 45.51 | 74.00 | 28.49 | Peak |
| 3 | 9585.00 | 38.12 | 7.77 | 43.63 | 44.30 | 46.56 | 74.00 | 27.44 | Peak |
| 4 | 12101.00 | 38.89 | 8.87 | 42.06 | 42.90 | 48.60 | 74.00 | 25.40 | Peak |
| 5 | 15399.00 | 38.82 | 10.40 | 43.62 | 41.65 | 47.25 | 74.00 | 26.75 | Peak |
| 6 | 17609.00 | 40.31 | 12.11 | 43.28 | 41.31 | 50.45 | 74.00 | 23.55 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 78 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 78
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2422MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4844.00 | 32.47 | 5.24 | 44.45 | 45.47 | 38.73 | 74.00 | 35.27 | Peak |
| 2 | 7266.00 | 36.21 | 6.69 | 44.07 | 43.99 | 42.82 | 74.00 | 31.18 | Peak |
| 3 | 10044.00 | 38.23 | 7.79 | 43.76 | 43.92 | 46.18 | 74.00 | 27.82 | Peak |
| 4 | 12577.00 | 39.32 | 9.08 | 41.39 | 40.75 | 47.76 | 74.00 | 26.24 | Peak |
| 5 | 14447.00 | 39.78 | 9.98 | 41.90 | 40.30 | 48.16 | 74.00 | 25.84 | Peak |
| 6 | 17626.00 | 40.37 | 12.12 | 43.26 | 40.84 | 50.07 | 74.00 | 23.93 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 79 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 79
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2437MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4874.00 | 32.54 | 5.28 | 44.42 | 47.21 | 40.61 | 74.00 | 33.39 | Peak |
| 2 | 7311.00 | 36.25 | 6.70 | 44.07 | 45.28 | 44.16 | 74.00 | 29.84 | Peak |
| 3 | 10826.00 | 38.78 | 8.18 | 43.14 | 43.17 | 46.99 | 74.00 | 27.01 | Peak |
| 4 | 13835.00 | 39.95 | 9.68 | 40.80 | 39.90 | 48.73 | 74.00 | 25.27 | Peak |
| 5 | 15280.00 | 39.02 | 10.36 | 43.52 | 41.85 | 47.71 | 74.00 | 26.29 | Peak |
| 6 | 17660.00 | 40.48 | 12.15 | 43.21 | 40.61 | 50.03 | 74.00 | 23.97 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 80 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 80
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5℃;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2437MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4874.00 | 32.54 | 5.28 | 44.42 | 46.75 | 40.15 | 74.00 | 33.85 | Peak |
| 2 | 7311.00 | 36.25 | 6.70 | 44.07 | 44.82 | 43.70 | 74.00 | 30.30 | Peak |
| 3 | 9704.00 | 38.14 | 7.77 | 43.68 | 44.38 | 46.61 | 74.00 | 27.39 | Peak |
| 4 | 12560.00 | 39.30 | 9.07 | 41.42 | 40.34 | 47.29 | 74.00 | 26.71 | Peak |
| 5 | 14940.00 | 39.53 | 10.22 | 43.13 | 41.00 | 47.62 | 74.00 | 26.38 | Peak |
| 6 | 17694.00 | 40.59 | 12.18 | 43.16 | 40.75 | 50.36 | 74.00 | 23.64 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 81 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 81
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2452MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4904.00 | 32.60 | 5.32 | 44.38 | 46.80 | 40.34 | 74.00 | 33.66 | Peak |
| 2 | 7356.00 | 36.28 | 6.71 | 44.06 | 44.65 | 43.58 | 74.00 | 30.42 | Peak |
| 3 | 10350.00 | 38.44 | 7.94 | 43.52 | 43.99 | 46.85 | 74.00 | 27.15 | Peak |
| 4 | 12577.00 | 39.32 | 9.08 | 41.39 | 41.37 | 48.38 | 74.00 | 25.62 | Peak |
| 5 | 14141.00 | 39.93 | 9.84 | 41.14 | 40.04 | 48.67 | 74.00 | 25.33 | Peak |
| 6 | 17660.00 | 40.48 | 12.15 | 43.21 | 41.17 | 50.59 | 74.00 | 23.41 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no. : 1# 966 Chamber Data no. : 82
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2452MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 4904.00 | 32.60 | 5.32 | 44.38 | 46.98 | 40.52 | 74.00 | 33.48 | Peak |
| 2 | 7356.00 | 36.28 | 6.71 | 44.06 | 44.96 | 43.89 | 74.00 | 30.11 | Peak |
| 3 | 10894.00 | 38.83 | 8.21 | 43.08 | 43.32 | 47.28 | 74.00 | 26.72 | Peak |
| 4 | 12747.00 | 39.47 | 9.15 | 41.16 | 40.48 | 47.94 | 74.00 | 26.06 | Peak |
| 5 | 14328.00 | 39.84 | 9.92 | 41.61 | 40.48 | 48.63 | 74.00 | 25.37 | Peak |
| 6 | 17677.00 | 40.53 | 12.17 | 43.18 | 41.19 | 50.71 | 74.00 | 23.29 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

**Radiated Band Edge**

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no. : 1# 966 Chamber Data no. : 83
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2422MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2390.00 | 27.43 | 3.55 | 45.01 | 60.83 | 46.80 | 54.00 | 7.20 | Average |
| 2 | 2390.00 | 27.43 | 3.55 | 45.01 | 83.85 | 69.82 | 74.00 | 4.18 | Peak |
| 3 | 2419.40 | 27.52 | 3.57 | 44.99 | 109.06 | 95.16 | 74.00 | -21.16 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 84 File: \\EMC-966-1\test data\2023\RF\X\Xing Bo Yue\WS-WN675X3.EM6 (144)




Site no. : 1# 966 Chamber Data no. : 84
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2422MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2390.00 | 27.43 | 3.55 | 45.01 | 55.30 | 41.27 | 54.00 | 12.73 | Average |
| 2 | 2390.00 | 27.43 | 3.55 | 45.01 | 69.99 | 55.96 | 74.00 | 18.04 | Peak |
| 3 | 2425.40 | 27.53 | 3.58 | 44.98 | 104.88 | 91.01 | 74.00 | -17.01 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no. : 1# 966 Chamber Data no. : 85
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5℃;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2452MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2450.40 | 27.61 | 3.59 | 44.96 | 108.36 | 94.60 | 74.00 | -20.60 | Peak |
| 2 | 2483.50 | 27.70 | 3.62 | 44.93 | 57.66 | 44.05 | 54.00 | 9.95 | Average |
| 3 | 2483.50 | 27.70 | 3.62 | 44.93 | 77.40 | 63.79 | 74.00 | 10.21 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no. : 1# 966 Chamber Data no. : 86
Dis. / Ant. : 3m BBHA9120D-2667 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:19.5°C;Humi:50%;Press:101.55kPa
Engineer : QQZ
EUT : WiFi 6E Tri-Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : IEEE 802.11n HT40 TX 2452MHz

| | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Amp Factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2450.64 | 27.61 | 3.59 | 44.96 | 110.72 | 96.96 | 74.00 | -22.96 | Peak |
| 2 | 2483.52 | 27.70 | 3.62 | 44.93 | 58.60 | 44.99 | 54.00 | 9.01 | Average |
| 3 | 2483.52 | 27.70 | 3.62 | 44.93 | 83.42 | 69.81 | 74.00 | 4.19 | Peak |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. All channels had been pre-test,only of the worst case channels were reported.

# 9. AC POWER LINE CONDUCTED EMISSIONS

## 9.1. Limit

| Frequency | | | Maximum RF Line Voltage | |
|---|---|---|---|---|
| | | | Quasi-Peak Level dB(μV) | Average Level dB(μV) |
| 150kHz | ~ | 500kHz | 66 ~ 56* | 56 ~ 46* |
| 500kHz | ~ | 5MHz | 56 | 46 |
| 5MHz | ~ | 30MHz | 60 | 50 |

Note:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

## 9.2. Test Setup




## 9.3. Spectrum Analyzer Setting

| Spectrum Parameters | Setting |
|---|---|
| RBW | 9KHz |
| VBW | 9KHz |
| Start frequency | 150KHz |
| Stop frequency | 30MHz |
| Sweep Time | Auto |
| Detector | QP/AVG |
| Trace Mode | Max Hold |

## 9.4. Test Procedure

a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
b. The EUT Power connected to the power mains through a line impedance stabilization network.
c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
d. Set the EUT transmit continuously with maximum output power.
e. Spectrum analyzer setting parameters in accordance with section 9.3.
f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
g. Record the results in the test report.

## 9.5. Test Result

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no : 2#CE Shield Room Data no. : 2
Env. / Ins. : Temp:24.8℃ Humi:55% Press:101.50kPa LINE Phase : LINE
Limit : FCC PART 15C QP
Engineer : XJF
EUT : WiFi 6E Tri- Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : TX Mode

| | Freq. (MHz) | LISN Factor (db) | Cable Loss (db) | Reading dBuV) | Emission Level (dBuv) | Limits (dBuv) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.200 | 10.16 | 9.93 | 15.58 | 35.67 | 53.62 | 17.95 | Average |
| 2 | 0.200 | 10.16 | 9.93 | 19.53 | 39.62 | 63.62 | 24.00 | QP |
| 3 | 0.264 | 10.15 | 9.91 | 15.53 | 35.59 | 51.29 | 15.70 | Average |
| 4 | 0.264 | 10.15 | 9.91 | 19.38 | 39.44 | 61.29 | 21.85 | QP |
| 5 | 0.396 | 10.10 | 9.90 | 8.07 | 28.07 | 47.95 | 19.88 | Average |
| 6 | 0.396 | 10.10 | 9.90 | 12.96 | 32.96 | 57.95 | 24.99 | QP |
| 7 | 15.470 | 10.48 | 10.07 | 8.01 | 28.56 | 50.00 | 21.44 | Average |
| 8 | 15.470 | 10.48 | 10.07 | 15.90 | 36.45 | 60.00 | 23.55 | QP |
| 9 | 17.475 | 10.58 | 10.17 | 8.64 | 29.39 | 50.00 | 20.61 | Average |
| 10 | 17.475 | 10.58 | 10.17 | 15.90 | 36.65 | 60.00 | 23.35 | QP |
| 11 | 19.532 | 10.69 | 10.28 | 14.63 | 35.60 | 50.00 | 14.40 | Average |
| 12 | 19.532 | 10.69 | 10.28 | 20.64 | 41.61 | 60.00 | 18.39 | QP |

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when useing a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878




Site no : 2#CE Shield Room Data no. : 4
Env. / Ins. : Temp:24.8℃ Humi:55% Press:101.50kPa LINE Phase : NEUTRAL
Limit : FCC PART 15C QP
Engineer : XJF
EUT : WiFi 6E Tri- Band AX5400 PCI-E Adapter
Power : AC 120V/60Hz
M/N : WS-WN675X3
Test Mode : TX Mode

| | Freq. (MHz) | LISN Factor (db) | Cable Loss (db) | Reading dBuV) | Emission Level (dBuv) | Limits (dBuv) | Margin (dB) | Remark |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.200 | 10.14 | 9.93 | 18.00 | 38.07 | 53.62 | 15.55 | Average |
| 2 | 0.200 | 10.14 | 9.93 | 21.30 | 41.37 | 63.62 | 22.25 | QP |
| 3 | 0.264 | 10.16 | 9.91 | 8.32 | 28.39 | 51.29 | 22.90 | Average |
| 4 | 0.264 | 10.16 | 9.91 | 12.95 | 33.02 | 61.29 | 28.27 | QP |
| 5 | 0.320 | 10.17 | 9.87 | 4.78 | 24.82 | 49.71 | 24.89 | Average |
| 6 | 0.320 | 10.17 | 9.87 | 11.63 | 31.67 | 59.71 | 28.04 | QP |
| 7 | 3.025 | 10.01 | 10.00 | 4.71 | 24.72 | 46.00 | 21.28 | Average |
| 8 | 3.025 | 10.01 | 10.00 | 10.59 | 30.60 | 56.00 | 25.40 | QP |
| 9 | 15.307 | 10.49 | 10.06 | 8.97 | 29.52 | 50.00 | 20.48 | Average |
| 10 | 15.307 | 10.49 | 10.06 | 15.66 | 36.21 | 60.00 | 23.79 | QP |
| 11 | 19.635 | 10.55 | 10.28 | 15.40 | 36.23 | 50.00 | 13.77 | Average |
| 12 | 19.635 | 10.55 | 10.28 | 21.40 | 42.23 | 60.00 | 17.77 | QP |

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when useing a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

# 10. ANTENNA REQUIREMENTS

## 10.1. Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

## 10.2. Test Result

The antennas used for this product is Internal antenna, so compliance with antenna requirements.
( Please refer to the EUT photo for details)

# 11. APPENDIX

Appendix A: DTS Bandwidth
Test Result

| TestMode | Antenna | Frequency[MHz] | DTS BW [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|---|---|---|---|---|---|---|---|
| 11B | Ant1 | 2412 | 10.080 | 2406.960 | 2417.040 | 0.5 | PASS |
| 11B | Ant2 | 2412 | 10.120 | 2406.920 | 2417.040 | 0.5 | PASS |
| 11B | Ant1 | 2437 | 10.120 | 2431.960 | 2442.080 | 0.5 | PASS |
| 11B | Ant2 | 2437 | 10.080 | 2431.960 | 2442.040 | 0.5 | PASS |
| 11B | Ant1 | 2462 | 10.080 | 2457.000 | 2467.080 | 0.5 | PASS |
| 11B | Ant2 | 2462 | 11.040 | 2456.000 | 2467.040 | 0.5 | PASS |
| 11G | Ant1 | 2412 | 16.280 | 2403.880 | 2420.160 | 0.5 | PASS |
| 11G | Ant2 | 2412 | 16.320 | 2403.840 | 2420.160 | 0.5 | PASS |
| 11G | Ant1 | 2437 | 16.320 | 2428.880 | 2445.200 | 0.5 | PASS |
| 11G | Ant2 | 2437 | 16.320 | 2428.880 | 2445.200 | 0.5 | PASS |
| 11G | Ant1 | 2462 | 16.320 | 2453.840 | 2470.160 | 0.5 | PASS |
| 11G | Ant2 | 2462 | 16.280 | 2453.880 | 2470.160 | 0.5 | PASS |
| 11N20MIMO | Ant1 | 2412 | 17.560 | 2403.240 | 2420.800 | 0.5 | PASS |
| 11N20MIMO | Ant2 | 2412 | 17.440 | 2403.240 | 2420.680 | 0.5 | PASS |
| 11N20MIMO | Ant1 | 2437 | 17.560 | 2428.240 | 2445.800 | 0.5 | PASS |
| 11N20MIMO | Ant2 | 2437 | 17.600 | 2428.200 | 2445.800 | 0.5 | PASS |
| 11N20MIMO | Ant1 | 2462 | 17.560 | 2453.200 | 2470.760 | 0.5 | PASS |
| 11N20MIMO | Ant2 | 2462 | 17.560 | 2453.200 | 2470.760 | 0.5 | PASS |
| 11N40MIMO | Ant1 | 2422 | 36.480 | 2403.760 | 2440.240 | 0.5 | PASS |
| 11N40MIMO | Ant2 | 2422 | 35.840 | 2403.760 | 2439.600 | 0.5 | PASS |
| 11N40MIMO | Ant1 | 2437 | 36.240 | 2418.840 | 2455.080 | 0.5 | PASS |
| 11N40MIMO | Ant2 | 2437 | 36.160 | 2419.080 | 2455.240 | 0.5 | PASS |
| 11N40MIMO | Ant1 | 2452 | 35.520 | 2433.920 | 2469.440 | 0.5 | PASS |
| 11N40MIMO | Ant2 | 2452 | 35.520 | 2434.560 | 2470.080 | 0.5 | PASS |
| 11AX20MIMO | Ant1 | 2412 | 18.160 | 2403.160 | 2421.320 | 0.5 | PASS |
| 11AX20MIMO | Ant2 | 2412 | 18.680 | 2402.640 | 2421.320 | 0.5 | PASS |
| 11AX20MIMO | Ant1 | 2437 | 18.800 | 2427.600 | 2446.400 | 0.5 | PASS |
| 11AX20MIMO | Ant2 | 2437 | 18.560 | 2427.840 | 2446.400 | 0.5 | PASS |
| 11AX20MIMO | Ant1 | 2462 | 18.440 | 2452.840 | 2471.280 | 0.5 | PASS |
| 11AX20MIMO | Ant2 | 2462 | 18.400 | 2452.880 | 2471.280 | 0.5 | PASS |
| 11AX40MIMO | Ant1 | 2422 | 37.760 | 2403.280 | 2441.040 | 0.5 | PASS |
| 11AX40MIMO | Ant2 | 2422 | 36.560 | 2404.480 | 2441.040 | 0.5 | PASS |
| 11AX40MIMO | Ant1 | 2437 | 37.520 | 2418.360 | 2455.880 | 0.5 | PASS |
| 11AX40MIMO | Ant2 | 2437 | 36.400 | 2419.480 | 2455.880 | 0.5 | PASS |
| 11AX40MIMO | Ant1 | 2452 | 37.200 | 2433.760 | 2470.960 | 0.5 | PASS |
| 11AX40MIMO | Ant2 | 2452 | 35.920 | 2433.600 | 2469.520 | 0.5 | PASS |

# Test Graphs

## 11B-Ant1-2412-PASS

## 11B-Ant2-2412-PASS

## 11B-Ant1-2437-PASS

11B-Ant2-2437-PASS

11B-Ant1-2462-PASS

11B-Ant2-2462-PASS

11G-Ant1-2412-PASS




11G-Ant2-2412-PASS

11G-Ant1-2437-PASS

11G-Ant2-2437-PASS




11G-Ant1-2462-PASS

11G-Ant2-2462-PASS



11N20MIMO-Ant1-2412-PASS

11N20MIMO-Ant2-2412-PASS

11N20MIMO-Ant1-2437-PASS

11N20MIMO-Ant2-2437-PASS

11N20MIMO-Ant1-2462-PASS

11N20MIMO-Ant2-2462-PASS

11N40MIMO-Ant1-2422-PASS

11N40MIMO-Ant2-2422-PASS

11N40MIMO-Ant1-2437-PASS

11N40MIMO-Ant2-2437-PASS

11N40MIMO-Ant1-2452-PASS

11N40MIMO-Ant2-2452-PASS



11AX20MIMO-Ant1-2412-PASS

11AX20MIMO-Ant2-2412-PASS

11AX20MIMO-Ant1-2437-PASS



11AX20MIMO-Ant2-2437-PASS




11AX20MIMO-Ant1-2462-PASS

11AX20MIMO-Ant2-2462-PASS

11AX40MIMO-Ant1-2422-PASS

11AX40MIMO-Ant2-2422-PASS

11AX40MIMO-Ant1-2437-PASS

11AX40MIMO-Ant2-2437-PASS

11AX40MIMO-Ant1-2452-PASS

11AX40MIMO-Ant2-2452-PASS

Appendix C: Maximum conducted output power
Test Result Peak

| TestMode | Antenna | Frequency[MHz] | Peak Powert[dBm] | Conducted Limit[dBm] | Verdict |
|---|---|---|---|---|---|
| 11AX20MIMO | Ant1 | 2412 | 12.96 | ≤30.00 | PASS |
| 11AX20MIMO | Ant2 | 2412 | 12.51 | ≤30.00 | PASS |
| 11AX20MIMO | total | 2412 | 15.75 | ≤30.00 | PASS |
| 11AX20MIMO | Ant1 | 2437 | 12.35 | ≤30.00 | PASS |
| 11AX20MIMO | Ant2 | 2437 | 11.94 | ≤30.00 | PASS |
| 11AX20MIMO | total | 2437 | 15.16 | ≤30.00 | PASS |
| 11AX20MIMO | Ant1 | 2462 | 12.84 | ≤30.00 | PASS |
| 11AX20MIMO | Ant2 | 2462 | 13.52 | ≤30.00 | PASS |
| 11AX20MIMO | total | 2462 | 16.20 | ≤30.00 | PASS |
| 11AX40MIMO | Ant1 | 2422 | 12.72 | ≤30.00 | PASS |
| 11AX40MIMO | Ant2 | 2422 | 13.04 | ≤30.00 | PASS |
| 11AX40MIMO | total | 2422 | 15.89 | ≤30.00 | PASS |
| 11AX40MIMO | Ant1 | 2437 | 12.30 | ≤30.00 | PASS |
| 11AX40MIMO | Ant2 | 2437 | 11.86 | ≤30.00 | PASS |
| 11AX40MIMO | total | 2437 | 15.10 | ≤30.00 | PASS |
| 11AX40MIMO | Ant1 | 2452 | 12.52 | ≤30.00 | PASS |
| 11AX40MIMO | Ant2 | 2452 | 13.05 | ≤30.00 | PASS |
| 11AX40MIMO | total | 2452 | 15.80 | ≤30.00 | PASS |
| 11B | Ant1 | 2412 | 13.70 | ≤30.00 | PASS |
| 11B | Ant2 | 2412 | 14.01 | ≤30.00 | PASS |
| 11B | Ant1 | 2437 | 14.04 | ≤30.00 | PASS |
| 11B | Ant2 | 2437 | 14.48 | ≤30.00 | PASS |
| 11B | Ant1 | 2462 | 14.92 | ≤30.00 | PASS |
| 11B | Ant2 | 2462 | 14.25 | ≤30.00 | PASS |
| 11G | Ant1 | 2412 | 15.23 | ≤30.00 | PASS |
| 11G | Ant2 | 2412 | 15.12 | ≤30.00 | PASS |
| 11G | Ant1 | 2437 | 15.22 | ≤30.00 | PASS |
| 11G | Ant2 | 2437 | 14.69 | ≤30.00 | PASS |
| 11G | Ant1 | 2462 | 15.82 | ≤30.00 | PASS |
| 11G | Ant2 | 2462 | 16.03 | ≤30.00 | PASS |
| 11N20MIMO | Ant1 | 2412 | 13.32 | ≤30.00 | PASS |
| 11N20MIMO | Ant2 | 2412 | 13.15 | ≤30.00 | PASS |
| 11N20MIMO | total | 2412 | 16.25 | ≤30.00 | PASS |
| 11N20MIMO | Ant1 | 2437 | 13.35 | ≤30.00 | PASS |
| 11N20MIMO | Ant2 | 2437 | 12.76 | ≤30.00 | PASS |
| 11N20MIMO | total | 2437 | 16.08 | ≤30.00 | PASS |
| 11N20MIMO | Ant1 | 2462 | 13.94 | ≤30.00 | PASS |
| 11N20MIMO | Ant2 | 2462 | 13.88 | ≤30.00 | PASS |

| | | | | | |
|---|---|---|---|---|---|
| 11N20MIMO | total | 2462 | 16.92 | ≤30.00 | PASS |
| 11N40MIMO | Ant1 | 2422 | 13.72 | ≤30.00 | PASS |
| 11N40MIMO | Ant2 | 2422 | 14.13 | ≤30.00 | PASS |
| 11N40MIMO | total | 2422 | 16.94 | ≤30.00 | PASS |
| 11N40MIMO | Ant1 | 2437 | 13.66 | ≤30.00 | PASS |
| 11N40MIMO | Ant2 | 2437 | 13.18 | ≤30.00 | PASS |
| 11N40MIMO | total | 2437 | 16.44 | ≤30.00 | PASS |
| 11N40MIMO | Ant1 | 2452 | 14.12 | ≤30.00 | PASS |
| 11N40MIMO | Ant2 | 2452 | 13.94 | ≤30.00 | PASS |
| 11N40MIMO | total | 2452 | 17.04 | ≤30.00 | PASS |

Test Graphs Peak

11AX20MIMO-Ant1-2412-PASS




11AX20MIMO-Ant2-2412-PASS

11AX20MIMO-Ant1-2437-PASS



11AX20MIMO-Ant2-2437-PASS




11AX20MIMO-Ant1-2462-PASS




11AX20MIMO-Ant2-2462-PASS