

# TEST REPORT

**Reference No.** ..... : WTS18S07118518-1W  
**FCC ID** ..... : NZ3-WN536A8  
**Applicant** ..... : Winstars Technology Limited  
**Address** ..... : Block 4, TaiSong Industrial Park, DaLang Street, LongHua Town,  
Bao'an district, Shenzhen, China  
**Manufacturer** ..... : Winstars Technology Limited  
**Address** ..... : Block 4, TaiSong Industrial Park, DaLang Street, LongHua Town,  
Bao'an district, Shenzhen, China  
**Product** ..... : Wi-Fi Router  
**Model(s)** ..... : WS-WN536A8, ARK T6, WS-WN533A8, Quantum Max, Quantum T10,  
Quantum T12, Quantum D4C, Quantum D4, Quantum D6Q, Quantum  
D6, Quantum T8, Quantum T6  
**Standards** ..... : FCC CFR47 Part 15 C Section 15.247: 2017  
**Date of Receipt sample** ..... : 2018-07-19  
**Date of Test** ..... : 2018-07-20 to 2018-08-09  
**Date of Issue** ..... : 2018-08-13  
**Test Result** ..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,  
Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Tested by:

Frank Yin

Frank Yin / Test Engineer

Approved by:




Philo Zhong

Philo Zhong / Manager

## 2. Laboratories Introduction

**Waltek Services (Shenzhen) Co., Ltd** is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

## 2.1 Test Facility

### A. Accreditations for Conformity Assessment (International)

| Country/Region                                                      | Accreditation Body                              | Scope                         | Note |
|---------------------------------------------------------------------|-------------------------------------------------|-------------------------------|------|
| USA                                                                 | <b>CNAS</b><br><b>(Registration No.: L3110)</b> | FCC ID \ DOC \ VOC            | 1    |
| Canada                                                              |                                                 | IC ID \ VOC                   | 2    |
| Japan                                                               |                                                 | MIC-T \ MIC-R                 | -    |
| Europe                                                              |                                                 | EMCD \ RED                    | -    |
| Taiwan                                                              |                                                 | NCC                           | -    |
| Hong Kong                                                           |                                                 | OFCA                          | -    |
| Australia                                                           |                                                 | RCM                           | -    |
| India                                                               |                                                 | <b>International Services</b> | WPC  |
| Thailand                                                            | NTC                                             |                               | -    |
| Singapore                                                           | IDA                                             |                               | -    |
| Note:                                                               |                                                 |                               |      |
| 1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476. |                                                 |                               |      |
| 2. IC Canada Registration No.: 7760A                                |                                                 |                               |      |

### B.TCBs and Notify Bodies Recognized Testing Laboratory.

| Recognized Testing Laboratory of ...     | Notify body number |
|------------------------------------------|--------------------|
| TUV Rheinland                            | Optional.          |
| Intertek                                 |                    |
| TUV SUD                                  |                    |
| SGS                                      |                    |
| Phoenix Testlab GmbH                     | 0700               |
| Element Materials Technology Warwick Ltd | 0891               |
| Timco Engineering, Inc.                  | 1177               |
| Eurofins Product Service GmbH            | 0681               |

### 3 Contents

|                                                        | <b>Page</b> |
|--------------------------------------------------------|-------------|
| <b>1 COVER PAGE.....</b>                               | <b>1</b>    |
| <b>2. LABORATORIES INTRODUCTION.....</b>               | <b>2</b>    |
| 2.1 TEST FACILITY.....                                 | 3           |
| <b>3 CONTENTS .....</b>                                | <b>4</b>    |
| <b>3. REVISION HISTORY .....</b>                       | <b>5</b>    |
| <b>4 GENERAL INFORMATION.....</b>                      | <b>6</b>    |
| 4.1 GENERAL DESCRIPTION OF E.U.T .....                 | 6           |
| 4.2 DETAILS OF E.U.T.....                              | 6           |
| 4.3 CHANNEL LIST.....                                  | 7           |
| 4.4 TEST MODE .....                                    | 8           |
| <b>5 EQUIPMENT USED DURING TEST .....</b>              | <b>9</b>    |
| 5.1 EQUIPMENTS LIST .....                              | 9           |
| 5.2 MEASUREMENT UNCERTAINTY .....                      | 10          |
| 5.3 TEST EQUIPMENT CALIBRATION .....                   | 10          |
| <b>6 TEST SUMMARY .....</b>                            | <b>11</b>   |
| <b>7 CONDUCTED EMISSION .....</b>                      | <b>12</b>   |
| 7.1 E.U.T. OPERATION .....                             | 12          |
| 7.2 EUT SETUP.....                                     | 12          |
| 7.3 MEASUREMENT DESCRIPTION .....                      | 12          |
| 7.4 CONDUCTED EMISSION TEST RESULT .....               | 13          |
| <b>8 RADIATED EMISSIONS.....</b>                       | <b>15</b>   |
| 8.1 EUT OPERATION.....                                 | 15          |
| 8.2 TEST SETUP .....                                   | 16          |
| 8.3 SPECTRUM ANALYZER SETUP .....                      | 17          |
| 8.4 TEST PROCEDURE .....                               | 18          |
| 8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....     | 18          |
| 8.6 SUMMARY OF TEST RESULTS.....                       | 19          |
| <b>9 BAND EDGE MEASUREMENT .....</b>                   | <b>31</b>   |
| 9.1 TEST PRODUCE.....                                  | 31          |
| 9.2 TEST RESULT .....                                  | 32          |
| <b>10 BANDWIDTH MEASUREMENT.....</b>                   | <b>40</b>   |
| 10.1 TEST PROCEDURE:.....                              | 40          |
| 10.2 TEST RESULT: .....                                | 40          |
| <b>11 MAXIMUM PEAK OUTPUT POWER .....</b>              | <b>53</b>   |
| 11.1 TEST PROCEDURE:.....                              | 53          |
| 11.2 TEST RESULT: .....                                | 53          |
| <b>12 POWER SPECTRAL DENSITY .....</b>                 | <b>55</b>   |
| 12.1 TEST PROCEDURE:.....                              | 55          |
| 12.2 TEST RESULT: .....                                | 55          |
| <b>13 ANTENNA REQUIREMENT .....</b>                    | <b>69</b>   |
| <b>14 RF EXPOSURE EVALUATION.....</b>                  | <b>70</b>   |
| <b>15 PHOTOGRAPHS – TEST SETUP PHOTOS AND EUT.....</b> | <b>71</b>   |

### 3. Revision History

| Test report #     | Date of Receipt sample | Date of Test               | Date of Issue | Purpose  | Comment | Approved |
|-------------------|------------------------|----------------------------|---------------|----------|---------|----------|
| WTS18S07118518-1W | 2018-07-19             | 2018-07-20<br>to2018-08-09 | 2018-08-13    | Original | -       | Valid    |

## 4 General Information

### 4.1 General Description of E.U.T

|                       |                                                                                                                                                                             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product:              | Wi-Fi Router                                                                                                                                                                |
| Model(s):             | WS-WN536A8, ARK T6, WS-WN533A8, Quantum Max, Quantum T10, Quantum T12, Quantum D4C, Quantum D4, Quantum D6Q, Quantum D6, Quantum T8, Quantum T6                             |
| Model Description:    | Only the model name and appearance is different. The test sample is WS-WN536A8                                                                                              |
| Operation Frequency:  | 802.11b/g/n HT20: 2412MHz ~ 2462MHz<br>802.11n HT40: 2422MHz~2452MHz                                                                                                        |
| RF output power       | Wifi: 13.17dBm                                                                                                                                                              |
| Antenna installation: | Integrated Antenna                                                                                                                                                          |
| Antenna Gain:         | 5.0dBi                                                                                                                                                                      |
| Type of modulation:   | IEEE 802.11b (CCK/QPSK/BPSK,11Mbps max.)<br>IEEE 802.11g (BPSK/QPSK/16QAM/64QAM,54Mbps max.)<br>IEEE 802.11n (BPSK/QPSK/16QAM/64QAM,HT20:72Mbps max.,<br>HT40:150Mbps max.) |

### 4.2 Details of E.U.T

|                |                                                     |
|----------------|-----------------------------------------------------|
| <b>Ratings</b> | Input: AC 100~240V, 50/60Hz, 0.6A<br>Output: 5V, 4A |
| <b>Adapter</b> | Model: P050W4000U                                   |

### 4.3 Channel List

#### WIFI

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 1           | 2412            | 2           | 2417            | 3           | 2422            | 4           | 2427            |
| 5           | 2432            | 6           | 2437            | 7           | 2442            | 8           | 2447            |
| 9           | 2452            | 10          | 2457            | 11          | 2462            | 12          | -               |

#### 4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

| Test Items                     | Mode         | Data Rate | Channel | TX/RX |
|--------------------------------|--------------|-----------|---------|-------|
| Maximum Peak Output Power      | 802.11b      | 11 Mbps   | 1/6/11  | TX    |
|                                | 802.11g      | 54 Mbps   | 1/6/11  | TX    |
|                                | 802.11n HT20 | 108 Mbps  | 1/6/11  | TX    |
|                                | 802.11n HT40 | 150 Mbps  | 3/6/9   | TX    |
| Power Spectral Density         | 802.11b      | 11 Mbps   | 1/6/11  | TX    |
|                                | 802.11g      | 54 Mbps   | 1/6/11  | TX    |
|                                | 802.11n HT20 | 108 Mbps  | 1/6/11  | TX    |
|                                | 802.11n HT40 | 150 Mbps  | 3/6/9   | TX    |
| Frequency Range                | 802.11b      | 11 Mbps   | 1/11    | TX    |
|                                | 802.11g      | 54 Mbps   | 1/11    | TX    |
|                                | 802.11n HT20 | 108 Mbps  | 1/11    | TX    |
|                                | 802.11n HT40 | 150 Mbps  | 3/6/9   | TX    |
| Transmitter Spurious Emissions | 802.11b      | 11 Mbps   | 1/6/11  | TX    |
|                                | 802.11g      | 54 Mbps   | 1/6/11  | TX    |
|                                | 802.11n HT20 | 108 Mbps  | 1/6/11  | TX    |
|                                | 802.11n HT40 | 150 Mbps  | 3/6/9   | TX    |

**Note** :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

## 5 Equipment Used during Test

### 5.1 Equipments List

| Conducted Emissions Test Site                              |                                  |                      |             |                 |                       |                      |
|------------------------------------------------------------|----------------------------------|----------------------|-------------|-----------------|-----------------------|----------------------|
| Item                                                       | Equipment                        | Manufacturer         | Model No.   | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1.                                                         | EMI Test Receiver                | R&S                  | ESCI        | 101155          | 2017-09-12            | 2018-09-11           |
| 2.                                                         | LISN                             | SCHWARZBECK          | NSLK 8128   | 8128-289        | 2017-09-12            | 2018-09-11           |
| 3.                                                         | Limiter                          | York                 | MTS-IMP-136 | 261115-001-0024 | 2017-09-12            | 2018-09-11           |
| 4.                                                         | Cable                            | LARGE                | RF300       | -               | 2017-09-12            | 2018-09-11           |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site |                                  |                      |             |                 |                       |                      |
| Item                                                       | Equipment                        | Manufacturer         | Model No.   | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1                                                          | Spectrum Analyzer                | R&S                  | FSP30       | 100091          | 2018-04-29            | 2019-04-28           |
| 2                                                          | Broad-band Horn Antenna          | SCHWARZBECK          | BBHA 9120 D | 667             | 2018-04-09            | 2019-04-08           |
| 3                                                          | Broadband Preamplifier           | COMPLIANCE DIRECTION | PAP-1G18    | 2004            | 2018-04-13            | 2019-04-12           |
| 4                                                          | Coaxial Cable (above 1GHz)       | Top                  | 1GHz-18GHz  | EW02014-7       | 2018-04-13            | 2019-04-12           |
| 5                                                          | Spectrum Analyzer                | R&S                  | FSP40       | 100501          | 2017-10-20            | 2018-10-19           |
| 6                                                          | Broad-band Horn Antenna          | SCHWARZBECK          | BBHA 9170   | 335             | 2017-09-14            | 2018-09-13           |
| 7                                                          | Microwave Broadband Preamplifier | SCHWARZBECK          | BBV 9721    | 100472          | 2017-10-25            | 2018-10-24           |
| 8                                                          | Cable                            | Top                  | 18GHz-40GHz | -               | 2017-10-25            | 2018-10-24           |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site |                                  |                      |             |                 |                       |                      |
| Item                                                       | Equipment                        | Manufacturer         | Model No.   | Serial No       | Last Calibration Date | Calibration Due Date |
| 1                                                          | Test Receiver                    | R&S                  | ESCI        | 101296          | 2018-04-13            | 2019-04-12           |
| 2                                                          | Ative Loop Antenna               | Beijing Dazhi        | ZN30900A    | -               | 2017-10-17            | 2018-10-16           |
| 3                                                          | Trilog Broadband Antenna         | SCHWARZBECK          | VULB9160    | 9160-3325       | 2018-04-08            | 2019-04-07           |
| 4                                                          | Amplifier                        | ANRITSU              | MH648A      | M43381          | 2018-04-13            | 2019-04-12           |
| 5                                                          | Cable                            | HUBER+SUHNER         | CBL2        | 525178          | 2018-04-13            | 2019-04-12           |
| 6                                                          | Coaxial Cable (below 1GHz)       | Top                  | TYPE16(13M) | -               | 2017-09-12            | 2018-09-11           |
| RF Conducted Testing                                       |                                  |                      |             |                 |                       |                      |
| Item                                                       | Equipment                        | Manufacturer         | Model No.   | Serial No.      | Last Calibration Date | Calibration Due Date |
| 1.                                                         | EMC Analyzer                     | Agilent              | E7405A      | MY45114943      | 2017-09-14            | 2018-09-13           |

|    |                                 |         |        |            |            |            |
|----|---------------------------------|---------|--------|------------|------------|------------|
|    | (9k~26.5GHz)                    |         |        |            |            |            |
| 2. | Spectrum Analyzer<br>(9k-6GHz)  | R&S     | FSL6   | 100959     | 2017-09-12 | 2018-09-11 |
| 3. | Signal Analyzer<br>(9k~26.5GHz) | Agilent | N9010A | MY50520207 | 2017-09-12 | 2018-09-11 |
| 4. | Coaxial Cable<br>(10Hz-30GHz)   | /       | /      | /          | 2017-09-12 | 2018-09-11 |
| 5. | Antenna Connector*              | /       | /      | /          | 2017-09-12 | 2018-09-11 |

“\*”: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 5.2 Measurement Uncertainty

| Parameter                         | Uncertainty                           |
|-----------------------------------|---------------------------------------|
| Radio Frequency                   | $\pm 1 \times 10^{-6}$                |
| RF Power                          | $\pm 1.0$ dB                          |
| RF Power Density                  | $\pm 2.2$ dB                          |
| Radiated Spurious Emissions test  | $\pm 5.03$ dB (30M~1000MHz)           |
|                                   | $\pm 5.47$ dB (1000M~25000MHz)        |
| Conducted Spurious Emissions test | $\pm 3.64$ dB (AC mains 150KHz~30MHz) |

## 5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by GUANG ZHOU GRG METROLOGY & TEST CO., LTD. address is No.163, Pingyun Rd. West of Huangpu Ave, Tianhe District, Guangzhou, Guangdong, China.

## 6 Test Summary

| Test Items                                                                | Test Requirement                 | Result |
|---------------------------------------------------------------------------|----------------------------------|--------|
| Spurious Radiated Emissions                                               | 15.247<br>15.205(a)<br>15.209(a) | C      |
| Conducted Emissions                                                       | 15.207(a)                        | C      |
| Conducted Spurious Emissions                                              | 15.247                           | C      |
| Bandwidth                                                                 | 15.247(a)(2)                     | C      |
| Maximum Peak Output Power                                                 | 15.247(b)(3),(4)                 | C      |
| Power Spectral Density                                                    | 15.247(e)                        | C      |
| Band Edge                                                                 | 15.247(d)                        | C      |
| Antenna Requirement                                                       | 15.203                           | C      |
| Maximum Permissible Exposure<br>(Exposure of Humans to RF Fields)         | 1.1307(b)(1)                     | C      |
| Note: C=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable. |                                  |        |

## 7 Conducted Emission

|                   |                                                                                                                        |
|-------------------|------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC CFR 47 Part 15 Section 15.207                                                                                      |
| Test Method:      | ANSI C63.10:2013                                                                                                       |
| Test Result:      | PASS                                                                                                                   |
| Frequency Range:  | 150kHz to 30MHz                                                                                                        |
| Class/Severity:   | Class B                                                                                                                |
| Limit:            | 66-56 dB $\mu$ V between 0.15MHz & 0.5MHz<br>56 dB $\mu$ V between 0.5MHz & 5MHz<br>60 dB $\mu$ V between 5MHz & 30MHz |
| Detector:         | Peak for pre-scan (9kHz Resolution Bandwidth)                                                                          |

### 7.1 E.U.T. Operation


Operating Environment :

|                       |                   |
|-----------------------|-------------------|
| Temperature:          | 21.5 °C           |
| Humidity:             | 51.9 % RH         |
| Atmospheric Pressure: | 101.2kPa          |
| EUT Operation :       | Transmitting mode |

The test was performed in Transmitting mode(For WIFI), Only the worst case 802.11b mode were record in the report.

### 7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.




### 7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.

Live line:



| No. | Freq.<br>(MHz) | Reading<br>(dBuV) | Factor<br>(dB) | Result<br>(dBuV) | Limit<br>dBuV | Margin<br>(dB) | Detector | Remark |
|-----|----------------|-------------------|----------------|------------------|---------------|----------------|----------|--------|
| 1   | 0.1500         | 50.33             | 9.75           | 60.08            | 65.99         | -5.91          | QP       |        |
| 2   | 0.1500         | 22.19             | 9.75           | 31.94            | 55.99         | -24.05         | AVG      |        |
| 3   | 0.1780         | 48.32             | 9.78           | 58.10            | 64.57         | -6.47          | QP       |        |
| 4   | 0.1780         | 21.75             | 9.78           | 31.53            | 54.57         | -23.04         | AVG      |        |
| 5   | 0.6180         | 42.96             | 9.84           | 52.80            | 56.00         | -3.20          | QP       |        |
| 6   | 0.6180         | 27.85             | 9.84           | 37.69            | 46.00         | -8.31          | AVG      |        |
| 7   | 1.4460         | 31.48             | 9.90           | 41.38            | 56.00         | -14.62         | QP       |        |
| 8   | 1.4460         | 19.24             | 9.90           | 29.14            | 46.00         | -16.86         | AVG      |        |
| 9   | 4.7940         | 29.23             | 10.05          | 39.28            | 56.00         | -16.72         | QP       |        |
| 10  | 4.7940         | 19.53             | 10.05          | 29.58            | 46.00         | -16.42         | AVG      |        |
| 11  | 10.1340        | 19.54             | 10.06          | 29.60            | 60.00         | -30.40         | QP       |        |
| 12  | 10.1340        | 8.95              | 10.06          | 19.01            | 50.00         | -30.99         | AVG      |        |

Neutral line:



| No. | Freq.<br>(MHz) | Reading<br>(dBuV) | Factor<br>(dB) | Result<br>(dBuV) | Limit<br>dBuV | Margin<br>(dB) | Detector | Remark |
|-----|----------------|-------------------|----------------|------------------|---------------|----------------|----------|--------|
| 1   | 0.1580         | 49.71             | 9.76           | 59.47            | 65.56         | -6.09          | QP       |        |
| 2   | 0.1580         | 21.34             | 9.76           | 31.10            | 55.56         | -24.46         | AVG      |        |
| 3   | 0.2020         | 46.75             | 9.77           | 56.52            | 63.52         | -7.00          | QP       |        |
| 4   | 0.2020         | 19.66             | 9.77           | 29.43            | 53.52         | -24.09         | AVG      |        |
| 5   | 0.6020         | 37.75             | 9.84           | 47.59            | 56.00         | -8.41          | QP       |        |
| 6   | 0.6020         | 25.84             | 9.84           | 35.68            | 46.00         | -10.32         | AVG      |        |
| 7   | 2.9420         | 26.43             | 9.93           | 36.36            | 56.00         | -19.64         | QP       |        |
| 8   | 2.9420         | 12.72             | 9.93           | 22.65            | 46.00         | -23.35         | AVG      |        |
| 9   | 4.4699         | 22.71             | 10.01          | 32.72            | 56.00         | -23.28         | QP       |        |
| 10  | 4.4699         | 15.23             | 10.01          | 25.24            | 46.00         | -20.76         | AVG      |        |
| 11  | 8.7780         | 19.38             | 10.08          | 29.46            | 60.00         | -30.54         | QP       |        |
| 12  | 8.7780         | 10.89             | 10.08          | 20.97            | 50.00         | -29.03         | AVG      |        |

## 8 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

| Frequency<br>(MHz) | Field Strength        |                 | Field Strength Limit at 3m Measurement Dist |                                       |
|--------------------|-----------------------|-----------------|---------------------------------------------|---------------------------------------|
|                    | uV/m                  | Distance<br>(m) | uV/m                                        | dBuV/m                                |
| 0.009 ~ 0.490      | $2400/F(\text{kHz})$  | 300             | $10000 * 2400/F(\text{kHz})$                | $20\log^{(2400/F(\text{kHz}))} + 80$  |
| 0.490 ~ 1.705      | $24000/F(\text{kHz})$ | 30              | $100 * 24000/F(\text{kHz})$                 | $20\log^{(24000/F(\text{kHz}))} + 40$ |
| 1.705 ~ 30         | 30                    | 30              | $100 * 30$                                  | $20\log^{(30)} + 40$                  |
| 30 ~ 88            | 100                   | 3               | 100                                         | $20\log^{(100)}$                      |
| 88 ~ 216           | 150                   | 3               | 150                                         | $20\log^{(150)}$                      |
| 216 ~ 960          | 200                   | 3               | 200                                         | $20\log^{(200)}$                      |
| Above 960          | 500                   | 3               | 500                                         | $20\log^{(500)}$                      |

### 8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


## 8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto  
 IF Bandwidth.....10kHz  
 Video Bandwidth.....10kHz  
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto  
 Detector ..... PK  
 Resolution Bandwidth.....100kHz  
 Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed ..... Auto  
 Detector ..... PK  
 Resolution Bandwidth.....1MHz  
 Video Bandwidth.....3MHz  
 Detector ..... Ave.  
 Resolution Bandwidth.....1MHz  
 Video Bandwidth.....10Hz

## 8.4 Test Procedure

1. The EUT is placed on a turntable. For below 1GHz, the EUT is 0.8m above ground plane;  
For above 1GHz, the EUT is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

## 8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

## 8.6 Summary of Test Results

### Test Frequency : 9kHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

### Test Frequency : 30MHz ~ 18GHz

| Frequency                | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                          |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                    | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11b: Low Channel 2412MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                    | 53.13            | PK          | 136              | 1.3        | H     | -17.46           | 35.67               | 40.00                   | -4.33  |
| 37.81                    | 35.70            | PK          | 235              | 1.4        | V     | -17.46           | 18.24               | 40.00                   | -21.76 |
| 4824.00                  | 53.12            | PK          | 235              | 1.9        | V     | -1.05            | 52.07               | 74.00                   | -21.93 |
| 4824.00                  | 42.10            | Ave         | 235              | 1.9        | V     | -1.05            | 41.05               | 54.00                   | -12.95 |
| 7236.00                  | 48.65            | PK          | 292              | 1.7        | H     | 1.34             | 49.99               | 74.00                   | -24.01 |
| 7236.00                  | 38.69            | Ave         | 292              | 1.7        | H     | 1.34             | 40.03               | 54.00                   | -13.97 |
| 2341.26                  | 46.13            | PK          | 256              | 1.9        | V     | -13.19           | 32.94               | 74.00                   | -41.06 |
| 2341.26                  | 37.60            | Ave         | 256              | 1.9        | V     | -13.19           | 24.41               | 54.00                   | -29.59 |
| 2357.97                  | 42.42            | PK          | 299              | 1.7        | H     | -13.15           | 29.27               | 74.00                   | -44.73 |
| 2357.97                  | 38.14            | Ave         | 299              | 1.7        | H     | -13.15           | 24.99               | 54.00                   | -29.01 |
| 2496.12                  | 42.10            | PK          | 318              | 1.8        | V     | -13.08           | 29.02               | 74.00                   | -44.98 |
| 2496.12                  | 38.62            | Ave         | 318              | 1.8        | V     | -13.08           | 25.54               | 54.00                   | -28.46 |

| Frequency                   | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                             |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                       | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11b: Middle Channel 2437MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                       | 52.19            | PK          | 73               | 1.3        | H     | -17.46           | 34.73               | 40.00                   | -5.27  |
| 37.81                       | 35.48            | PK          | 189              | 1.6        | V     | -17.46           | 18.02               | 40.00                   | -21.98 |
| 4874.00                     | 50.76            | PK          | 232              | 1.0        | V     | -0.63            | 50.13               | 74.00                   | -23.87 |
| 4874.00                     | 42.77            | Ave         | 232              | 1.0        | V     | -0.63            | 42.14               | 54.00                   | -11.86 |
| 7311.00                     | 51.57            | PK          | 63               | 1.7        | H     | 2.21             | 53.78               | 74.00                   | -20.22 |
| 7311.00                     | 41.39            | Ave         | 63               | 1.7        | H     | 2.21             | 43.60               | 54.00                   | -10.40 |
| 2311.57                     | 46.79            | PK          | 26               | 1.4        | V     | -13.19           | 33.60               | 74.00                   | -40.40 |
| 2311.57                     | 39.35            | Ave         | 26               | 1.4        | V     | -13.19           | 26.16               | 54.00                   | -27.84 |
| 2357.34                     | 44.21            | PK          | 6                | 1.6        | H     | -13.14           | 31.07               | 74.00                   | -42.93 |
| 2357.34                     | 38.64            | Ave         | 6                | 1.6        | H     | -13.14           | 25.50               | 54.00                   | -28.50 |
| 2495.06                     | 43.96            | PK          | 44               | 1.9        | V     | -13.09           | 30.87               | 74.00                   | -43.13 |
| 2495.06                     | 36.71            | Ave         | 44               | 1.9        | V     | -13.09           | 23.62               | 54.00                   | -30.38 |

| Frequency                 | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                           |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                     | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11b: High Channel 2462MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                     | 51.80            | PK          | 10               | 1.2        | H     | -17.46           | 34.34               | 40.00                   | -5.66  |
| 37.81                     | 34.51            | PK          | 235              | 1.9        | V     | -17.46           | 17.05               | 40.00                   | -22.95 |
| 4924.00                   | 49.37            | PK          | 295              | 1.8        | V     | -0.25            | 49.12               | 74.00                   | -24.88 |
| 4924.00                   | 44.77            | Ave         | 295              | 1.8        | V     | -0.25            | 44.52               | 54.00                   | -9.48  |
| 7386.00                   | 52.59            | PK          | 86               | 1.0        | H     | 2.85             | 55.44               | 74.00                   | -18.56 |
| 7386.00                   | 40.93            | Ave         | 86               | 1.0        | H     | 2.85             | 43.78               | 54.00                   | -10.22 |
| 2316.12                   | 46.66            | PK          | 238              | 1.2        | V     | -13.19           | 33.47               | 74.00                   | -40.53 |
| 2316.12                   | 37.31            | Ave         | 238              | 1.2        | V     | -13.19           | 24.12               | 54.00                   | -29.88 |
| 2368.20                   | 43.64            | PK          | 146              | 1.4        | H     | -13.14           | 30.50               | 74.00                   | -43.50 |
| 2368.20                   | 38.73            | Ave         | 146              | 1.4        | H     | -13.14           | 25.59               | 54.00                   | -28.41 |
| 2495.25                   | 43.01            | PK          | 210              | 1.3        | V     | -13.09           | 29.92               | 74.00                   | -44.08 |
| 2495.25                   | 36.64            | Ave         | 210              | 1.3        | V     | -13.09           | 23.55               | 54.00                   | -30.45 |

| Frequency                | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                          |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                    | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11g: Low Channel 2412MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                    | 53.60            | PK          | 137              | 1.3        | H     | -17.46           | 36.14               | 40.00                   | -3.86  |
| 37.81                    | 34.75            | PK          | 163              | 1.3        | V     | -17.46           | 17.29               | 40.00                   | -22.71 |
| 4824.00                  | 48.03            | PK          | 34               | 1.2        | V     | -1.06            | 46.97               | 74.00                   | -27.03 |
| 4824.00                  | 37.25            | Ave         | 34               | 1.2        | V     | -1.06            | 36.19               | 54.00                   | -17.81 |
| 7236.00                  | 49.63            | PK          | 8                | 1.1        | H     | 1.35             | 50.98               | 74.00                   | -23.02 |
| 7236.00                  | 43.90            | Ave         | 8                | 1.1        | H     | 1.35             | 45.25               | 54.00                   | -8.75  |
| 2329.20                  | 45.29            | PK          | 78               | 1.3        | V     | -13.19           | 32.10               | 74.00                   | -41.90 |
| 2329.20                  | 39.02            | Ave         | 78               | 1.3        | V     | -13.19           | 25.83               | 54.00                   | -28.17 |
| 2354.05                  | 42.82            | PK          | 70               | 1.4        | H     | -13.14           | 29.68               | 74.00                   | -44.32 |
| 2354.05                  | 37.49            | Ave         | 70               | 1.4        | H     | -13.14           | 24.35               | 54.00                   | -29.65 |
| 2496.59                  | 44.05            | PK          | 357              | 1.2        | V     | -13.08           | 30.97               | 74.00                   | -43.03 |
| 2496.59                  | 38.59            | Ave         | 357              | 1.2        | V     | -13.08           | 25.51               | 54.00                   | -28.49 |

| Frequency                   | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                             |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                       | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11g: Middle Channel 2437MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                       | 51.77            | PK          | 289              | 1.8        | H     | -17.46           | 34.31               | 40.00                   | -5.69  |
| 37.81                       | 37.16            | PK          | 101              | 1.9        | V     | -17.46           | 19.70               | 40.00                   | -20.30 |
| 4874.00                     | 50.81            | PK          | 331              | 1.2        | V     | -0.62            | 50.19               | 74.00                   | -23.81 |
| 4874.00                     | 44.14            | Ave         | 331              | 1.2        | V     | -0.62            | 43.52               | 54.00                   | -10.48 |
| 7311.00                     | 48.80            | PK          | 153              | 1.4        | H     | 2.20             | 51.00               | 74.00                   | -23.00 |
| 7311.00                     | 35.58            | Ave         | 153              | 1.4        | H     | 2.20             | 37.78               | 54.00                   | -16.22 |
| 2321.97                     | 45.65            | PK          | 331              | 2.0        | V     | -13.19           | 32.46               | 74.00                   | -41.54 |
| 2321.97                     | 37.17            | Ave         | 331              | 2.0        | V     | -13.19           | 23.98               | 54.00                   | -30.02 |
| 2358.74                     | 42.89            | PK          | 163              | 1.6        | H     | -13.15           | 29.74               | 74.00                   | -44.26 |
| 2358.74                     | 37.64            | Ave         | 163              | 1.6        | H     | -13.15           | 24.49               | 54.00                   | -29.51 |
| 2489.87                     | 44.50            | PK          | 149              | 1.0        | V     | -13.09           | 31.41               | 74.00                   | -42.59 |
| 2489.87                     | 37.97            | Ave         | 149              | 1.0        | V     | -13.09           | 24.88               | 54.00                   | -29.12 |

| Frequency                 | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                           |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                     | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| 11g: High Channel 2462MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                     | 53.74            | PK          | 176              | 1.8        | H     | -17.46           | 36.28               | 40.00                   | -3.72  |
| 37.81                     | 35.48            | PK          | 238              | 1.5        | V     | -17.46           | 18.02               | 40.00                   | -21.98 |
| 4924.00                   | 53.27            | PK          | 68               | 1.3        | V     | -0.25            | 53.02               | 74.00                   | -20.98 |
| 4924.00                   | 45.09            | Ave         | 68               | 1.3        | V     | -0.25            | 44.84               | 54.00                   | -9.16  |
| 7386.00                   | 46.40            | PK          | 53               | 1.2        | H     | 2.86             | 49.26               | 74.00                   | -24.74 |
| 7386.00                   | 35.80            | Ave         | 53               | 1.2        | H     | 2.86             | 38.66               | 54.00                   | -15.34 |
| 2341.56                   | 45.36            | PK          | 72               | 1.8        | V     | -13.19           | 32.17               | 74.00                   | -41.83 |
| 2341.56                   | 37.27            | Ave         | 72               | 1.8        | V     | -13.19           | 24.08               | 54.00                   | -29.92 |
| 2384.52                   | 43.91            | PK          | 225              | 1.2        | H     | -13.14           | 30.77               | 74.00                   | -43.23 |
| 2384.52                   | 37.50            | Ave         | 225              | 1.2        | H     | -13.14           | 24.36               | 54.00                   | -29.64 |
| 2486.82                   | 44.36            | PK          | 53               | 1.2        | V     | -13.08           | 31.28               | 74.00                   | -42.72 |
| 2486.82                   | 37.23            | Ave         | 53               | 1.2        | V     | -13.08           | 24.15               | 54.00                   | -29.85 |

| Frequency                | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                          |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                    | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n20: Low Channel 2412MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                    | 52.04            | PK          | 337              | 2.0        | H     | -17.46           | 34.58               | 40.00                   | -5.42  |
| 37.81                    | 34.41            | PK          | 87               | 1.7        | V     | -17.46           | 16.95               | 40.00                   | -23.05 |
| 4824.00                  | 46.87            | PK          | 235              | 1.3        | V     | -1.06            | 45.81               | 74.00                   | -28.19 |
| 4824.00                  | 41.05            | Ave         | 235              | 1.3        | V     | -1.06            | 39.99               | 54.00                   | -14.01 |
| 7236.00                  | 47.67            | PK          | 25               | 1.8        | H     | 1.34             | 49.01               | 74.00                   | -24.99 |
| 7236.00                  | 39.49            | Ave         | 25               | 1.8        | H     | 1.34             | 40.83               | 54.00                   | -13.17 |
| 2337.05                  | 45.72            | PK          | 85               | 1.5        | V     | -13.19           | 32.53               | 74.00                   | -41.47 |
| 2337.05                  | 39.56            | Ave         | 85               | 1.5        | V     | -13.19           | 26.37               | 54.00                   | -27.63 |
| 2387.92                  | 42.01            | PK          | 262              | 1.8        | H     | -13.14           | 28.87               | 74.00                   | -45.13 |
| 2387.92                  | 38.49            | Ave         | 262              | 1.8        | H     | -13.14           | 25.35               | 54.00                   | -28.65 |
| 2497.29                  | 42.53            | PK          | 138              | 1.4        | V     | -13.08           | 29.45               | 74.00                   | -44.55 |
| 2497.29                  | 37.19            | Ave         | 138              | 1.4        | V     | -13.08           | 24.11               | 54.00                   | -29.89 |

| Frequency                   | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                             |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                       | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n20: Middle Channel 2437MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                       | 52.42            | PK          | 144              | 1.7        | H     | -17.46           | 34.96               | 40.00                   | -5.04  |
| 37.81                       | 35.99            | PK          | 316              | 1.8        | V     | -17.46           | 18.53               | 40.00                   | -21.47 |
| 4874.00                     | 50.58            | PK          | 313              | 1.0        | V     | -0.61            | 49.97               | 74.00                   | -24.03 |
| 4874.00                     | 41.68            | Ave         | 313              | 1.0        | V     | -0.61            | 41.07               | 54.00                   | -12.93 |
| 7311.00                     | 46.68            | PK          | 293              | 1.0        | H     | 2.21             | 48.89               | 74.00                   | -25.11 |
| 7311.00                     | 40.79            | Ave         | 293              | 1.0        | H     | 2.21             | 43.00               | 54.00                   | -11.00 |
| 2331.26                     | 46.19            | PK          | 100              | 1.7        | V     | -13.19           | 33.00               | 74.00                   | -41.00 |
| 2331.26                     | 39.22            | Ave         | 100              | 1.7        | V     | -13.19           | 26.03               | 54.00                   | -27.97 |
| 2363.76                     | 44.56            | PK          | 260              | 1.8        | H     | -13.14           | 31.42               | 74.00                   | -42.58 |
| 2363.76                     | 37.77            | Ave         | 260              | 1.8        | H     | -13.14           | 24.63               | 54.00                   | -29.37 |
| 2497.86                     | 43.37            | PK          | 48               | 1.7        | V     | -13.09           | 30.28               | 74.00                   | -43.72 |
| 2497.86                     | 36.52            | Ave         | 48               | 1.7        | V     | -13.09           | 23.44               | 54.00                   | -30.56 |

| Frequency                 | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                           |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                     | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n20: High Channel 2462MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                     | 53.10            | PK          | 132              | 1.8        | H     | -17.46           | 35.64               | 40.00                   | -4.36  |
| 37.81                     | 34.81            | PK          | 310              | 1.4        | V     | -17.46           | 17.35               | 40.00                   | -22.65 |
| 4924.00                   | 50.92            | PK          | 149              | 1.3        | V     | -0.24            | 50.68               | 74.00                   | -23.32 |
| 4924.00                   | 42.95            | Ave         | 149              | 1.3        | V     | -0.24            | 42.71               | 54.00                   | -11.29 |
| 7386.00                   | 48.88            | PK          | 65               | 1.8        | H     | 2.83             | 51.71               | 74.00                   | -22.29 |
| 7386.00                   | 41.55            | Ave         | 65               | 1.8        | H     | 2.83             | 44.38               | 54.00                   | -9.62  |
| 2333.42                   | 46.84            | PK          | 25               | 1.5        | V     | -13.19           | 33.65               | 74.00                   | -40.35 |
| 2333.42                   | 37.43            | Ave         | 25               | 1.5        | V     | -13.19           | 24.24               | 54.00                   | -29.76 |
| 2368.79                   | 44.06            | PK          | 291              | 1.1        | H     | -13.14           | 30.92               | 74.00                   | -43.08 |
| 2368.79                   | 38.96            | Ave         | 291              | 1.1        | H     | -13.14           | 25.82               | 54.00                   | -28.18 |
| 2491.79                   | 43.37            | PK          | 359              | 1.8        | V     | -13.08           | 30.29               | 74.00                   | -43.71 |
| 2491.79                   | 37.25            | Ave         | 359              | 1.8        | V     | -13.08           | 24.17               | 54.00                   | -29.83 |

| Frequency                | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                          |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                    | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n40: Low Channel 2422MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                    | 53.78            | PK          | 36               | 1.8        | H     | -17.46           | 36.32               | 40.00                   | 36.32  |
| 37.81                    | 35.48            | PK          | 110              | 1.8        | V     | -17.46           | 18.02               | 40.00                   | 18.02  |
| 4844.00                  | 43.87            | PK          | 157              | 1.6        | V     | -1.06            | 42.81               | 74.00                   | 42.81  |
| 4844.00                  | 36.06            | Ave         | 157              | 1.6        | V     | -1.06            | 35.00               | 54.00                   | 35.00  |
| 7266.00                  | 44.42            | PK          | 155              | 1.9        | H     | 1.34             | 45.76               | 74.00                   | 45.76  |
| 7266.00                  | 35.57            | Ave         | 155              | 1.9        | H     | 1.34             | 36.91               | 54.00                   | 36.91  |
| 2345.62                  | 45.59            | PK          | 158              | 1.7        | V     | -13.19           | 32.40               | 74.00                   | 32.40  |
| 2345.62                  | 38.15            | Ave         | 158              | 1.7        | V     | -13.19           | 24.96               | 54.00                   | 24.96  |
| 2377.55                  | 42.59            | PK          | 162              | 1.4        | H     | -13.14           | 29.45               | 74.00                   | 29.45  |
| 2377.55                  | 36.57            | Ave         | 162              | 1.4        | H     | -13.14           | 23.43               | 54.00                   | 23.43  |
| 2487.68                  | 44.59            | PK          | 149              | 1.7        | V     | -13.08           | 31.51               | 74.00                   | 31.51  |
| 2487.68                  | 37.53            | Ave         | 149              | 1.7        | V     | -13.08           | 24.45               | 54.00                   | 24.45  |

| Frequency                   | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                             |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                       | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n40: Middle Channel 2437MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                       | 52.34            | PK          | 64               | 1.1        | H     | -17.46           | 34.88               | 40.00                   | -5.12  |
| 37.81                       | 36.14            | PK          | 206              | 1.5        | V     | -17.46           | 18.68               | 40.00                   | -21.32 |
| 4874.00                     | 46.79            | PK          | 287              | 2.0        | V     | -0.61            | 46.18               | 74.00                   | -27.82 |
| 4874.00                     | 36.86            | Ave         | 287              | 2.0        | V     | -0.61            | 36.25               | 54.00                   | -17.75 |
| 7311.00                     | 38.50            | PK          | 169              | 1.2        | H     | 2.21             | 40.71               | 74.00                   | -33.29 |
| 7311.00                     | 33.27            | Ave         | 169              | 1.2        | H     | 2.21             | 35.48               | 54.00                   | -18.52 |
| 2323.66                     | 45.35            | PK          | 259              | 1.8        | V     | -13.19           | 32.16               | 74.00                   | -41.84 |
| 2323.66                     | 37.63            | Ave         | 259              | 1.8        | V     | -13.19           | 24.44               | 54.00                   | -29.56 |
| 2374.21                     | 44.71            | PK          | 212              | 1.3        | H     | -13.14           | 31.57               | 74.00                   | -42.43 |
| 2374.21                     | 37.57            | Ave         | 212              | 1.3        | H     | -13.14           | 24.43               | 54.00                   | -29.57 |
| 2490.81                     | 44.82            | PK          | 141              | 1.2        | V     | -13.09           | 31.73               | 74.00                   | -42.27 |
| 2490.81                     | 36.88            | Ave         | 141              | 1.2        | V     | -13.09           | 23.79               | 54.00                   | -30.21 |

| Frequency                 | Receiver Reading | Detector    | Turn table Angle | RX Antenna |       | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 |        |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
|                           |                  |             |                  | Height     | Polar |                  |                     | Limit                   | Margin |
| (MHz)                     | (dBμV)           | (PK/QP/Ave) | Degree           | (m)        | (H/V) | (dB)             | (dBμV/m)            | (dBμV/m)                | (dB)   |
| n40: High Channel 2452MHz |                  |             |                  |            |       |                  |                     |                         |        |
| 37.81                     | 53.69            | PK          | 50               | 1.2        | H     | -17.46           | 36.23               | 40.00                   | -3.77  |
| 37.81                     | 35.16            | PK          | 30               | 1.7        | V     | -17.46           | 17.70               | 40.00                   | -22.30 |
| 4904.00                   | 49.31            | PK          | 338              | 1.2        | V     | -0.24            | 49.07               | 74.00                   | -24.93 |
| 4904.00                   | 38.34            | Ave         | 338              | 1.2        | V     | -0.24            | 38.10               | 54.00                   | -15.90 |
| 7356.00                   | 36.63            | PK          | 180              | 1.7        | H     | 2.83             | 39.46               | 74.00                   | -34.54 |
| 7356.00                   | 30.78            | Ave         | 180              | 1.7        | H     | 2.83             | 33.61               | 54.00                   | -20.39 |
| 2333.88                   | 45.80            | PK          | 252              | 1.6        | V     | -13.19           | 32.61               | 74.00                   | -41.39 |
| 2333.88                   | 37.78            | Ave         | 252              | 1.6        | V     | -13.19           | 24.59               | 54.00                   | -29.41 |
| 2354.49                   | 43.16            | PK          | 321              | 1.2        | H     | -13.14           | 30.02               | 74.00                   | -43.98 |
| 2354.49                   | 37.62            | Ave         | 321              | 1.2        | H     | -13.14           | 24.48               | 54.00                   | -29.52 |
| 2491.98                   | 44.28            | PK          | 153              | 1.9        | V     | -13.08           | 31.20               | 74.00                   | -42.80 |
| 2491.98                   | 38.76            | Ave         | 153              | 1.9        | V     | -13.08           | 25.68               | 54.00                   | -28.32 |

**Test Frequency: 18GHz~25GHz**

The measurements were more than 20 dB below the limit and not recorded.

## 9 Band Edge Measurement

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC CFR47 Part 15 Section 15.247                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Method:      | 558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Limit:       | Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |
| Test Mode:        | Transmitting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

### 9.1 Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.2 Test Result

Test result plots shown as follows:


ANT1:

TX 11b: Band edge-left side




Date: 30.JUL.2018 07:55:23

TX 11b: Band edge-right side




Date: 30.JUL.2018 07:45:13

TX 11g: Band edge-left side




Date: 30.JUL.2018 07:58:48

TX 11g: Band edge-right side




Date: 30.JUL.2018 07:37:55

TX 11n HT20: Band edge-left side




Date: 30.JUL.2018 07:31:19

## TX 11n HT20: Band edge-right side




Date: 30.JUL.2018 07:34:25

TX 11n HT40: Band edge-left side



Date: 30.JUL.2018 07:23:25


TX 11n HT40: Band edge-right side



Date: 30.JUL.2018 07:14:44


ANT2:

TX 11b: Band edge-left side




Date: 30.JUL.2018 21:45:41

TX 11b: Band edge-right side




Date: 30.JUL.2018 21:47:41

TX 11g: Band edge-left side




Date: 30.JUL.2018 21:44:12

TX 11g: Band edge-right side




Date: 30.JUL.2018 21:50:04

TX 11n HT20: Band edge-left side




Date: 30.JUL.2018 21:41:31

## TX 11n HT20: Band edge-right side




Date: 30.JUL.2018 21:51:36

## TX 11n HT40: Band edge-left side



Date: 30.JUL.2018 21:38:46

## TX 11n HT40: Band edge-right side



Date: 30.JUL.2018 21:36:33

## 10 Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 DTS Meas Guidance V04

### 10.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

### 10.2 Test Result:

#### ANT1:


| Operation mode | 6dB Bandwidth (MHz) |           |            | 99% Bandwidth (MHz) |           |            |
|----------------|---------------------|-----------|------------|---------------------|-----------|------------|
| TX 11b         | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 8.000               | 8.080     | 8.080      | 12.640              | 12.600    | 12.600     |
| TX 11g         | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 15.150              | 15.150    | 15.150     | 16.350              | 16.300    | 16.300     |
| TX 11n HT20    | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 15.174              | 15.120    | 15.120     | 17.496              | 17.496    | 17.496     |
| TX 11n HT40    | Channel 3           | Channel 6 | Channel 9  | Channel 3           | Channel 6 | Channel 9  |
|                | 35.180              | 35.200    | 35.160     | 35.750              | 35.750    | 35.750     |

#### ANT2:

| Operation mode | 6dB Bandwidth (MHz) |           |            | 99% Bandwidth (MHz) |           |            |
|----------------|---------------------|-----------|------------|---------------------|-----------|------------|
| TX 11b         | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 8.080               | 8.560     | 8.040      | 12.600              | 12.640    | 12.600     |
| TX 11g         | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 15.150              | 15.150    | 15.160     | 16.350              | 16.300    | 16.300     |
| TX 11n HT20    | Channel 1           | Channel 6 | Channel 11 | Channel 1           | Channel 6 | Channel 11 |
|                | 15.120              | 15.120    | 15.120     | 17.496              | 17.496    | 17.496     |
| TX 11n HT40    | Channel 3           | Channel 6 | Channel 9  | Channel 3           | Channel 6 | Channel 9  |
|                | 35.240              | 35.200    | 35.200     | 35.860              | 35.750    | 35.750     |


ANT1

Mode: TX 11b channel 1




Date: 30.JUL.2018 05:55:04


Mode: TX 11b channel 6




Date: 30.JUL.2018 05:56:43




Date: 30.JUL.2018 05:58:19



Date: 30.JUL.2018 06:00:21




Date: 30.JUL.2018 06:02:17




Date: 30.JUL.2018 06:04:15

## Mode: TX 11n HT20 channel 1




Date: 30.JUL.2018 06:06:23


## Mode: TX 11n HT20 channel 6



Date: 30.JUL.2018 06:08:30




Date: 30.JUL.2018 06:10:06




Date: 30.JUL.2018 06:12:25

## Mode: TX 11n HT40 channel 6



Date: 30.JUL.2018 06:15:25


## Mode: TX 11n HT40 channel 9



Date: 30.JUL.2018 06:17:10


ANT2

Mode: TX 11b channel 1




Date: 30.JUL.2018 20:00:22


Mode: TX 11b channel 6




Date: 30.JUL.2018 20:02:32




Date: 30.JUL.2018 20:04:38



Date: 30.JUL.2018 20:13:20




Date: 30.JUL.2018 20:11:39




Date: 30.JUL.2018 20:08:58

Mode: TX 11n HT20 channel 1




Date: 30.JUL.2018 20:15:48


Mode: TX 11n HT20 channel 6



Date: 30.JUL.2018 20:18:43




Date: 30.JUL.2018 20:20:00




Date: 30.JUL.2018 20:34:24

Mode: TX 11n HT40 channel 6



Date: 30.JUL.2018 20:30:53

Mode: TX 11n HT40 channel 9



Date: 30.JUL.2018 20:25:31

## 11 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

558074 D01 DTS Meas Guidance V04

### 11.1 Test Procedure:

558074 D01 DTS Meas Guidance V04

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak, Set the span to fully encompass the DTS bandwidth.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

### 11.2 Test Result:

ANT1:

|                                 |         |         |
|---------------------------------|---------|---------|
| Test mode :TX 11b               |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.82                           | 10.73   | 10.76   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11g               |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.27                           | 10.21   | 10.30   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11n HT20          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.13                           | 10.17   | 10.10   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11n HT40          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2422MHz                         | 2437MHz | 2452MHz |
| 9.67                            | 9.82    | 9.83    |
| Limit: 1W/30dBm                 |         |         |

**ANT2:**

|                                 |         |         |
|---------------------------------|---------|---------|
| Test mode :TX 11b               |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.80                           | 10.92   | 10.95   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11g               |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.23                           | 10.32   | 10.27   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11n HT20          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 10.12                           | 10.14   | 10.08   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11n HT40          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2422MHz                         | 2437MHz | 2452MHz |
| 9.84                            | 9.76    | 9.79    |
| Limit: 1W/30dBm                 |         |         |

**ANT1+ANT2:**

|                                 |         |         |
|---------------------------------|---------|---------|
| Test mode :TX 11n HT20          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2412MHz                         | 2437MHz | 2462MHz |
| 13.14                           | 13.17   | 13.10   |
| Limit: 1W/30dBm                 |         |         |
| Test mode :TX 11n HT40          |         |         |
| Maximum Peak Output Power (dBm) |         |         |
| 2422MHz                         | 2437MHz | 2452MHz |
| 12.77                           | 12.80   | 12.82   |
| Limit: 1W/30dBm                 |         |         |

## 12 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: 558074 D01 DTS Meas Guidance V04

### 12.1 Test Procedure:

558074 D01 DTS Meas Guidance V04

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section  
Submit this plot.

### 12.2 Test Result:

#### ANT1:

|                               |         |         |
|-------------------------------|---------|---------|
| Test mode :TX 11b             |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -14.32                        | -14.68  | -15.18  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11g             |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -15.82                        | -15.92  | -17.27  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11n HT20        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -15.60                        | -16.65  | -15.30  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11n HT40        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2422MHz                       | 2437MHz | 2452MHz |
| -18.07                        | -18.92  | -19.04  |
| Limit: 8dBm per 3kHz          |         |         |

**ANT2:**


|                               |         |         |
|-------------------------------|---------|---------|
| Test mode :TX 11b             |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -15.99                        | -16.13  | -17.07  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11g             |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -16.75                        | -16.73  | -17.62  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11n HT20        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -15.69                        | -13.97  | -16.97  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11n HT40        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2422MHz                       | 2437MHz | 2452MHz |
| -18.57                        | -19.16  | -19.63  |
| Limit: 8dBm per 3kHz          |         |         |

**ANT1+ANT2:**

|                               |         |         |
|-------------------------------|---------|---------|
| Test mode :TX 11n HT20        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2412MHz                       | 2437MHz | 2462MHz |
| -12.63                        | -12.10  | -13.04  |
| Limit: 8dBm per 3kHz          |         |         |
| Test mode :TX 11n HT40        |         |         |
| Power Spectral (dBm per 3kHz) |         |         |
| 2422MHz                       | 2437MHz | 2452MHz |
| -15.30                        | -16.03  | -16.31  |
| Limit: 8dBm per 3kHz          |         |         |


ANT1:

Model: TX 11b Low Channel




Date: 30.JUL.2018 06:52:15


Model: TX 11b Middle channel




Date: 30.JUL.2018 06:53:21




Date: 30.JUL.2018 06:55:22




Date: 30.JUL.2018 06:57:03




Date: 30.JUL.2018 06:58:28




Date: 30.JUL.2018 06:59:38




Date: 30.JUL.2018 07:00:43




Date: 30.JUL.2018 07:01:19




Date: 30.JUL.2018 07:02:08



Date: 30.JUL.2018 07:07:30




Date: 30.JUL.2018 07:09:23



Date: 30.JUL.2018 07:09:58


ANT2:

Model: TX 11b Low Channel




Date: 30.JUL.2018 21:21:25


Model: TX 11b Middle channel




Date: 30.JUL.2018 21:22:08




Date: 30.JUL.2018 21:22:43




Date: 30.JUL.2018 21:23:44




Date: 30.JUL.2018 21:24:33




Date: 30.JUL.2018 21:25:39




Date: 30.JUL.2018 21:27:13




Date: 30.JUL.2018 21:28:25




Date: 30.JUL.2018 21:29:25



Date: 30.JUL.2018 21:31:07



Date: 30.JUL.2018 21:32:24



Date: 30.JUL.2018 21:33:31


### 13 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT have two Integrated Antenna, meets the requirements of FCC 15.203.



## **14 RF Exposure Evaluation**

Please refer to RF Exposure report.

## **15 Photographs – Test Setup Photos and EUT**

Refer to the file WS-WN536A8\_External Photos, WS-WN536A8\_Internal Photos and WS-WN536A8\_Test Setup Photos.

=====End of Report=====