

Model Information	
FCC ID:	NZLFDMHL6B
Model:	FDMHL6B
# of Transmitters Simultaneously Transmitting	3
Distance to User (cm)	20
Mobile or Portable	Mobile
Field Strength or Worse Case Output Power	
Radiated Field Strength - 288MHz(dBuV/m)	82.11
Radiated Field Strength - 310MHz(dBuV/m)	84.23
Radiated Field Strength - 365MHz(dBuV/m)	84.46
Radiated Field Strength - 430MHz(dBuV/m)	86.24
Worse Case Output Power - 902-928MHz (dBm)	6.127
Worse Case Output Power - BLE - 2.4GHz (dBm)	4.22
Antenna Gain	
Worse Case Antenna Gain - HL High Band (dBi)	-9.48
Worse Case Antenna Gain - BLE (dBi)	2.24

Requirements	
Distance to User (cm):	d≥20
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	288
Measured Field Strength (dBuV/m):	82.11
Distance to User (cm):	20
dBuV/m to V/m	0.013
Worst Case EIRP (mW)	0.048766
Power Density (mW/cm ²)	0.000010
Power Density Limit (mW/cm ²)	0.2
Ratio	4.85089E-05

Exposure Evaluation
Equation from page 18 of OET Bulletin 65, Edition 97-01
 $S=(PG)/4\pi R^2$
Where S: power density
P: power input to the antenna
G: power gain of the antenna in the direction of interest relative to an isotropic radiator.
R: distance to the center of radiation of the antenna

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	Permissible Exposure (MPE)
(ii) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	<30	
1.34-30	824/f	2.19/f	*(180/f ²)	<30	
30-300	27.5	0.073	0.2	<30	
300-1,500			f/1500	<30	
1,500-100,000			1.0	<30	

f = frequency in MHz. * = Plane-wave equivalent power density.

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

Requirements	
Distance to User (cm):	d>20
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	310
Measured Field Strength (dBuV/m):	84.23
Distance to User (cm):	20
dBuV/m to V/m	0.016
Worst Case EIRP (mW)	0.079455
Power Density (mW/cm ²)	0.000016
Power Density Limit (mW/cm ²)	0.206666667
Ratio	7.64858E-05

Exposure Evaluation
Equation from page 18 of OET Bulletin 65, Edition 97-01
 $S=(PG)/4\pi R^2$
Where S: power density
P: power input to the antenna
G: power gain of the antenna in the direction of interest relative to an isotropic radiator.
R: distance to the center of radiation of the antenna

Table 1 from 47 CFR 1.1310—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

Requirements	
Distance to User (cm):	d≥20
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	365
Measured Field Strength (dBuV/m):	84.46
Distance to User (cm):	20
dBuV/m to V/m	0.017
Worst Case EIRP (mW)	0.083776
Power Density (mW/cm ²)	0.000017
Power Density Limit (mW/cm ²)	0.24333333
Ratio	6.84936E-05

Exposure Evaluation
Equation from page 18 of OET Bulletin 65, Edition 97-01
 $S=(PG)/4\pi R^2$
Where S: power density
P: power input to the antenna
G: power gain of the antenna in the direction of interest relative to an isotropic radiator.
R: distance to the center of radiation of the antenna

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	Permissible Exposure (MPE)
(ii) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	<30	
1.34-30	824/f	2.19/f	*(180/f ²)	<30	
30-300	27.5	0.073	0.2	<30	
300-1,500			f/1500	<30	
1,500-100,000			1.0	<30	

f = frequency in MHz. * = Plane-wave equivalent power density.

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

Requirements	
Distance to User (cm):	d≥20
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	430
Measured Field Strength (dBuV/m):	86.24
Distance to User (cm):	20
dBuV/m to V/m	0.021
Worst Case EIRP (mW)	0.126218
Power Density (mW/cm ²)	0.000025
Power Density Limit (mW/cm ²)	0.286666667
Ratio	8.7594E-05

Exposure Evaluation
Equation from page 18 of OET Bulletin 65, Edition 97-01
 $S=(PG)/4\pi R^2$
Where S: power density
P: power input to the antenna
G: power gain of the antenna in the direction of interest relative to an isotropic radiator.
R: distance to the center of radiation of the antenna

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	Permissible Exposure (MPE)
(ii) Limits for General Population/Uncontrolled Exposure					
0.3-1.34	614	1.63	*(100)	<30	
1.34-30	824/f	2.19/f	*(180/f ²)	<30	
30-300	27.5	0.073	0.2	<30	
300-1,500			f/1500	<30	
1,500-100,000			1.0	<30	

f = frequency in MHz. * = Plane-wave equivalent power density.

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

Requirements	
Distance to User (cm):	$d \geq 20$
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	902
Distance to User (cm):	20
Worse Case Output Power (dBm):	6.13
Distance to User (cm):	20.1
Antenna Gain (dBi)	-9.48
Numerical Antenna Gain	0.112719746
Tune Up Adjustment (dB)	1
Worse Case Output Power with tune up tolerance (dBm):	7.13
Worse Case Output Power with tune up tolerance (mW):	5.161
EIRP (mW)	0.581701
Power Density (mW/cm^2)	0.001027
Power Density Limit (mW/cm^2)	0.601333333
Ratio	0.001708186

Exposure Evaluation

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	$824/f$	$2.19/f$	*($180/f^2$)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			$f/1500$	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Permissible Exposure (MPE)

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

Requirements	
Distance to User (cm):	$d \geq 20$
Exposure Condition:	Mobile
Model Information	
Frequency (MHz):	2402
Distance to User (cm):	20
Worse Case Output Power (dBm):	4.22
Distance to User (cm):	20
Antenna Gain (dBi)	2.24
Numerical Antenna Gain	1.674942876
Tune Up Adjustment (dB)	1
Worse Case Output Power with tune up tolerance (dBm):	5.22
Worse Case Output Power with tune up tolerance (mW):	3.327
EIRP (mW)	5.571857
Power Density (mW/cm^2)	0.001109
Power Density Limit (mW/cm^2)	1
Ratio	0.001109048

Exposure Evaluation

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

Table 1 from 47 CFR 1.1310—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	$824/f$	$2.19/f$	*($180/f^2$)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			$f/1500$	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

According to KDB447498 Section 3, the RF exposure guidelines adopted by the FCC are based on SAR and MPE limits. The basic restrictions for human exposure is defined by SAR limits. MPE limits are derived from the SAR limits, in terms of free-space field strength and power density.

FCC Total Exposure Ratio	
Specification/Frequency Band	Worse Case
15.231 - 286-440MHz	0.000088
15.247 - 902-928MHz	0.001708
15.247 - 2.4GHz (BLE)	0.001109
Total Exposure Ratio=	0.003316