





Test Report No.:
FCCSZ2023-0011-H

RF Test Report

FCC ID : O3Q10-8231
EUT : Smart PDM assembly
MODEL : 10-8231
BRAND NAME : N/A
APPLICANT : THERMASOL STEAMBATH CO.
Classification Of Test : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.

Applicant		Name: THERMASOL STEAMBATH CO. Address: 1958 STEAM WAY ROUND ROCK, TX 78665 USA	
Manufacturer		Name: Chengdu Vantron Technology Co., Ltd. Address: No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, P.R. China	
Equipment Under Test		Product Name: Smart PDM assembly Model/Type: 10-8231 Brand Name: N/A Serial NO.: N/A Sample NO.: 2-1	
Date of Receipt.	2023.10.16	Date of Testing	2023.10.16~2023.11.02
Test Specification		Test Result	
FCC Part 2 (Section 2.1091) KDB 447498 D04 IEEE C95.3		PASS	
Evaluation of Test Result		The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2023.11.06	
Tested by:  <u>Liang Jiatong</u> Name Signature	Tested by:  <u>Huang Meng</u> Name Signature	Approved by:  <u>Dong Sanbi</u> Name Signature	
Other Aspects: NONE.			
Abbreviations: OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 GENERAL PRODUCT INFORMATION	5
2 RF EXPOSURE LIMITGENERAL INFORMATION	6
2.1 CLASSIFICATION	6
2.2 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (FCC)	6
2.3 CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER	7

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2023-0011-H	Original release	2023.11.06

1 GENERAL PRODUCT INFORMATION

PRODUCT	Smart PDM assembly
BRAND	N/A
TEST MODEL	10-8231
ADDITIONAL MODEL	N/A
POWER SUPPLY	DC 24V host unit
STANDARDS	FCC Part 2 (Section 2.1091)
	KDB 447498 D04
	IEEE C95.3

2 RF EXPOSURE LIMIT GENERAL INFORMATION

2.1 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.2 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (FCC)

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda / 2 \pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda / 4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF SOURCE FREQUENCY (MHZ)	THRESHOLD ERP(W)
0.3 -1.34	$1,920 R^2$
1.34 - 30	$3,450 R^2 F^2$
30 -300	$3.83 R^2$
300-1500	$0.0128 R^2 F$
1500-100,000	$19.2 R^2$

2.3 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The measured conducted Power

Mode	Conducted Power (dBm)
BT-EDR	6.04(Note)
BT-LE	4.91
2.4G WIFI	13.87
5.1G WIFI	14.84
5.8G WIFI	11.67

Note:BT-EDR is peak power

The tuned conducted Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT-EDR	2402-2480	6	± 1	5	7
BT-LE	2402-2480	5	± 1	4	6
2.4G WIFI	2412-2472	14	± 1	13	15
5.1G WIFI	5180-5240	15	± 1	14	16
5.8G WIFI	5745-5825	12	± 1	11	13

MAXIMUM PERMISSIBLE EXPOSURE (FCC)

Mode	Frequency (MHz)	Max Power (dBm)	Antenna Gain (dBi)	R (cm)	EIRP (dBm)	ERP (dBm)	EIRP (W)	Threshold ERP(W)	Ratio
BT-EDR	2402-2480	7	2.75	20	9.75	7.6	0.0057	0.77	0.007
BT-LE	2402-2480	6	2.75	20	8.75	6.6	0.0046	0.77	0.006
2.4G WIFI	2412-2472	15	2.75	20	17.75	15.6	0.0363	0.77	0.047
5.1G WIFI	5180-5240	16	2.64	20	18.64	16.49	0.0446	0.77	0.058
5.8G WIFI	5745-5825	13	3.20	20	16.2	14.05	0.0254	0.77	0.033
Sum of ratio = BT-EDR + 5.1G WIFI									0.065

Note1: This device can operate simultaneously in BT and WIFI.

Note2: ERP=EIRP-2.15dB

Conclusion:

Therefore, the worst-case situation is 0.065(Sum of Ratios), which is less than "1". This confirmed that the device compliance with FCC RF exposure requirements..

----- End of the Report -----

Important

- (1) The test report is valid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

***The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented. ***

Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street,
Longhua District, Shenzhen, Guangdong, 518110, P. R. China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>