



FCC – Radio Frequency Exposure Report

Report Number : **607902509901S01** Date of Issue: September 4, 2025

Model/HVIN : RS HMI Control 01, RS HMI Control 00, RS HMI Control 02
RS HMI Control 03, RS HMI Control 04

Product Type : RS HMI Control

Applicant : Dayton Industrial Co., Ltd.

Address : 2 – 12 Kwai Fat Road, 11-A Kwai Chung, New Territories, Hong Kong

Production Facility : Kendy Electronics (Dongguan) Co., Ltd.

Address : No.2, Xianlin Second Road, Xinsi Huangtang Village, Hengli Town,
Dongguan City, Guangdong, China

Test Result : **n Positive** o Negative

Total pages including Appendices : 2

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

RF Exposure Estimation – SAR Exempt Evaluation

This exposure evaluation is intended for **FCC ID: O4G387**

Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy levels in excess of the Commission's guideline.

According to 447498 D01 General RF Exposure Guidance v06, no SAR is required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

Calculation method

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The Max Power according to the RF Report No.: 6079009901R01.

Conducted Power + tune up tolerance

= -1.82 dBm + 1 dB

= 0.82 dBm

= 1.21 mW

Distance = 5 mm

$f(\text{GHz}) = 2.480 \text{ GHz}$

$[1.21 / 5] \cdot \text{SQRT}(2.480) = 0.38$

As $0.38 \leq 3.0$

Therefore, this device is exempt from stand-alone SAR test requirements.

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -


Reviewed by:

Prepared by:


Tested by:



Eric LI
Section Manager



Kevin DU
EMC Project Engineer



Carry Cai
Test Engineer