



Interocean EMC Technology Corp.

No.5-2 Lin 1 Tin-Fu Tsun, Lin-Kou Hsiang,
Taipei County, Taiwan R.O.C. 244
TEL : +886 2 2600 6861 FAX : +886 2 2600 6859
E-mail : kent@emc-online.net

September 7, 2000

Ref. No. : 0KF090701

TO : Errol Chang / FCC

Subject : FCC ID 04GSP10506-T

Applicant: Dayton Industrial Co., Ltd.

Correspondence Reference Number: 15888

731 Confirmation Number: EA98226

Dear Mr. Chang,

The operational description as page 2 & 3 of operation manual.

The operational description during test explaining as following pages.

If you have any further question please contact me.

Sincerely,

Kent J.K. Hsu

Engineering Dept.

Interocean EMC Technology Co.



Radiated Emission (0.009MHz~0.490MHz)

1. The transmitter mounted on the cylinder.
2. The loop receive antenna stand far away the transmitter in 20cm.
3. The spectrum set up in max hold mode to record the signal curve.
4. The magnet screw getting close to transmitter to trigger magnet switch and reduce signal then leave away.
5. repeat step 4 until obtain the curve as page 9 of test report.

Radiated Emission (30MHz~300MHz)

1. The transmitter mounted on the cylinder and the magnet screw mounted on rotary music box(simulator tool) as following figure 1.
Note: the rotary music box is construed by spring clockwork type.
2. Every time the magnet screw close to transmitter then trigger and reduce the signal.




Fig.1 Top view