

CETECOM ICT Services GmbH

Test report no.: **2_2690-B/01** Issue Date: 22.10.2001 Page 16
(33)

Equipment under test : **U952T**

Ambient temperature : **23....°C**

Relative humidity : **44 %**

SPURIOUS RADIATIONS (RADIATED)

SUBCLAUSE 8.5

Transmitter on STANDBY

SPURIOUS EMISSIONS LEVEL (nW)									
Orientation	CH 1(449.8 MHz)			CHANNEL 2			CHANNEL 3		
	f (MHz)	Band-width	Level (nW)	f (MHz)	Band-width	Level (nW)	f (MHz)	Band-width	Level (nW)
Vert.	35.07	100	0.5	35.07	100	1.0	35.02	100	0.2
Vert.	53.45	100	1.0	44.56	100	0.5	55.30	100	0.6
Vert.	55.30	100	1.8	55.7	100	1.9	77.42	100	0.6
Vert.	125.00	100	0.5	57.14	100	1.9	125.00	100	0.1
Vert.	187.50	100	0.6	77.42	100	1.0	187.52	100	0.9
Vert.	250.00	100	1.9	88.43	100	0.3	250.00	100	1.8
Vert.	500.00	100	0.3	414.07	100	0.8	454.40	100	1.8
Vert.	795.66	100	1.9	750.00	100	0.5	670.63	100	1.9
Vert.	830.74		1.8				704.38	100	1.9
Vert.							920.70	100	1.9
.							947.85	100	1.9
							1125.00	1000	1.2
Measurement Uncertainty						±3 dB			

LIMITS
TABLE 3

SUBCLAUSE 5.1.1

25 MHz to 1000 MHz	2.0 nW / -57 dBm
> 1 GHz to 4 GHz	20.0 nW / -47 dBm