



FCC RF Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : 802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card
BRAND NAME : Lenovo
MODEL NAME : QCNFA344A
FCC ID : O57-QCNFA344AH
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was installed into Notebook Computer (Brand Name: Lenovo, Model Name: Lenovo YOGA 920-13IKBXXXXXX, 80Y7XXXXXX, Lenovo YOGA 920-13IKB GlassXXXXXX, 80Y8XXXXXX, Lenovo YOGA 6 ProXXXXXX (The "X" in model name can be 0 to 9, A to Z, a to z, "-" or blank), Marketing Name: Lenovo YOGA 920) during test.

The product was received on Jun. 02, 2017 and testing was completed on Jul. 04, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



Sporton International (KunShan) INC.

No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification of Equipment Under Test.....	6
1.4 Keypart List.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Descriptions of Test Mode	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
3 TEST RESULT	12
3.1 Peak and Average Output Power Measurement.....	12
3.2 Radiated Band Edges and Spurious Emission Measurement	15
3.3 AC Conducted Emission Measurement.....	21
3.4 Antenna Requirements.....	25
4 LIST OF MEASURING EQUIPMENT.....	26
5 UNCERTAINTY OF EVALUATION.....	27
APPENDIX A. RADIATED SPURIOUS EMISSION	
APPENDIX B. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR760219A	Rev. 01	Initial issue of report	Jul. 12, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
-	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	1
-	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	1
-	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	1
-	15.247(a)(1)	20dB Bandwidth	NA	Pass	1
-	-	99% Bandwidth	-	Pass	1
3.1	15.247(b)(1)	Peak and Average Output Power	$\leq 125\text{ mW}$	Pass	-
-	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	1
-	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	1
3.2	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.23 dB at 32.910 MHz
3.3	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.5 dB at 0.198 MHz
3.4	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Remark:

- All conducted test items were leverage from module RF report which can refer to Report No. "RF150107E06B-2".

1 General Description

1.1 Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.

NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	802.11a/b/g/n/ac + BT 4.1 M.2 2230 Type Card
Brand Name	Lenovo
Model Name	QCNFA344A
FCC ID	O57-QCNFA344AH
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n/ac HT20/HT40/VHT20/VHT40 WLAN 5GHz 802.11a/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth v3.0+EDR, Bluetooth v4.0 LE, Bluetooth v4.1 LE
EUT Stage	Identical Prototype

Host Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	Lenovo YOGA 920-13IKBXXXXXX, 80Y7XXXXXX, Lenovo YOGA 920-13IKB GlassXXXXXX, 80Y8XXXXXX, Lenovo YOGA 6 ProXXXXXX (The "X" in model name can be 0 to 9, A to Z, a to z, "-" or blank)
Marketing Name	Lenovo YOGA 920
Applicant	Lenovo (Shanghai) Electronics Technology Co., Ltd. NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, Shanghai, 200131 China
Manufacturer	Lenovo PC HK Limited 23/F, Lincoln House, Taikoo Place, 979 King's Road, Quarry Bay Hong Kong

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum (Peak) Output Power to antenna	Bluetooth BR(1Mbps) : 7.72 dBm (0.0059 W) Bluetooth EDR (2Mbps) : 9.03 dBm (0.0080 W) Bluetooth EDR (3Mbps) : 9.29 dBm (0.0085 W)
Antenna Type / Gain	PIFA Antenna with gain 0.56 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.4 Keypart List

There are five configurations of samples under test, the keypart list are shown in the following table:

	Supplier	Description
CPU	Intel	Intel i7-8550U 1.8G/4C/8M
		Intel i5-8250U 1.6G/4C/6M
RAM	/	DDR4 8/12/16GB
SSD	Samsung	MZVLW256HEHP 256G
	Toshiba	TSB XG4 256G
	Samsung	MZVLW512HMJP 512G
	Toshiba	TSB XG4 512G
	Samsung	MZVLW1T0HMLH-000L2 1TB
LCD	LGD	LP139UD1-SPC1
	AUO	B139HAN03.0
Adapter	Chicony	ADLX65YCC3A 20V3.25A
	Liteon	ADLX65YLC3A 20V3.25A
	Delta	ADLX65YDC3A 20V3.25A
	Acbel	ADLX65YAC3A 20V3.25A
Battery	Simplo	L16M4P60
	Celxpert	L16C4P61
WLAN	Qualcomm Atheros	QCNFA344A
Camera	BISON	BNG119VSN
	Chicony	CKFGH44
	AVC	HAA-8NC302
Active Pen (optional)	Wacom	ESP101Bxxxx, x=0~9,A-Z,a~z, for marketing use only.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	Sporton International (KunShan) INC.			
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	CO01-KS	03CH03-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Peak Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.63 dBm	8.18 dBm	8.50 dBm
Ch39	2441MHz	7.15 dBm	8.58 dBm	8.84 dBm
Ch78	2480MHz	7.72 dBm	9.03 dBm	9.29 dBm

Channel	Frequency	Bluetooth RF Average Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.62 dBm	6.55 dBm	6.74 dBm
Ch39	2441MHz	6.95 dBm	6.75 dBm	6.67 dBm
Ch78	2480MHz	7.39 dBm	7.14 dBm	6.96 dBm

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). The worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Radiated Test Cases	Bluetooth BR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 1 + USB Link with U Disk USB Port + Paly H Plane + Adapter 1 With Type C 1 + USB Link with Type C 2 for Sample 1
	Mode 2 : Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 1 + USB Link with U Disk USB Port + MPEG4/Color Bar + Adapter 1 With Type C 1 + USB Link with Type C 2 for Sample 1
	Mode 3 : Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 2 + USB Link with U Disk USB Port + Adapter 2 With Type C 1 + USB Link with Type C 2 for Sample 2
	Mode 4 : Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 3 + USB Link with U Disk USB Port + Adapter 3 With Type C 1 + USB Link with Type C 2 for Sample 3
	Mode 5 : Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 4 + USB Link with U Disk USB Port + Adapter 4 With Type C 1 + USB Link with Type C 2 for Sample 4
	Mode 6 : Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 5 + USB Link with U Disk USB Port + Adapter 1 With Type C 1 + USB Link with Type C 2 for Sample 5
Remark: 1. The worst case of conducted emission is mode 3; only the test data of it was reported. 2. Type C 1 is USB charging port, Type C 2 is USB link port.	

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

3 Test Result

3.1 Peak and Average Output Power Measurement

3.1.1 Limit of Peak and Average Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.63	20.97	Pass
39	2441	7.15	20.97	Pass
78	2480	7.72	20.97	Pass

Test Mode :	2Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	8.18	20.97	Pass
39	2441	8.58	20.97	Pass
78	2480	9.03	20.97	Pass

Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	8.50	20.97	Pass
39	2441	8.84	20.97	Pass
78	2480	9.29	20.97	Pass

3.1.6 Test Result of Average Output Power (Report Only)

Test Mode :	1Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.62	-	-
39	2441	6.95	-	-
78	2480	7.39	-	-

Test Mode :	2Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.55	-	-
39	2441	6.75	-	-
78	2480	7.14	-	-

Test Mode :	3Mbps	Temperature :	21~25°C
Test Engineer :	Silent Hai	Relative Humidity :	51~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	6.74	-	-
39	2441	6.67	-	-
78	2480	6.96	-	-

3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz




3.2.5 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.891 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.891 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.891 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100\text{ms}) = -24.76 \text{ dB}$$

3.2.6 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.2.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A and B.

3.2.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A and B.

3.3 AC Conducted Emission Measurement

3.3.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

7. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
8. Connect EUT to the power mains through a line impedance stabilization network (LISN).
9. All the support units are connecting to the other LISN.
10. The LISN provides 50 ohm coupling impedance for the measuring instrument.
11. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
12. Both sides of AC line were checked for maximum conducted interference.
13. The frequency range from 150 kHz to 30 MHz was searched.
14. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.3.4 Test Setup





3.3.5 Test Result of AC Conducted Emission

Test Mode :	Mode 3	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 2 + USB Link with U Disk USB Port + Adapter 2 With Type C 1 + USB Link with Type C 2 for Sample 2		




Site : CO01-KS
Condition : FCC PART 15C LISN-L-161017-060103 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.198	49.21	-14.50	63.71	38.60	0.28	10.33	QP
2 *	0.198	43.21	-10.50	53.71	32.60	0.28	10.33	Average
3	0.336	41.10	-18.21	59.31	30.60	0.27	10.23	QP
4	0.336	33.10	-16.21	49.31	22.60	0.27	10.23	Average
5	0.564	40.75	-15.25	56.00	30.31	0.26	10.18	QP
6	0.564	31.75	-14.25	46.00	21.31	0.26	10.18	Average
7	0.675	40.73	-15.27	56.00	30.30	0.25	10.18	QP
8	0.675	29.93	-16.07	46.00	19.50	0.25	10.18	Average
9	4.224	39.95	-16.05	56.00	29.50	0.21	10.24	QP
10	4.224	29.75	-16.25	46.00	19.30	0.21	10.24	Average
11	4.647	39.65	-16.35	56.00	29.20	0.21	10.24	QP
12	4.647	30.75	-15.25	46.00	20.30	0.21	10.24	Average



Test Mode :	Mode 3	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN (2.4G) Link + Camera + Earphone + Battery 2 + USB Link with U Disk USB Port + Adapter 2 With Type C 1 + USB Link with Type C 2 for Sample 2		



Site : CO01-KS
Condition : FCC PART 15C LISN-N-161017-060103 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.204	46.86	-16.59	63.45	36.20	0.33	10.33	QP
2	0.204	35.96	-17.49	53.45	25.30	0.33	10.33	Average
3	1.303	37.79	-18.21	56.00	27.20	0.40	10.19	QP
4	1.303	26.19	-19.81	46.00	15.60	0.40	10.19	Average
5	1.698	37.50	-18.50	56.00	26.90	0.41	10.19	QP
6	1.698	25.90	-20.10	46.00	15.30	0.41	10.19	Average
7	1.810	38.20	-17.80	56.00	27.60	0.41	10.19	QP
8	1.810	25.80	-20.20	46.00	15.20	0.41	10.19	Average
9	2.055	38.80	-17.20	56.00	28.20	0.41	10.19	QP
10	2.055	25.20	-20.80	46.00	14.60	0.41	10.19	Average
11	2.334	37.80	-18.20	56.00	27.20	0.40	10.20	QP
12	2.334	23.20	-22.80	46.00	12.60	0.40	10.20	Average
13	2.474	37.21	-18.79	56.00	26.61	0.40	10.20	QP
14	2.474	22.81	-23.19	46.00	12.21	0.40	10.20	Average
15	4.027	42.13	-13.87	56.00	31.50	0.39	10.24	QP
16	4.027	31.93	-14.07	46.00	21.30	0.39	10.24	Average
17 *	4.407	43.83	-12.17	56.00	33.21	0.38	10.24	QP
18	4.407	33.53	-12.47	46.00	22.91	0.38	10.24	Average
19	4.598	42.83	-13.17	56.00	32.21	0.38	10.24	QP
20	4.598	32.93	-13.07	46.00	22.31	0.38	10.24	Average



3.4 Antenna Requirements

3.4.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.4.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.4.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Jun. 09, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Jun. 09, 2017	Jan. 18, 2018	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 09, 2016	Jun. 15, 2017	Aug. 08, 2017	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Jun. 15, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Jun. 15, 2017	Nov. 22, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Jun. 15, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Jun. 15, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz ~40GHz	Oct. 19, 2016	Jun. 15, 2017	Oct. 18, 2017	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz ~1000MHz / 32 dB	Apr. 18, 2017	Jun. 15, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
High Gain Amplifier	MITEQ	AMF-7D-001018 00-30-10P	2025788	1GHz~18GHz	Apr. 18, 2017	Jun. 15, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 13, 2016	Jun. 15, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Oct. 13, 2016	Jun. 15, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 15, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 15, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 15, 2017	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Apr. 20, 2017	Jul. 04, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Jul. 04, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Jul. 04, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Jul. 04, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
--	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
--	-------



Appendix A. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2356.15	49.37	-24.63	74	54.9	25.55	5.43	36.51	313	223	P	H
		2356.15	24.61	-29.39	54	-	-	-	-	-	-	A	H
	*	2402	99.66	-	-	104.81	25.8	5.47	36.42	313	223	P	H
	*	2402	74.90	-	-	-	-	-	-	-	-	A	H
		2364.21	49.3	-24.7	74	54.83	25.55	5.43	36.51	395	64	P	V
		2364.21	24.54	-29.46	54	-	-	-	-	-	-	A	V
	*	2402	98.23	-	-	103.38	25.8	5.47	36.42	395	64	P	V
	*	2402	73.47	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2375.78	49.04	-24.96	74	54.38	25.67	5.45	36.46	321	160	P	H
		2375.78	24.28	-29.72	54	-	-	-	-	-	-	A	H
	*	2442	100.84	-	-	105.91	25.89	5.49	36.45	321	160	P	H
	*	2442	76.08	-	-	-	-	-	-	-	-	A	H
		2493.42	49.36	-24.64	74	54.35	25.97	5.52	36.48	321	160	P	H
		2493.42	24.60	-29.40	54	-	-	-	-	-	-	A	H
		2377.99	49.05	-24.95	74	54.39	25.67	5.45	36.46	380	57	P	V
		2377.99	24.29	-29.71	54	-	-	-	-	-	-	A	V
	*	2442	99.41	-	-	104.48	25.89	5.49	36.45	380	57	P	V
	*	2442	74.65	-	-	-	-	-	-	-	-	A	V
		2486.07	49.64	-24.36	74	54.66	25.94	5.51	36.47	380	57	P	V
		2486.07	24.88	-29.12	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	100.85	-	-	105.87	25.94	5.51	36.47	347	159	P	H
	*	2480	76.09	-	-	-	-	-	-	-	-	A	H
		2483.9	54.9	-19.1	74	59.92	25.94	5.51	36.47	347	159	P	H
		2483.9	30.14	-23.86	54	-	-	-	-	-	-	A	H
	*	2480	99.16	-	-	104.18	25.94	5.51	36.47	372	53	P	V
	*	2480	74.40	-	-	-	-	-	-	-	-	A	V
		2483.69	53.67	-20.33	74	58.69	25.94	5.51	36.47	372	53	P	V
		2483.69	28.91	-25.09	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4806	41.49	-32.51	74	39.66	30.62	7.71	36.5	160	360	P	H
		4806	41.42	-32.58	74	39.59	30.62	7.71	36.5	160	0	P	V
BT CH 39 2441MHz		4884	41.19	-32.81	74	39.11	30.85	7.76	36.53	160	0	P	H
		7320	46.78	-27.22	74	38.4	34.85	9.78	36.25	160	0	P	H
		4884	42.05	-31.95	74	39.97	30.85	7.76	36.53	160	360	P	V
		7320	46.65	-27.35	74	38.27	34.85	9.78	36.25	160	360	P	V
BT CH 78 2480MHz		4962	43.59	-30.41	74	41.21	31.13	7.82	36.57	160	360	P	H
		7440	45.72	-28.28	74	36.97	35.17	9.87	36.29	160	360	P	H
		4960	41.89	-32.11	74	39.51	31.13	7.82	36.57	160	0	P	V
		7440	46.23	-27.77	74	37.48	35.17	9.87	36.29	160	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		34.85	32.58	-7.42	40	38.47	25.7	0.71	32.3	140	35	P	H
		95.96	25.34	-18.16	43.5	37.97	18.44	1.18	32.25	-	-	P	H
		153.19	26.55	-16.95	43.5	39.86	17.47	1.5	32.28	-	-	P	H
		202.66	33.88	-9.62	43.5	47.39	17.01	1.73	32.25	-	-	P	H
		353.01	26.42	-19.58	46	34.34	21.85	2.31	32.08	-	-	P	H
		701.24	29.14	-16.86	46	29.5	27.97	3.35	31.68	-	-	P	H
		32.91	32.77	-7.23	40	38.24	26.14	0.69	32.3	100	20	P	V
		46.49	32.04	-7.96	40	45.23	18.2	0.84	32.23	-	-	P	V
		93.05	27.44	-16.06	43.5	40.39	18.14	1.16	32.25	-	-	P	V
		323.91	27.07	-18.93	46	36.33	20.61	2.21	32.08	-	-	P	V
		476.2	26.94	-19.06	46	31.83	24.31	2.73	31.93	-	-	P	V
		709	28.87	-17.13	46	29.44	27.75	3.37	31.69	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)



Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix B. Radiated Spurious Emission Plots

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																		
		BT CH00 2402MHz																																																		
		Horizontal					Fundamental																																													
Peak		Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SMT-Auto Model : (FR) 760219 Plane : 1 Pad-X : Full-directivity IMEI : #4 IMEI : 3005 <table><thead><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2356.15</td><td>49.37</td><td>-24.63</td><td>74.00</td><td>54.90</td><td>25.55</td><td>5.43</td><td>36.51</td><td>313</td><td>223 Peak</td><td>HORIZONTAL</td></tr></tbody></table>										Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas		Freq	Level	Line	Level	Factor						MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	2356.15	49.37	-24.63	74.00	54.90	25.55	5.43	36.51	313	223 Peak	HORIZONTAL
		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																										
	Freq	Level	Line	Level	Factor																																															
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																											
1	2356.15	49.37	-24.63	74.00	54.90	25.55	5.43	36.51	313	223 Peak	HORIZONTAL																																									
	Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SMT-Auto Model : (FR) 760219 Plane : 1 Pad-X : Full-directivity IMEI : #4 IMEI : 3005 <table><thead><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>99.66</td><td>25.66</td><td>74.00</td><td>104.81</td><td>25.80</td><td>5.47</td><td>36.42</td><td>313</td><td>223 Peak</td><td>HORIZONTAL</td></tr></tbody></table>										Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas		Freq	Level	Line	Level	Factor						MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	2402.00	99.66	25.66	74.00	104.81	25.80	5.47	36.42	313	223 Peak	HORIZONTAL	
	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																											
	Freq	Level	Line	Level	Factor																																															
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																											
1	2402.00	99.66	25.66	74.00	104.81	25.80	5.47	36.42	313	223 Peak	HORIZONTAL																																									






BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																				
		BT CH00 2402MHz																																																																				
		Vertical	Fundamental																																																																			
Peak	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Plan : (FR) 760219 Mode : I Plane : Pad-X Full-directivity : Full-directivity MEI : 84 SMB : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2364.21</td><td>49.30</td><td>-24.70</td><td>74.00</td><td>54.83</td><td>25.55</td><td>5.43</td><td>36.51</td><td>395</td><td>64 Peak VERTICAL</td></tr></table>		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg			1	2364.21	49.30	-24.70	74.00	54.83	25.55	5.43	36.51	395	64 Peak VERTICAL	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Plan : (FR) 760219 Mode : I Plane : Pad-X Full-directivity : Full-directivity MEI : 84 SMB : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2402.00</td><td>98.23</td><td>24.23</td><td>74.00</td><td>183.38</td><td>25.80</td><td>5.47</td><td>36.42</td><td>395</td><td>64 Peak VERTICAL</td></tr></table>		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg			1	2402.00	98.23	24.23	74.00	183.38	25.80	5.47	36.42	395	64 Peak VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																														
1	2364.21	49.30	-24.70	74.00	54.83	25.55	5.43	36.51	395	64 Peak VERTICAL																																																												
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																												
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																														
1	2402.00	98.23	24.23	74.00	183.38	25.80	5.47	36.42	395	64 Peak VERTICAL																																																												





BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																				
		BT CH39 2441MHz																																																																				
		Horizontal	Fundamental																																																																			
Peak	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SAT:Auto Node : (FR) 760219 Plane : 2 Pad:K Full-directivity IMEI : #4 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2375.78</td><td>49.04</td><td>-24.96</td><td>74.00</td><td>54.38</td><td>25.67</td><td>5.45</td><td>36.46</td><td>321</td><td>160 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	2375.78	49.04	-24.96	74.00	54.38	25.67	5.45	36.46	321	160 Peak	HORIZONTAL	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SAT:Auto Node : (FR) 760219 Plane : 2 Pad:K Full-directivity IMEI : #4 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2441.00</td><td>100.84</td><td>26.64</td><td>74.00</td><td>105.91</td><td>25.89</td><td>5.49</td><td>36.45</td><td>321</td><td>160 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	2441.00	100.84	26.64	74.00	105.91	25.89	5.49	36.45	321	160 Peak	HORIZONTAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																													
1	2375.78	49.04	-24.96	74.00	54.38	25.67	5.45	36.46	321	160 Peak	HORIZONTAL																																																											
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																												
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																													
1	2441.00	100.84	26.64	74.00	105.91	25.89	5.49	36.45	321	160 Peak	HORIZONTAL																																																											
Peak	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SAT:Auto Node : (FR) 760219 Plane : 2 Pad:K Full-directivity IMEI : #4 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2403.42</td><td>49.36</td><td>-24.64</td><td>74.00</td><td>54.35</td><td>25.97</td><td>5.52</td><td>36.48</td><td>321</td><td>160 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	2403.42	49.36	-24.64	74.00	54.35	25.97	5.52	36.48	321	160 Peak	HORIZONTAL																																			
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																												
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																													
1	2403.42	49.36	-24.64	74.00	54.35	25.97	5.52	36.48	321	160 Peak	HORIZONTAL																																																											





BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																
		BT CH39 2441MHz																																																																
	Vertical	Fundamental																																																																
Peak	 Site Condition : 03CH03-K5 FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Node : (FR) 760219 Plane : 2 Pad-X : Pad-X Plane : Full-directivity IME1 : 84 IME1 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2377.99</td><td>49.85</td><td>-24.95</td><td>74.00</td><td>54.39</td><td>25.67</td><td>5.45</td><td>36.46</td><td>300</td><td>57 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2377.99	49.85	-24.95	74.00	54.39	25.67	5.45	36.46	300	57 Peak	VERTICAL	 Site Condition : 03CH03-K5 FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Node : (FR) 760219 Plane : 2 Pad-X : Pad-X Plane : Full-directivity IME1 : 84 IME1 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2442.00</td><td>99.41</td><td>25.41</td><td>74.00</td><td>104.48</td><td>25.89</td><td>5.49</td><td>36.45</td><td>300</td><td>57 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2442.00	99.41	25.41	74.00	104.48	25.89	5.49	36.45	300	57 Peak	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																								
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2377.99	49.85	-24.95	74.00	54.39	25.67	5.45	36.46	300	57 Peak	VERTICAL																																																							
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2442.00	99.41	25.41	74.00	104.48	25.89	5.49	36.45	300	57 Peak	VERTICAL																																																							
Peak	 Site Condition : 03CH03-K5 FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Node : (FR) 760219 Plane : 2 Pad-X : Pad-X Plane : Full-directivity IME1 : 84 IME1 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2486.07</td><td>49.64</td><td>-24.36</td><td>74.00</td><td>54.66</td><td>25.94</td><td>5.51</td><td>36.47</td><td>300</td><td>57 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	2486.07	49.64	-24.36	74.00	54.66	25.94	5.51	36.47	300	57 Peak	VERTICAL																																	
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																										
1	2486.07	49.64	-24.36	74.00	54.66	25.94	5.51	36.47	300	57 Peak	VERTICAL																																																							



BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																																																												
		BT CH78 2480MHz																																																																												
		Horizontal					Fundamental																																																																							
Peak	 Site : 03CH83-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : (FR) 760219 Node : 3 Plane : PadK Full-directivity IME1 : 84 IME2 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2483.90</td><td>54.90</td><td>-19.10</td><td>74.00</td><td>59.92</td><td>25.94</td><td>5.51</td><td>36.47</td><td>347</td><td>159 Peak</td><td>HORIZONTAL</td></tr></table>  Site : 03CH83-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : (FR) 760219 Node : 3 Plane : PadK Full-directivity IME1 : 84 IME2 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>2480.00</td><td>106.85</td><td>26.85</td><td>74.00</td><td>105.87</td><td>25.94</td><td>5.51</td><td>36.47</td><td>347</td><td>159 Peak</td><td>HORIZONTAL</td></tr></table>										Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg			1	2483.90	54.90	-19.10	74.00	59.92	25.94	5.51	36.47	347	159 Peak	HORIZONTAL	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg			1	2480.00	106.85	26.85	74.00	105.87	25.94	5.51	36.47	347	159 Peak	HORIZONTAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																			
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																																					
1	2483.90	54.90	-19.10	74.00	59.92	25.94	5.51	36.47	347	159 Peak	HORIZONTAL																																																																			
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																				
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																																						
1	2480.00	106.85	26.85	74.00	105.87	25.94	5.51	36.47	347	159 Peak	HORIZONTAL																																																																			





BT		2.4GHz 2400~2483.5MHz Band Edge @ 3m																																									
		BT CH78 2480MHz																																									
		Vertical					Fundamental																																				
Peak		Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT/Auto Node : (FR) 760219 Plane : 3 PadX : Plane : Full-directivity IMEI : 84 IMEI : 30MS <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2483.69</td><td>53.67</td><td>-20.33</td><td>74.00</td><td>58.69</td><td>25.94</td><td>5.51</td><td>36.47</td><td>372</td><td>53 Peak VERTICAL</td></tr></tbody></table>									Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	2483.69	53.67	-20.33	74.00	58.69	25.94	5.51	36.47	372	53 Peak VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																		
1	2483.69	53.67	-20.33	74.00	58.69	25.94	5.51	36.47	372	53 Peak VERTICAL																																	
	Site : 03CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT/Auto Node : (FR) 760219 Plane : 3 PadX : Plane : Full-directivity IMEI : 84 IMEI : 30MS <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>99.16</td><td>25.16</td><td>74.00</td><td>104.18</td><td>25.94</td><td>5.51</td><td>36.47</td><td>372</td><td>53 Peak VERTICAL</td></tr></tbody></table>									Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	2480.00	99.16	25.16	74.00	104.18	25.94	5.51	36.47	372	53 Peak VERTICAL	
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																		
1	2480.00	99.16	25.16	74.00	104.18	25.94	5.51	36.47	372	53 Peak VERTICAL																																	



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																											
	BT CH00 2402MHz																																																																											
	Horizontal										Vertical																																																																	
Peak Avg.																																																																												
	Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SMT-Auto Project : (FR) 760219 Node : 1 Plane : Pad-X Plane : Full-directivity IMEI : #4 IMEI : 3085 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>4886.00</td><td>41.49</td><td>-32.51</td><td>74.00</td><td>39.66</td><td>38.62</td><td>7.71</td><td>36.58</td><td>168</td><td>360 Peak HORIZONTAL</td></tr></tbody></table>										Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg			1	4886.00	41.49	-32.51	74.00	39.66	38.62	7.71	36.58	168	360 Peak HORIZONTAL	Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Project : (FR) 760219 Node : 1 Plane : Pad-X Plane : Full-directivity IMEI : #4 IMEI : 3085 <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>4886.00</td><td>41.42</td><td>-32.58</td><td>74.00</td><td>39.59</td><td>38.62</td><td>7.71</td><td>36.58</td><td>168</td><td>0 Peak VERTICAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg			1	4886.00	41.42	-32.58	74.00	39.59	38.62	7.71	36.58	168
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																		
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																				
1	4886.00	41.49	-32.51	74.00	39.66	38.62	7.71	36.58	168	360 Peak HORIZONTAL																																																																		
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																		
MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																				
1	4886.00	41.42	-32.58	74.00	39.59	38.62	7.71	36.58	168	0 Peak VERTICAL																																																																		



BT		2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																							
		BT CH39 2441MHz																																																							
		Horizontal																																																							
Peak Avg.	Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SWT/Auto Node : (FR) 760219 Plane : 2 Plane : Pad-X Plane : Full-directivity IMEI : 84 IMEI : 3045 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4884.80</td><td>41.19</td><td>-32.81</td><td>74.00</td><td>39.11</td><td>30.85</td><td>7.76</td><td>36.53</td><td>160</td><td>0 Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>7320.80</td><td>46.78</td><td>-27.22</td><td>74.00</td><td>38.40</td><td>34.85</td><td>9.78</td><td>36.25</td><td>160</td><td>0 Peak</td><td>HORIZONTAL</td></tr></table>											Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg			1	4884.80	41.19	-32.81	74.00	39.11	30.85	7.76	36.53	160	0 Peak	HORIZONTAL	2	7320.80	46.78	-27.22	74.00	38.40	34.85	9.78	36.25	160	0 Peak	HORIZONTAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																														
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																	
1	4884.80	41.19	-32.81	74.00	39.11	30.85	7.76	36.53	160	0 Peak	HORIZONTAL																																														
2	7320.80	46.78	-27.22	74.00	38.40	34.85	9.78	36.25	160	0 Peak	HORIZONTAL																																														
Site : 03CH03-K5 Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SWT/Auto Node : (FR) 760219 Plane : 2 Plane : Pad-X Plane : Full-directivity IMEI : 84 IMEI : 3045 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4884.80</td><td>42.05</td><td>-31.95</td><td>74.00</td><td>39.97</td><td>30.85</td><td>7.76</td><td>36.53</td><td>160</td><td>360 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>7320.80</td><td>46.65</td><td>-27.35</td><td>74.00</td><td>38.27</td><td>34.85</td><td>9.78</td><td>36.25</td><td>160</td><td>360 Peak</td><td>VERTICAL</td></tr></table>											Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg			1	4884.80	42.05	-31.95	74.00	39.97	30.85	7.76	36.53	160	360 Peak	VERTICAL	2	7320.80	46.65	-27.35	74.00	38.27	34.85	9.78	36.25	160	360 Peak	VERTICAL	
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																															
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																	
1	4884.80	42.05	-31.95	74.00	39.97	30.85	7.76	36.53	160	360 Peak	VERTICAL																																														
2	7320.80	46.65	-27.35	74.00	38.27	34.85	9.78	36.25	160	360 Peak	VERTICAL																																														





BT		2.4GHz 2400~2483.5MHz Harmonic @ 3m																																																																																												
		BT CH78 2480MHz																																																																																												
		Horizontal																																																																																												
		Vertical																																																																																												
Peak Avg.	Site : 83CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 HORIZONTAL Project : SMT-Auto Mode : (FR) 760219 Plane : 3 Plane : Pad-X Plane : Full-directivity IME1 : 44 IME1 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4962.00</td><td>43.59</td><td>-38.41</td><td>74.00</td><td>41.23</td><td>31.13</td><td>7.82</td><td>36.57</td><td>160</td><td>360 Peak</td><td>HORIZONTAL</td></tr><tr><td>2</td><td>7440.00</td><td>45.72</td><td>-28.28</td><td>74.00</td><td>36.97</td><td>35.17</td><td>9.87</td><td>36.29</td><td>160</td><td>360 Peak</td><td>HORIZONTAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	4962.00	43.59	-38.41	74.00	41.23	31.13	7.82	36.57	160	360 Peak	HORIZONTAL	2	7440.00	45.72	-28.28	74.00	36.97	35.17	9.87	36.29	160	360 Peak	HORIZONTAL	Site : 83CH03-KS Condition : FCC PART 15C 3m HF ANT-201704-91280 VERTICAL Project : SMT-Auto Mode : (FR) 760219 Plane : 3 Plane : Pad-X Plane : Full-directivity IME1 : 44 IME1 : 30MS <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>41.89</td><td>-32.11</td><td>74.00</td><td>39.51</td><td>31.13</td><td>7.82</td><td>36.57</td><td>160</td><td>0 Peak</td><td>VERTICAL</td></tr><tr><td>2</td><td>7440.00</td><td>46.23</td><td>-27.77</td><td>74.00</td><td>37.48</td><td>35.17</td><td>9.87</td><td>36.29</td><td>160</td><td>0 Peak</td><td>VERTICAL</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	4960.00	41.89	-32.11	74.00	39.51	31.13	7.82	36.57	160	0 Peak	VERTICAL	2	7440.00	46.23	-27.77	74.00	37.48	35.17	9.87	36.29	160	0 Peak	VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																					
1	4962.00	43.59	-38.41	74.00	41.23	31.13	7.82	36.57	160	360 Peak	HORIZONTAL																																																																																			
2	7440.00	45.72	-28.28	74.00	36.97	35.17	9.87	36.29	160	360 Peak	HORIZONTAL																																																																																			
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																					
1	4960.00	41.89	-32.11	74.00	39.51	31.13	7.82	36.57	160	0 Peak	VERTICAL																																																																																			
2	7440.00	46.23	-27.77	74.00	37.48	35.17	9.87	36.29	160	0 Peak	VERTICAL																																																																																			



Emission below 1GHz

2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz																																																																																																																																																																													
	BT LF																																																																																																																																																																													
	Horizontal	Vertical																																																																																																																																																																												
QP / Peak	 Site : 03CH03-K5 Condition : FCC PART 15C 3m LF ANT 600 201704 HORIZONTAL Project : SMT/Aniso Project : (FR) 760219 Mode : 3 Plane : Pad+K Full-directivity IME1 : #4 30MS <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>34.85</td><td>32.58</td><td>-7.42</td><td>40.00</td><td>38.47</td><td>25.78</td><td>0.71</td><td>32.38</td><td>140</td><td>25 Peak HORIZONTAL</td></tr><tr><td>2</td><td>95.86</td><td>25.34</td><td>-18.16</td><td>43.58</td><td>37.97</td><td>18.44</td><td>1.18</td><td>32.25</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>3</td><td>153.19</td><td>26.55</td><td>-16.95</td><td>43.58</td><td>39.86</td><td>17.47</td><td>1.58</td><td>32.28</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>4</td><td>282.66</td><td>33.88</td><td>-9.62</td><td>43.58</td><td>47.39</td><td>17.81</td><td>1.73</td><td>32.25</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>5</td><td>353.81</td><td>26.42</td><td>-19.58</td><td>46.00</td><td>34.34</td><td>21.85</td><td>2.31</td><td>32.68</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>6</td><td>781.24</td><td>29.14</td><td>-16.86</td><td>46.00</td><td>29.58</td><td>27.97</td><td>3.35</td><td>31.68</td><td>---</td><td>Peak HORIZONTAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	34.85	32.58	-7.42	40.00	38.47	25.78	0.71	32.38	140	25 Peak HORIZONTAL	2	95.86	25.34	-18.16	43.58	37.97	18.44	1.18	32.25	---	Peak HORIZONTAL	3	153.19	26.55	-16.95	43.58	39.86	17.47	1.58	32.28	---	Peak HORIZONTAL	4	282.66	33.88	-9.62	43.58	47.39	17.81	1.73	32.25	---	Peak HORIZONTAL	5	353.81	26.42	-19.58	46.00	34.34	21.85	2.31	32.68	---	Peak HORIZONTAL	6	781.24	29.14	-16.86	46.00	29.58	27.97	3.35	31.68	---	Peak HORIZONTAL	 Site : 03CH03-K5 Condition : FCC PART 15C 3m LF ANT 600 201704 VERTICAL Project : SMT/Aniso Project : (FR) 760219 Mode : 3 Plane : Pad+K Full-directivity IME1 : #4 30MS <table><thead><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>32.91</td><td>32.77</td><td>-7.23</td><td>40.00</td><td>38.24</td><td>26.14</td><td>0.69</td><td>32.38</td><td>180</td><td>28 Peak VERTICAL</td></tr><tr><td>2</td><td>46.49</td><td>32.04</td><td>-7.96</td><td>40.00</td><td>45.13</td><td>18.29</td><td>0.84</td><td>32.23</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>3</td><td>93.85</td><td>27.44</td><td>-16.06</td><td>43.58</td><td>48.39</td><td>18.14</td><td>1.16</td><td>32.25</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>4</td><td>323.91</td><td>27.07</td><td>-18.93</td><td>46.00</td><td>56.33</td><td>20.61</td><td>2.23</td><td>32.88</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>5</td><td>478.28</td><td>26.94</td><td>-19.06</td><td>46.00</td><td>31.83</td><td>24.31</td><td>2.73</td><td>31.93</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>6</td><td>789.00</td><td>28.87</td><td>-17.13</td><td>46.00</td><td>29.44</td><td>27.75</td><td>3.37</td><td>31.69</td><td>---</td><td>Peak VERTICAL</td></tr></tbody></table>	Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	32.91	32.77	-7.23	40.00	38.24	26.14	0.69	32.38	180	28 Peak VERTICAL	2	46.49	32.04	-7.96	40.00	45.13	18.29	0.84	32.23	---	Peak VERTICAL	3	93.85	27.44	-16.06	43.58	48.39	18.14	1.16	32.25	---	Peak VERTICAL	4	323.91	27.07	-18.93	46.00	56.33	20.61	2.23	32.88	---	Peak VERTICAL	5	478.28	26.94	-19.06	46.00	31.83	24.31	2.73	31.93	---	Peak VERTICAL	6	789.00	28.87	-17.13	46.00	29.44	27.75	3.37	31.69	---	Peak VERTICAL
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																																						
1	34.85	32.58	-7.42	40.00	38.47	25.78	0.71	32.38	140	25 Peak HORIZONTAL																																																																																																																																																																				
2	95.86	25.34	-18.16	43.58	37.97	18.44	1.18	32.25	---	Peak HORIZONTAL																																																																																																																																																																				
3	153.19	26.55	-16.95	43.58	39.86	17.47	1.58	32.28	---	Peak HORIZONTAL																																																																																																																																																																				
4	282.66	33.88	-9.62	43.58	47.39	17.81	1.73	32.25	---	Peak HORIZONTAL																																																																																																																																																																				
5	353.81	26.42	-19.58	46.00	34.34	21.85	2.31	32.68	---	Peak HORIZONTAL																																																																																																																																																																				
6	781.24	29.14	-16.86	46.00	29.58	27.97	3.35	31.68	---	Peak HORIZONTAL																																																																																																																																																																				
Freq	Level	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																																						
1	32.91	32.77	-7.23	40.00	38.24	26.14	0.69	32.38	180	28 Peak VERTICAL																																																																																																																																																																				
2	46.49	32.04	-7.96	40.00	45.13	18.29	0.84	32.23	---	Peak VERTICAL																																																																																																																																																																				
3	93.85	27.44	-16.06	43.58	48.39	18.14	1.16	32.25	---	Peak VERTICAL																																																																																																																																																																				
4	323.91	27.07	-18.93	46.00	56.33	20.61	2.23	32.88	---	Peak VERTICAL																																																																																																																																																																				
5	478.28	26.94	-19.06	46.00	31.83	24.31	2.73	31.93	---	Peak VERTICAL																																																																																																																																																																				
6	789.00	28.87	-17.13	46.00	29.44	27.75	3.37	31.69	---	Peak VERTICAL																																																																																																																																																																				