FCC RF Test Report

APPLICANT	:	Lenovo(Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT	:	Portable Tablet Computer
BRAND NAME	:	Lenovo
MODEL NAME	:	ThinkBook Plus G5 Tab
FCC ID	:	O5721N8G5
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Jan. 26, 2024 ~ Feb. 23, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 6
1.7 Test Software 7
1.8 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB and 99% Bandwidth Measurement 12
3.2 Output Power Measurement 13
3.3 Power Spectral Density Measurement 14
3.4 Conducted Band Edges and Spurious Emission Measurement 15
3.5 Radiated Band Edges and Spurious Emission Measurement 16
3.6 AC Conducted Emission Measurement 20
3.7 Antenna Requirements 22
4 LIST OF MEASURING EQUIPMENT **23**
5 MEASUREMENT UNCERTAINTY **24**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3D2703B	Rev. 01	Initial issue of report	Mar. 01, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 12.35 dB at 2483.50 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.75 dB at 0.180 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.
Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2 Manufacturer

Lenovo PC HK Limited
23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	ThinkBook Plus G5 Tab
FCC ID	O5721N8G5
SN Code	Conducted: HA1Z2Z61 Conduction: HA1Z0ZL5 Radiation: HA1Z04H8
HW Version	ThinkBook Plus G5 Tab
SW Version	TB610FU_RF01_240221
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	**<Ant 1>** BLE 1Mbps: 12.97 dBm (0.0198 W) BLE 2Mbps: 13.43 dBm (0.0220 W) **<Ant 2>** BLE 1Mbps: 9.03 dBm (0.0080 W) BLE 2Mbps: 9.24 dBm (0.0084 W)
99% Occupied Bandwidth	**<Ant 1>** BLE 1Mbps:1.019MHz BLE 2Mbps:1.019MHz **<Ant 2>** BLE 1Mbps:2.006MHz BLE 2Mbps:2.010MHz
Antenna Type / Gain	**<Ant 1>**FPC Antenna type with gain -3.8 dBi **<Ant 2>**FPC Antenna type with gain -3.1 dBi
Type of Modulation	Bluetooth LE : GFSK

Remark: BLE of ant1&2 only supports SISO mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performance with Adapter and USB Cable	

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Adapter	Chenyang	N/A	N/A	N/A	N/A
5.	USB Cable	Lenovo	SLQ-A217A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.19 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 2.19 + 10 = 12.19 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2023	Jan. 26, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Mar. 24, 2023	Jan. 26, 2024~ Feb. 23, 2024	Mar. 23, 2024	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Jan. 26, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Jan. 26, 2024~ Feb. 23, 2024	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Jan. 26, 2024~ Feb. 23, 2024	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2024	Jan. 26, 2024~ Feb. 23, 2024	Jan. 04, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 06, 2023	Jan. 26, 2024~ Feb. 23, 2024	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2024	Jan. 26, 2024~ Feb. 23, 2024	Jan. 04, 2025	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz-18Ghz	Oct. 10, 2023	Jan. 26, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz-18Ghz	Jan. 03, 2024	Jan. 26, 2024~ Feb. 23, 2024	Jan. 02, 2025	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 26, 2024~ Feb. 23, 2024	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 26, 2024~ Feb. 23, 2024	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 26, 2024~ Feb. 23, 2024	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Feb. 22, 2024	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Feb. 22, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Feb. 22, 2024	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Feb. 22, 2024	Oct. 10, 2024	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Jan. 30, 2024~ Feb. 21, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Jan. 30, 2024~ Feb. 21, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Jan. 30, 2024~ Feb. 21, 2024	Jan. 01, 2025	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.26 dB**
Occupied Channel Bandwidth	**±0.1%**
Conducted Power	**±0.46 dB**
Conducted Power Spectral Density	**±0.88 dB**
Frequency	**±0.4 Hz**

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.84 dB**

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.30 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**6.28 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.88 dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.26 dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Ambient Condition: 25 ℃, 45 %RH	
According Standard: ■Part15C	
Test Date: 2024.1.30~2024.2.21	**Test Engineer:** Jiang Jun

DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant2	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant1	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant2	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant1	2480	0.68	2479.66	2480.34	0.5	PASS
	Ant2	2480	0.68	2479.66	2480.34	0.5	PASS
BLE_2M	Ant1	2402	1.16	2401.43	2402.59	0.5	PASS
	Ant2	2402	1.16	2401.42	2402.58	0.5	PASS
	Ant1	2440	1.15	2439.43	2440.58	0.5	PASS
	Ant2	2440	1.15	2439.43	2440.58	0.5	PASS
	Ant1	2480	1.16	2479.42	2480.58	0.5	PASS
	Ant2	2480	1.16	2479.42	2480.58	0.5	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.019	2401.5005	2402.5195	---	---
	Ant2	2402	1.019	2401.4965	2402.5155	---	---
	Ant1	2440	1.015	2439.5005	2440.5155	---	---
	Ant2	2440	1.019	2439.4965	2440.5155	---	---
	Ant1	2480	1.015	2479.5005	2480.5155	---	---
	Ant2	2480	1.019	2479.4965	2480.5155	---	---
BLE_2M	Ant1	2402	2.006	2401.0170	2403.0230	---	---
	Ant2	2402	2.01	2401.0090	2403.0190	---	---
	Ant1	2440	2.006	2439.0130	2441.0190	---	---
	Ant2	2440	2.01	2439.0090	2441.0190	---	---
	Ant1	2480	2.006	2479.0130	2481.0190	---	---
	Ant2	2480	2.01	2479.0090	2481.0190	---	---

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail
BLE1M	Ant1	0	**12.97**	30.00	-3.8	**9.17**	36.00	Pass
		19	12.29	30.00	-3.8	8.49	36.00	Pass
		39	12.84	30.00	-3.8	9.04	36.00	Pass
BLE2M	Ant1	0	**13.43**	30.00	-3.8	**9.63**	36.00	Pass
		19	12.78	30.00	-3.8	8.98	36.00	Pass
		39	13.32	30.00	-3.8	9.52	36.00	Pass
BLE1M	Ant2	0	8.55	30.00	-3.1	5.45	36.00	Pass
		19	**9.03**	30.00	-3.1	**5.93**	36.00	Pass
		39	7.06	30.00	-3.1	3.96	36.00	Pass
BLE2M	Ant2	0	8.74	30.00	-3.1	5.64	36.00	Pass
		19	**9.24**	30.00	-3.1	**6.14**	36.00	Pass
		39	7.22	30.00	-3.1	4.12	36.00	Pass

Test Result Average

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE1M	Ant1	0	2.07	**12.79**
		19	2.07	11.90
		39	2.07	12.75
BLE2M	Ant1	0	4.87	12.77
		19	4.87	12.32
		39	4.87	**12.80**
BLE1M	Ant2	0	2.07	8.26
		19	2.07	**8.79**
		39	2.07	6.72
BLE2M	Ant2	0	4.81	8.16
		19	4.81	**8.65**
		39	4.81	6.68

Remark: Power setting is the AUTO (AUTO is the default).

Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-2.50	≤8.00	PASS
	Ant2	2402	-6.63	≤8.00	PASS
	Ant1	2440	-3.31	≤8.00	PASS
	Ant2	2440	-6.02	≤8.00	PASS
	Ant1	2480	-2.60	≤8.00	PASS
	Ant2	2480	-7.86	≤8.00	PASS
BLE_2M	Ant1	2402	-5.28	≤8.00	PASS
	Ant2	2402	-9.55	≤8.00	PASS
	Ant1	2440	-6.04	≤8.00	PASS
	Ant2	2440	-8.91	≤8.00	PASS
	Ant1	2480	-5.29	≤8.00	PASS
	Ant2	2480	-10.80	≤8.00	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant1	2402	2402.01	11.88
	Ant2	2402	2402.01	7.75
	Ant1	2440	2440.01	11.05
	Ant2	2440	2440.01	8.29
	Ant1	2480	2480.01	11.77
	Ant2	2480	2480.01	6.49
BLE_2M	Ant1	2402	2402.01	12.07
	Ant2	2402	2402.01	7.75
	Ant1	2440	2440.01	11.25
	Ant2	2440	2440.01	8.30
	Ant1	2480	2480.01	12.02
	Ant2	2480	2480.01	6.46

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
BLE_1M	Ant1	Low	2402	11.88	-43.89	≤-8.12	PASS
	Ant2	Low	2402	7.75	-44	≤-12.25	PASS
	Ant1	High	2480	11.77	-42.83	≤-8.23	PASS
	Ant2	High	2480	6.49	-43.57	≤-13.51	PASS
BLE_2M	Ant1	Low	2402	12.07	-35.54	≤-7.93	PASS
	Ant2	Low	2402	7.75	-34.62	≤-12.25	PASS
	Ant1	High	2480	12.02	-43.34	≤-7.98	PASS
	Ant2	High	2480	6.46	-43.34	≤-13.54	PASS

Test Graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant2_Low_2402



BLE_1M_Ant1_High_2480



BLE_1M_Ant2_High_2480



BLE_2M_Ant1_Low_2402



BLE_2M_Ant2_Low_2402



BLE_2M_Ant1_High_2480



BLE_2M_Ant2_High_2480



Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant1	2402	30~1000	11.88	-45.75	≤-8.12	PASS
			1000~26500	11.88	-35.34	≤-8.12	PASS
	Ant2	2402	30~1000	7.75	-44.9	≤-12.25	PASS
			1000~26500	7.75	-36.37	≤-12.25	PASS
	Ant1	2440	30~1000	11.05	-45.27	≤-8.95	PASS
			1000~26500	11.05	-36.1	≤-8.95	PASS
	Ant2	2440	30~1000	8.29	-45.6	≤-11.71	PASS
			1000~26500	8.29	-36.22	≤-11.71	PASS
	Ant1	2480	30~1000	11.77	-45.14	≤-8.23	PASS
			1000~26500	11.77	-36.06	≤-8.23	PASS
	Ant2	2480	30~1000	6.49	-45.84	≤-13.51	PASS
			1000~26500	6.49	-36.86	≤-13.51	PASS
BLE_2M	Ant1	2402	30~1000	12.07	-44.88	≤-7.93	PASS
			1000~26500	12.07	-35.3	≤-7.93	PASS
	Ant2	2402	30~1000	7.75	-45.99	≤-12.25	PASS
			1000~26500	7.75	-36.03	≤-12.25	PASS
	Ant1	2440	30~1000	11.25	-45.95	≤-8.75	PASS
			1000~26500	11.25	-36.41	≤-8.75	PASS
	Ant2	2440	30~1000	8.30	-45.35	≤-11.7	PASS
			1000~26500	8.30	-36.03	≤-11.7	PASS
	Ant1	2480	30~1000	12.02	-45.24	≤-7.98	PASS
			1000~26500	12.02	-36.16	≤-7.98	PASS
	Ant2	2480	30~1000	6.46	-45.48	≤-13.54	PASS
			1000~26500	6.46	-36.09	≤-13.54	PASS

Test Graphs

BLE_1M_Ant1_2402_30~1000



BLE_1M_Ant1_2402_1000~26500



BLE_1M_Ant2_2402_30~1000



BLE_1M_Ant2_2402_1000~26500



BLE_1M_Ant1_2440_30~1000



BLE_1M_Ant1_2440_1000~26500



BLE_1M_Ant2_2440_30~1000



BLE_1M_Ant2_2440_1000~26500



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500



BLE_1M_Ant2_2480_30~1000



BLE_1M_Ant2_2480_1000~26500



BLE_2M_Ant1_2402_30~1000



BLE_2M_Ant1_2402_1000~26500



BLE_2M_Ant2_2402_30~1000



BLE_2M_Ant2_2402_1000~26500



BLE_2M_Ant1_2440_30~1000



BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant2_2440_30~1000



BLE_2M_Ant2_2440_1000~26500



BLE_2M_Ant1_2480_30~1000



BLE_2M_Ant1_2480_1000~26500



BLE_2M_Ant2_2480_30~1000



BLE_2M_Ant2_2480_1000~26500



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15E RSS247-QP LISN-060105-L 2023 LINE

	Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1	0.162	46.96	-18.38	65.34	36.50	0.04	10.42	QP
2	0.162	33.66	-21.68	55.34	23.20	0.04	10.42	Average
3 *	0.180	51.75	-12.75	64.50	41.30	0.04	10.41	QP
4	0.180	40.55	-13.95	54.50	30.10	0.04	10.41	Average
5	0.227	34.22	-28.35	62.57	23.80	0.03	10.39	QP
6	0.227	22.32	-30.25	52.57	11.90	0.03	10.39	Average
7	0.279	37.69	-23.16	60.85	27.30	0.04	10.35	QP
8	0.279	27.09	-23.76	50.85	16.70	0.04	10.35	Average
9	0.549	35.36	-20.64	56.00	25.20	-0.04	10.20	QP
10	0.549	18.76	-27.24	46.00	8.60	-0.04	10.20	Average
11	1.396	34.26	-21.74	56.00	24.30	-0.12	10.08	QP
12	1.396	21.76	-24.24	46.00	11.80	-0.12	10.08	Average

Test Engineer :	Amos Zhang	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15E RSS247-QP LISN-060105-N 2023 NEUTRAL

		Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1		0.176	48.36	-16.32	64.68	37.90	0.05	10.41	QP
2	*	0.176	39.56	-15.12	54.68	29.10	0.05	10.41	Average
3		0.256	39.76	-21.80	61.56	29.41	-0.01	10.36	QP
4		0.256	30.46	-21.10	51.56	20.11	-0.01	10.36	Average
5		0.343	37.36	-21.77	59.13	27.10	-0.05	10.31	QP
6		0.343	27.56	-21.57	49.13	17.30	-0.05	10.31	Average
7		0.576	36.02	-19.98	56.00	25.90	-0.07	10.19	QP
8		0.576	27.02	-18.98	46.00	16.90	-0.07	10.19	Average
9		0.759	38.35	-17.65	56.00	28.31	-0.08	10.12	QP
10		0.759	29.65	-16.35	46.00	19.61	-0.08	10.12	Average
11		1.456	32.87	-23.13	56.00	22.90	-0.11	10.08	QP
12		1.456	21.27	-24.73	46.00	11.30	-0.11	10.08	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	levi zhao	Relative Humidity :	41~42％
		Temperature :	22~23℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	1	Bluetooth-LE	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	1	Bluetooth-LE	39	2480	2Mbps	-	-
Mode 7	2400-2483.5	2	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 8	2400-2483.5	2	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 9	2400-2483.5	2	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 10	2400-2483.5	2	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 11	2400-2483.5	2	Bluetooth-LE	19	2440	2Mbps	-	-
Mode 12	2400-2483.5	2	Bluetooth-LE	39	2480	2Mbps	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE	00	2389.69	38.29	54.00	-15.71	V	AVERAGE	Pass	Band Edge
1	Bluetooth-LE	00	4804.00	39.82	74.00	-34.18	H	PEAK	Pass	Harmonic
2	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
2	Bluetooth-LE	19	7320.00	41.88	74.00	-32.12	V	PEAK	Pass	Harmonic
3	Bluetooth-LE	39	2483.68	39.54	54.00	-14.46	H	AVERAGE	Pass	Band Edge
3	Bluetooth-LE	39	7440.00	40.08	74.00	-33.92	H	Peak	Pass	Harmonic
4	Bluetooth-LE	00	2388.65	38.97	54.00	-15.03	V	AVERAGE	Pass	Band Edge
4	Bluetooth-LE	00	4804.00	39.49	74.00	-34.51	H	PEAK	Pass	Harmonic
5	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
5	Bluetooth-LE	19	7320.00	41.64	74.00	-32.36	V	PEAK	Pass	Harmonic
6	Bluetooth-LE	39	2483.50	40.20	54.00	-13.80	H	AVERAGE	Pass	Band Edge
6	Bluetooth-LE	39	7440.00	41.79	74.00	-32.21	V	PEAK	Pass	Harmonic
7	Bluetooth-LE	00	2381.76	38.40	54.00	-15.60	H	AVERAGE	Pass	Band Edge
7	Bluetooth-LE	00	4804.00	40.36	74.00	-33.64	V	PEAK	Pass	Harmonic
8	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
8	Bluetooth-LE	19	7320.00	43.32	74.00	-30.68	V	PEAK	Pass	Harmonic
9	Bluetooth-LE	39	2483.74	39.20	54.00	-14.80	H	AVERAGE	Pass	Band Edge
9	Bluetooth-LE	39	7440.00	41.99	74.00	-32.01	V	PEAK	Pass	Harmonic
10	Bluetooth-LE	00	2389.95	39.08	54.00	-14.92	V	AVERAGE	Pass	Band Edge
10	Bluetooth-LE	00	4804.00	40.36	74.00	-33.64	H	PEAK	Pass	Harmonic
11	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
11	Bluetooth-LE	19	7320.00	41.43	74.00	-32.57	H	PEAK	Pass	Harmonic
12	Bluetooth-LE	39	2483.50	41.65	54.00	-12.35	H	AVERAGE	Pass	Band Edge
12	Bluetooth-LE	39	7440.00	42.01	74.00	-31.99	V	PEAK	Pass	Harmonic

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2323.26 49.11 74.00 -24.89 41.04 31.87 7.00 36.80 6.00 100 244 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 105.02 ------ ------ 96.62 32.11 7.12 36.83 6.00 100 244 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2386.57 38.23 54.00 -15.77 29.90 32.06 7.10 36.83 6.00 100 244 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 103.88 ------ ------ 95.48 32.11 7.12 36.83 6.00 100 244 AVERAGE

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2362.13 49.80 74.00 -24.20 41.60 31.99 7.06 36.85 6.00 266 252 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 102.53 ------ ------ 94.13 32.11 7.12 36.83 6.00 266 252 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.69 38.29 54.00 -15.71 29.94 32.07 7.11 36.83 6.00 266 252 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 101.40 ------ ------ 93.00 32.11 7.12 36.83 6.00 266 252 AVERAGE

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 39.82 74.00 -34.18 60.97 33.90 10.20 65.25 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 39.23 74.00 -34.77 60.38 33.90 10.20 65.25 0.00 -- -- PEAK

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH19_2440MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 39.86 74.00 -34.14 60.94 33.90 10.30 65.28 0.00 -- -- PEAK 2 7320.00 41.84 74.00 -32.16 59.89 35.70 12.72 66.47 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 39.71 74.00 -34.29 60.79 33.90 10.30 65.28 0.00 -- -- PEAK 2 7320.00 41.88 74.00 -32.12 59.93 35.70 12.72 66.47 0.00 -- -- PEAK

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 51.78 74.00 -22.22 42.98 32.52 7.26 36.98 6.00 127 237 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2400.00 103.56 ------ ------ 94.78 32.52 7.25 36.97 6.00 127 237 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.68 39.54 54.00 -14.46 30.74 32.52 7.26 36.98 6.00 127 237 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2400.00 102.55 ------ ------ 93.77 32.50 7.25 36.97 6.00 127 237 AVERAGE

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.56 50.46 74.00 -23.54 41.66 32.52 7.26 36.98 6.00 277 247 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2400.00 100.65 ------ ------ 91.87 32.50 7.25 36.97 6.00 277 247 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.86 39.06 54.00 -14.94 30.26 32.52 7.26 36.98 6.00 277 247 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2400.00 99.78 ------ ------ 91.00 32.50 7.25 36.97 6.00 277 247 AVERAGE

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 38.29 74.00 -35.71 59.18 34.02 10.40 65.31 0.00 -- -- Peak 2 7440.00 40.08 74.00 -33.92 58.37 35.74 12.78 66.81 0.00 -- -- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 38.11 74.00 -35.89 59.00 34.02 10.40 65.31 0.00 -- -- Peak 2 7440.00 39.88 74.00 -34.12 58.17 35.74 12.78 66.81 0.00 -- -- Peak

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2375.13 49.09 74.00 -24.91 40.82 32.03 7.08 36.84 6.00 129 234 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 105.31 ------ ------ 96.91 32.11 7.12 36.83 6.00 129 234 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2375.91 38.94 54.00 -15.06 30.67 32.03 7.08 36.84 6.00 129 234 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 103.15 ------ ------ 94.75 32.11 7.12 36.83 6.00 129 234 AVERAGE