FCC Test Report

(PART 27)

Report No.: RF160520W001-5

FCC ID: O57PB2650Y

Test Model: Lenovo PB2-650Y

Received Date: May 20, 2016

Test Date: May 21, 2016 ~ Jun. 13, 2016

Issued Date: Jun. 14, 2016

Applicant: Lenovo(Shanghai) Electronics Technology Co., Ltd.

Address: NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Cau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencie

Table of Contents

RELEASE CONTROL RECORD 3

1 Certificate of Conformity 4

2 Summary of Test Results 5

2.1 Measurement Uncertainty 5
2.2 Test Site And Instruments 6

3 General Information 7

3.1 General Description of EUT 7
3.2 Configuration of System Under Test 11
3.2.1 Description Of Support Units 11
3.3 Test Mode Applicability and Tested Channel Detail 12
3.4 EUT Operating Conditions 17
3.5 General Description of Applied Standards 18

4 Test Types and Results 19

4.1 Output Power Measurement 19
4.1.1 Limits of Output Power Measurement 19
4.1.2 Test Procedures 19
4.1.3 Test Setup 20
4.1.4 Test Results 21
4.2 Frequency Stability Measurement 39
4.2.1 Limits of Frequency Stabiliity Measurement 39
4.2.2 Test Procedure 39
4.2.3 Test Setup 39
4.2.4 Test Results 40
4.3 Occupied Bandwidth Measurement 43
4.3.1 Limits Of Occupied Bandwidth Measurement 43
4.3.2 Test Setup 43
4.3.3 Test Procedures 43
4.3.4 Test Result 44
4.4 Peak To Average Ratio 52
4.4.1 Limits of Peak To Average Ratio Measurement 52
4.4.2 Test Setup 52
4.4.3 Test Procedures 52
4.4.4 Test Results 53
4.5 Band Edge Measurement 61
4.5.1 Limits of Band Edge Measurement 61
4.5.2 Test Setup 61
4.5.3 Test Procedures 61
4.5.4 Test Results 62
4.6 Conducted Spurious Emissions 77
4.6.1 Limits of Conducted Spurious Emissions Measurement 77
4.6.2 Test Procedure 77
4.6.3 Test Setup 77
4.6.4 Test Results 78
4.7 Radiated Emission Measurement 82
4.7.1 Limits of Radiated Emission Measurement 82
4.7.2 Test Procedure 82
4.7.3 Deviation from Test Standard 82
4.7.4 Test Setup 83
4.7.5 Test Results 84

5 Pictures of Test Arrangements 112

Appendix – Information on the Testing Laboratories 117

RELEASE CONTROL RECORD

Issue No.	Description	Date Issued
RF160520W001-5	Original release	Jun. 14, 2016

1 Certificate of Conformity

Product: Lenovo Mobile Phone

Brand: Lenovo

Test Model: Lenovo PB2-650Y

Sample Status: Identical Prototype

Applicant: Lenovo(Shanghai) Electronics Technology Co., Ltd..

Test Date: May 21, 2016 ~ Jun. 13, 2016

Standards: **FCC Part 27, Subpart C, L**
FCC Part 2

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** Jun. 14, 2016
Amyee Qian / Engineer

Approved by : _____ , **Date:** Jun. 14, 2016
William Chung / Manager

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -21.26dB at 5197.50MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 Test Site And Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 05,16	Apr. 04,17
Bilog Antenna 1	Teseq	CBL 6111D	30643	Jun. 25,15	Jun. 24,16
Bilog Antenna 2	Teseq	CBL 6111D	27089	Jun. 25,15	Jun. 24,16
Horn Antenna	ETS-Lindgren	3117	00062558	May 30,14	May 29,17
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 21,14	Jan. 20,17
Amplifier	Burgeon	BPA-530	100220	Apr. 05,16	Apr. 04,17
Pre-Amplifier	HP	8449B	3008A00409	Apr. 24,16	Apr. 23,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 11,15	Nov. 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	Feb.19,16	Feb. 18,17
Power Sensor	Anritsu	MA2411B	1126068	Feb.19,16	Feb. 18,17
Power Sensor	Keysight	U2021XA	MY55060016	May 27,15	May 26,17
Power Sensor	Keysight	U2021XA	MY55060018	May 27,15	May 26,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct. 11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 09,15	Nov. 08,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Apr. 21, 16	Apr. 20, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Sep. 01,15	Aug. 31,16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Oct. 12, 15	Oct. 11, 16

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 4.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 460141.
6. The IC Site Registration No. is IC7450F-4.

3 General Information

3.1 General Description of EUT

PRODUCT	Lenovo Mobile Phone	
BRAND	Lenovo	
MODEL NAME	Lenovo PB2-650Y	
POWER SUPPLY	5.2Vdc (adapter or host equipment) 3.8Vdc (battery)	
MODULATION TECHNOLOGY	**WCDMA IV**	BPSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	**WCDMA IV**	1712.4MHz ~ 1752.6MHz
	LTE Band 4 Channel Bandwidth: 1.4MHz	1710.7MHz ~ 1754.3MHz
	LTE Band 4 Channel Bandwidth: 3MHz	1711.5MHz ~ 1753.5MHz
	LTE Band 4 Channel Bandwidth: 5MHz	1712.5MHz ~ 1752.5MHz
	LTE Band 4 Channel Bandwidth: 10MHz	1715.0MHz ~ 1750.0MHz
	LTE Band 4 Channel Bandwidth: 15MHz	1717.5MHz ~ 1747.5MHz
	LTE Band 4 Channel Bandwidth: 20MHz	1720.0MHz ~ 1745.0MHz
	LTE Band 12 Channel Bandwidth: 1.4MHz	699.7MHz ~ 715.3MHz
	LTE Band 12 Channel Bandwidth: 3MHz	700.5MHz ~ 714.5MHz
	LTE Band 12 Channel Bandwidth: 5MHz	701.5MHz ~ 713.5MHz
	LTE Band 12 Channel Bandwidth: 10MHz	704.0MHz ~ 711.0MHz
	LTE Band 13 Channel Bandwidth: 5MHz	779.5MHZ ~ 784.5MHZ
	LTE Band 13 Channel Bandwidth: 10MHz	782.0MHZ
	LTE Band 17 Channel Bandwidth: 5MHz	706.5MHz ~ 713.5MHz
	LTE Band 17 Channel Bandwidth: 10MHz	709.0MHz ~ 711.0MHz
EMISSION DESIGNATOR	**WCDMA IV**	4M23F9W
	LTE Band 4 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M08W7D
	LTE Band 4 Channel Bandwidth: 3MHz	QPSK: 2M68G7D
		16QAM: 2M68W7D
	LTE Band 4 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M48W7D
	LTE Band 4 Channel Bandwidth: 10MHz	QPSK: 8M93G7D
		16QAM: 8M94W7D

EMISSION DESIGNATOR	LTE Band 4 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D
	LTE Band 4 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M9W7D
	LTE Band 12 Channel Bandwidth: 1.4MHz	QPSK: 1M08G7D
		16QAM: 1M08W7D
	LTE Band 12 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M68W7D
	LTE Band 12 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M47W7D
	LTE Band 12 Channel Bandwidth: 10MHz	QPSK: 8M96G7D
		16QAM: 8M96W7D
	LTE Band 13 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M49W7D
	LTE Band 13 Channel Bandwidth: 10MHz	QPSK: 8M92G7D
		16QAM: 8M90W7D
	LTE Band 17 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M47W7D
	LTE Band 17 Channel Bandwidth: 10MHz	QPSK: 8M93G7D
		16QAM: 8M94W7D
MAX. ERP/EIRP POWER	WCDMA IV	235mW
	LTE Band 4 Channel Bandwidth: 1.4MHz	312mW
	LTE Band 4 Channel Bandwidth: 3MHz	314mW
	LTE Band 4 Channel Bandwidth: 5MHz	317mW
	LTE Band 4 Channel Bandwidth: 10MHz	333mW
	LTE Band 4 Channel Bandwidth: 15MHz	312mW
	LTE Band 4 Channel Bandwidth: 20MHz	274mW
	LTE Band 12 Channel Bandwidth: 1.4MHz	134mW
	LTE Band 12 Channel Bandwidth: 3MHz	136mW
	LTE Band 12 Channel Bandwidth: 5MHz	132mW
	LTE Band 12 Channel Bandwidth: 10MHz	120mW

	LTE Band 13 Channel Bandwidth: 5MHz	197mW
	LTE Band 13 Channel Bandwidth: 10MHz	168mW
	LTE Band 17 Channel Bandwidth: 5MHz	101mW
	LTE Band 17 Channel Bandwidth: 10MHz	90mW
ANTENNA TYPE	**LTE Band 4**	Fixed Internal Antenna with -0.58dBi
	LTE Band 12	Fixed Internal Antenna with -3.99dBi
	LTE Band 13	Fixed Internal Antenna with -3.59dBi
	LTE Band 17	Fixed Internal Antenna with -3.99dBi
HW VERSION	LenovoPad PB2-650Y	
SW VERSION	PB2-650Y_160517	
ACCESSORY DEVICE	Refer to note as below	
DATA CABLE	USB cable: non-shielded, detachable, 1.0m	

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
2. There were Sample A and Sample B for this project, the difference is as below:

SAMPLE	EUT CONFIGURATION INFORMATION
A	LCD panel +TP1+Front camera 1+back camera 1+eMMC 1/ eMMC 2+speaker 1+receiver 1+vibrator 1+battery 1
B	LCD panel +TP2+Front camera 2+back camera 2+eMMC 3/ eMMC 4+speaker 2+receiver 2+vibrator 2+battery 2

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

LIST OF ACCESSORIES:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
AC Adapter 1	Lenovo	Acbel	C-P35	I/P:100-240Vac, 500mA O/P:5.2Vdc, 2000mA
AC Adapter 2	Lenovo	Huntkey	C-P35	I/P:100-240Vac, 500mA O/P:5.2Vdc, 2000mA
Battery 1	Lenovo	SCUD	L16D1P31	Rating: 3.8Vdc, 4050mAh
Battery 2	Lenovo	SUNWODA	L16D1P32	Rating: 3.8Vdc, 4050mAh
USB Cable 1	LIQI	--	LQ-025254	1.0m non-shielded cable w/o core
USB Cable 2	STARW	--	XJ-007046-1	1.0m non-shielded cable w/o core
LCD Panel+TP1	Tianma	--	TM065JVSP03-00IPS gold MIPI	--
LCD Panel+TP2	GIS	--	TC064GFL01 IPS Black MIPI	--
Front Camera 1	O-Film	--	L5693F20	--
Front Camera 2	Q Technology Limited	--	F5693AQ	--
Back Camera 1	Q Technology Limited	--	F3M2YBX	--
Back Camera 2	Sunny Opotech	--	F13S05Y	--
eMMC 1	SAMSUNG	--	KMRX1000BM-B614	32G
eMMC2	Samsung	--	KMQE10013M-B318	16G
eMMC 3	Hynix	--	H9TQ26ADFTACUR-KUM	32G
eMMC 4	Hynix	--	H9TQ17ABJTACUR-KUM	16G
Speaker 1	Haosheng	--	P9898_SPK_BOX_ASM	--
Speaker 2	Midi	--	P9898_SPK_BOX_ASM_MD	--
receiver 1	Xichun	--	KFR1506G2.8-32-HV	--
receiver 2	Midi	--	MIDRC1506M2.8	--
vibrator 1	Hongzhifa	--	HZF1027A-P02L9	--
vibrator 2	AWA SEIMITSU	--	LC-B68L	--

3.2 Configuration of System Under Test

FOR RADIATION EMISSION TEST



FOR E.R.P./E.I.R.P TEST



3.2.1 Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter + USB Cable + Earphone with LTE link**
B	EUT + Battery + USB Cable + Earphone with **LTE link**

WCDMA MODE

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
A	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
B	Frequency Stability	1312 to 1513	1413	WCDMA
A	Occupied Bandwidth	1312 to 1513	1312, 1413, 1513	WCDMA
A	Band Edge	1312 to 1513	1312, 1513	WCDMA
A	Peak To Average Ratio	1312 to 1513	1312, 1413, 1513	WCDMA
A	Condcudeted Emission	1312 to 1513	1312, 1413, 1513	WCDMA
A	Radiated Emission Below 1GHz	1312 to 1513	1312	WCDMA
A	Radiated Emission Above 1GHz	1312 to 1513	1312, 1413, 1513	WCDMA

LTE BAND 4

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	19957 to 20393	19957	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20393	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20385	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20375	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20350	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	BAND EDGE	20025 to 20325	20025	15MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			20325	15MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset

			20300	20MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

LTE BAND 12

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	ERP	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	23017 to 23173	23017	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			23173	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		23025 to 23165	23025	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			23165	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		23035 to 23155	23035	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23155	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23130	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	CONDCUDETED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset

LTE BAND 13

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	ERP	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	23205 to 23255	23230	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	23205 to 23255	23205	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23255	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23230	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	CONDCUDETED EMISSION	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset

LTE BAND 17

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	ERP	23755 to 23825	23755, 23790, 23825	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23755 to 23825	23790	5MHz	QPSK	1 RB / 0 RB Offset
		23780 to 23800	23790	10MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	23755 to 23825	23755, 23790, 23825	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	23755 to 23825	23755, 23790, 23825	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	23755 to 23825	23755	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23825	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23780 to 23800	23780	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23800	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	CONDCUDETED EMISSION	23755 to 23825	23790	5MHz	QPSK	1 RB / 0 RB Offset
		23780 to 23800	23790	10MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	23755 to 23825	23790	5MHz	QPSK	1 RB / 0 RB Offset
		23780 to 23800	23790	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	21deg. C, 71%RH 22deg. C, 71%RH	DC 3.8V from battery	Yuqiang Yin
Frequency Stability	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Occupied Bandwidth	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Band Edge	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Condcudeted Emission	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Radiated Emission	21deg. C, 71%RH	5.2Vdc from adapter	Alex Chen

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB Publication 971168 D02

ANSI/TIA/EIA-603-D

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

4.1.2 Test Procedures

EIRP / ERP Measurement:

a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5MHz for WCDMA mode, and 10MHz for LTE mode.

b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn

e. E.R.P = E.I.R.P- 2.15 dB

Conducted Power Measurement:

a. The EUT was set up for the maximum power with WCDMA & LTE link data modulation and link up with simulator.

b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

AVERAGE CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	22.42	22.57	**22.66**
HSPA			
HSDPA Subtest-1	20.51	20.63	20.75
HSDPA Subtest-2	20.49	20.57	20.73
HSDPA Subtest-3	20.46	20.58	20.72
HSDPA Subtest-4	20.45	20.64	20.70
HSUPA Subtest-1	21.43	21.57	21.68
HSUPA Subtest-2	20.42	20.49	20.46
HSUPA Subtest-3	20.43	20.59	20.63
HSUPA Subtest-4	19.03	19.08	19.12
HSUPA Subtest-5	21.46	21.52	21.66

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393	MPR
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz	
1.4MHz	QPSK	1	0	22.54	22.62	22.66	0
		1	2	22.37	22.53	22.54	0
		1	5	22.43	22.58	22.53	0
		3	0	22.52	22.60	22.64	0
		3	1	22.35	22.51	22.52	0
		3	3	22.41	22.56	22.51	0
		6	0	21.48	21.62	21.65	1
	16QAM	1	0	21.66	21.79	21.75	1
		1	2	21.54	21.80	21.70	1
		1	5	21.53	21.82	21.75	1
		3	0	21.65	21.78	21.74	1
		3	1	21.53	21.79	21.69	1
		3	3	21.52	21.81	21.74	1
		6	0	20.47	20.71	20.66	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385	MPR
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz	
3 MHz	QPSK	1	0	22.55	22.63	22.67	0
		1	7	22.38	22.54	22.55	0
		1	14	22.44	22.59	22.54	0
		8	0	21.58	21.62	21.65	1
		8	3	21.49	21.58	21.59	1
		8	7	21.53	21.61	21.61	1
		15	0	21.49	21.63	21.66	1
	16QAM	1	0	21.67	21.80	21.76	1
		1	7	21.55	21.81	21.71	1
		1	14	21.54	21.83	21.76	1
		8	0	20.58	20.61	20.65	2
		8	3	20.45	20.65	20.67	2
		8	7	20.44	20.58	20.62	2
		15	0	20.48	20.72	20.67	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375	MPR
				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz	
5 MHz	QPSK	1	0	22.58	22.66	22.70	0
		1	12	22.41	22.57	22.58	0
		1	24	22.47	22.62	22.57	0
		12	0	21.61	21.65	21.68	1
		12	6	21.52	21.61	21.62	1
		12	13	21.56	21.64	21.64	1
		25	0	21.52	21.66	21.69	1
	16QAM	1	0	21.70	21.83	21.79	1
		1	12	21.58	21.84	21.74	1
		1	24	21.57	21.86	21.79	1
		12	0	20.61	20.64	20.68	2
		12	6	20.48	20.68	20.70	2
		12	13	20.47	20.61	20.65	2
		25	0	20.51	20.75	20.70	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350	MPR
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz	
10 MHz	QPSK	1	0	22.62	22.70	22.74	0
		1	24	22.45	22.61	22.62	0
		1	49	22.51	22.66	22.61	0
		25	0	21.65	21.69	21.72	1
		25	12	21.56	21.65	21.66	1
		25	25	21.60	21.68	21.68	1
		50	0	21.56	21.70	21.73	1
	16QAM	1	0	21.74	21.87	21.83	1
		1	24	21.62	21.88	21.78	1
		1	49	21.61	21.90	21.83	1
		25	0	20.65	20.68	20.72	2
		25	12	20.52	20.72	20.74	2
		25	25	20.51	20.65	20.69	2
		50	0	21.50	21.55	21.27	2

LTE Band 4							
BW	**Modulation**	**RB Size**	**RB Offset**	**Low CH 20025**	**Mid CH 20175**	**High CH 20325**	**MPR**
				Frequency 1717.5 MHz	**Frequency 1732.5 MHz**	**Frequency 1747.5 MHz**	
15 MHz	**QPSK**	1	0	22.68	22.76	22.80	0
		1	37	22.51	22.67	22.68	0
		1	74	22.57	22.72	22.67	0
		36	0	21.71	21.75	21.78	1
		36	19	21.62	21.71	21.72	1
		36	39	21.66	21.74	21.74	1
		75	0	21.62	21.76	21.79	1
	16QAM	1	0	21.80	21.93	21.89	1
		1	37	21.68	21.94	21.84	1
		1	74	21.67	21.96	21.89	1
		36	0	20.71	20.74	20.78	2
		36	19	20.58	20.78	20.80	2
		36	39	20.57	20.71	20.75	2
		75	0	20.61	20.85	20.80	2

LTE Band 4							
BW	**Modulation**	**RB Size**	**RB Offset**	**Low CH 20050**	**Mid CH 20175**	**High CH 20300**	**MPR**
				Frequency 1720 MHz	**Frequency 1732.5 MHz**	**Frequency 1745 MHz**	
20MHz	**QPSK**	1	0	22.71	22.79	**22.83**	0
		1	50	22.54	22.70	22.71	0
		1	99	22.60	22.75	22.70	0
		50	0	21.74	21.78	21.81	1
		50	25	21.65	21.74	21.75	1
		50	50	21.69	21.77	21.77	1
		100	0	21.65	21.79	21.82	1
	16QAM	1	0	21.83	21.96	21.92	1
		1	50	21.71	21.97	21.87	1
		1	99	21.70	21.99	21.92	1
		50	0	20.74	20.77	20.81	2
		50	25	20.61	20.81	20.83	2
		50	50	20.60	20.74	20.78	2
		100	0	20.64	20.88	20.83	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23017 Frequency 699.7 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23173 Frequency 715.3 MHz	MPR
1.4 MHz	QPSK	1	0	22.78	22.74	22.82	0
		1	2	22.71	22.73	22.72	0
		1	5	22.68	22.68	22.71	0
		3	0	22.76	22.72	22.80	0
		3	1	22.69	22.71	22.70	0
		3	3	22.66	22.66	22.69	0
		6	0	21.77	21.79	21.81	1
	16QAM	1	0	21.77	21.76	21.84	1
		1	2	21.76	21.80	21.80	1
		1	5	21.83	21.84	21.85	1
		3	0	21.76	21.75	21.83	1
		3	1	21.75	21.79	21.79	1
		3	3	21.82	21.83	21.84	1
		6	0	20.74	20.79	20.75	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23025 Frequency 700.5 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23165 Frequency 714.5 MHz	MPR
3 MHz	QPSK	1	0	22.82	22.78	22.86	0
		1	7	22.75	22.77	22.76	0
		1	14	22.72	22.72	22.75	0
		8	0	21.78	21.79	21.78	1
		8	3	21.80	21.82	21.80	1
		8	7	21.82	21.84	21.87	1
		15	0	21.81	21.83	21.85	1
	16QAM	1	0	21.81	21.80	21.88	1
		1	7	21.80	21.84	21.84	1
		1	14	21.87	21.88	21.89	1
		8	0	20.72	20.75	20.78	2
		8	3	20.76	20.82	20.78	2
		8	7	20.72	20.83	20.81	2
		15	0	20.78	20.83	20.79	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23035	Mid CH 23095	High CH 23155	MPR
				Frequency 701.5 MHz	Frequency 707.5 MHz	Frequency 713.5 MHz	
5 MHz	QPSK	1	0	22.88	22.84	22.92	0
		1	12	22.81	22.83	22.82	0
		1	24	22.78	22.78	22.81	0
		12	0	21.84	21.85	21.84	1
		12	6	21.86	21.88	21.86	1
		12	13	21.88	21.90	21.93	1
		25	0	21.87	21.89	21.91	1
	16QAM	1	0	21.87	21.86	21.94	1
		1	12	21.86	21.90	21.90	1
		1	24	21.93	21.94	21.95	1
		12	0	20.78	20.81	20.84	2
		12	6	20.82	20.88	20.84	2
		12	13	20.78	20.89	20.87	2
		25	0	20.84	20.89	20.85	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23060	Mid CH 23095	High CH 23130	MPR
				Frequency 704 MHz	Frequency 707.5 MHz	Frequency 711 MHz	
10 MHz	QPSK	1	0	22.91	22.87	**22.95**	0
		1	24	22.84	22.86	22.85	0
		1	49	22.81	22.81	22.84	0
		25	0	21.87	21.88	21.87	1
		25	12	21.89	21.91	21.89	1
		25	25	21.91	21.93	21.96	1
		50	0	21.90	21.92	21.94	1
	16QAM	1	0	21.90	21.89	21.97	1
		1	24	21.89	21.93	21.93	1
		1	49	21.96	21.97	21.98	1
		25	0	20.81	20.84	20.87	2
		25	12	20.85	20.91	20.87	2
		25	25	20.81	20.92	20.90	2
		50	0	20.87	20.92	20.88	2

LTE Band 13							
BW	**Modulation**	**RB Size**	**RB Offset**	**Low CH 23205**	**Mid CH 23230**	**High CH 23255**	**MPR**
				Frequency 779.5 MHz	**Frequency 782.0 MHz**	**Frequency 784.5 MHz**	
5 MHz	**QPSK**	1	0	22.97	22.90	22.90	0
		1	12	22.91	22.91	22.92	0
		1	24	22.86	22.83	22.80	0
		12	0	21.96	21.98	21.97	1
		12	6	21.98	21.99	21.98	1
		12	13	21.97	21.94	21.99	1
		25	0	21.97	21.93	21.94	1
	16QAM	1	0	21.98	21.99	21.98	1
		1	12	21.90	21.89	21.90	1
		1	24	21.97	21.95	21.96	1
		12	0	21.01	20.96	20.98	2
		12	6	20.98	20.98	20.96	2
		12	13	20.95	20.94	21.00	2
		25	0	20.95	20.93	20.96	2

LTE Band 13							
BW	**Modulation**	**RB Size**	**RB Offset**	**CH**	**CH 23230**	**CH**	**MPR**
				Frequency MHz	**Frequency 782.0 MHz**	**Frequency MHz**	
10 MHz	**QPSK**	1	0	-	**22.96**	-	0
		1	24	-	22.91	-	0
		1	49	-	22.85	-	0
		25	0	-	21.97	-	1
		25	12	-	21.93	-	1
		25	25	-	21.95	-	1
		50	0	-	21.94	-	1
	16QAM	1	0	-	22.13	-	1
		1	24	-	22.06	-	1
		1	49	-	22.10	-	1
		25	0	-	20.98	-	2
		25	12	-	20.92	-	2
		25	25	-	20.96	-	2
		50	0	-	20.99	-	2

LTE Band 17							
BW	**Modulation**	**RB Size**	**RB Offset**	**Low CH 23755**	**Mid CH 23790**	**High CH 23825**	**MPR**
				Frequency 706.5 MHz	**Frequency 710 MHz**	**Frequency 713.5 MHz**	
5 MHz	**QPSK**	1	0	22.79	22.85	22.84	0
		1	12	22.78	22.77	22.76	0
		1	24	22.69	22.72	22.70	0
		12	0	21.79	21.78	21.75	1
		12	6	21.80	21.81	21.79	1
		12	13	21.81	21.85	21.81	1
		25	0	21.80	21.84	21.79	1
	16QAM	1	0	21.79	21.83	21.87	1
		1	12	21.94	21.90	21.85	1
		1	24	21.89	21.84	21.90	1
		12	0	20.79	20.78	20.80	2
		12	6	20.77	20.80	20.78	2
		12	13	20.78	20.79	20.79	2
		25	0	20.80	20.82	20.80	2

LTE Band 17							
BW	**Modulation**	**RB Size**	**RB Offset**	**Low CH 23780**	**Mid CH 23790**	**High CH 23800**	**MPR**
				Frequency 709 MHz	**Frequency 710 MHz**	**Frequency 711 MHz**	
10 MHz	**QPSK**	1	0	22.83	**22.89**	22.88	0
		1	24	22.82	22.81	22.80	0
		1	49	22.73	22.76	22.74	0
		25	0	21.83	21.82	21.79	1
		25	12	21.84	21.85	21.83	1
		25	25	21.85	21.89	21.85	1
		50	0	21.84	21.88	21.83	1
	16QAM	1	0	21.83	21.87	21.91	1
		1	24	21.98	21.94	21.89	1
		1	49	21.93	21.88	21.94	1
		25	0	20.83	20.82	20.84	2
		25	12	20.81	20.84	20.82	2
		25	25	20.82	20.83	20.83	2
		50	0	20.84	20.86	20.84	2

EIRP

WCDMA IV

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
1312	1712.4	-18.83	41.39	22.56	180.26	H
1413	1732.6	-18.62	41.36	22.74	187.93	H
1513	1752.6	-18.91	42.63	23.72	**235.45**	H
1312	1712.4	-23.91	44.17	20.26	106.07	V
1413	1732.6	-23.25	44.20	20.95	124.45	V
1513	1752.6	-23.75	44.35	20.60	114.68	V

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-21.61	41.29	19.68	92.98	H	1
20175	1732.5	-22.08	41.36	19.28	84.72	H	1
20393	1754.3	-22.53	42.74	20.21	104.91	H	1
19957	1710.7	-19.31	44.25	24.94	**311.53**	V	1
20175	1732.5	-19.50	44.20	24.70	295.12	V	1
20393	1754.3	-19.44	44.09	24.65	291.41	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-22.48	41.29	18.81	76.10	H	1
20175	1732.5	-23.01	41.36	18.35	68.39	H	1
20393	1754.3	-23.49	42.74	19.25	84.10	H	1
19957	1710.7	-20.18	44.25	24.07	254.98	V	1
20175	1732.5	-20.43	44.20	23.77	238.23	V	1
20393	1754.3	-20.40	44.09	23.69	233.61	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-21.59	41.27	19.68	92.83	H	1
20175	1732.5	-22.14	41.36	19.22	83.56	H	1
20385	1753.5	-22.48	42.76	20.28	106.59	H	1
19965	1711.5	-19.29	44.26	24.97	**314.20**	V	1
20175	1732.5	-19.56	44.20	24.64	291.07	V	1
20385	1753.5	-19.39	44.23	24.84	304.93	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-22.66	41.27	18.61	72.56	H	1
20175	1732.5	-23.03	41.36	18.33	68.08	H	1
20385	1753.5	-23.47	42.76	19.29	84.86	H	1
19965	1711.5	-20.36	44.26	23.90	245.58	V	1
20175	1732.5	-20.45	44.20	23.75	237.14	V	1
20385	1753.5	-20.38	44.23	23.85	242.77	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-21.65	41.39	19.74	94.17	H	1
20175	1732.5	-22.09	41.36	19.27	84.53	H	1
20375	1752.5	-22.43	42.63	20.20	104.69	H	1
19975	1712.5	-19.35	44.17	24.82	303.11	V	1
20175	1732.5	-19.51	44.20	24.69	294.44	V	1
20375	1752.5	-19.34	44.35	25.01	**316.59**	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-22.48	41.39	18.91	77.79	H	1
20175	1732.5	-23.11	41.36	18.25	66.83	H	1
20375	1752.5	-23.53	42.63	19.10	81.26	H	1
19975	1712.5	-20.18	44.17	23.99	250.38	V	1
20175	1732.5	-20.53	44.20	23.67	232.81	V	1
20375	1752.5	-20.44	44.35	23.91	245.75	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-21.46	41.49	20.03	100.60	H	1
20175	1732.5	-22.03	41.36	19.33	85.70	H	1
20350	1750.0	-22.30	42.28	19.98	99.61	H	1
20000	1715.0	-19.16	44.06	24.90	309.24	V	1
20175	1732.5	-19.45	44.20	24.75	298.54	V	1
20350	1750.0	-19.21	44.43	25.22	**332.66**	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-22.61	41.49	18.88	77.20	H	1
20175	1732.5	-23.13	41.36	18.23	66.53	H	1
20350	1750.0	-23.46	42.28	18.82	76.26	H	1
20000	1715.0	-20.31	44.06	23.75	237.30	V	1
20175	1732.5	-20.55	44.20	23.65	231.74	V	1
20350	1750.0	-20.37	44.43	24.06	254.68	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-21.47	41.34	19.87	97.01	H	1
20175	1732.5	-22.10	41.36	19.26	84.33	H	1
20325	1747.5	-22.37	42.09	19.72	93.67	H	1
20025	1717.5	-19.17	44.04	24.87	307.18	V	1
20175	1732.5	-19.52	44.20	24.68	293.76	V	1
20325	1747.5	-19.28	44.22	24.94	**311.53**	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-22.33	41.34	19.01	79.58	H	1
20175	1732.5	-22.97	41.36	18.39	69.02	H	1
20325	1747.5	-23.22	42.09	18.87	77.02	H	1
20025	1717.5	-20.03	44.04	24.01	252.00	V	1
20175	1732.5	-20.39	44.20	23.81	240.44	V	1
20325	1747.5	-20.13	44.22	24.09	256.15	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-22.05	41.28	19.23	83.77	H	1
20175	1732.5	-22.55	41.36	18.81	76.05	H	1
20300	1745.0	-22.95	41.96	19.01	79.56	H	1
20050	1720.0	-19.75	44.14	24.39	**274.47**	V	1
20175	1732.5	-19.97	44.20	24.23	264.61	V	1
20300	1745.0	-19.86	43.88	24.02	252.46	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-22.98	41.28	18.30	67.62	H	1
20175	1732.5	-23.62	41.36	17.74	59.44	H	1
20300	1745.0	-23.78	41.96	18.18	65.72	H	1
20050	1720.0	-20.68	44.14	23.46	221.56	V	1
20175	1732.5	-21.04	44.20	23.16	206.82	V	1
20300	1745.0	-20.69	43.88	23.19	208.55	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-9.34	32.77	21.28	**134.28**	H	3
23095	707.5	-9.93	33.23	21.15	130.32	H	3
23173	715.3	-10.36	33.14	20.63	115.56	H	3
23017	699.7	-12.85	32.42	17.42	55.16	V	3
23095	707.5	-13.61	32.60	16.84	48.31	V	3
23173	715.3	-14.23	32.19	15.81	38.07	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-10.17	32.77	20.45	110.92	H	3
23095	707.5	-10.95	33.23	20.13	103.04	H	3
23173	715.3	-11.46	33.14	19.53	89.70	H	3
23017	699.7	-13.68	32.42	16.59	45.56	V	3
23095	707.5	-14.63	32.60	15.82	38.19	V	3
23173	715.3	-15.33	32.19	14.71	29.55	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-9.15	32.63	21.33	**135.86**	H	3
23095	707.5	-9.87	33.23	21.21	132.13	H	3
23165	714.5	-10.23	33.21	20.83	120.92	H	3
23025	700.5	-12.66	32.33	17.52	56.45	V	3
23095	707.5	-13.55	32.60	16.90	48.98	V	3
23165	714.5	-14.10	32.30	16.05	40.28	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-10.30	32.63	20.18	104.26	H	3
23095	707.5	-10.97	33.23	20.11	102.57	H	3
23165	714.5	-11.39	33.21	19.67	92.58	H	3
23025	700.5	-13.81	32.33	16.37	43.32	V	3
23095	707.5	-14.65	32.60	15.80	38.02	V	3
23165	714.5	-15.26	32.30	14.89	30.84	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-9.16	32.53	21.22	**132.28**	H	3
23095	707.5	-9.94	33.23	21.14	129.96	H	3
23155	713.5	-10.30	33.29	20.84	121.26	H	3
23035	701.5	-12.67	32.25	17.43	55.39	V	3
23095	707.5	-13.62	32.60	16.83	48.19	V	3
23155	713.5	-14.17	32.39	16.07	40.42	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-10.02	32.53	20.36	108.52	H	3
23095	707.5	-10.81	33.23	20.27	106.37	H	3
23155	713.5	-11.15	33.29	19.99	99.70	H	3
23035	701.5	-13.53	32.25	16.57	45.44	V	3
23095	707.5	-14.49	32.60	15.96	39.45	V	3
23155	713.5	-15.02	32.39	15.22	33.24	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-9.74	32.68	20.79	**120.03**	H	3
23095	707.5	-10.39	33.23	20.69	117.22	H	3
23130	711.0	-10.88	33.39	20.36	108.57	H	3
23060	704.0	-13.25	32.37	16.97	49.75	V	3
23095	707.5	-14.07	32.60	16.38	43.45	V	3
23130	711.0	-14.75	32.56	15.66	36.77	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-10.67	32.68	19.86	96.89	H	3
23095	707.5	-11.46	33.23	19.62	91.62	H	3
23130	711.0	-11.71	33.39	19.53	89.68	H	3
23060	704.0	-14.18	32.37	16.04	40.16	V	3
23095	707.5	-15.14	32.60	15.31	33.96	V	3
23130	711.0	-15.58	32.56	14.83	30.37	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
23205	779.5	-7.67	32.60	22.78	189.67	H	3
23230	782.0	-7.89	32.75	22.71	186.64	H	3
23255	784.5	-7.98	33.08	22.95	**197.24**	H	3
23205	779.5	-13.72	31.54	15.67	36.90	V	3
23230	782.0	-13.94	31.70	15.61	36.39	V	3
23255	784.5	-14.12	31.97	15.70	37.15	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
23205	779.5	-8.45	32.60	22.00	158.49	H	3
23230	782.0	-8.76	32.75	21.84	152.76	H	3
23255	784.5	-8.86	33.08	22.07	161.06	H	3
23205	779.5	-14.64	31.54	14.75	29.85	V	3
23230	782.0	-14.81	31.70	14.74	29.79	V	3
23255	784.5	-14.87	31.97	14.95	31.26	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 13

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23230	782.0	-8.34	32.75	22.26	**168.27**	H	3
23230	782.0	-14.39	31.70	15.16	32.81	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23230	782.0	-9.41	32.75	21.19	131.52	H	3
23230	782.0	-15.46	31.70	14.09	25.64	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 17

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23755	706.5	-10.95	32.64	19.54	89.85	H	3
23790	710.0	-10.86	32.92	19.91	97.95	H	3
23825	713.5	-10.64	32.83	20.04	**100.83**	H	3
23755	706.5	-15.82	32.14	14.17	26.10	V	3
23790	710.0	-15.39	32.18	14.64	29.11	V	3
23825	713.5	-15.07	31.95	14.73	29.74	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23755	706.5	-11.81	32.64	18.68	73.71	H	3
23790	710.0	-11.73	32.92	19.04	80.17	H	3
23825	713.5	-11.49	32.83	19.19	82.91	H	3
23755	706.5	-16.10	32.14	13.89	24.47	V	3
23790	710.0	-16.26	32.18	13.77	23.82	V	3
23825	713.5	-15.92	31.95	13.88	24.46	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 17

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23780	709.0	-11.53	32.90	19.22	83.46	H	3
23790	710.0	-11.31	32.92	19.46	88.27	H	3
23800	711.0	-11.22	32.92	19.55	**90.18**	H	3
23780	709.0	-15.82	32.20	14.23	26.45	V	3
23790	710.0	-15.84	32.18	14.19	26.25	V	3
23800	711.0	-15.65	32.13	14.33	27.11	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23780	709.0	-12.46	32.90	18.29	67.38	H	3
23790	710.0	-12.38	32.92	18.39	68.99	H	3
23800	711.0	-12.05	32.92	18.72	74.49	H	3
23780	709.0	-16.75	32.20	13.30	21.36	V	3
23790	710.0	-16.91	32.18	13.12	20.52	V	3
23800	711.0	-16.48	32.13	13.50	22.39	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stabiliity Measurement

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

FREQUENCY ERROR VS. VOLTAGE

	FREQUENCY ERROR (PPM)							
VOLTAGE (Volts)	WCDMA	LTE Band 4						LIMIT (ppm)
		1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
3.8	0.0013	0.0012	0.0015	0.0017	0.0015	0.0015	0.0012	2.5
3.5	-0.0019	-0.0018	-0.0018	-0.0022	-0.0020	-0.0019	-0.0018	2.5
4.4	-0.0016	-0.0014	-0.0016	-0.0019	-0.0018	-0.0019	-0.0017	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.4Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

	Frequency Error (PPM)							
TEMP. (℃)	WCDMA	LTE Band 4						LIMIT (ppm)
		1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
-30	-0.0050	-0.0058	-0.0058	-0.0060	-0.0060	-0.0061	-0.0064	2.5
-20	-0.0044	-0.0050	-0.0049	-0.0052	-0.0053	-0.0054	-0.0058	2.5
-10	-0.0038	-0.0044	-0.0046	-0.0044	-0.0046	-0.0047	-0.0051	2.5
0	-0.0032	-0.0036	-0.0036	-0.0035	-0.0039	-0.0039	-0.0042	2.5
10	-0.0026	-0.0029	-0.0029	-0.0028	-0.0031	-0.0032	-0.0030	2.5
20	-0.0020	-0.0022	-0.0022	-0.0021	-0.0024	-0.0025	-0.0023	2.5
30	-0.0014	-0.0014	-0.0015	-0.0012	-0.0018	-0.0018	-0.0016	2.5
40	-0.0007	-0.0007	-0.0009	-0.0005	-0.0010	-0.0011	-0.0008	2.5
50	-0.0001	0.0000	-0.0001	0.0002	-0.0002	-0.0004	-0.0002	2.5
60	0.0005	0.0005	0.0005	0.0007	0.0004	0.0003	0.0004	2.5

LTE BAND 12

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	
3.8	0.0029	0.0036	0.0035	0.0043	2.5
3.5	-0.0037	-0.0043	-0.0051	-0.0046	2.5
4.4	-0.0031	-0.0046	-0.0046	-0.0052	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.4Vdc.

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	
-30	-0.0150	-0.0153	-0.0155	-0.0152	2.5
-20	-0.0133	-0.0136	-0.0138	-0.0135	2.5
-10	-0.0115	-0.0119	-0.0122	-0.0116	2.5
0	-0.0097	-0.0101	-0.0105	-0.0099	2.5
10	-0.0077	-0.0083	-0.0088	-0.0079	2.5
20	-0.0060	-0.0067	-0.0071	-0.0058	2.5
30	-0.0042	-0.0046	-0.0054	-0.0041	2.5
40	-0.0022	-0.0030	-0.0037	-0.0021	2.5
50	-0.0003	-0.0013	-0.0020	-0.0005	2.5
60	0.0010	0.0006	-0.0002	0.0012	2.5

	FREQUENCY ERROR (ppm)				
VOLTAGE (Volts)	LTE Band 13		LTE Band 17		LIMIT (ppm)
	5MHz	10MHz	5MHz	10MHz	
3.8	0.0027	0.0026	0.0043	0.0046	2.5
3.5	-0.0039	-0.0039	-0.0015	-0.0036	2.5
4.4	-0.0032	-0.0035	-0.0013	-0.0030	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.4Vdc.

	FREQUENCY ERROR (ppm)				
TEMP. (℃)	LTE Band 13		LTE Band 17		LIMIT (ppm)
	5MHz	10MHz	5MHz	10MHz	
-30	-0.0130	-0.0132	-0.0147	0.0150	2.5
-20	-0.0112	-0.0116	-0.0129	-0.0135	2.5
-10	-0.0095	-0.0102	-0.0111	-0.0119	2.5
0	-0.0077	-0.0086	-0.0092	-0.0104	2.5
10	-0.0061	-0.0069	-0.0076	-0.0087	2.5
20	-0.0044	-0.0054	-0.0061	-0.0071	2.5
30	-0.0027	-0.0040	-0.0045	-0.0054	2.5
40	-0.0013	-0.0027	-0.0030	-0.0034	2.5
50	-0.0001	-0.0011	-0.0012	-0.0017	2.5
60	0.0011	0.0004	0.0007	-0.0002	2.5

4.3 Occupied Bandwidth Measurement

4.3.1 Limits Of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.3.2 Test Setup



4.3.3 Test Procedures

a. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
b. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.4 Test Result

Channel	FREQ. (MHz)	99% Occupied Bandwidth (MHz)	Channel	FREQ. (MHz)	26dB Bandwidth (MHz)
		WCDMA			WCDMA
1312	1712.40	4.23	1312	1712.40	4.90
1413	1732.60	4.23	1413	1732.60	4.90
1513	1752.60	4.23	1513	1752.60	4.95

WCDMA

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.09	1.08	19965	1711.5	2.68	2.68
20175	1732.5	1.09	1.08	20175	1732.5	2.68	2.68
20393	1754.3	1.09	1.08	20385	1753.5	2.68	2.68

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.49	4.47	20000	1715	8.93	8.91
20175	1732.5	4.48	4.47	20175	1732.5	8.93	8.93
20375	1752.5	4.48	4.48	20350	1750	8.92	8.94

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK

5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.45	13.42	20050	1720	17.93	17.89
20175	1732.5	13.42	13.41	20175	1732.5	17.90	17.83
20325	1747.5	13.41	13.42	20300	1745	17.92	17.84

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK

15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.08	1.08	23025	700.5	2.68	2.68
23095	707.5	1.08	1.08	23095	707.5	2.68	2.68
23173	715.3	1.08	1.08	23165	714.5	2.69	2.68

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK

1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.49	4.46	23060	704	8.96	8.95
23095	707.5	4.49	4.47	23095	707.5	8.96	8.96
23155	713.5	4.49	4.47	23130	711	8.91	8.91

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK

5MHz / 16QAM

10MHz / QPSK

10MHz / 16QAM



LTE BAND 13

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	4.48	4.47	-	-	-	-
23230	782	4.48	4.47	23230	782	8.92	8.90
23255	784.5	4.49	4.49	-	-	-	-

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK

10MHz / 16QAM



LTE BAND 17

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	4.49	4.47	23780	709	8.93	8.94
23790	710	4.48	4.46	23790	710	8.91	8.91
23825	713.5	4.48	4.47	23800	711	8.90	8.91

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK

5MHz / 16QAM



10MHz / QPSK

10MHz / 16QAM



4.4 Peak To Average Ratio

4.4.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 Test Setup



4.4.3 Test Procedures

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.4.4 Test Results

Channel	Frequency (MHz)	Peak To Average Ratio (dB)
		WCDMA
1413	1732.6	2.45

SPECTRUM PLOT OF WORST VALUE
WCDMA



LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	5.18	5.83	19965	1711.5	5.26	5.85
20175	1732.5	5.11	5.82	20175	1732.5	5.20	5.84
20393	1754.3	5.18	5.87	20385	1753.5	5.31	5.85

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	5.47	6.01	20000	1715	5.34	5.90
20175	1732.5	5.35	6.00	20175	1732.5	5.16	5.83
20375	1752.5	5.42	6.00	20350	1750	5.25	5.86

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM

10MHz / QPSK



10MHz / 16QAM



CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	5.38	6.02	20050	1720	5.51	6.14
20175	1732.5	5.28	5.91	20175	1732.5	5.32	6.05
20325	1747.5	5.24	5.87	20300	1745	5.40	6.04

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	4.93	5.75	23025	700.5	4.84	5.62
23095	707.5	5.60	6.32	23095	707.5	5.69	6.32
23173	715.3	4.35	5.21	23165	714.5	4.40	5.17

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	5.04	5.72	23060	704	5.37	6.00
23095	707.5	5.69	6.36	23095	707.5	5.28	6.04
23155	713.5	4.98	5.67	23130	711	5.00	5.81

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM

10MHz / QPSK



10MHz / 16QAM



LTE BAND 13

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	5.44	6.22	-	-	-	-
23230	782	5.72	6.34	23230	782	5.86	6.51
23255	784.5	5.93	6.63	-	-	-	-

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



LTE BAND 17

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	5.64	6.30	23780	709	5.08	5.91
23790	710	5.44	6.17	23790	710	5.00	5.83
23825	713.5	4.99	5.67	23800	711	5.05	5.81

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



4.5 Band Edge Measurement

4.5.1 Limits of Band Edge Measurement

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.
However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

4.5.2 Test Setup



4.5.3 Test Procedures

a. The EUT was set up for the maximum peak power with WCDMA & LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).

b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 20kHz and VB of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz. (LTE bandwidth 3MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 50kHz and VB of the spectrum is 200kHz. (LTE bandwidth 5MHz)

g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz. (LTE bandwidth 10MHz)

h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 15MHz)

i. he center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 20MHz)

j. Record the max trace plot into the test report.

4.5.4 Test Results

WCDMA IV			
CHANNEL	1312	CHANNEL	1513

LTE BAND 4

Channel Bandwidth: 1.4MHz					
CHANNEL	19957	1 RB	CHANNEL	20393	1 RB
CHANNEL	19957	Full RB	CHANNEL	20393	Full RB

Channel Bandwidth: 3MHz

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB

Channel Bandwidth: 5MHz

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB

CHANNEL	19975	Full RB	CHANNEL	20375	Full RB

Channel Bandwidth: 10MHz

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

Channel Bandwidth: 15MHz

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB
CHANNEL	20025	Full RB	CHANNEL	20325	Full RB
					

Channel Bandwidth: 20MHz

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB

LTE BAND 12

Channel Bandwidth: 1.4MHz					
CHANNEL	23017	1 RB	CHANNEL	23173	1 RB
CHANNEL	23017	Full RB	CHANNEL	23173	Full RB

Channel Bandwidth: 3MHz

CHANNEL	23025	1 RB	CHANNEL	23165	1 RB

CHANNEL	23025	Full RB	CHANNEL	23165	Full RB

Channel Bandwidth: 5MHz

CHANNEL	23035	1 RB	CHANNEL	23155	1 RB

CHANNEL	23035	Full RB	CHANNEL	23155	Full RB

Channel Bandwidth: 10MHz

CHANNEL	23060	1 RB	CHANNEL	23130	1 RB

CHANNEL	23060	Full RB	CHANNEL	23130	Full RB

LTE BAND 13

Channel Bandwidth: 5MHz					
CHANNEL	23205	1 RB	CHANNEL	23255	1 RB
CHANNEL	23205	Full RB	CHANNEL	23255	Full RB

Channel Bandwidth: 10MHz

CHANNEL	23230	1 RB	CHANNEL	23230	1 RB

CHANNEL	23230	Full RB	CHANNEL	23230	Full RB

LTE BAND 17

Channel Bandwidth: 5MHz					
CHANNEL	23755	1 RB	CHANNEL	23825	1 RB
CHANNEL	23755	Full RB	CHANNEL	23825	Full RB

Channel Bandwidth: 10MHz

CHANNEL	23780	1 RB	CHANNEL	23800	1 RB

CHANNEL	23780	Full RB	CHANNEL	23800	Full RB

4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission is equal to -13dBm.

4.6.2 Test Procedure

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.

b. Measuring frequency range is from 30MHz to 19.1GHz for WCDMA IV & LTE Band 4, 30 MHz to 9GHz for LTE Band 12 & LTE Band 13 & LTE Band 17. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.3 Test Setup



4.6.4 Test Results

WCDMA

CHANNEL 1413

FREQUENCY RANGE : 30MHz~1GHz



FREQUENCY RANGE : 1GHz~3GHz

FREQUENCY RANGE : 3GHz~7GHz



FREQUENCY RANGE : 7GHz~13GHz

FREQUENCY RANGE : 13GHz~19.1GHz



LTE BAND 4

CHANNEL 20175	CHANNEL 20175
1.4MHz / QPSK	**3MHz / QPSK**
FREQUENCY RANGE : 30MHz~19.1GHz	**FREQUENCY RANGE : 30MHz~19.1GHz**
5MHz / QPSK	**10MHz / QPSK**
FREQUENCY RANGE : 30MHz~19.1GHz	**FREQUENCY RANGE : 30MHz~19.1GHz**
15MHz / QPSK	**20MHz / QPSK**
FREQUENCY RANGE : 30MHz~19.1GHz	**FREQUENCY RANGE : 30MHz~19.1GHz**

LTE BAND 12

CHANNEL 23095	CHANNEL 23095
1.4MHz / QPSK	**3MHz / QPSK**
FREQUENCY RANGE : 30MHz~9GHZ	**FREQUENCY RANGE : 30MHz~9GHZ**
	
CHANNEL 23095	**CHANNEL 23095**
5MHz / QPSK	**10MHz / QPSK**
FREQUENCY RANGE : 30MHz~9GHz	**FREQUENCY RANGE : 30MHz~9GHz**
	

LTE BAND 13

CHANNEL 23230	CHANNEL 23230
5MHz / QPSK	10MHz / QPSK
FREQUENCY RANGE : 30MHz~9GHz	FREQUENCY RANGE : 30MHz~9GHz
	

LTE BAND 17

CHANNEL 23790	CHANNEL 23790
5MHz / QPSK	10MHz / QPSK
FREQUENCY RANGE : 30MHz~9GHz	FREQUENCY RANGE : 30MHz~9GHz
	

4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

In the FCC 27.53(m) (4), On any frequency outside a licensee's frequency block, The power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB. The emission limit equal to -13dBm.

4.7.2 Test Procedure

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G.
c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

BELOW 1GHz WORST-CASE DATA

LTE Band 4:



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	45.520	-50.08	-57.31	-13.00	-37.08	7.23	Peak	Horizontal
2	89.170	-60.23	-51.30	-13.00	-47.23	-8.93	Peak	Horizontal
3	152.220	-69.56	-50.58	-13.00	-56.56	-18.98	Peak	Horizontal
4	195.870	-58.78	-41.44	-13.00	-45.78	-17.34	Peak	Horizontal
5	474.260	-75.82	-65.42	-13.00	-62.82	-10.40	Peak	Horizontal
6	814.730	-68.53	-64.58	-13.00	-55.53	-3.95	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	46.490	-42.96	-39.32	-13.00	-29.96	-3.64	Peak	Vertical
2		77.530	-60.05	-48.49	-13.00	-47.05	-11.56	Peak	Vertical
3		194.900	-57.74	-46.46	-13.00	-44.74	-11.28	Peak	Vertical
4		427.700	-75.04	-65.13	-13.00	-62.04	-9.91	Peak	Vertical
5		638.190	-72.71	-65.80	-13.00	-59.71	-6.91	Peak	Vertical
6		782.720	-70.48	-65.05	-13.00	-57.48	-5.43	Peak	Vertical

ABOVE 1GHz DATA

WCDMA Band IV:



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : WCDMA Band4
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-52.93	-54.98	-13.00	-39.93	2.05	Peak	Horizontal
2	PP	5197.500	-42.65	-51.26	-13.00	-29.65	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : WCDMA Band4
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-52.62	-55.15	-13.00	-39.62	2.53	Peak	Vertical
2	PP	5197.500	-43.98	-51.96	-13.00	-30.98	7.98	Peak	Vertical

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(1.4M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-48.06	-50.11	-13.00	-35.06	2.05	Peak	Horizontal
2	PP	5197.500	-37.81	-46.42	-13.00	-24.81	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(1.4M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-47.01	-49.54	-13.00	-34.01	2.53	Peak	Vertical
2	PP	5197.500	-44.74	-52.72	-13.00	-31.74	7.98	Peak	Vertical

CHANNEL BANDWIDTH: 3MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(3M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-46.59	-48.64	-13.00	-33.59	2.05	Peak	Horizontal
2	PP	5197.500	-37.53	-46.14	-13.00	-24.53	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(3M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-43.46	-45.99	-13.00	-30.46	2.53	Peak	Vertical
2	PP	5197.500	-42.10	-50.08	-13.00	-29.10	7.98	Peak	Vertical

CHANNEL BANDWIDTH: 5MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(5M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-45.96	-48.01	-13.00	-32.96	2.05	Peak	Horizontal
2	PP	5197.500	-35.81	-44.42	-13.00	-22.81	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(5M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-47.18	-49.71	-13.00	-34.18	2.53	Peak	Horizontal
2	PP	5197.500	-38.56	-46.54	-13.00	-25.56	7.98	Peak	Horizontal

CHANNEL BANDWIDTH: 10MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3465.000	-51.65	-53.68	-13.00	-38.65	2.03	Peak	Horizontal
2 PP	5197.500	-36.39	-45.00	-13.00	-23.39	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-52.11	-54.64	-13.00	-39.11	2.53	Peak	Vertical
2	PP	5197.500	-37.99	-45.97	-13.00	-24.99	7.98	Peak	Vertical

CHANNEL BANDWIDTH: 15MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(15M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-52.62	-54.67	-13.00	-39.62	2.05	Peak	Horizontal
2	PP	5197.500	-37.56	-46.17	-13.00	-24.56	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(15M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3470.000	-52.28	-54.81	-13.00	-39.28	2.53	Peak	Vertical
2	PP	5197.500	-40.73	-48.71	-13.00	-27.73	7.98	Peak	Vertical

CHANNEL BANDWIDTH: 20MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band4(20M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3465.000	-47.42	-49.45	-13.00	-34.42	2.03	Peak	Horizontal
2	PP	5197.500	-34.26	-42.87	-13.00	-21.26	8.61	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band4(20M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		3465.000	-52.34	-54.87	-13.00	-39.34	2.53	Peak	Vertical
2	PP	5197.500	-38.16	-46.14	-13.00	-25.16	7.98	Peak	Vertical

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(1.4M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-58.58	-51.86	-13.00	-45.58	-6.72	Peak	Horizontal
2	PP	2122.500	-50.38	-48.45	-13.00	-37.38	-1.93	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(1.4M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-60.16	-54.72	-13.00	-47.16	-5.44	Peak	Vertical
2	PP	2122.500	-46.30	-46.06	-13.00	-33.30	-0.24	Peak	Vertical

CHANNEL BANDWIDTH: 3MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(3M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-59.94	-53.22	-13.00	-46.94	-6.72	Peak	Horizontal
2	PP	2122.500	-51.56	-49.63	-13.00	-38.56	-1.93	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(3M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1415.000	-59.50	-54.05	-13.00	-46.50	-5.45	Peak	Vertical
2	PP	2122.500	-45.86	-45.62	-13.00	-32.86	-0.24	Peak	Vertical

CHANNEL BANDWIDTH: 5MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(5M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-59.89	-53.17	-13.00	-46.89	-6.72	Peak	Horizontal
2	PP	2122.500	-51.65	-49.72	-13.00	-38.65	-1.93	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(5M)
Plan : Y-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-59.91	-54.47	-13.00	-46.91	-5.44	Peak	Vertical
2	PP	2122.500	-49.00	-48.76	-13.00	-36.00	-0.24	Peak	Vertical

CHANNEL BANDWIDTH: 10MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-60.82	-54.10	-13.00	-47.82	-6.72	Peak	Horizontal
2	PP	2122.500	-50.58	-48.65	-13.00	-37.58	-1.93	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 12(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-58.83	-53.39	-13.00	-45.83	-5.44	Peak	Vertical
2	PP	2122.500	-51.46	-51.22	-13.00	-38.46	-0.24	Peak	Vertical

LTE Band 13

CHANNEL BANDWIDTH: 5MHz / QPSK



Condition: FCC Part 27(B13) 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 13(5M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1546.000	-60.37	-54.55	-13.00	-47.37	-5.82	Peak	Horizontal
2	PP	2352.000	-55.40	-53.65	-13.00	-42.40	-1.75	Peak	Horizontal



Condition: FCC Part 27(B13) 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 13(5M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1546.000	-56.95	-52.45	-13.00	-43.95	-4.50	Peak	Vertical
2	PP	2352.000	-54.84	-54.64	-13.00	-41.84	-0.20	Peak	Vertical

CHANNEL BANDWIDTH: 10MHz / QPSK



Condition: FCC Part 27(B13) 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 13(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1546.000	-56.01	-50.19	-13.00	-43.01	-5.82	Peak	Horizontal
2	PP	2352.000	-47.03	-45.28	-13.00	-34.03	-1.75	Peak	Horizontal



Condition: FCC Part 27(B13) 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 13(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1546.000	-55.98	-51.48	-13.00	-42.98	-4.50	Peak	Vertical
2	PP	2352.000	-50.07	-49.87	-13.00	-37.07	-0.20	Peak	Vertical

LTE Band 17

CHANNEL BANDWIDTH: 5MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 17(5M)
Plan : Z-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-60.75	-54.03	-13.00	-47.75	-6.72	Peak	Horizontal
2	PP	2130.000	-43.85	-41.92	-13.00	-30.85	-1.93	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 17(5M)
Plan : Z-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-60.33	-54.89	-13.00	-47.33	-5.44	Peak	Vertical
2	PP	2130.000	-51.05	-50.81	-13.00	-38.05	-0.24	Peak	Vertical

CHANNEL BANDWIDTH: 10MHz / QPSK



Condition: FCC Part 27 3m Horizontal
EUT : Lenovo PB2-650Y
Mode : LTE Band 17(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1420.000	-60.04	-53.35	-13.00	-47.04	-6.69	Peak	Horizontal
2	PP	2118.000	-51.51	-49.57	-13.00	-38.51	-1.94	Peak	Horizontal



Condition: FCC Part 27 3m Vertical
EUT : Lenovo PB2-650Y
Mode : LTE Band 17(10M)
Plan : X-Plan
Remark : IMEI 869985020015014/022
Test By : Alex Chen

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1416.000	-59.56	-54.12	-13.00	-46.56	-5.44	Peak	Vertical
2	PP	2130.000	-51.25	-51.01	-13.00	-38.25	-0.24	Peak	Vertical

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab/Telecom Lab
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---