

FCC RF Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : lenovo
MODEL NAME : Lenovo TAB 2 A10-70F
FCC ID : O57TAB2A1070F
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Dec. 18, 2014 and testing was completed on Jan. 15, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency Channel	8
2.2 Pre-Scanned RF Power.....	9
2.3 Test Mode.....	10
2.4 Connection Diagram of Test System.....	11
2.5 Support Unit used in test configuration and system	12
2.6 EUT Operation Test Setup	12
2.7 Measurement Results Explanation Example.....	13
3 TEST RESULT.....	14
3.1 6dB and 99% Bandwidth Measurement	14
3.2 Output Power Measurement.....	17
3.3 Power Spectral Density Measurement	20
3.4 Conducted Band Edges and Spurious Emission Measurement	23
3.5 Radiated Band Edges and Spurious Emission Measurement	36
3.6 AC Conducted Emission Measurement.....	40
3.7 Antenna Requirements.....	44
4 LIST OF MEASURING EQUIPMENT	45
5 UNCERTAINTY OF EVALUATION	46
APPENDIX A. RADIATED TEST RESULTS	
APPENDIX B. SETUP PHOTOGRAPHS	

**REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4D1801-01C	Rev. 01	Initial issue of report	Jan. 29, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.09 dB at 2390.000 MHz
3.6	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 17.77 dB at 4.500 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.

No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ, Shanghai, China

1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	lenovo
Model Name	Lenovo TAB 2 A10-70F
FCC ID	O57TAB2A1070F
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n (HT20/HT40)/ WLAN 5GHz 802.11a/ Bluetooth v3.0 + EDR / Bluetooth v4.0 LE
HW Version	A1990_MB_PCB_V2.0
SW Version	A7-30HC_S000007_141017_ROW
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples is only for memory capacity, sample 1 is 32GB, sample 2 is 16GB.



1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	<2412 MHz ~ 2462 MHz> 802.11b : 15.38 dBm (0.0345 W) 802.11g : 21.91 dBm (0.1552 W) 802.11n HT20 : 22.22 dBm (0.1667 W) 802.11n HT40 : 22.15 dBm (0.1641 W)
99% Occupied Bandwidth	<2412 MHz ~ 2462 MHz> 802.11b : 14.55MHz 802.11g : 17.75MHz 802.11n HT20 : 18.45MHz 802.11n HT40 : 36.60MHz
Antenna Type / Gain	PIFA Antenna with gain 1.66 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH01-KS	03CH01-KS	CO01-KS	149928/4086E-1

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X/Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	15.03	CH 11	15.28	15.34	15.15
CH 06	2437 MHz	15.18				
CH 11	2462 MHz	15.38				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	21.42	CH 11	21.88	21.83	21.89	21.81	21.75	21.85	21.77
CH 06	2437 MHz	21.84								
CH 11	2462 MHz	21.91								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	21.74	CH 11	22.09	22.14	22.06	22.11	22.17	22.03	22.18
CH 06	2437 MHz	22.18								
CH 11	2462 MHz	22.22								

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	21.86	CH 09	20.58	20.71	20.42	20.34	20.77	21.12	20.97
CH 06	2437 MHz	21.84								
CH 09	2452 MHz	22.15								


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB and 99% BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN(2.4G) Link + USB Cable (Charging from Adapter) + Earphone			
Remark: For Radiated TCs, the tests were performed with adapter, earphone and USB cable.				

2.4 Connection Diagram of Test System


<WLAN 11b Tx Mode>



<WLAN 11n HT20/HT40 Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
2.	Bluetooth Earphone	Lenovo	LBH505	N/A	N/A	N/A
3.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2 m	N/A
4.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

Offset(dB) = RF cable loss(dB) = 5.5 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup



**3.1.5 Test Result of 6dB and 99% Occupied Bandwidth**

Test Band :	2.4GHz	Temperature :	24~25℃
Test Engineer :	Issac Song	Relative Humidity :	49~51%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	99% Bandwidth (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.55	10.08	0.5	Pass
11b	1Mbps	1	6	2437	14.45	10.08	0.5	Pass
11b	1Mbps	1	11	2462	14.45	10.08	0.5	Pass
11g	6Mbps	1	1	2412	17.75	16.36	0.5	Pass
11g	6Mbps	1	6	2437	17.65	16.32	0.5	Pass
11g	6Mbps	1	11	2462	17.70	16.32	0.5	Pass
HT20	MCS0	1	1	2412	18.45	17.56	0.5	Pass
HT20	MCS0	1	6	2437	18.40	17.56	0.5	Pass
HT20	MCS0	1	11	2462	18.40	17.60	0.5	Pass
HT40	MCS0	1	3	2422	36.60	35.92	0.5	Pass
HT40	MCS0	1	6	2437	36.50	35.68	0.5	Pass
HT40	MCS0	1	9	2452	36.40	36.00	0.5	Pass



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



**3.2.5 Test Result of Peak Output Power**

Test Mode :	2.4GHz	Temperature :	24~25℃
Test Engineer :	Issac Song	Relative Humidity :	49~51%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	15.03	30	1.66	Pass
11b	1Mbps	1	6	2437	15.18	30	1.66	Pass
11b	1Mbps	1	11	2462	15.38	30	1.66	Pass
11g	6Mbps	1	1	2412	21.42	30	1.66	Pass
11g	6Mbps	1	6	2437	21.84	30	1.66	Pass
11g	6Mbps	1	11	2462	21.91	30	1.66	Pass
HT20	MCS0	1	1	2412	21.74	30	1.66	Pass
HT20	MCS0	1	6	2437	22.18	30	1.66	Pass
HT20	MCS0	1	11	2462	22.22	30	1.66	Pass
HT40	MCS0	1	3	2422	21.86	30	1.66	Pass
HT40	MCS0	1	6	2437	21.84	30	1.66	Pass
HT40	MCS0	1	9	2452	22.15	30	1.66	Pass

Note: Measured power (dBm) has offset with cable loss.

3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	2.4GHz	Temperature :	24~25°C
Test Engineer :	Issac Song	Relative Humidity :	49~51%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.08	12.74	30	1.66	Pass
11b	1Mbps	1	6	2437	0.08	12.92	30	1.66	Pass
11b	1Mbps	1	11	2462	0.08	12.98	30	1.66	Pass
11g	6Mbps	1	1	2412	0.50	11.86	30	1.66	Pass
11g	6Mbps	1	6	2437	0.50	12.12	30	1.66	Pass
11g	6Mbps	1	11	2462	0.50	12.37	30	1.66	Pass
HT20	MCS0	1	1	2412	0.50	12.06	30	1.66	Pass
HT20	MCS0	1	6	2437	0.50	12.31	30	1.66	Pass
HT20	MCS0	1	11	2462	0.50	12.51	30	1.66	Pass
HT40	MCS0	1	3	2422	1.03	10.89	30	1.66	Pass
HT40	MCS0	1	6	2437	1.03	10.81	30	1.66	Pass
HT40	MCS0	1	9	2452	1.03	11.05	30	1.66	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup




**3.3.5 Test Result of Power Spectral Density**

Test Mode :	2.4GHz	Temperature :	24~25℃
Test Engineer :	Issac Song	Relative Humidity :	49~51%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-8.32	8	1.66	Pass
11b	1Mbps	1	6	2437	-9.84	8	1.66	Pass
11b	1Mbps	1	11	2462	-9.54	8	1.66	Pass
11g	6Mbps	1	1	2412	-14.49	8	1.66	Pass
11g	6Mbps	1	6	2437	-12.72	8	1.66	Pass
11g	6Mbps	1	11	2462	-12.03	8	1.66	Pass
HT20	MCS0	1	1	2412	-13.65	8	1.66	Pass
HT20	MCS0	1	6	2437	-12.59	8	1.66	Pass
HT20	MCS0	1	11	2462	-11.53	8	1.66	Pass
HT40	MCS0	1	3	2422	-15.09	8	1.66	Pass
HT40	MCS0	1	6	2437	-12.44	8	1.66	Pass
HT40	MCS0	1	9	2452	-11.13	8	1.66	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 5.JAN.2015 16:03:39

Low Channel Plot




Date: 5.JAN.2015 16:03:58

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:04:44

Spurious Emission 2GHz~25GHz




Date: 5.JAN.2015 16:05:02



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 5.JAN.2015 16:08:20

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:08:44

Spurious Emission 2GHz~25GHz




Date: 5.JAN.2015 16:09:02



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 5.JAN.2015 16:14:10

High Channel Plot




Date: 5.JAN.2015 16:14:28

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:14:54

Spurious Emission 2GHz~25GHz




Date: 5.JAN.2015 16:15:12

Test Mode :	802.11g	Temperature :	24~25℃
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 15.JAN.2015 10:05:05

Low Channel Plot




Date: 15.JAN.2015 10:05:26

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:09:17

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:09:35



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 15.JAN.2015 10:17:41

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:18:09

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:18:27



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 15.JAN.2015 10:22:21

High Channel Plot




Date: 15.JAN.2015 10:22:49

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:23:16

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:23:34



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 15.JAN.2015 10:28:19

Low Channel Plot




Date: 15.JAN.2015 10:28:49

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:29:22

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:29:40

Test Mode :	802.11n HT20	Temperature :	24~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 15.JAN.2015 10:32:36

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:34:51

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:35:09



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 15.JAN.2015 10:38:48

High Channel Plot




Date: 15.JAN.2015 10:39:27

Spurious Emission 30MHz~3GHz



Date: 15.JAN.2015 10:40:10

Spurious Emission 2GHz~25GHz




Date: 15.JAN.2015 10:40:28



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	03	Test Engineer :	Issac Song


WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level




Date: 5.JAN.2015 16:37:57

Low Channel Plot




Date: 5.JAN.2015 16:38:17

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:39:25

Spurious Emission 2GHz~25GHz




Date: 5.JAN.2015 16:39:43



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 5.JAN.2015 16:43:45

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:46:30

Spurious Emission 2GHz~25GHz




Date: 5.JAN.2015 16:46:48



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	09	Test Engineer :	Issac Song


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 5.JAN.2015 16:49:38

High Channel Plot




Date: 5.JAN.2015 16:49:58

Spurious Emission 30MHz~3GHz



Date: 5.JAN.2015 16:53:50

Spurious Emission 2GHz~25GHz



Date: 5.JAN.2015 16:51:49

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.13	-	-	10Hz
802.11g	89.17	1.40	0.71	1KHz
2.4GHz 802.11n HT20	89.04	1.32	0.76	1KHz
2.4GHz 802.11n HT40	78.85	0.66	1.52	3KHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eko Zhang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN(2.4G) Link + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

mode	: Mode 1							
	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	44.41	-21.55	65.96	32.10	1.94	10.37	QP
2	0.15	35.51	-20.45	55.96	23.20	1.94	10.37	Average
3	2.38	32.93	-23.07	56.00	22.10	0.11	10.72	QP
4	2.38	23.13	-22.87	46.00	12.30	0.11	10.72	Average
5	2.78	31.78	-24.22	56.00	20.89	0.13	10.76	QP
6	2.78	21.18	-24.82	46.00	10.29	0.13	10.76	Average
7	3.60	34.49	-21.51	56.00	23.50	0.17	10.82	QP
8	3.60	24.49	-21.51	46.00	13.50	0.17	10.82	Average
9	3.82	35.21	-20.79	56.00	24.20	0.18	10.83	QP
10 *	3.82	26.31	-19.69	46.00	15.30	0.18	10.83	Average
11	4.01	34.61	-21.39	56.00	23.60	0.18	10.83	QP
12	4.01	25.61	-20.49	46.00	14.50	0.18	10.83	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eko Zhang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN(2.4G) Link + USB Cable (Charging from Adapter) + Earphone		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	39.74	-26.13	65.87	27.49	1.87	10.38	QP
2	0.15	32.14	-23.73	55.87	19.89	1.87	10.38	Average
3	3.74	31.10	-24.90	56.00	20.10	0.18	10.82	QP
4	3.74	23.60	-22.40	46.00	12.60	0.18	10.82	Average
5	3.99	33.11	-22.89	56.00	22.10	0.18	10.83	QP
6	3.99	25.21	-20.79	46.00	14.20	0.18	10.83	Average
7	4.29	33.83	-22.17	56.00	22.80	0.19	10.84	QP
8	4.29	27.53	-18.47	46.00	16.50	0.19	10.84	Average
9	4.50	33.83	-22.17	56.00	22.80	0.19	10.84	QP
10 *	4.50	28.23	-17.77	46.00	17.20	0.19	10.84	Average
11	4.82	32.64	-23.46	56.00	21.49	0.20	10.85	QP
12	4.82	26.94	-19.06	46.00	15.89	0.20	10.85	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Dec. 31, 2014 ~Jan. 15, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Feb. 27, 2014	Dec. 31, 2014 ~Jan. 15, 2015	Feb. 26, 2015	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Feb. 27, 2014	Dec. 31, 2014 ~Jan. 15, 2015	Feb. 26, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 25, 2014	Jan. 13, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Jan. 13, 2015	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Jan. 13, 2015	Nov. 12, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30Mhz-2Ghz	Sep. 13, 2014	Jan. 13, 2015	Sep. 12, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Jan. 13, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Jan. 13, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Jan. 13, 2015	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Jan. 13, 2015	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Oct. 28, 2014	Jan. 13, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 13, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 13, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 13, 2015	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Dec. 25, 2014	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Dec. 25, 2014	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Dec. 25, 2014	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Dec. 25, 2014	Oct. 24, 2015	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5 dB
---	--------



Appendix A. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preampl	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz	*	2412	103.83	-	-	99.39	32.89	4.82	33.27	100	175	P	H
	*	2412	97.74	-	-	93.3	32.89	4.82	33.27	100	175	A	H
		2355.54	50.18	-23.82	74	45.84	32.81	4.78	33.25	100	175	P	H
		2375.52	38.06	-15.94	54	33.7	32.83	4.79	33.26	100	175	A	H
	*	2412	99.65	-	-	95.21	32.89	4.82	33.27	188	226	P	V
	*	2412	93.51	-	-	89.07	32.89	4.82	33.27	188	226	A	V
		2376.06	47.97	-26.03	74	43.61	32.83	4.79	33.26	188	226	P	V
		2375.43	35.92	-18.08	54	31.56	32.83	4.79	33.26	188	226	A	V
802.11b CH 06 2437MHz	*	2437	104.27	-	-	99.75	32.95	4.85	33.28	142	175	P	H
	*	2437	100.64	-	-	96.12	32.95	4.85	33.28	142	175	A	H
	*	2437	99.76	-	-	95.24	32.95	4.85	33.28	191	263	P	V
	*	2437	94.66	-	-	90.14	32.95	4.85	33.28	191	263	A	V
802.11b CH 11 2462MHz	*	2462	104.41	-	-	99.85	32.98	4.87	33.29	127	144	P	H
	*	2462	97.91	-	-	93.35	32.98	4.87	33.29	127	144	A	H
		2495.65	52.36	-21.64	74	47.71	33.05	4.9	33.3	127	144	P	H
		2490.43	37.74	-16.26	54	33.09	33.05	4.9	33.3	127	144	A	H
	*	2462	96.07	-	-	91.51	32.98	4.87	33.29	197	272	P	V
	*	2462	89.64	-	-	85.08	32.98	4.87	33.29	197	272	A	V
		2489.5	48.25	-25.75	74	43.6	33.05	4.9	33.3	197	252	P	V
		2490.64	34.41	-19.59	54	29.76	33.05	4.9	33.3	197	252	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	55.91	-18.09	74	47.97	35.17	6.57	33.8	100	313	P	H
	!	4824	49.04	-4.96	54	41.1	35.17	6.57	33.8	100	313	A	H
		4824	53.5	-20.5	74	45.56	35.17	6.57	33.8	100	172	P	V
		4824	44.64	-9.36	54	36.7	35.17	6.57	33.8	100	172	A	V
802.11b CH 06 2437MHz		4874	55.29	-18.71	74	47.29	35.18	6.62	33.8	100	313	P	H
	!	4874	49.02	-4.98	54	41.02	35.18	6.62	33.8	100	313	A	H
		7312	50.88	-23.12	74	40.64	36.2	8.17	34.13	100	314	P	H
		4874	53.5	-20.5	74	45.5	35.18	6.62	33.8	100	237	P	V
		4874	43.1	-10.9	54	35.1	35.18	6.62	33.8	100	237	A	V
		7312	50.45	-23.55	74	40.21	36.2	8.17	34.13	100	214	P	V
802.11b CH 11 2462MHz		4924	55.45	-18.55	74	47.44	35.19	6.62	33.8	100	304	P	H
		4924	47.76	-6.24	54	39.75	35.19	6.62	33.8	100	304	A	H
		7386	48.6	-25.4	74	38.24	36.24	8.28	34.16	200	124	P	H
		4924	53.61	-20.39	74	45.6	35.19	6.62	33.8	100	170	P	V
		4924	45.27	-8.73	54	37.26	35.19	6.62	33.8	100	170	A	V
		7386	50.81	-23.19	74	40.45	36.24	8.28	34.16	100	215	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz	*	2412	111.21	-	-	106.77	32.89	4.82	33.27	177	56	P	H
	*	2412	99.9	-	-	95.46	32.89	4.82	33.27	177	56	A	H
	!	2389.65	69.57	-4.43	74	65.16	32.86	4.81	33.26	177	56	P	H
	!	2390.0	50.91	-3.09	54	46.5	32.86	4.81	33.26	177	56	A	H
	*	2412	108.98	-	-	104.54	32.89	4.82	33.27	100	350	P	V
	*	2412	98.19	-	-	93.75	32.89	4.82	33.27	100	350	A	V
		2389.65	66.87	-7.13	74	62.46	32.86	4.81	33.26	100	350	P	V
	!	2390	48.65	-5.35	54	44.24	32.86	4.81	33.26	100	350	A	V
802.11g CH 06 2437MHz	*	2437	108.06	-	-	103.54	32.95	4.85	33.28	170	58	P	H
	*	2437	97.27	-	-	92.75	32.95	4.85	33.28	170	58	A	H
	*	2437	107.37	-	-	102.85	32.95	4.85	33.28	110	65	P	V
	*	2437	97.27	-	-	92.75	32.95	4.85	33.28	110	65	A	V
802.11g CH 11 2462MHz	*	2462	108.99	-	-	104.43	32.98	4.87	33.29	198	55	P	H
	*	2462	98.07	-	-	93.51	32.98	4.87	33.29	198	55	A	H
	!	2483.62	68.5	-5.5	74	63.9	33.01	4.88	33.29	198	55	P	H
	!	2483.5	48.2	-5.8	54	43.6	33.01	4.88	33.29	198	55	A	H
	*	2462	107.32	-	-	102.76	32.98	4.87	33.29	100	360	P	V
	*	2462	96.2	-	-	91.64	32.98	4.87	33.29	100	360	A	V
		2483.71	64.65	-9.35	74	60.05	33.01	4.88	33.29	100	360	P	V
		2483.5	43.79	-10.21	54	39.19	33.01	4.88	33.29	100	360	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	50.28	-23.72	74	42.34	35.17	6.57	33.8	166	345	P	H
		4824	49.07	-24.93	74	41.13	35.17	6.57	33.8	112	330	P	V
802.11g CH 06 2437MHz		4874	51.1	-22.9	74	43.1	35.18	6.62	33.8	156	310	P	H
		4874	43.2	-10.8	54	35.2	35.18	6.62	33.8	156	310	A	H
		7311	49.86	-24.14	74	39.62	36.2	8.17	34.13	133	269	P	H
		4874	47.81	-26.19	74	39.81	35.18	6.62	33.8	170	290	P	V
		7311	49.29	-24.71	74	39.05	36.2	8.17	34.13	140	290	P	V
802.11g CH 11 2462MHz		4924	50.61	-23.39	74	42.6	35.19	6.62	33.8	100	280	P	H
		7386	50.2	-23.8	74	39.84	36.24	8.28	34.16	120	350	P	H
		4924	49.06	-24.94	74	41.05	35.19	6.62	33.8	145	298	P	V
		7386	49.95	-24.05	74	39.59	36.24	8.28	34.16	164	220	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz	*	2412	108.33	-	-	103.89	32.89	4.82	33.27	125	65	P	H
	*	2412	97.3	-	-	92.86	32.89	4.82	33.27	125	65	A	H
	!	2389.47	70.56	-3.44	74	66.15	32.86	4.81	33.26	125	65	P	H
	!	2390	48.9	-5.1	54	44.49	32.86	4.81	33.26	125	65	A	H
	*	2412	107.04	-	-	102.6	32.89	4.82	33.27	123	339	P	V
	*	2412	96.45	-	-	92.01	32.89	4.82	33.27	123	339	A	V
	!	2389.47	69.71	-4.29	74	65.3	32.86	4.81	33.26	123	339	P	V
	!	2390	49.77	-4.23	54	45.36	32.86	4.81	33.26	123	339	A	V
802.11n HT20 CH 06 2437MHz	*	2437	106.86	-	-	102.34	32.95	4.85	33.28	172	50	P	H
	*	2437	96.83	-	-	92.31	32.95	4.85	33.28	172	50	A	H
	*	2437	108.19	-	-	103.67	32.95	4.85	33.28	118	0	P	V
	*	2437	97.74	-	-	93.22	32.95	4.85	33.28	118	0	A	V
802.11n HT20 CH 11 2462MHz	*	2462	107.42	-	-	102.86	32.98	4.87	33.29	200	47	P	H
	*	2462	96.12	-	-	91.56	32.98	4.87	33.29	200	47	A	H
		2483.59	67.62	-6.38	74	63.02	33.01	4.88	33.29	200	47	P	H
		2483.53	46.95	-7.05	54	42.35	33.01	4.88	33.29	200	47	A	H
	*	2462	107.02	-	-	102.46	32.98	4.87	33.29	118	344	P	V
	*	2462	95.98	-	-	91.42	32.98	4.87	33.29	118	344	A	V
		2483.95	66.91	-7.09	74	62.31	33.01	4.88	33.29	118	342	P	V
		2483.59	47.62	-6.38	54	43.02	33.01	4.88	33.29	118	344	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	48.86	-25.14	74	40.92	35.17	6.57	33.8	115	270	P	H
		4824	47.81	-26.19	74	39.87	35.17	6.57	33.8	170	270	P	V
802.11n HT20 CH 06 2437MHz		4874	49.68	-24.32	74	41.68	35.18	6.62	33.8	100	120	P	H
		7311	50.72	-23.28	74	40.48	36.2	8.17	34.13	150	69	P	H
		4874	48.45	-25.55	74	40.45	35.18	6.62	33.8	115	350	P	V
		7311	49.46	-24.54	74	39.22	36.2	8.17	34.13	145	340	P	V
802.11n HT20 CH 11 2462MHz		4924	49.33	-24.67	74	41.32	35.19	6.62	33.8	124	260	P	H
		7386	50.47	-23.53	74	40.11	36.24	8.28	34.16	150	290	P	H
		4924	47.47	-26.53	74	39.46	35.19	6.62	33.8	110	245	P	V
		7386	50.02	-23.98	74	39.66	36.24	8.28	34.16	154	198	P	V
Remark	1. Average measurement was not performed if peak level went lower than the average limit. 2. All results are PASS against limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz	*	2422	102.09	-	-	97.61	32.92	4.84	33.28	118	53	P	H
	*	2422	91.26	-	-	86.78	32.92	4.84	33.28	118	53	A	H
	!	2389.38	68.56	-5.44	74	64.15	32.86	4.81	33.26	118	53	P	H
	!	2390	49.29	-4.71	54	44.88	32.86	4.81	33.26	118	53	A	H
		2485.9	51.93	-22.07	74	47.33	33.01	4.88	33.29	118	53	P	H
		2483.5	39.92	-14.08	54	35.32	33.01	4.88	33.29	118	53	A	H
	*	2422	102.16	-	-	97.68	32.92	4.84	33.28	128	340	P	V
	*	2422	91.05	-	-	86.57	32.92	4.84	33.28	128	340	A	V
	!	2389.74	70.44	-3.56	74	66.03	32.86	4.81	33.26	128	340	P	V
	!	2389.92	50.39	-3.61	54	45.98	32.86	4.81	33.26	128	340	A	V
		2483.95	52.71	-21.29	74	48.11	33.01	4.88	33.29	128	340	P	V
		2483.53	40.88	-13.12	54	36.28	33.01	4.88	33.29	128	340	A	V
802.11n HT40 CH 06 2437MHz	*	2437	101.35	-	-	96.83	32.95	4.85	33.28	173	135	P	H
	*	2437	89.76	-	-	85.24	32.95	4.85	33.28	173	135	A	H
		2387.04	52.19	-21.81	74	47.78	32.86	4.81	33.26	173	135	P	H
		2390	39.14	-14.86	54	34.73	32.86	4.81	33.26	173	135	A	H
		2483.89	55	-19	74	50.4	33.01	4.88	33.29	173	135	P	H
		2483.68	40.45	-13.55	54	35.85	33.01	4.88	33.29	173	135	A	H
	*	2437	101.19	-	-	96.67	32.95	4.85	33.28	168	317	P	V
	*	2437	90.77	-	-	86.25	32.95	4.85	33.28	168	317	A	V
		2389.74	55.19	-18.81	74	50.78	32.86	4.81	33.26	168	317	P	V
		2389.83	41.36	-12.64	54	36.95	32.86	4.81	33.26	168	317	A	V
		2483.86	54.24	-19.76	74	49.64	33.01	4.88	33.29	168	317	P	V
		2483.5	39.82	-14.18	54	35.22	33.01	4.88	33.29	168	317	A	V



802.11n HT40 CH 09 2452MHz	*	2452	100.08	-	-	95.56	32.95	4.85	33.28	200	130	P	H
	*	2452	89.37	-	-	84.85	32.95	4.85	33.28	200	130	A	H
		2485.66	64.79	-9.21	74	60.19	33.01	4.88	33.29	200	130	P	H
		2484.01	43.92	-10.08	54	39.32	33.01	4.88	33.29	200	130	A	H
		2388.21	49	-25	74	44.59	32.86	4.81	33.26	200	130	P	H
		2389.47	37.49	-16.51	54	33.08	32.86	4.81	33.26	200	130	A	H
	*	2452	101.51	-	-	96.99	32.95	4.85	33.28	155	320	P	V
	*	2452	90.39	-	-	85.87	32.95	4.85	33.28	155	320	A	V
		2483.5	65.03	-8.97	74	60.43	33.01	4.88	33.29	155	320	P	V
		2483.74	44.2	-9.8	54	39.6	33.01	4.88	33.29	155	320	A	V
		2383.08	50.57	-23.43	74	46.21	32.83	4.79	33.26	155	320	P	V
		2382.54	38.83	-15.17	54	34.47	32.83	4.79	33.26	155	320	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		4844	47.56	-26.44	74	39.57	35.18	6.61	33.8	110	260	P	H
		7266	49.77	-24.23	74	39.52	36.19	8.17	34.11	100	230	P	H
		4844	47.13	-26.87	74	39.14	35.18	6.61	33.8	170	290	P	V
		7266	49.9	-24.1	74	39.65	36.19	8.17	34.11	122	156	P	V
802.11n HT40 CH 06 2437MHz		4874	48.07	-25.93	74	40.07	35.18	6.62	33.8	130	160	P	H
		7312	49.48	-24.52	74	39.24	36.2	8.17	34.13	131	210	P	H
		4874	47.34	-26.66	74	39.34	35.18	6.62	33.8	100	140	P	V
		7312	49.87	-24.13	74	39.63	36.2	8.17	34.13	155	190	P	V
802.11n HT40 CH 09 2452MHz		4904	48.97	-25.03	74	40.96	35.19	6.62	33.8	110	210	P	H
		7356	49.54	-24.46	74	39.23	36.22	8.24	34.15	150	320	P	H
		4904	48.38	-25.62	74	40.37	35.19	6.62	33.8	100	330	P	V
		7356	50.02	-23.98	74	39.71	36.22	8.24	34.15	140	260	P	V
Remark	1. Average measurement was not performed if peak level went lower than the average limit. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	24.77	-15.23	40	39.86	18	0.48	33.57	102	47	P	H
		100.81	21.72	-21.78	43.5	43.78	10.62	0.93	33.61			P	H
		192.96	30.87	-12.63	43.5	54.52	8.64	1.27	33.56			P	H
		256.98	23.68	-22.32	46	43.53	12.1	1.48	33.43			P	H
		343.31	21.17	-24.83	46	38.48	14.35	1.7	33.36			P	H
		478.14	19.93	-26.07	46	34.26	16.83	2	33.16			P	H
		47.46	29.99	-10.01	40	54.45	8.5	0.64	33.6	102	145	P	V
		71.71	25.1	-14.9	40	52.44	5.46	0.79	33.59			P	V
		194.9	27.41	-16.09	43.5	50.94	8.75	1.28	33.56			P	V
		256.01	25.16	-20.84	46	45.03	12.09	1.47	33.43			P	V
		345.25	22.9	-23.1	46	40.16	14.4	1.7	33.36			P	V
		444.19	22.98	-23.02	46	37.96	16.27	1.96	33.21			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.