



FCC Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : TB300FU
FCC ID : O57TB300FU
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Aug. 14, 2022 ~ Aug. 25, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	6
1.6. Test Location	7
1.7. Test Software	7
1.8. Applicable Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System	10
2.3. Support Unit used in test configuration and system	10
2.4. EUT Operation Test Setup	11
3. TEST RESULT	12
3.1. Test of AC Conducted Emission Measurement	12
3.2. Test of Radiated Emission Measurement	16
4. LIST OF MEASURING EQUIPMENT	21
5. UNCERTAINTY OF EVALUATION	22
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC272505	Rev. 01	Initial issue of report	Sep. 02, 2022

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.72 dB at 0.162 MHz for Quasi-Peak
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 5.12 dB at 239.520 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. General Description

1.1. Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.

Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2. Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	TB300FU
FCC ID	O57TB300FU
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE GNSS,FM
HW Version	Lenovo Tablet TB300FU
SW Version	TB300FU_RF01_220812
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are six types of EUT. The sample 1 is 2+32GB capacity + Battery 1, the sample 2 is 3+32GB capacity + Battery 1, the sample 3 is 4+64GB capacity + Battery 1, the sample 4 is 2+32GB capacity + Battery 2, the sample 5 is 3+32GB capacity + Battery 2 and the sample 6 is 4+64GB capacity + Battery 2. According to the difference, we choose sample 3 to full test and the sample 1/2/4/5/6 are verified the difference.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Rx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz
Antenna Type	WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna FM : External Earphone Antenna
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable1 (Charging from Adapter1) + Earphone + Battery 1 For Sample 3
	Mode 2: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable2 (Charging from Adapter2) + Earphone + Battery 1 For Sample 3
	Mode 3: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 3
	Mode 4: Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 1 For Sample 3
	Mode 5: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + EUT (SD) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 3
	Mode 6: Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (SD) + Earphone + Battery 1 For Sample 3
	Mode 7: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 3
	Mode 8: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable2 (Charging from Adapter2) + Earphone + Battery 2 For Sample 5
	Mode 9: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 2 For Sample 5
	Mode 10 : Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 1
	Mode 11 : Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 2 For Sample 4
	Mode 12 : Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 2
	Mode 13 : Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 2 For Sample 6

Radiated Emissions	Mode 1: Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable1 (Charging from Adapter1) + Earphone + Battery 1 For Sample 3 Mode 2: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable2 (Charging from Adapter2) + Earphone + Battery 1 For Sample 3 Mode 3: Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 3 Mode 4: Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 1 For Sample 3 Mode 5: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + EUT (SD) USB Data Link to PC/NB + Earphone + Battery 1 For Sample 3 Mode 6: Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (SD) + Earphone + Battery 1 For Sample 3 Mode 7: Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 2(Data Link with Notebook) + PC/NB USB Data Link to EUT (SD) + Earphone + Battery 1 + SIM 2 For Sample 3 Mode 8: Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable2 (Charging from Adapter2) + Earphone + Battery 2 For Sample 5 Mode 9: Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 2 For Sample 5 Mode 10 : Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 1 For Sample 1 Mode 11 : Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 2 For Sample 4 Mode 12 : Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 1 For Sample 2 Mode 13 : Bluetooth Idle + WLAN (5G) Idle + FM Rx(98MHz) + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + Earphone + Battery 2 For Sample 6
Remark: 1. The worst case of AC is mode 2; only the test data of this mode is reported. 2. The worst case of RE is mode 12; only the test data of this mode is reported. 3. Data Link with NB/PC means data application transferred mode between EUT and Notebook.	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Signal Generator	R&S	SMBV100A	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
4.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
5.	Notebook	Lenovo	V130-14IKB001	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
6.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
7.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
8.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
9.	SD Card	Kingston	8GB	N/A	N/A	N/A
10.	SD Card	SanDisk	Ultra	N/A	N/A	N/A

2.4. EUT Operation Test Setup

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on FM function to make the EUT receive continuous signals from FM station.
5. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : FCC CLASS-B LISN-060105-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.156	55.69	-10.00	65.69	45.20	0.02	10.47	QP
2	0.156	39.99	-15.70	55.69	29.50	0.02	10.47	Average
3	0.174	46.25	-18.52	64.77	35.80	0.03	10.42	QP
4	0.174	27.95	-26.82	54.77	17.50	0.03	10.42	Average
5	0.213	46.20	-16.90	63.10	35.80	0.04	10.36	QP
6	0.213	29.20	-23.90	53.10	18.80	0.04	10.36	Average
7	0.323	39.87	-19.75	59.62	29.50	0.07	10.30	QP
8	0.323	28.97	-20.65	49.62	18.60	0.07	10.30	Average
9	0.637	40.84	-15.16	56.00	30.49	0.11	10.24	QP
10	0.637	27.14	-18.86	46.00	16.79	0.11	10.24	Average
11	14.907	37.29	-22.71	60.00	26.60	0.30	10.39	QP
12	14.907	22.89	-27.11	50.00	12.20	0.30	10.39	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC CLASS-B LISN-060105-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.162	60.66	-4.72	65.38	50.10	0.11	10.45	QP
2	0.162	45.36	-10.02	55.38	34.80	0.11	10.45	Average
3	0.171	58.33	-6.57	64.90	47.79	0.11	10.43	QP
4	0.171	38.73	-16.17	54.90	28.19	0.11	10.43	Average
5	0.209	54.06	-9.17	63.23	43.60	0.10	10.36	QP
6	0.209	31.66	-21.57	53.23	21.20	0.10	10.36	Average
7	0.221	52.65	-10.14	62.79	42.20	0.10	10.35	QP
8	0.221	38.65	-14.14	52.79	28.20	0.10	10.35	Average
9	0.267	49.22	-11.98	61.20	38.80	0.10	10.32	QP
10	0.267	31.02	-20.18	51.20	20.60	0.10	10.32	Average
11	0.377	45.18	-13.16	58.34	34.80	0.10	10.28	QP
12	0.377	30.58	-17.76	48.34	20.20	0.10	10.28	Average
13	0.527	42.15	-13.85	56.00	31.80	0.11	10.24	QP
14	0.527	27.65	-18.45	46.00	17.20	0.11	10.24	Average
15	0.641	44.85	-11.15	56.00	34.50	0.11	10.24	QP
16	0.641	25.05	-20.95	46.00	14.70	0.11	10.24	Average
17	0.694	43.85	-12.15	56.00	33.50	0.11	10.24	QP
18	0.694	30.45	-15.55	46.00	20.10	0.11	10.24	Average
19	15.635	45.95	-14.05	60.00	35.20	0.34	10.41	QP
20	15.635	30.05	-19.95	50.00	19.30	0.34	10.41	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Test Engineer :	Feng	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#2 is FM Rx signal which can be ignored.		




Site : 03CH02-KS
Condition : FCC CLASS-B 3m CBL 6111D 59913 HORIZONTAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	cm	deg
			dB	dBuV/m	dBuV	dB/m	dB	dB		
1	62.01	32.77	-7.23	40.00	52.47	11.60	1.10	32.40	---	Peak
2	97.90	35.99			51.46	15.50	1.43	32.40	---	Peak
3	184.23	25.99	-17.51	43.50	41.80	14.60	1.99	32.40	---	Peak
4	239.52	31.19	-14.81	46.00	44.30	17.20	2.09	32.40	---	Peak
5	281.23	26.78	-19.22	46.00	38.06	18.74	2.38	32.40	---	Peak
6	480.08	27.81	-18.19	46.00	33.67	23.40	3.14	32.40	---	Peak
7	758.47	29.79	-16.21	46.00	29.79	28.17	4.10	32.27	---	Peak
8	3907.00	44.24	-29.76	74.00	34.76	33.41	9.33	33.26	---	Peak
9	6916.00	46.88	-27.12	74.00	31.27	35.97	12.56	32.92	---	Peak
10	9194.00	46.99	-27.01	74.00	30.39	36.45	14.33	34.18	---	Peak
11	11438.00	48.98	-25.02	74.00	29.99	38.16	16.12	35.29	---	Peak
12	13801.00	48.47	-25.53	74.00	26.99	38.84	17.85	35.21	---	Peak
13	17099.00	49.70	-24.30	74.00	22.54	42.42	19.77	35.03	---	Peak



Test Engineer :	Feng	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#2 is FM Rx signal which can be ignored.		



Site : 03CH02-KS
Condition : FCC CLASS-B 3m CBL 6111D 59913 VERTICAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	62.98	29.80	-10.20	40.00	49.38	11.70	1.12	32.40	---	---	Peak
2	97.90	36.03			51.50	15.50	1.43	32.40	---	---	Peak
3	239.52	40.88	-5.12	46.00	53.99	17.20	2.09	32.40	100	0	Peak
4	398.60	27.67	-18.33	46.00	35.32	21.76	2.99	32.40	---	---	Peak
5	480.08	30.53	-15.47	46.00	36.39	23.40	3.14	32.40	---	---	Peak
6	561.56	30.40	-15.60	46.00	33.47	26.03	3.30	32.40	---	---	Peak
7	719.67	32.94	-13.06	46.00	34.30	27.00	4.00	32.36	---	---	Peak
8	5029.00	44.61	-29.39	74.00	30.76	35.49	10.57	32.21	---	---	Peak
9	7800.00	47.24	-26.76	74.00	32.52	35.70	13.24	34.22	---	---	Peak
10	10707.00	46.97	-27.03	74.00	27.65	38.72	15.74	35.14	---	---	Peak
11	12951.00	47.67	-26.33	74.00	26.45	39.61	17.20	35.59	---	---	Peak
12	14889.00	49.31	-24.69	74.00	24.80	41.19	18.44	35.12	---	---	Peak
13	17558.00	49.63	-24.37	74.00	23.46	41.31	20.09	35.23	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 16, 2021	Aug. 14, 2022~Aug. 25, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 16, 2021	Aug. 14, 2022~Aug. 25, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 22, 2021	Aug. 14, 2022~Aug. 25, 2022	Dec. 21, 2022	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 30, 2021	Aug. 14, 2022~Aug. 25, 2022	Oct. 29, 2022	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2022	Aug. 14, 2022~Aug. 25, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2022	Aug. 14, 2022~Aug. 25, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan 5, 2022	Aug. 14, 2022~Aug. 25, 2022	Jan 4, 2023	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 16, 2021	Aug. 14, 2022~Aug. 25, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 14, 2022~Aug. 25, 2022	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 14, 2022~Aug. 25, 2022	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 14, 2022~Aug. 25, 2022	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May. 24, 2022	Aug. 15, 2022~Aug. 25, 2022	May. 23, 2023	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 14, 2021	Aug. 15, 2022~Aug. 25, 2022	Oct. 13, 2022	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May. 24, 2022	Aug. 15, 2022~Aug. 25, 2022	May. 23, 2023	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 14, 2021	Aug. 15, 2022~Aug. 25, 2022	Oct. 13, 2022	Conduction (CO01-KS)

NCR: No Calibration Required

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------