


Spot Check Evaluation

APPLICANT : Lenovo(Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : TB353ZU
FCC ID : O57TB353ZU
STANDARD : 47 CFR Part 22(H), 24(E), 27(L), 27(M), 27(H), 27(F),
27(N), 27(O), 27(Q), 90(S)
47 CFR Part 15 Subpart C §15.225
47 CFR Part 15 Subpart C §15.247
47 CFR Part 15 Subpart E §15.407
TEST DATE(S) : Mar. 26, 2026 ~ Apr. 03, 2026

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
1 GENERAL DESCRIPTION.....	4
1.1 Applicant.....	4
1.2 Manufacturer.....	4
1.3 Product Feature of Equipment Under Test.....	4
1.4 Modification of EUT	4
1.5 Testing Site.....	5
1.6 Test Software.....	5
1.7 Applicable Standards.....	5
2 RE-USE OF MEASURED DATA.....	6
2.1 Introduction Section.....	6
2.2 Model Difference Information	6
2.3 Reference detail Section:	7
2.4 Spot Check Verification Data Section.....	8
3 LIST OF MEASURING EQUIPMENT.....	11
4 MEASUREMENT UNCERTAINTY	13
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
610729A	Rev. 01	Initial issue of report	Apr. 13, 2026
610729A	Rev. 02	Removed Co-location test data This report is an updated version , replacing the report issued on Apr. 13, 2026.	May 15, 2026

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.

Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2 Manufacturer

Lenovo Ireland International Limited

Viscount House, 6/7 Fitzwilliam Square East, Dublin, D02 Y447, Ireland

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	TB353ZU
FCC ID	O57TB353ZU
IMEI/SN Code	Conducted: HA2E1PHK for WLAN 865704080022776/865704080022784 for WWAN Radiation: HA2DJJZT for WLAN 865704080017792 for WWAN
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-KS 03CH04-KS 03CH05-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH02-KS	AUDIX	E3	6.2009-8-24al
3.	03CH04-KS	AUDIX	E3	210616
4.	03CH05-KS	AUDIX	E3	210616

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 484596 D01 Referencing Test Data v03
- ♦ 47 CFR Part 22(H), 24(E), 27(L), 27(M), 27(H), 27(F), 27(N), 27(O), 27(Q), 90(S)
- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ 47 CFR Part 15 Subpart E §15.407
- ♦ ANSI C63.10-2020+Cor.1-2023
- ♦ ANSI C63.26-2015



2 Re-use of Measured Data

2.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: TB353ZU, FCC ID: O57TB353ZU) is electrically identical to the reference device (Model: TB353ZA, FCC ID: O57TB353ZA) for the portions of the circuitry corresponding to the data being re-used, following the FCC KDB 484596 D01 Referencing Test Data v03.

ECR Data Referencing Inquiry has been approved by TCB, and the data referencing and spot check test plan includes RF/EMC, the details are presented in section 2.3 of this report, and for SAR Reference detail, please refer to FCC SAR report FA610729.

The criteria set in section 3 of KDB 484596 D01 v03 is followed to determine whether the data referencing is justified. For SAR, the higher between the referenced value and the spot check value is used to determine compliance in both standalone and simultaneous transmission conditions

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID: O57TB353ZU .

2.2 Model Difference Information

The **main** difference between FCC ID: O57TB353ZA and FCC ID: O57TB353ZU is as below:

- Remove LTE B14/29/30/48/71 and 5G NR n12/n14/n25/n30/n48.
- Add LTE B1/3/7/8/18/19/20/28/38/40 and 5G NR n1/n3/n7/n8/n20/n26/n28/n38/n40/n78.
- 5G NR n41 disables PC2 via software and only supports PC3.

Other differences and all the details of similarity and difference can be found in the confidential documents (O57TB353ZU Operational Description of Product Equality Declaration).



2.3 Reference detail Section:

Rule Part	Equipment Class	Frequency Band (MHz)	Reference FCC ID (Parent)	Reference on test	Reference Title	FCC ID Filling (Variant)	Test on the variant	Data Referencing (Y/N)
15C	DSS (BR/EDR)	2400~2483.5	O57TB353ZA	Full test	FR610727A	O57TB353ZU	Spot check	Y, All test items
	DTS (BLE)	2400~2483.5	O57TB353ZA	Full test	FR610727B	O57TB353ZU	Spot check	Y, All test items
	DTS (WLAN)	2400~2483.5	O57TB353ZA	Full test	FR610727C	O57TB353ZU	Spot check	Y, All test items
	DXX (NFC)	13.56	O57TB353ZA	Full test	FR610727D	O57TB353ZU	Spot check	Y, All test items
15E	U-NII	5180~5240	O57TB353ZA	Full test	FR610727E	O57TB353ZU	Spot check	Y, All test items
		5260~5320	O57TB353ZA	Full test	FR610727E	O57TB353ZU	Spot check	Y, All test items
		5500~5720	O57TB353ZA	Full test	FR610727E	O57TB353ZU	Spot check	Y, All test items
		5745~5825	O57TB353ZA	Full test	FR610727E	O57TB353ZU	Spot check	Y, All test items
		5260~5320 5500~5720	O57TB353ZA	Full test	FZ610727	O57TB353ZU	Spot check	Y, All test items
	6XD	5925~7125	O57TB353ZA	Full test	FR610727F	O57TB353ZU	Spot check	Y, All test items
22, 24, 27, 90	PCB (LTE)	B2/4/5/12/13/25/26/41/ 66 ULCA 2C/5B/41C	O57TB353ZA	Full test	FG610727A FG610727B FG610727D	O57TB353ZU	Spot check	Y, All test items
	PCB (NR)	n2/5/41/66/71/77	O57TB353ZA	Full test	FG610727I FG610727J FG610727N FG610727O	O57TB353ZU	Spot check	Y, All test items

Y: Pointer to spot-check exhibit; N: Pointer to full test exhibit

2.4 Spot Check Verification Data Section

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

All test procedures follow the related section of parent report.

Spot-check measurements, while being always compliant with the applicable rule part(s) for the test under consideration, show a deviation d_{dB} from the reference data no larger than 3 dB:

$$d_{dB} = |V_{dB} - R_{dB}| \leq 3 \text{ dB} \quad (1)$$

V_{dB} , the variant spot-check level

R_{dB} , the corresponding measurement level for the reference model

An alternative to the limit of eq. (1) is available, and is based on considering how far the reference data R_{dB} is from the compliance threshold C_{dB} (also expressed in dB), for the particular test under consideration. In this case, if $M_{dB} = |C_{dB} - R_{dB}|$ is the margin in dB from the compliance limit, a spot check may be considered acceptable when the deviation d_{dB} from the reference data satisfies the following condition:

$$d_{dB} = |V_{dB} - R_{dB}| \leq (3 + M_{dB} / 20) \text{ dB} , \text{ for } 0 \leq M_{dB} \leq 60 \text{ dB} \quad (2)$$

$$d_{dB} = |V_{dB} - R_{dB}| = 6 \text{ dB} , \text{ for } M_{dB} > 60 \text{ dB}$$

where “| |” is the absolute value of the measured quantity.

When using the option in eq. (2), d_{dB} increases linearly from 3 dB to 6 dB.

Summary for spot check for each rule entry and technology is listed as below:



Summary for spot check for each rule entry and technology is listed as below:

Test Item	Mode	O57TB353ZA Parent Worst mode Test Result	O57TB353ZU Variant Check Test Result	Deviation (dB)	Deviation Limit (dB)
Conducted Power (dBm)	Peak power				
	BT BR/EDR Ant6	8.88	8.53	0.35	3
	BLE 1Mbps Ant6	8.88	8.48	0.40	3
	BLE 2Mbps Ant6	9.12	8.74	0.38	3
	BT BR/EDR Ant7	8.45	8.08	0.37	3
	BLE 1Mbps Ant7	8.48	8.00	0.48	3
	BLE 2Mbps Ant7	8.71	8.05	0.66	3
	11n HE20, 2.4GHz Ant6+7	22.78	22.63	0.15	3
	Average power				
	BT BR/EDR Ant6	8.79	8.56	0.23	3
	BLE 1Mbps Ant6	8.68	8.26	0.42	3
	BLE 2Mbps Ant6	8.78	8.33	0.45	3
	BT BR/EDR Ant7	8.36	7.98	0.38	3
	BLE 1Mbps Ant7	8.28	7.11	1.17	3
	BLE 2Mbps Ant7	8.35	7.23	1.12	3
	11n HE20, 2.4GHz Ant6+7	16.41	16.38	0.03	3
	11a, 5.2GHz Ant6+7	20.79	20.74	0.05	3
	11a, 5.3GHz Ant6+7	20.81	20.8	0.01	3
	11a, 5.5GHz Ant6+7	20.98	20.96	0.02	3
	11a, 5.8GHz Ant6+7	20.9	20.89	0.01	3
	11ax HE20, 5.2GHz Ant6+7	19.51	19.5	0.01	3
	11ax HE20, 5.3GHz Ant6+7	19.59	19.52	0.07	3
	11ax HE20, 5.5GHz Ant6+7	19.8	19.68	0.12	3
	11ax HE20, 5.8GHz Ant6+7	19.69	19.57	0.12	3
	11ax HE40, 5.2GHz Ant6+7	19.2	19.11	0.09	3
	11ax HE40, 5.3GHz Ant6+7	19.27	19.15	0.12	3
	11ax HE40, 5.5GHz Ant6+7	19.8	19.64	0.16	3
	11ax HE40, 5.8GHz Ant6+7	19.77	19.71	0.06	3
	11ax HE80, 5.2GHz Ant6+7	17.5	17.38	0.12	3
	11ax HE80, 5.3GHz Ant6+7	17.29	17.22	0.07	3
	11ax HE80, 5.5GHz Ant6+7	20.35	20.19	0.16	3
	11ax HE80, 5.8GHz Ant6+7	20.42	20.35	0.07	3
	11ax HE160, 5.5GHz Ant6+7	17.19	17.14	0.05	3
	11ax HE160, 5.8GHz Ant6+7	16.48	16.39	0.09	3
	11ax HE20, U-NII-5 Ant6+7	10.42	10.37	0.05	3
	11ax HE20, U-NII-6 Ant6+7	10.26	10.15	0.11	3
	11ax HE20, U-NII-7 Ant6+7	10.88	10.38	0.5	3
	11ax HE20, U-NII-8 Ant6+7	11.69	11.42	0.27	3
	11ax HE40, U-NII-5 Ant6+7	12.94	12.88	0.06	3
	11ax HE40, U-NII-6 Ant6+7	13.37	13.34	0.03	3
	11ax HE40, U-NII-7 Ant6+7	14.07	13.48	0.59	3
	11ax HE40, U-NII-8 Ant6+7	15.01	14.11	0.9	3
	11ax HE80, U-NII-5 Ant6+7	16.46	16.38	0.08	3
	11ax HE80, U-NII-6 Ant6+7	16.71	16.58	0.13	3
	11ax HE80, U-NII-7 Ant6+7	16.74	15.87	0.87	3



	11ax HE80, U-NII-8 Ant6+7	17.01	16.68	0.33	3
	11ax HE160, U-NII-5 Ant6+7	19	18.97	0.03	3
	11ax HE160, U-NII-6 Ant6+7	19.12	19	0.12	3
	11ax HE160, U-NII-7 Ant6+7	19.19	19.14	0.05	3
	11ax HE160, U-NII-8 Ant6+7	19.73	19.71	0.02	3
	LTE B2	23.1	23.07	0.03	3
	LTE B4	23.28	23.25	0.03	3
	LTE B5	23.11	23.08	0.03	3
	LTE B12	23.18	23.19	0.01	3
	LTE B13	23.36	23.29	0.07	3
	LTE B25	23.2	23.11	0.09	3
	LTE B26	23.08	23.02	0.06	3
	LTE B66	23.27	23.23	0.04	3
	LTE B41	26.27	26.22	0.05	3
	n2	23.78	23.24	0.54	3
	n5	23.77	23.42	0.35	3
	n41	23.46	22.70	0.76	3
	n66	23.89	23.59	0.30	3
	n71	23.9	23.57	0.33	3
	n77_27O	25.98	25.07	0.91	3
	n77_27Q	25.86	25.64	0.22	3

Test Item	Mode	O57TB353ZA Parent Worst mode Test Result	O57TB353ZU Variant Check Test Result	Deviation (dB)	Deviation Limit (dB)
Radiated Spurious Emission(dBuV/m)	Bluetooth BR_GFSK CH78	59.59	57.46	2.13	3
	Bluetooth-LE_GFSK CH39 (2M)	45.71	43.87	1.84	3
	802.11n40 CH03	50.77	49.75	1.02	3
	802.11ax40 CH38	50.9	48.73	2.17	3
	802.11ax20 CH1	59.57	58.60	0.97	3
	NFC	15.94	15.81	0.13	3
Radiated Spurious Emission(dBm)	Part 27F LTE B13 BW=5M	-49.06	-52.00	2.94	3

Conclusion:

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

Based on the spot check test result, the test data from the original model is representative for the variant model. All spot check test data are shown within expected level compliant to limit line.

We are using power and ERP/EIRP measurements from the original parent model reports to list on the grant.

We confirm that the test data referencing policy of FCC KDB 484596 D01 Referencing Test Data v03 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.



3 List of Measuring Equipment

For NFC:

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Ma x 30dBm	Oct. 10, 2025	Apr. 03, 2026	Oct. 09, 2026	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Apr. 03, 2026	Aug. 09, 2026	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	59915	30MHz~1GHz	Aug. 12, 2025	Apr. 03, 2026	Aug. 11, 2026	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	413740	9KHz~1GHz	Dec. 25, 2025	Apr. 03, 2026	Dec. 24, 2026	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Apr. 03, 2026	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Apr. 03, 2026	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Apr. 03, 2026	NCR	Radiation (03CH02-KS)

For BT/WIFI:

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Mar. 26, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jul. 07, 2025	Mar. 26, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Dec. 25, 2025	Mar. 26, 2026	Dec. 24, 2026	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;Ma x 30dBm	Jul. 02, 2025	Apr. 03, 2026	Jul. 01, 2026	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz~44G,MAX 30dB	Oct. 10, 2025	Apr. 03, 2026	Oct. 10, 2026	Radiation (03CH05-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Apr. 03, 2026	Aug. 09, 2026	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	Mar. 23, 2026	Apr. 03, 2026	Mar. 22, 2027	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 14, 2025	Apr. 03, 2026	Apr. 13, 2026	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 18, 2025	Apr. 03, 2026	Oct. 19, 2026	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380827	9KHz~1GHz	Jul. 03, 2025	Apr. 03, 2026	Jul. 02, 2026	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Dec. 26, 2025	Apr. 03, 2026	Dec.25 , 2026	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060843	1Ghz~18Ghz	Dec. 25, 2025	Apr. 03, 2026	Dec.24 , 2026	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Dec. 25, 2025	Apr. 03, 2026	Dec.24 , 2026	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 03, 2026	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 03, 2026	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 03, 2026	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required.



For WWAN Bands:

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Apr. 01, 2026~ Apr. 02, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Apr. 01, 2026~ Apr. 02, 2026	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 02, 2025	Apr. 01, 2026~ Apr. 02, 2026	Jul. 01, 2026	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 10, 2025	Apr. 01, 2026	Oct. 09, 2026	Radiation (03CH04-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Apr. 01, 2026	Aug. 09, 2026	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Nov. 22, 2025	Apr. 01, 2026	Nov. 21, 2026	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 22, 2025	Apr. 01, 2026	Aug. 21, 2026	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 10, 2026	Apr. 01, 2026	Jan. 09, 2027	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 02, 2025	Apr. 01, 2026	Jul. 01, 2026	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060852	18~40GHz	Dec. 24, 2025	Apr. 01, 2026	Dec. 23, 2026	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060890	1Ghz-18Ghz	May 23, 2025	Apr. 01, 2026	May 22, 2026	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz-18Ghz	Oct. 11, 2025	Apr. 01, 2026	Oct. 10, 2026	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 01, 2026	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 01, 2026	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 01, 2026	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required.

4 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.90 dB

03CH02-KS(NFC):

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.18 dB
---	---------

03CH05-KS(BT/WIF):

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.18 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.88 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.36 dB
---	---------

**03CH04-KS(WWAN):****Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)**

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.82 dB
---	---------

-THE END-