



FCC RF Test Report

APPLICANT : Lenovo(Shanghai) Electronics
Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : Lenovo TB-8604F
FCC ID : O57TB8604F
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Mar. 08, 2019 and testing was completed on Apr. 09, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Laboratory SPORTON INTERNATIONAL INC.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Component List.....	5
1.5 Product Specification of Equipment Under Test.....	6
1.6 Modification of EUT	6
1.7 Testing Location	6
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 AC Conducted Emission Measurement.....	31
3.7 Antenna Requirements.....	33
4 LIST OF MEASURING EQUIPMENT	34
5 UNCERTAINTY OF EVALUATION	35
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR930802C	Rev. 01	Initial issue of report	Apr. 18, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm/3kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.07 dB at 2483.98 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.44 dB at 0.497 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.

NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	Lenovo TB-8604F
FCC ID	O57TB8604F
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver/GNSS
HW Version	Lenovo Tablet TB-8604F
SW Version	TB-8604F_RF01_190415
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Component List

Note: There are two types of EUT, the detail difference please refer to the follow table, according to the difference, we choose sample 1 to full test.

Component	Sample 1		Sample 2	
	Specifications	Supplier	Specifications	Supplier
CPU	APQ-8017-0-720BNSP-T	Qualcomm	APQ-8017-0-720BNSP-TR-0	Qualcomm
FLASH (2+32)	KMQD60013M-B318	Samsung	KMQD60013M-B318	Samsung
Rear Camera	LCK5A01	TIANSI	LE5104AM	LCE
Battery	L16D1P34	SCUD	L16D1P34	SCUD
usb	SLQ-A055A	SAIBAO	SLQ-A055A	SAIBAO
Panel	TV080WXM-NL5	BOE	TV080WXM-NL5	BOE

1.5 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum Output Power to antenna	802.11b : 17.30 dBm (0.0537 W) 802.11g : 16.40 dBm (0.0437 W) 802.11n HT20 : 15.40 dBm (0.0347 W)
Antenna Type / Gain	IFA Antenna type with gain -5 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.6 Modification of EUT

No modifications are made to the EUT during all test items.

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS	CN5013	630927

SPORTON INTERNATIONAL INC. is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and under the FCC-recognized accredited testing laboratories by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist. Taoyuan City Taiwan Tel: 886-3-327-3456 FAX: +886-3-327-0978	
Test Site No.	Sporton Site No.	FCC designation No.
	TH05-HY	TW1190

Remark: Test data subcontracted: all conducted test item in this report



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		


2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link(2.4G) + Battery 1 + Earphone + USB Cable 1(Charging from Adapter) for Sample1
Remark: 1. For Radiated Test Cases, The tests were performance with Adapter, Battery 1, Earphone, USB Cable 1 and Sample 1	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
3.	Notebook	Lenovo	G480	PRC4	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Router	D-link	DIR-855	KA2DIR855A2		Unshielded,1.8m
5.	Earphone	Lenovo	P121	N/A	N/A	Unshielded,1.2m
6.	Adapter	MOTO	SC-61	N/A	N/A	N/A
7.	SD Card	Kingston	8GB	N/A	N/A	N/A
8.	BT Base Station	R S	CBT	Fcc Doc	BT Base Station	R S
9.	Earphone	Lenovo	SH100	N/A	Earphone	Lenovo



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 20 = 24.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.2.3 AVGPM power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Luffy Lin / Rebecca Li	Temperature :	21~25°C
		Relative Humidity :	51~54%


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 2.APR.2019 10:09:26

Spurious Emission 30MHz~3GHz



Date: 2.APR.2019 10:09:48


Spurious Emission 2GHz~25GHz



Date: 2.APR.2019 10:10:07




Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 2.APR.2019 10:34:22

Spurious Emission 30MHz~3GHz



Date: 2.APR.2019 10:35:44


Spurious Emission 2GHz~25GHz



Date: 2.APR.2019 10:35:00




Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	01
-------------	--------------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----

100kHz PSD reference Level




Date: 2.APR.2019 10:57:41

Spurious Emission 30MHz~3GHz



Date: 2.APR.2019 10:57:59


Spurious Emission 2GHz~25GHz



Date: 2.APR.2019 10:58:18



Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Nov. 05, 2018	Mar. 20, 2019~ Apr. 02, 2019	Nov. 04, 2019	Conducted (TH05-HY)
Power Sensor	DARE	RadiPower	15I00041S NO09	10MHz~6GHz	May. 07, 2018	Mar. 20, 2019~ Apr. 02, 2019	May. 06, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz~40GHz	Nov. 21, 2018	Mar. 20, 2019~ Apr. 02, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW107090 3	N/A	Dec 19 2018	Mar. 20, 2019~ Apr. 02, 2019	Dec 18 2019	Conducted (TH05-HY)
EMI Test Receiver	Keysight	N9038A	MY572901 51	3Hz~8.5GHz;M ax 30dBm	Jun. 25, 2018	Apr. 09, 2019	Jun. 24, 2019	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz~44GHz	Apr. 17, 2018	Apr. 09, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Apr. 09, 2019	Oct. 18, 2019	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	Jun. 12, 2018	Apr. 09, 2019	Jun. 11, 2019	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Apr. 09, 2019	Jan. 26, 2020	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Apr. 09, 2019	Jan. 04, 2020	Radiation (03CH05-KS)
Amplifier	com-power	PA-103A	161069	1MHz ~1000MHz / 32 dB	Apr. 17, 2018	Apr. 09, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Amplifier	MITEQ	TTA1840-35- HG	2014749	18~40GHz	Jan. 14, 2019	Apr. 09, 2019	Jan.13, 2020	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Apr. 09, 2019	Apr. 16, 2019	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY572801 06	500MHz~26.5G Hz	Apr. 18, 2018	Apr. 09, 2019	Apr. 17, 2019	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Apr. 09, 2019	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 09, 2019	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 09, 2019	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Apr. 02, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Apr. 02, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Apr. 02, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Apr. 02, 2019	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Test Engineer:	Luffy Lin / Rebecca Li	Temperature:	21~25	°C
Test Date:	2019/3/20~2019/4/2	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	13.05	-	8.54	-	0.50	Pass
11b	1Mbps	1	6	2437	13.05	-	8.04	-	0.50	Pass
11b	1Mbps	1	11	2462	13.05	-	8.06	-	0.50	Pass
11g	6Mbps	1	1	2412	17.05	-	16.32	-	0.50	Pass
11g	6Mbps	1	6	2437	17.05	-	16.36	-	0.50	Pass
11g	6Mbps	1	11	2462	17.10	-	16.32	-	0.50	Pass
HT20	MCS0	1	1	2412	18.10	-	17.58	-	0.50	Pass
HT20	MCS0	1	6	2437	18.15	-	17.58	-	0.50	Pass
HT20	MCS0	1	11	2462	18.00	-	17.58	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	17.10	-	-	30.00	-	-5.00	-	12.10	-	36.00	-	Pass
11b	1Mbps	1	6	2437	17.30	-		30.00	-	-5.00	-	12.30	-	36.00	-	Pass
11b	1Mbps	1	11	2462	17.30	-		30.00	-	-5.00	-	12.30	-	36.00	-	Pass
11g	6Mbps	1	1	2412	16.40	-		30.00	-	-5.00	-	11.40	-	36.00	-	Pass
11g	6Mbps	1	6	2437	16.30	-		30.00	-	-5.00	-	11.30	-	36.00	-	Pass
11g	6Mbps	1	11	2462	16.40	-		30.00	-	-5.00	-	11.40	-	36.00	-	Pass
HT20	MCS0	1	1	2412	15.30	-		30.00	-	-5.00	-	10.30	-	36.00	-	Pass
HT20	MCS0	1	6	2437	15.20	-		30.00	-	-5.00	-	10.20	-	36.00	-	Pass
HT20	MCS0	1	11	2462	15.40	-		30.00	-	-5.00	-	10.40	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-5.35	-	-	-5.00	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-5.47	-	-	-5.00	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-5.09	-	-	-5.00	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-8.72	-	-	-5.00	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-9.16	-	-	-5.00	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-8.24	-	-	-5.00	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-9.47	-	-	-5.00	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-10.29	-	-	-5.00	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-9.37	-	-	-5.00	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Amos Zhang	Temperature :	23.3~24.2℃
		Relative Humidity :	28~30%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15C LISN-N-181119-060105 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.464	41.00	-15.63	56.63	30.60	0.15	10.25	QP
2	0.464	26.00	-20.63	46.63	15.60	0.15	10.25	Average
3	0.513	37.98	-18.02	56.00	27.59	0.15	10.24	QP
4	0.513	27.88	-18.12	46.00	17.49	0.15	10.24	Average
5	0.585	32.88	-23.12	56.00	22.50	0.14	10.24	QP
6	0.585	21.58	-24.42	46.00	11.20	0.14	10.24	Average
7	0.989	34.66	-21.34	56.00	24.30	0.13	10.23	QP
8	0.989	21.56	-24.44	46.00	11.20	0.13	10.23	Average
9	1.959	31.58	-24.42	56.00	21.20	0.15	10.23	QP
10	1.959	21.28	-24.72	46.00	10.90	0.15	10.23	Average
11	3.025	29.61	-26.39	56.00	19.21	0.16	10.24	QP
12	3.025	20.71	-25.29	46.00	10.31	0.16	10.24	Average



Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz	*	2412	110.71	-	-	105.04	31.33	6.14	31.8	141	263	P	H
	*	2410	107.26	-	-	101.59	31.33	6.14	31.8	141	263	A	H
		2339.9	63.25	-10.75	74	57.76	31.22	6.07	31.8	141	263	P	H
		2386.05	49.91	-4.09	54	44.27	31.3	6.14	31.8	141	263	A	H
	*	2412	106.87	-	-	101.2	31.33	6.14	31.8	286	280	P	V
	*	2414	103.78	-	-	98.11	31.33	6.14	31.8	286	280	A	V
		2339.77	55.63	-18.37	74	50.14	31.22	6.07	31.8	286	280	P	V
		2386.44	47.66	-6.34	54	42.02	31.3	6.14	31.8	286	280	A	V
802.11b CH 11 2462MHz	*	2462	109.36	-	-	103.6	31.41	6.15	31.8	112	265	P	H
	*	2462	106.18	-	-	100.42	31.41	6.15	31.8	112	265	A	H
		2490.52	56.08	-17.92	74	50.25	31.47	6.16	31.8	112	265	P	H
		2483.8	47.05	-6.95	54	41.25	31.44	6.16	31.8	112	265	A	H
	*	2462	106.44	-	-	100.68	31.41	6.15	31.8	316	294	P	V
	*	2464	103.23	-	-	97.47	31.41	6.15	31.8	316	294	A	V
		2483.56	55.12	-18.88	74	49.32	31.44	6.16	31.8	316	294	P	V
		2484.04	45.85	-8.15	54	40.05	31.44	6.16	31.8	316	294	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	36.63	-37.37	74	52.52	35.65	8.41	59.95	100	360	P	H
		4824	37.56	-36.44	74	53.45	35.65	8.41	59.95	100	360	P	V
802.11b CH 06 2437MHz		4872	37.82	-36.18	74	53.62	35.61	8.53	59.94	100	360	P	H
		7308	39.87	-34.13	74	54.45	35.89	10.4	60.87	100	360	P	H
		4872	37.78	-36.22	74	53.58	35.61	8.53	59.94	100	360	P	V
		7308	39.82	-34.18	74	54.4	35.89	10.4	60.87	100	360	P	V
802.11b CH 11 2462MHz		4926	36.5	-37.5	74	52.15	35.57	8.71	59.93	100	360	P	H
		7386	42.48	-31.52	74	57.11	35.94	10.39	60.96	100	360	P	H
		4926	37.93	-36.07	74	53.58	35.57	8.71	59.93	100	360	P	V
		7386	44.43	-29.57	74	59.06	35.94	10.39	60.96	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz	*	2416	106.59	-	-	100.92	31.33	6.14	31.8	143	267	P	H
	*	2408	98.53	-	-	92.86	31.33	6.14	31.8	143	267	A	H
		2388.91	66.81	-7.19	74	61.17	31.3	6.14	31.8	143	267	P	H
		2389.82	51.46	-2.54	54	45.82	31.3	6.14	31.8	143	267	A	H
	*	2420	103.61	-	-	97.91	31.36	6.14	31.8	285	280	P	V
	*	2416	95.65	-	-	89.98	31.33	6.14	31.8	285	280	A	V
		2389.95	64.88	-9.12	74	59.24	31.3	6.14	31.8	285	280	P	V
		2389.43	48.25	-5.75	54	42.61	31.3	6.14	31.8	285	280	A	V
802.11g CH 11 2462MHz	*	2464	106.96	-	-	101.2	31.41	6.15	31.8	110	259	P	H
	*	2458	99.05	-	-	93.29	31.41	6.15	31.8	110	259	A	H
		2483.98	72.93	-1.07	74	67.13	31.44	6.16	31.8	110	259	P	H
		2483.68	52.79	-1.21	54	46.99	31.44	6.16	31.8	110	259	A	H
	*	2456	101.66	-	-	95.9	31.41	6.15	31.8	285	280	P	V
	*	2456	93.94	-	-	88.18	31.41	6.15	31.8	285	280	A	V
		2483.98	61.76	-12.24	74	55.96	31.44	6.16	31.8	285	280	P	V
		2483.5	46.29	-7.71	54	40.49	31.44	6.16	31.8	285	280	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	39.08	-34.92	74	54.97	35.65	8.41	59.95	100	360	P	H
		14472	46.94	-27.06	74	50.99	40.81	15.76	60.62	100	0	P	H
		4824	38.57	-35.43	74	54.46	35.65	8.41	59.95	100	360	P	V
		14472	53.78	-20.22	74	57.83	40.81	15.76	60.62	100	246	P	V
		14472	44.07	-9.93	54	48.12	40.81	15.76	60.62	100	246	A	V
802.11g CH 06 2437MHz		4872	39.36	-34.64	74	55.16	35.61	8.53	59.94	100	360	P	H
		7308	41.12	-32.88	74	55.7	35.89	10.4	60.87	100	360	P	H
		4872	38.23	-35.77	74	54.03	35.61	8.53	59.94	100	360	P	V
		7308	41.94	-32.06	74	56.52	35.89	10.4	60.87	100	360	P	V
		14625	56.45	-17.55	74	60.16	40.95	15.93	60.59	100	247	P	V
		14625	44.56	-9.44	54	48.27	40.95	15.93	60.59	100	247	A	V
802.11g CH 11 2462MHz		4926	37.97	-36.03	74	53.62	35.57	8.71	59.93	100	360	P	H
		7386	40.77	-33.23	74	55.4	35.94	10.39	60.96	100	360	P	H
		4926	38.48	-35.52	74	54.13	35.57	8.71	59.93	100	360	P	V
		7386	40.61	-33.39	74	55.24	35.94	10.39	60.96	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz	*	2418	105.67	-	-	100	31.33	6.14	31.8	110	263	P	H
	*	2418	97.04	-	-	91.37	31.33	6.14	31.8	110	263	A	H
		2388.78	67.87	-6.13	74	62.23	31.3	6.14	31.8	110	263	P	H
		2389.95	51.32	-2.68	54	45.68	31.3	6.14	31.8	110	263	A	H
	*	2404	101.07	-	-	95.4	31.33	6.14	31.8	334	288	P	V
	*	2404	93.75	-	-	88.08	31.33	6.14	31.8	334	288	A	V
		2389.82	62.55	-11.45	74	56.91	31.3	6.14	31.8	334	288	P	V
		2389.82	48.24	-5.76	54	42.6	31.3	6.14	31.8	334	288	A	V
802.11n HT20 CH 11 2462MHz	*	2462	106.24	-	-	100.48	31.41	6.15	31.8	110	263	P	H
	*	2458	98.26	-	-	92.5	31.41	6.15	31.8	110	263	A	H
		2483.74	69.78	-4.22	74	63.98	31.44	6.16	31.8	110	263	P	H
		2483.62	50.75	-3.25	54	44.95	31.44	6.16	31.8	110	263	A	H
	*	2466	102.31	-	-	96.55	31.41	6.15	31.8	334	288	P	V
	*	2468	94.03	-	-	88.27	31.41	6.15	31.8	334	288	A	V
		2484.22	68.5	-5.5	74	62.7	31.44	6.16	31.8	334	288	P	V
		2483.98	47.67	-6.33	54	41.87	31.44	6.16	31.8	334	288	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	39.77	-34.23	74	55.66	35.65	8.41	59.95	100	360	P	H
		4824	39.44	-34.56	74	55.33	35.65	8.41	59.95	100	360	P	V
802.11n HT20 CH 06 2437MHz		4872	38.75	-35.25	74	54.55	35.61	8.53	59.94	100	360	P	H
		7308	40.91	-33.09	74	55.49	35.89	10.4	60.87	100	360	P	H
		4872	37.85	-36.15	74	53.65	35.61	8.53	59.94	100	360	P	V
		7308	41.56	-32.44	74	56.14	35.89	10.4	60.87	100	360	P	V
802.11n HT20 CH 11 2462MHz		4926	38.62	-35.38	74	54.27	35.57	8.71	59.93	100	360	P	H
		7386	40.28	-33.72	74	54.91	35.94	10.39	60.96	100	360	P	H
		4926	38.46	-35.54	74	54.11	35.57	8.71	59.93	100	360	P	V
		7386	42.11	-31.89	74	56.74	35.94	10.39	60.96	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	20.77	-19.23	40	29.09	24.2	0.46	32.98	-	-	P	H
		96.93	20.32	-23.18	43.5	36.19	16.1	0.96	32.93	-	-	P	H
		224.97	23.81	-22.19	46	39.44	15.77	1.55	32.95	-	-	P	H
		477.17	27.26	-18.74	46	35.23	22.98	2.29	33.24	100	0	P	H
		793.39	23.9	-22.1	46	27.76	26.02	3.13	33.01	-	-	P	H
		871.96	25.03	-20.97	46	27.8	26.39	3.31	32.47	-	-	P	H
		35.82	28.21	-11.79	40	39.82	20.84	0.51	32.96	100	0	P	V
		96.93	29.19	-14.31	43.5	45.06	16.1	0.96	32.93	-	-	P	V
		475.23	22.53	-23.47	46	30.53	22.95	2.29	33.24	-	-	P	V
		602.3	23.76	-22.24	46	29.9	24.61	2.6	33.35	-	-	P	V
		826.37	24.55	-21.45	46	27.92	26.2	3.21	32.78	-	-	P	V
		893.3	24.8	-21.2	46	27.35	26.47	3.34	32.36	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	96.43	8.180	0.122	0.13KHz
802.11g	87.26	1.370	0.730	0.75KHz
802.11n HT20	86.15	1.275	0.784	0.82KHz

802.11b




Date: 20.MAR.2019 01:04:19

802.11g



Date: 20.MAR.2019 03:16:02

802.11n20



Date: 20.MAR.2019 03:21:47