# FCC SAR TEST REPORT

| | | |
|---|---|---|
| APPLICANT | : | Lenovo(Shanghai) Electronics Technology Co., Ltd. |
| EQUIPMENT | : | Portable Tablet Computer |
| BRAND NAME | : | Lenovo |
| Model Name | : | Lenovo TB-Q706F |
| FCC ID | : | O57TBQ706F |
| STANDARD | : | FCC 47 CFR Part 2 (2.1093) |

**We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been in compliance with the applicable technical standards.**

**The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.**

Nick Hu

**Reviewed by: Nick Hu / Supervisor**

Kat Yin

**Approved by: Kat Yin / Manager**

ACCREDITED
Cert #5145.02

***Sporton International (Kunshan) Inc.***
***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China***

# Table of Contents

**1. Statement of Compliance** ..... **4**
**2. Administration Data** ..... **5**
**3. Guidance Applied** ..... **5**
**4. Equipment Under Test (EUT) Information** ..... **6**
4.1 General Information ..... 6
**5. Proximity Sensor Triggering Test** ..... **7**
**6. RF Exposure Limits** ..... **13**
6.1 Uncontrolled Environment ..... 13
6.2 Controlled Environment ..... 13
**7. Specific Absorption Rate (SAR)** ..... **14**
7.1 Introduction ..... 14
7.2 SAR Definition ..... 14
**8. System Description and Setup** ..... **15**
8.1 E-Field Probe ..... 16
8.2 Data Acquisition Electronics (DAE) ..... 16
8.3 Phantom ..... 17
8.4 Device Holder ..... 18
**9. Measurement Procedures** ..... **19**
9.1 Spatial Peak SAR Evaluation ..... 19
9.2 Power Reference Measurement ..... 20
9.3 Area Scan ..... 20
9.4 Zoom Scan ..... 21
9.5 Volume Scan Procedures ..... 21
9.6 Power Drift Monitoring ..... 21
**10. Test Equipment List** ..... **22**
**11. System Verification** ..... **23**
11.1 Tissue Simulating Liquids ..... 23
11.2 Tissue Verification ..... 24
11.3 System Performance Check Results ..... 25
**12. RF Exposure Positions** ..... **26**
12.1 SAR Testing for Tablet ..... 26
**13. Conducted RF Output Power (Unit: dBm)** ..... **27**
**14. Antenna Location** ..... **29**
**15. SAR Test Results** ..... **31**
15.1 Body SAR ..... 32
15.2 Repeated SAR Measurement ..... 33
**16. Simultaneous Transmission Analysis** ..... **34**
16.1 Body Exposure Conditions ..... 34
**17. Uncertainty Assessment** ..... **35**
**18. References** ..... **36**
**Appendix A. Plots of System Performance Check**
**Appendix B. Plots of High SAR Measurement**
**Appendix C. DASY Calibration Certificate**
**Appendix D. Test Setup Photos**
**Appendix E. Conducted RF Output Power Table**

# History of this test report

| Report No. | Version | Description | Issued Date |
|---|---|---|---|
| FA161617 | Rev. 01 | Initial issue of report | Aug. 13, 2021 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

# 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Lenovo(Shanghai) Electronics Technology Co., Ltd., Portable Tablet Computer, Lenovo TB-Q706F,** are as follows.

| Highest Standalone 1g SAR Summary | | | | |
|---|---|---|---|---|
| Equipment Class | Frequency Band | | Body (Separation 0mm) 1g SAR (W/kg) | Highest Simultaneous Transmission 1g SAR (W/kg) |
| DTS | WLAN | 2.4GHz WLAN | **1.08** | 1.08 |
| NII | | 5GHz WLAN | 1.05 | 1.43 |
| DSS | Bluetooth | Bluetooth | 0.38 | 1.43 |
| Date of Testing: | | 2021/7/7 ~ 2021/7/26 | | |

| Declaration of Conformity: |
|---|
| The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. |
| Comments and Explanations: |
| The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

## 2. Administration Data

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

| Testing Laboratory | | |
|---|---|---|
| Test Firm | Sporton International (Kunshan) Inc. | |
| Test Site Location | No. 1098, Pengxi North Road, Kunshan Economic Development Zone<br>Jiangsu Province 215300 People's Republic of China<br>TEL : +86-512-57900158<br>FAX : +86-512-57900958 | |
| Test Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | CN1257 | 314309 |

| Applicant | |
|---|---|
| Company Name | Lenovo(Shanghai) Electronics Technology Co., Ltd. |
| Address | Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone |

| Manufacturer | |
|---|---|
| Company Name | Lenovo PC HK Limited |
| Address | 23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China |

## 3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02

# 4. Equipment Under Test (EUT) Information

## 4.1 General Information

| Product Feature & Specification | |
|---|---|
| Equipment Name | Portable Tablet Computer |
| Brand Name | Lenovo |
| Model Name | Lenovo TB-Q706F |
| FCC ID | O57TBQ706F |
| SN Code | Sample 1: HA1DQ8F6<br>Sample 2: HA1E5KK6 |
| Wireless Technology and Frequency Range | WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz<br>WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz<br>WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz<br>WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz<br>WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz<br>NFC(WLC): 13.56MHz |
| Mode | WLAN 2.4GHz 802.11b/g/n HT20/HT40<br>WLAN 2.4GHz 802.11ax HE20/HE40<br>WLAN 5GHz 802.11a/n HT20/HT40<br>WLAN 5GHz 802.11ac VHT20/VHT40/VHT80<br>WLAN 5GHz 802.11ax HE20/HE40/HE80<br>Bluetooth BR/EDR/LE<br>NFC(WLC): ASK |
| HW Version | Lenovo TB-Q706F |
| SW Version | TB-Q706F_RF01_210811 |
| EUT Stage | Identical Prototype |

**Remark:**

1. This device has no voice function.
2. The 2.4GHz/5GHz WLAN can transmit in SISO/MIMO antenna mode.
3. The device supports NFC wireless charging (WLC) function, and the NFC supports the function of charging the stylus only.
4. RF Exposure report for WPT will be separately submitted. About co-located SAR with WLAN/Bluetooth, always chose higher SAR of WPT SAR.
5. The device employs proximity sensors that detect the presence of the user's body also a finger or hand near the bottom face, edge 1 of the device, reduced power will be active for all WLAN bands. (P-sensor can't work at detecting presence of the user's body at other edges of the device.)
6. There are two types of EUT sample 1 and sample 2, the difference between them can refer to Lenovo TB-Q706F_Operational Description of Product Equality Declaration submitted. According to the difference, we chose sample 1 to perform full SAR testing and sample 2 verified the worst case.

# 5. Proximity Sensor Triggering Test

## <Proximity Sensor Triggering Distance (KDB 616217 D04 section 6.2)>:

1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency 5850MHz and lowest 2450MHz frequency was used for proximity sensor triggering testing.
2. Capacitive proximity sensor placed coincident with antenna elements at the Bottom Face, and Edge 1 of the device are utilized to determine when the device comes in proximity of the user's body at the Bottom Face or Edge 1 side of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.
3. When the sensor is active, WLAN 2.4GHz / WLAN 5.2GHz / WLAN 5.3GHz / WLAN 5.5GHz / WLAN 5.8GHz reduced power will be active.
4. The sensors used to detect the proximity of the user's body at the Bottom Face, Edge 1 side of the device use a detection threshold distance. The data shown in the sections below shows the distance(s).




| Proximity Sensor Triggering Distance (mm) | | | | |
|---|---|---|---|---|
| Position | Bottom Face | | Edge 1 | |
| | Moving towards | Moving away | Moving towards | Moving away |
| Minimum | 11 | 16 | 14 | 18 |

## <Proximity Sensor Triggering Coverage (KDB 616217 D04 section 6.3)>:

If a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. For p-sensor coverage testing, the device is moved and "along the direction of maximum antenna and sensor offset".
Illustrated in the internal photo exhibit, although the senor is spatially offset, there is no trigger condition where the antenna is next to the user but the sensor is laterally further away, therefore proximity sensor coverage testing is not required.
This procedure is not required because antenna and sensor are collocated and the peak SAR location is overlapping with the sensor.

**<Tablet Tilt angle influences to proximity sensor triggering (KDB 616217 D04 section 6.4)>:**

The influence of table tilt angles to proximity sensor triggering was determined by positioning each tablet edge that contains a transmitting antenna, perpendicular to the flat phantom, at 14mm for Edge 1 separation for WLAN bands. Rotating the tablet around the edge next to the phantom in ≤ 10° increments until the tablet is ± 45° from the vertical position at 0°, and the maximum output power remains in the reduced mode.




| The Sensor Trigger Distance (mm) | |
|---|---|
| Position | Edge 1 |
| Minimum | 14 |

## Proximity sensor power reduction

| Exposure Position / wireless mode | Bottom Face(1) | Edge 1(1) | Edge 2 | Edge 3 | Edge 4 |
|---|---|---|---|---|---|
| WLAN 2.4GHz ANT1 | 8.0 dB | 8.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 2.4GHz ANT2 | 8.0 dB | 8.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 2.4GHz ANT1+2 | 8.0 dB | 8.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.2GHz ANT1 | 10.0 dB | 10.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.2GHz ANT2 | 9.5 dB | 9.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.2GHz ANT1+2 | 10.0 dB | 10.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.3GHz ANT1 | 10.0 dB | 10.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.3GHz ANT2 | 9.5 dB | 9.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.3GHz ANT1+2 | 10.0 dB | 10.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.5GHz ANT1 | 11.5 dB | 11.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.5GHz ANT2 | 11.0 dB | 11.0 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.5GHz ANT1+2 | 11.5 dB | 11.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.8GHz ANT1 | 10.5 dB | 10.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.8GHz ANT2 | 10.5 dB | 10.5 dB | 0 dB | 0 dB | 0 dB |
| WLAN 5.8GHz ANT1+2 | 10.5 dB | 10.5 dB | 0 dB | 0 dB | 0 dB |

**Remark:**

1. (1): Reduced maximum limit applied by activation of proximity sensor.
2. Tests were performed in accordance with KDB 616217 D04 section 6.1, 6.2, 6.3, 6.4 and 6.5 and compliant results are shown and described in exhibit “P-Sensor operational description
3. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed:
   - Bottom Face: 10 mm
   - Edge 1: 13 mm

## Power Measurement during Sensor Trigger distance testing

| Band/Mode | Measured power reduction (dBm) | | Reduction Levels |
|---|---|---|---|
| | w/o power back-off | w/ power back-off | (dB) |
| WLAN 2.4GHz ANT1 | 20.50 | 12.50 | 8.0 |
| WLAN 2.4GHz ANT2 | 20.00 | 12.00 | 8.0 |
| WLAN 2.4GHz ANT1+2 | 23.50 | 15.50 | 8.0 |
| WLAN 5.2GHz ANT1 | 19.50 | 9.50 | 10.0 |
| WLAN 5.2GHz ANT2 | 20.00 | 10.50 | 9.5 |
| WLAN 5.2GHz ANT1+2 | 23.00 | 13.00 | 10.0 |
| WLAN 5.3GHz ANT1 | 20.00 | 10.00 | 10.0 |
| WLAN 5.3GHz ANT2 | 20.00 | 10.50 | 9.5 |
| WLAN 5.3GHz ANT1+2 | 23.00 | 13.00 | 10.0 |
| WLAN 5.5GHz ANT1 | 20.00 | 8.50 | 11.5 |
| WLAN 5.5GHz ANT2 | 20.00 | 9.00 | 11.0 |
| WLAN 5.5GHz ANT1+2 | 23.00 | 11.50 | 11.5 |
| WLAN 5.8GHz ANT1 | 20.50 | 10.00 | 10.5 |
| WLAN 5.8GHz ANT2 | 19.50 | 9.00 | 10.5 |
| WLAN 5.8GHz ANT1+2 | 23.00 | 12.50 | 10.5 |


Bottom Face
(moving toward phantom)
Power (dBm)
Distance from the rear face of the device (mm)
WLAN2.4GHz Ant1
WLAN2.4GHz Ant2
WLAN2.4GHz Ant1+2
WLAN5.2GHz Ant1
WLAN5.2GHz Ant2
WLAN5.2GHz Ant1+2
WLAN5.3GHz Ant1
WLAN5.3GHz Ant2
WLAN5.3GHz Ant1+2
WLAN5.5GHz Ant1
WLAN5.5GHz Ant2
WLAN5.5GHz Ant1+2
WLAN5.8GHz Ant1
WLAN5.8GHz Ant2
WLAN5.8GHz Ant1+2


Bottom Face
(moving away phantom)
Power (dBm)
Distance from the front face of the devnce (mm)
WLAN2.4GHz Ant1
WLAN2.4GHz Ant2
WLAN2.4GHz Ant1+2
WLAN5.2GHz Ant1
WLAN5.2GHz Ant2
WLAN5.2GHz Ant1+2
WLAN5.3GHz Ant1
WLAN5.3GHz Ant2
WLAN5.3GHz Ant1+2
WLAN5.5GHz Ant1
WLAN5.5GHz Ant2
WLAN5.5GHz Ant1+2
WLAN5.8GHz Ant1
WLAN5.8GHz Ant2
WLAN5.8GHz Ant1+2


Edge 1
(moving toward phantom)
Power (dBm)
Distance from the rear face of the device (mm)
WLAN2.4GHz Ant1
WLAN2.4GHz Ant2
WLAN2.4GHz Ant1+2
WLAN5.2GHz Ant1
WLAN5.2GHz Ant2
WLAN5.2GHz Ant1+2
WLAN5.3GHz Ant1
WLAN5.3GHz Ant2
WLAN5.3GHz Ant1+2
WLAN5.5GHz Ant1
WLAN5.5GHz Ant2
WLAN5.5GHz Ant1+2
WLAN5.8GHz Ant1
WLAN5.8GHz Ant2
WLAN5.8GHz Ant1+2


Edge 1
(moving away phantom)
Power (dBm)
Distance from the rear face of the device (mm)
WLAN2.4GHz Ant1
WLAN2.4GHz Ant2
WLAN2.4GHz Ant1+2
WLAN5.2GHz Ant1
WLAN5.2GHz Ant2
WLAN5.2GHz Ant1+2
WLAN5.3GHz Ant1
WLAN5.3GHz Ant2
WLAN5.3GHz Ant1+2
WLAN5.5GHz Ant1
WLAN5.5GHz Ant2
WLAN5.5GHz Ant1+2
WLAN5.8GHz Ant1
WLAN5.8GHz Ant2
WLAN5.8GHz Ant1+2

# 6. RF Exposure Limits

## 6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

## 6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|---|---|---|
| 0.4 | 8.0 | 20.0 |

**Limits for General Population/Uncontrolled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|---|---|---|
| 0.08 | 1.6 | 4.0 |

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

# 7. Specific Absorption Rate (SAR)

## 7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

## 7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\mathbf{dm}}\right) = \frac{\mathbf{d}}{\mathbf{dt}}\left(\frac{\mathbf{dW}}{\boldsymbol{\rho}\mathbf{dv}}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

$$\mathbf{SAR} = \frac{\boldsymbol{\sigma}|\mathbf{E}|^2}{\boldsymbol{\rho}}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

# 8. System Description and Setup

**The DASY system used for performing compliance tests consists of the following items:**




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## 8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**<EX3DV4 Probe>**

| | |
|---|---|
| **Construction** | Symmetric design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| **Frequency** | 10 MHz – >6 GHz<br>Linearity: ±0.2 dB (30 MHz – 6 GHz) |
| **Directivity** | ±0.3 dB in TSL (rotation around probe axis)<br>±0.5 dB in TSL (rotation normal to probe axis) |
| **Dynamic Range** | 10 μW/g – >100 mW/g<br>Linearity: ±0.2 dB (noise: typically <1 μW/g) |
| **Dimensions** | Overall length: 337 mm (tip: 20 mm)<br>Tip diameter: 2.5 mm (body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm |

## 8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

**Photo of DAE**

## 8.3 Phantom

**<SAM Twin Phantom>**

| | | |
|---|---|---|
| **Shell Thickness** | 2 ± 0.2 mm;<br>Center ear point: 6 ± 0.2 mm | |
| **Filling Volume** | Approx. 25 liters | |
| **Dimensions** | Length: 1000 mm; Width: 500 mm; Height: adjustable feet | |
| **Measurement Areas** | Left Hand, Right Hand, Flat Phantom | |

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

**<ELI Phantom>**

| | | |
|---|---|---|
| **Shell Thickness** | 2 ± 0.2 mm (sagging: <1%) | |
| **Filling Volume** | Approx. 30 liters | |
| **Dimensions** | Major ellipse axis: 600 mm<br>Minor axis: 400 mm | |

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

## 8.4 Device Holder

**<Mounting Device for Hand-Held Transmitter>**

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.

Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

**<Mounting Device for Laptops and other Body-Worn Transmitters>**

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.

Mounting Device for Laptops

# 9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

(a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
(b) Read the WWAN RF power level from the base station simulator.
(c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
(d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

(a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
(b) Place the EUT in the positions as Appendix D demonstrates.
(c) Set scan area, grid size and other setting on the DASY software.
(d) Measure SAR results for the highest power channel on each testing position.
(e) Find out the largest SAR result on these testing positions of each band
(f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

(a) Power reference measurement
(b) Area scan
(c) Zoom scan
(d) Power drift measurement

## 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

(a) Extraction of the measured data (grid and values) from the Zoom Scan
(b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
(c) Generation of a high-resolution mesh within the measured volume
(d) Interpolation of all measured values form the measurement grid to the high-resolution grid
(e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
(f) Calculation of the averaged SAR within masses of 1g and 10g

## 9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

## 9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

| | ≤ 3 GHz | > 3 GHz |
|---|---|---|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | 5 ± 1 mm | ½·δ·ln(2) ± 0.5 mm |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location | 30° ± 1° | 20° ± 1° |
| Maximum area scan spatial resolution: $\Delta x_{Area}$, $\Delta y_{Area}$ | ≤ 2 GHz: ≤ 15 mm<br>2 – 3 GHz: ≤ 12 mm | 3 – 4 GHz: ≤ 12 mm<br>4 – 6 GHz: ≤ 10 mm |
| | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. | |

## 9.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

| | | | ≤ 3 GHz | > 3 GHz |
|---|---|---|---|---|
| Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$, $\Delta y_{Zoom}$ | | | ≤ 2 GHz: ≤ 8 mm<br>2 – 3 GHz: ≤ 5 mm* | 3 – 4 GHz: ≤ 5 mm*<br>4 – 6 GHz: ≤ 4 mm* |
| Maximum zoom scan spatial resolution, normal to phantom surface | uniform grid: $\Delta z_{Zoom}(n)$ | | ≤ 5 mm | 3 – 4 GHz: ≤ 4 mm<br>4 – 5 GHz: ≤ 3 mm<br>5 – 6 GHz: ≤ 2 mm |
| | graded grid | $\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface | ≤ 4 mm | 3 – 4 GHz: ≤ 3 mm<br>4 – 5 GHz: ≤ 2.5 mm<br>5 – 6 GHz: ≤ 2 mm |
| | | $\Delta z_{Zoom}(n>1)$: between subsequent points | $\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$ | |
| Minimum zoom scan volume | x, y, z | | ≥ 30 mm | 3 – 4 GHz: ≥ 28 mm<br>4 – 5 GHz: ≥ 25 mm<br>5 – 6 GHz: ≥ 22 mm |

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

## 9.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## 9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

# 10. Test Equipment List

| Manufacturer | Name of Equipment | Type/Model | Serial Number | Calibration | |
|---|---|---|---|---|---|
| | | | | Last Cal. | Due Date |
| SPEAG | 2450MHz System Validation Kit | D2450V2 | 908 | 2019/3/25 | 2022/3/23 |
| SPEAG | 5000MHz System Validation Kit | D5GHzV2 | 1113 | 2019/9/24 | 2022/9/23 |
| SPEAG | Data Acquisition Electronics | DAE4 | 1649 | 2021/2/3 | 2022/2/2 |
| SPEAG | Dosimetric E-Field Probe | EX3DV4 | 7627 | 2021/2/10 | 2022/2/9 |
| SPEAG | ELI4 Phantom | ELI V8.0 | TP-2135 | NCR | NCR |
| Testo | Hygrometer | 608-H1 | 1241332126 | 2021/1/7 | 2022/1/6 |
| SPEAG | Phone Positioner | N/A | N/A | NCR | NCR |
| Agilent | ENA Series Network Analyzer | E5071C | MY46112129 | 2020/10/17 | 2021/10/16 |
| SPEAG | Dielectric Probe Kit | DAK-3.5 | 1144 | 2020/12/2 | 2021/12/1 |
| Anritsu | Vector Signal Generator | MG3710A | 6201682672 | 2021/1/7 | 2022/1/6 |
| Rohde & Schwarz | Power Meter | NRVD | 102081 | 2020/8/13 | 2021/8/12 |
| Rohde & Schwarz | Power Sensor | NRV-Z5 | 100538 | 2020/8/13 | 2021/8/12 |
| Rohde & Schwarz | Power Sensor | NRV-Z5 | 100539 | 2020/8/13 | 2021/8/12 |
| R&S | CBT BLUETOOTH TESTER | CBT | 101246 | 2021/4/12 | 2022/4/11 |
| EXA | Spectrum Analyzer | FSV7 | 101632 | 2021/1/7 | 2022/1/6 |
| FLUKE | DIGITAC THERMOMETER | 51II | 97240029 | 2020/8/14 | 2021/8/13 |
| ARRA | Power Divider | A3200-2 | N/A | Note 1 | |
| MCL | Attenuation1 | BW-S10W5+ | N/A | Note 1 | |
| MCL | Attenuation2 | BW-S10W5+ | N/A | Note 1 | |
| MCL | Attenuation3 | BW-S10W5+ | N/A | Note 1 | |
| BONN | POWER AMPLIFIER | BLMA 0830-3 | 087193A | Note 1 | |
| BONN | POWER AMPLIFIER | BLMA 2060-2 | 087193B | Note 1 | |
| Agilent | Dual Directional Coupler | 778D | 20500 | Note 1 | |
| Agilent | Dual Directional Coupler | 11691D | MY48151020 | Note 1 | |

**Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

# 11. System Verification

## 11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1.

**Fig 11.1 Photo of Liquid Height for Body SAR**

## 11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Frequency (MHz) | Water (%) | Sugar (%) | Cellulose (%) | Salt (%) | Preventol (%) | DGBE (%) | Conductivity (σ) | Permittivity (εr) |
|---|---|---|---|---|---|---|---|---|
| For Head | | | | | | | | |
| 2450 | 55.0 | 0 | 0 | 0 | 0 | 45.0 | 1.80 | 39.2 |

Simulating Liquid for 5GHz, Manufactured by SPEAG

| Ingredients | (% by weight) |
|---|---|
| Water | 64~78% |
| Mineral oil | 11~18% |
| Emulsifiers | 9~15% |
| Additives and Salt | 2~3% |

### <Tissue Dielectric Parameter Check Results>

| Frequency (MHz) | Tissue Type | Liquid Temp. (℃) | Conductivity (σ) | Permittivity ($\varepsilon_r$) | Conductivity Target (σ) | Permittivity Target ($\varepsilon_r$) | Delta (σ) (%) | Delta ($\varepsilon_r$) (%) | Limit (%) | Date |
|---|---|---|---|---|---|---|---|---|---|---|
| 2450 | Head | 22.7 | 1.856 | 39.175 | 1.80 | 39.20 | 3.11 | -0.06 | ±5 | 2021/7/7 |
| 5250 | Head | 22.9 | 4.677 | 36.317 | 4.71 | 35.90 | -0.70 | 1.16 | ±5 | 2021/7/13 |
| 5600 | Head | 22.6 | 5.018 | 35.708 | 5.07 | 35.50 | -1.03 | 0.59 | ±5 | 2021/7/18 |
| 5750 | Head | 22.8 | 5.258 | 35.377 | 5.22 | 35.40 | 0.73 | -0.06 | ±5 | 2021/7/26 |

## 11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

| Date | Frequency (MHz) | Tissue Type | Input Power (mW) | Dipole S/N | Probe S/N | DAE S/N | Measured 1g SAR (W/kg) | Targeted 1g SAR (W/kg) | Normalized 1g SAR (W/kg) | Deviation (%) |
|---|---|---|---|---|---|---|---|---|---|---|
| 2021/7/7 | 2450 | Head | 50 | 908 | 7627 | 1649 | 2.51 | 52.80 | 50.2 | -4.92 |
| 2021/7/13 | 5250 | Head | 50 | 1113 | 7627 | 1649 | 3.80 | 80.50 | 76 | -5.59 |
| 2021/7/18 | 5600 | Head | 50 | 1113 | 7627 | 1649 | 4.18 | 83.40 | 83.6 | 0.24 |
| 2021/7/26 | 5750 | Head | 50 | 1113 | 7627 | 1649 | 3.88 | 80.00 | 77.6 | -3.00 |




Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

# 12. RF Exposure Positions

## 12.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

**<EUT Setup Photos>**

Please refer to Appendix D for the test setup photos.

# 13. Conducted RF Output Power (Unit: dBm)

**<WLAN Conducted Power>**

**General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
   a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
   b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
   c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. 802.11ax supports full tone size and partial tone size, for full tone size with higher power level, So only chose full tone size to perform SAR testing.

## <2.4GHz Bluetooth>

**General Note:**

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.90 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to100% for Bluetooth reported SAR calculation.

**Bluetooth time-domain plot**



# 14. Antenna Location




***Front Face***

## <SAR test exclusion table>

**General Note:**

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:
   [(*max. power of channel, including tune-up tolerance, mW*)/(*min. test separation distance, mm*)] ·[√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
   - f(GHz) is the RF channel transmit frequency in GHz
   - Power and distance are rounded to the nearest mW and mm before calculation
   - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
   a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)·( f(MHz)/150)] mW, at 100 MHz to 1500 MHz
   b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz

| | Wireless Interface | BT | 2.4GHz WLAN ANT 1 | 2.4GHz WLAN ANT 2 | 2.4GHz WLAN ANT 1+2 | 5GHz WLAN ANT 1 | 5GHz WLAN ANT 2 | 5GHz WLAN ANT 1+2 |
|---|---|---|---|---|---|---|---|---|
| Exposure Position | Calculated Frequency | 2480MHz | 2462MHz | 2462MHz | 2462MHz | 5825MHz | 5825MHz | 5825MHz |
| | Maximum power (dBm) | 7 | 20.5 | 20 | 23.5 | 20.5 | 20 | 23 |
| | Maximum rated power(mW) | 5.0 | 112.0 | 100.0 | 224.0 | 112.0 | 100.0 | 200.0 |
| Bottom Face | Separation distance(mm) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| | exclusion threshold | 1.6 | 35.2 | 31.4 | 70.3 | 54.1 | 48.3 | 96.5 |
| | Testing required? | No | Yes | Yes | Yes | Yes | Yes | Yes |
| Edge 1 | Separation distance(mm) | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 |
| | exclusion threshold | 1.6 | 35.2 | 31.4 | 70.3 | 54.1 | 48.3 | 96.5 |
| | Testing required? | No | Yes | Yes | Yes | Yes | Yes | Yes |
| Edge 2 | Separation distance(mm) | 101.0 | 101.0 | 172.0 | 101.0 | 101.0 | 172.0 | 101.0 |
| | exclusion threshold | 605.0 | 606.0 | 1316.0 | 606.0 | 572.0 | 1282.0 | 572.0 |
| | Testing required? | No | No | No | No | No | No | No |
| Edge 3 | Separation distance(mm) | 180.0 | 180.0 | 180.0 | 180.0 | 180.0 | 180.0 | 180.0 |
| | exclusion threshold | 1395.0 | 1396.0 | 1396.0 | 1396.0 | 1362.0 | 1362.0 | 1362.0 |
| | Testing required? | No | No | No | No | No | No | No |
| Edge 4 | Separation distance(mm) | 165.0 | 165.0 | 101.0 | 101.0 | 165.0 | 101.0 | 101.0 |
| | exclusion threshold | 1245.0 | 1246.0 | 606.0 | 606.0 | 1212.0 | 572.0 | 572.0 |
| | Testing required? | No | No | No | No | No | No | No |

# 15. SAR Test Results

**General Note:**

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
   a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
   b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
   c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
   · ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
   · ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
   · ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.

**WLAN Note:**

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.
6. SISO and MIMO all supported by WLAN2.4GHz/WLAN5GHz, for SISO mode power is less than per chain power of MIMO mode. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power.
7. For the conducted power measurement is MIMO chains transmitting simultaneously and measured the separately conducted power for both chains and then based on the conducted power of SISO antenna respectively to calculate sum of the power for MIMO mode.
8. 802.11ax full tone size and partial tone size, for full tone size with higher power level, So only chose full tone size to perform SAR testing
9. Only chose MIMO power to perform SAR testing.

## 15.1 Body SAR

### <WLAN2.4GHz SAR>

| Plot No. | Sample | Band | Mode | Test Position | Gap (mm) | Antenna | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Bottom Face | 0mm | Ant 1+2 | Reduced | 1 | 2412 | 14.53 | 15.50 | 1.250 | 98.29 | 1.017 | 0.07 | 0.540 | 0.687 |
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 1 | 2412 | 14.53 | 15.50 | 1.250 | 98.29 | 1.017 | 0.06 | 0.801 | 1.018 |
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 6 | 2437 | 14.27 | 15.50 | 1.327 | 98.29 | 1.017 | 0.01 | 0.698 | 0.942 |
| 01 | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 11 | 2462 | 14.30 | 15.50 | 1.318 | 98.29 | 1.017 | -0.04 | 0.802 | **1.075** |
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Bottom Face | 10mm | Ant 1+2 | Full | 1 | 2412 | 22.12 | 23.50 | 1.374 | 98.29 | 1.017 | 0.04 | 0.546 | 0.763 |
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 13mm | Ant 1+2 | Full | 11 | 2462 | 21.70 | 23.50 | 1.514 | 98.29 | 1.017 | 0.02 | 0.601 | 0.925 |
| | 2 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 11 | 2462 | 14.30 | 15.50 | 1.318 | 98.29 | 1.017 | 0.07 | 0.801 | 1.074 |
| tablet with stylus | | | | | | | | | | | | | | | | | |
| | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 11 | 2462 | 14.30 | 15.50 | 1.318 | 98.29 | 1.017 | -0.06 | 0.791 | 1.060 |

### <Bluetooth SAR>

| Plot No. | Sample | Band | Mode | Test Position | Gap (mm) | Antenna | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 1 | Bluetooth | 1Mbps | Bottom Face | 0mm | Ant 1 | Full | 39 | 2441 | 6.80 | 7.00 | 1.047 | 76.9 | 1.300 | 0.07 | 0.172 | 0.234 |
| | 1 | Bluetooth | 1Mbps | Edge 1 | 0mm | Ant 1 | Full | 39 | 2441 | 6.80 | 7.00 | 1.047 | 76.9 | 1.300 | 0.1 | 0.219 | 0.298 |
| | 1 | Bluetooth | 1Mbps | Edge 1 | 0mm | Ant 1 | Full | 0 | 2402 | 6.30 | 7.00 | 1.175 | 76.9 | 1.300 | 0.02 | 0.239 | 0.365 |
| 02 | 1 | Bluetooth | 1Mbps | Edge 1 | 0mm | Ant 1 | Full | 78 | 2480 | 6.00 | 7.00 | 1.259 | 76.9 | 1.300 | 0.07 | 0.233 | **0.381** |
| | 2 | Bluetooth | 1Mbps | Edge 1 | 0mm | Ant 1 | Full | 78 | 2480 | 6.00 | 7.00 | 1.259 | 76.9 | 1.300 | 0.07 | 0.191 | 0.313 |
| tablet with stylus | | | | | | | | | | | | | | | | | |
| | 1 | Bluetooth | 1Mbps | Edge 1 | 0mm | Ant 1 | Full | 78 | 2480 | 6.00 | 7.00 | 1.259 | 76.9 | 1.300 | 0.02 | 0.211 | 0.345 |

### <WLAN5G SAR>

| Plot No. | Sample | Band | Mode | Test Position | Gap (mm) | Antenna | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 1 | WLAN5.3GHz | 802.11ac-VHT80 MCS0 | Bottom Face | 0mm | Ant 1+2 | Reduced | 58 | 5290 | 12.02 | 13.00 | 1.253 | 100 | 1.000 | -0.01 | 0.611 | 0.766 |
| 03 | 1 | WLAN5.3GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 58 | 5290 | 12.02 | 13.00 | 1.253 | 100 | 1.000 | 0.09 | 0.799 | **1.001** |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Edge 2 | 0mm | Ant 1+2 | Full | 54 | 5270 | 21.94 | 23.00 | 1.276 | 100 | 1.000 | 0.09 | 0.169 | 0.216 |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Edge 3 | 0mm | Ant 1+2 | Full | 54 | 5270 | 21.94 | 23.00 | 1.276 | 100 | 1.000 | 0.02 | 0.051 | 0.065 |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Edge 4 | 0mm | Ant 1+2 | Full | 54 | 5270 | 21.94 | 23.00 | 1.276 | 100 | 1.000 | 0.04 | 0.224 | 0.286 |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Bottom Face | 10mm | Ant 1+2 | Full | 54 | 5270 | 21.94 | 23.00 | 1.276 | 100 | 1.000 | -0.06 | 0.459 | 0.586 |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Bottom Face | 10mm | Ant 1+2 | Full | 62 | 5310 | 19.53 | 20.50 | 1.250 | 100 | 1.000 | 0.02 | 0.395 | 0.494 |
| | 1 | WLAN5.3GHz | 802.11n-HT40 MCS0 | Edge 1 | 13mm | Ant 1+2 | Full | 54 | 5270 | 21.94 | 23.00 | 1.276 | 100 | 1.000 | 0.05 | 0.317 | 0.405 |
| | 2 | WLAN5.3GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 58 | 5290 | 12.02 | 13.00 | 1.253 | 100 | 1.000 | 0.04 | 0.453 | 0.568 |
| tablet with stylus | | | | | | | | | | | | | | | | | |
| | 1 | WLAN5.3GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 58 | 5290 | 12.02 | 13.00 | 1.253 | 100 | 1.000 | 0.08 | 0.646 | 0.810 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Bottom Face | 0mm | Ant 1+2 | Reduced | 138 | 5690 | 10.45 | 11.50 | 1.274 | 100 | 1.000 | -0.05 | 0.418 | 0.532 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 138 | 5690 | 10.45 | 11.50 | 1.274 | 100 | 1.000 | -0.03 | 0.635 | 0.809 |
| 04 | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 106 | 5530 | 10.23 | 11.50 | 1.340 | 100 | 1.000 | 0.03 | 0.755 | **1.011** |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 122 | 5610 | 9.80 | 11.50 | 1.479 | 100 | 1.000 | 0.01 | 0.454 | 0.672 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 2 | 0mm | Ant 1+2 | Full | 138 | 5690 | 22.40 | 23.00 | 1.148 | 100 | 1.000 | 0.09 | 0.132 | 0.152 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 3 | 0mm | Ant 1+2 | Full | 138 | 5690 | 22.40 | 23.00 | 1.148 | 100 | 1.000 | 0.02 | 0.057 | 0.065 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 4 | 0mm | Ant 1+2 | Full | 138 | 5690 | 22.40 | 23.00 | 1.148 | 100 | 1.000 | 0.01 | 0.172 | 0.197 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Bottom Face | 10mm | Ant 1+2 | Full | 138 | 5690 | 22.40 | 23.00 | 1.148 | 100 | 1.000 | 0.06 | 0.463 | 0.532 |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 13mm | Ant 1+2 | Full | 138 | 5690 | 22.40 | 23.00 | 1.149 | 100 | 1.000 | -0.02 | 0.420 | 0.482 |
| | 2 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 106 | 5530 | 10.23 | 11.50 | 1.340 | 100 | 1.000 | 0.03 | 0.428 | 0.573 |
| tablet with stylus | | | | | | | | | | | | | | | | | |
| | 1 | WLAN5.5GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 106 | 5530 | 10.23 | 11.50 | 1.340 | 100 | 1.000 | 0.05 | 0.543 | 0.727 |

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Bottom Face | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.08 | 0.520 | 0.676 |
| 05 | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.02 | 0.808 | **1.051** |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 2 | 0mm | Ant 1+2 | Full | 155 | 5775 | 22.09 | 23.00 | 1.233 | 100 | 1.000 | 0.09 | 0.149 | 0.184 |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 3 | 0mm | Ant 1+2 | Full | 155 | 5775 | 22.09 | 23.00 | 1.233 | 100 | 1.000 | -0.02 | 0.042 | 0.052 |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 4 | 0mm | Ant 1+2 | Full | 155 | 5775 | 22.09 | 23.00 | 1.233 | 100 | 1.000 | 0.04 | 0.257 | 0.317 |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Bottom Face | 10mm | Ant 1+2 | Full | 155 | 5775 | 22.09 | 23.00 | 1.233 | 100 | 1.000 | 0.09 | 0.370 | 0.456 |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 13mm | Ant 1+2 | Full | 155 | 5775 | 22.09 | 23.00 | 1.233 | 100 | 1.000 | 0.03 | 0.464 | 0.572 |
| | 2 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.08 | 0.437 | 0.568 |
| tablet with stylus | | | | | | | | | | | | | | | | | |
| | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.04 | 0.691 | 0.898 |

## 15.2 Repeated SAR Measurement

| No. | Sample | Band | Modulation | Test Position | Gap (mm) | Antenna | Power Reduction | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Ratio | Reported 1g SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1st | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 11 | 2462 | 14.30 | 15.50 | 1.318 | 98.29 | 1.017 | -0.04 | 0.802 | 1 | 1.075 |
| 2nd | 1 | WLAN2.4GHz | 802.11b 1Mbps | Edge 1 | 0mm | Ant 1+2 | Reduced | 11 | 2462 | 14.30 | 15.50 | 1.318 | 98.29 | 1.017 | 0.02 | 0.795 | 1.009 | 1.066 |
| 1st | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.02 | 0.808 | 1 | 1.051 |
| 2nd | 1 | WLAN5.8GHz | 802.11ac-VHT80 MCS0 | Edge 1 | 0mm | Ant 1+2 | Reduced | 155 | 5775 | 11.36 | 12.50 | 1.300 | 100 | 1.000 | 0.06 | 0.802 | 1.007 | 1.043 |

**General Note:**

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR <1.45W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

# 16. Simultaneous Transmission Analysis

| NO. | Simultaneous Transmission Configurations | Portable Tablet Computer |
|---|---|---|
| | | Body |
| 1. | WLAN5GHz + Bluetooth | Yes |
| 2. | WLAN 2.4GHz + NFC(WLC) | Yes |
| 3. | WLAB 5GHz + Bluetooth + NFC(WLC) | Yes |

**General Note:**

1. The 2.4GHz/5GHz WLAN can transmit in SISO/MIMO antenna mode.
2. RF Exposure report for WPT will be separately submitted. About co-located SAR with WLAN/Bluetooth, always chose higher SAR of WPT SAR.
3. For WLAN SAR testing was performed on dual antenna, due to the single antenna RF power in MIMO mode is larger than the single antenna RF power in SISO mode. Therefore, the following summations in MIMO mode can represent the absolute worst cases in SISO mode for simultaneous transmission.
4. EUT will choose either 2.4GHz WLAN or 5GHz WLAN according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
5. 2.4GHz WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
6. According to the EUT characteristic, WLAN 5GHz and Bluetooth can transmit simultaneously.
7. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
   i) 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
   ii) SPLSR = (SAR1 + SAR2)^1.5 / (min. separation distance, mm), and the peak separation distance is determined from the square root of [(x1-x2)2 + (y1-y2)2 + (z1-z2)2], where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
   iii) If SPLSR ≤ 0.04 for 1g SAR and SPLSR≤ 0.10 for 10g SAR , simultaneously transmission SAR measurement is not necessary.
   iv) Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
8. For simultaneous transmission SAR analysis, it is more conservative to choose SAR result tested without stylus since it is worse than tested with stylus.

## 16.1 Body Exposure Conditions

| Exposure Position | 1 | 2 | 3 | 4 | 2+3+4 | 1+4 |
|---|---|---|---|---|---|---|
| | 2.4GHz WLAN Ant 1+2 | 5GHz WLAN Ant 1+2 | Bluetooth Ant 1 | NFC(WLC) | Summed | Summed |
| | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) | 1g SAR (W/kg) |
| Bottom Face at 10mm | 0.763 | 0.586 | | 0.001 | 0.59 | 0.76 |
| Edge 1 at 13mm | 0.925 | 0.572 | | 0.001 | 0.57 | 0.93 |
| Bottom Face at 0mm | 0.687 | 0.766 | 0.234 | 0.001 | 1.00 | 0.69 |
| Edge 1 at 0mm | 1.075 | 1.051 | 0.381 | 0.001 | **1.43** | **1.08** |
| Edge 2 at 0mm | | 0.216 | 0.381 | 0.001 | 0.60 | 0.00 |
| Edge 3 at 0mm | | 0.065 | 0.381 | 0.001 | 0.45 | 0.00 |
| Edge 4 at 0mm | | 0.317 | 0.381 | 0.001 | 0.70 | 0.00 |

**Test Engineer :** Nick Hu, Seven Xu, Bruce Li

# 17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be ≤ 30%, for a confidence interval of k = 2. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

# 18. References


[1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”

[2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992

[3] IEEE Std. 1528-2013, “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, Sep 2013

[4] SPEAG DASY System Handbook

[5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.

[6] FCC KDB 865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations” Oct 2015.

[7] FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 2015

[8] FCC KDB 248227 D01 v02r02, “SAR Guidance for IEEE 802.11 (WiFi) Transmitters”, Oct 2015.

[9] FCC KDB 616217 D04 v01r02, “SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers”, Oct 2015


------THE END------

# Appendix A. Plots of System Performance Check

The plots are shown as follows.

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.7

**System Check_Head_2450MHz**

**DUT: D2450V2 - SN:908**

Communication System: UID 0, CW (0); Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: HSL_2450 Medium parameters used: f = 2450 MHz; $\sigma$ = 1.856 S/m; $\varepsilon_r$ = 39.175; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(8, 8, 8) @ 2450 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 3.71 W/kg

**Pin=50mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 46.96 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 4.69 W/kg
**SAR(1 g) = 2.51 W/kg; SAR(10 g) = 1.21 W/kg**
Maximum value of SAR (measured) = 3.82 W/kg




0 dB = 3.82 W/kg = 5.82 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.13

**System Check_Head_5250MHz**

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5250 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5250 MHz; $\sigma$ = 4.677 S/m; $\varepsilon_r$ = 36.317; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(5.69, 5.69, 5.69) @ 5250 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 8.97 W/kg

**Pin=50mW/Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 38.68 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 15.1 W/kg
**SAR(1 g) = 3.8 W/kg; SAR(10 g) = 1.1 W/kg**
Maximum value of SAR (measured) = 9.46 W/kg




0 dB = 9.46 W/kg = 9.76 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.18

**System Check_Head_5600MHz**

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5600 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5600 MHz; $\sigma$ = 5.018 S/m; $\varepsilon_r$ = 35.708; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(4.89, 4.89, 4.89) @ 5600 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 10.2 W/kg

**Pin=50mW/Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 40.22 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 18.4 W/kg
**SAR(1 g) = 4.18 W/kg; SAR(10 g) = 1.19 W/kg**
Maximum value of SAR (measured) = 10.8 W/kg




0 dB = 10.8 W/kg = 10.33 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.26

**System Check_Head_5750MHz**

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5750 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5750 MHz; $\sigma$ = 5.258 S/m; $\varepsilon_r$ = 35.377; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(4.92, 4.92, 4.92) @ 5750 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 9.61 W/kg

**Pin=50mW/Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 38.51 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 17.8 W/kg
**SAR(1 g) = 3.88 W/kg; SAR(10 g) = 1.11 W/kg**
Maximum value of SAR (measured) = 10.1 W/kg




0 dB = 10.1 W/kg = 10.04 dBW/kg

# Appendix B. Plots of SAR Measurement

The plots are shown as follows.

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.7

**01_WLAN2.4GHz_802.11b 1Mbps_Edge 1_0mm_Ch11**

Communication System: UID 0, WLAN2.4GHz (0); Frequency: 2462 MHz;Duty Cycle: 1:1.017
Medium: HSL_2450 Medium parameters used: f = 2462 MHz; $\sigma$ = 1.871 S/m; $\varepsilon_r$ = 39.21; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(8, 8, 8) @ 2462 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x151x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.4 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 27.11 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 2.99 W/kg
**SAR(1 g) = 0.802 W/kg; SAR(10 g) = 0.272 W/kg**
Maximum value of SAR (measured) = 1.89 W/kg




0 dB = 1.89 W/kg = 2.76 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.7

**02_Bluetooth_1Mbps_Edge 1_0mm_Ch78**

Communication System: UID 0, Bluetooth (0); Frequency: 2480 MHz;Duty Cycle: 1:1.3
Medium: HSL_2450 Medium parameters used: f = 2480 MHz; $\sigma$ = 1.885 S/m; $\varepsilon_r$ = 39.225; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(8, 8, 8) @ 2480 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (31x251x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.428 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.32 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 0.840 W/kg
**SAR(1 g) = 0.233 W/kg; SAR(10 g) = 0.081 W/kg**
Maximum value of SAR (measured) = 0.555 W/kg




0 dB = 0.555 W/kg = -2.56 dBW/kg

**03_WLAN5GHz_802.11ac-VHT80 MCS0_Edge 1_0mm_Ch58**

Communication System: UID 0, WLAN5GHz (0); Frequency: 5290 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5290 MHz; $\sigma$ = 4.683 S/m; $\varepsilon_r$ = 36.4; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：22.9 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(5.69, 5.69, 5.69) @ 5290 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x141x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.40 W/kg

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 19.29 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 5.56 W/kg
**SAR(1 g) = 0.799 W/kg; SAR(10 g) = 0.187 W/kg**
Maximum value of SAR (measured) = 2.48 W/kg




0 dB = 2.48 W/kg = 3.94 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.18

**04_WLAN5GHz_802.11ac-VHT80 MCS0_Edge 1_0mm_Ch106**

Communication System: UID 0, WLAN5GHz (0); Frequency: 5530 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5530 MHz; $\sigma$ = 4.962 S/m; $\varepsilon_r$ = 35.774; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(4.89, 4.89, 4.89) @ 5530 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x141x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.33 W/kg

**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 17.88 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 5.57 W/kg
**SAR(1 g) = 0.755 W/kg; SAR(10 g) = 0.176 W/kg**
Maximum value of SAR (measured) = 2.40 W/kg




0 dB = 2.40 W/kg = 3.80 dBW/kg

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 2021.7.26

**05_WLAN5GHz_802.11ac-VHT80 MCS0_Edge 1_0mm_Ch155**

Communication System: UID 0, WLAN5GHz (0); Frequency: 5775 MHz;Duty Cycle: 1:1
Medium: HSL_5000 Medium parameters used: f = 5775 MHz; $\sigma$ = 5.284 S/m; $\varepsilon_r$ = 35.508; $\rho$ = 1000 kg/m$^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7627; ConvF(4.92, 4.92, 4.92) @ 5775 MHz; Calibrated: 2021.2.10
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1649; Calibrated: 2021.2.3
- Phantom: ELI Phantom; Type: ELI V8.0; Serial: TP-2135
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (51x141x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.61 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 17.71 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 6.08 W/kg
**SAR(1 g) = 0.808 W/kg; SAR(10 g) = 0.189 W/kg**
Maximum value of SAR (measured) = 2.68 W/kg




0 dB = 2.68 W/kg = 4.28 dBW/kg

# Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.

In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client **Sporton** **Certificate No: Z19-60087**

# CALIBRATION CERTIFICATE

| | |
|---|---|
| Object | D2450V2 - SN: 908 |
| Calibration Procedure(s) | FF-Z11-003-01<br>Calibration Procedures for dipole validation kits |
| Calibration date: | March 25, 2019 |

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|---|---|---|---|
| Power Meter NRP2 | 106277 | 20-Aug-18 (CTTL, No.J18X06862) | Aug-19 |
| Power sensor NRP8S | 104291 | 20-Aug-18 (CTTL, No.J18X06862) | Aug-19 |
| Reference Probe EX3DV4 | SN 3617 | 31-Jan-19(SPEAG,No.EX3-3617_Jan19) | Jan-20 |
| DAE4 | SN 1331 | 06-Feb-19(SPEAG,No.DAE4-1331_Feb19) | Feb-20 |
| **Secondary Standards** | **ID #** | **Cal Date(Calibrated by, Certificate No.)** | **Scheduled Calibration** |
| Signal Generator E4438C | MY49071430 | 23-Jan-19 (CTTL, No.J19X00336) | Jan-20 |
| NetworkAnalyzer E5071C | MY46110673 | 24-Jan-19 (CTTL, No.J19X00547) | Jan-20 |

| | Name | Function | Signature |
|---|---|---|---|
| Calibrated by: | Zhao Jing | SAR Test Engineer | |
| Reviewed by: | Lin Hao | SAR Test Engineer | |
| Approved by: | Qi Dianyuan | SAR Project Leader | |

Issued: March 28, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

**Glossary:**

| | |
|---|---|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORMx,y,z |
| N/A | not applicable or not measured |

**Calibration is Performed According to the Following Standards:**

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

b) IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016

c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010

d) KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

**Additional Documentation:**

e) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|---|---|---|
| **DASY Version** | DASY52 | 52.10.2.1495 |
| **Extrapolation** | Advanced Extrapolation | |
| **Phantom** | Triple Flat Phantom 5.1C | |
| **Distance Dipole Center - TSL** | 10 mm | with Spacer |
| **Zoom Scan Resolution** | dx, dy, dz = 5 mm | |
| **Frequency** | 2450 MHz ± 1 MHz | |

## Head TSL parameters

The following parameters and calculations were applied.

| | **Temperature** | **Permittivity** | **Conductivity** |
|---|---|---|---|
| **Nominal Head TSL parameters** | 22.0 °C | 39.2 | 1.80 mho/m |
| **Measured Head TSL parameters** | (22.0 ± 0.2) °C | 39.6 ± 6 % | 1.84 mho/m ± 6 % |
| **Head TSL temperature change during test** | <1.0 °C | ---- | ---- |

## SAR result with Head TSL

| **SAR averaged over 1 $cm^3$ (1 g) of Head TSL** | Condition | |
|---|---|---|
| SAR measured | 250 mW input power | 13.3 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **52.8 W/kg ± 18.8 % (k=2)** |
| **SAR averaged over 10 $cm^3$ (10 g) of Head TSL** | Condition | |
| SAR measured | 250 mW input power | 6.07 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **24.2 W/kg ± 18.7 % (k=2)** |

## Body TSL parameters

The following parameters and calculations were applied.

| | **Temperature** | **Permittivity** | **Conductivity** |
|---|---|---|---|
| **Nominal Body TSL parameters** | 22.0 °C | 52.7 | 1.95 mho/m |
| **Measured Body TSL parameters** | (22.0 ± 0.2) °C | 53.8 ± 6 % | 2.00 mho/m ± 6 % |
| **Body TSL temperature change during test** | <1.0 °C | ---- | ---- |

## SAR result with Body TSL

| **SAR averaged over 1 $cm^3$ (1 g) of Body TSL** | Condition | |
|---|---|---|
| SAR measured | 250 mW input power | 12.8 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | **50.8 W/kg ± 18.8 % (k=2)** |
| **SAR averaged over 10 $cm^3$ (10 g) of Body TSL** | Condition | |
| SAR measured | 250 mW input power | 5.91 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | **23.6 W/kg ± 18.7 % (k=2)** |

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

## Appendix (Additional assessments outside the scope of CNAS L0570)

### Antenna Parameters with Head TSL

| | |
|---|---|
| Impedance, transformed to feed point | 57.3Ω+ 5.18 jΩ |
| Return Loss | - 21.6dB |

### Antenna Parameters with Body TSL

| | |
|---|---|
| Impedance, transformed to feed point | 52.6Ω+ 5.81 jΩ |
| Return Loss | - 24.1dB |

### General Antenna Parameters and Design

| | |
|---|---|
| Electrical Delay (one direction) | 1.020 ns |

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

| | |
|---|---|
| Manufactured by | SPEAG |

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Head TSL** Date: 03.25.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 908**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz; $\sigma$ = 1.841 S/m; $\varepsilon_r$ = 39.63; $\rho$ = 1000 kg/m3

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.62, 7.62, 7.62) @ 2450 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Dipole Calibration**/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.04 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 28.3 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.07 W/kg**

Maximum value of SAR (measured) = 22.4 W/kg




**0 dB = 22.4 W/kg = 13.50 dBW/kg**

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

## Impedance Measurement Plot for Head TSL



In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Body TSL** Date: 03.25.2019

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 908**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz; $\sigma$ = 2.003 S/m; $\varepsilon_r$ = 53.78; $\rho$ = 1000 kg/m3

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.79, 7.79, 7.79) @ 2450 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Dipole Calibration**/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.51 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 27.1 W/kg

**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.91 W/kg**

Maximum value of SAR (measured) = 21.4 W/kg




**0 dB = 21.4 W/kg = 13.30 dBW/kg**

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

## Impedance Measurement Plot for Body TSL



# D2450V2, Serial No. 908 Extended Dipole Calibrations

Referring to KDB 865664 D01 v01r02, if dipoles are verified in return loss (<-20dB, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended.

| D2450V2 – serial no. 908 | | | | | | |
|---|---|---|---|---|---|---|
| 2450 Head | | | | | | |
| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
| 2019.3.25 | -21.60 | | 57.28 | | 5.18 | |
| 2020.3.24 | -22.7 | -0.05 | 57.5 | -0.18 | 2.4 | 2.81 |
| 2021.3.24 | -21.30 | 0.01 | 55.80 | 1.49 | 5.67 | -0.49 |

**<Justification of the extended calibration>**

The return loss is < -20dB, within 20% of prior calibration; the impedance is within 5 ohm of prior calibration. Therefore the verification result should support extended calibration.

**Dipole Verification Data> D2450V2, serial no. 908**

**2450MHz – Head----2020.3.24**




**2450MHz – Head----2021.3.24**





***SPORTON INTERNATIONAL (KUNSHAN) INC.***

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

**Calibration Laboratory of**
Schmid & Partner
Engineering AG
**Zeughausstrasse 43, 8004 Zurich, Switzerland**

**S** Schweizerischer Kalibrierdienst
**C** Service suisse d'étalonnage
Servizio svizzero di taratura
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates**

**Accreditation No.: SCS 0108**

**Client** Sporton

**Certificate No: D5GHzV2-1113_Sep19**

# CALIBRATION CERTIFICATE

| | |
|---|---|
| Object | D5GHzV2 - SN:1113 |
| Calibration procedure(s) | QA CAL-22.v4<br>Calibration Procedure for SAR Validation Sources between 3-6 GHz |
| Calibration date: | September 24, 2019 |

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|---|---|---|---|
| Power meter NRP | SN: 104778 | 03-Apr-19 (No. 217-02892/02893) | Apr-20 |
| Power sensor NRP-Z91 | SN: 103244 | 03-Apr-19 (No. 217-02892) | Apr-20 |
| Power sensor NRP-Z91 | SN: 103245 | 03-Apr-19 (No. 217-02893) | Apr-20 |
| Reference 20 dB Attenuator | SN: 5058 (20k) | 04-Apr-19 (No. 217-02894) | Apr-20 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 04-Apr-19 (No. 217-02895) | Apr-20 |
| Reference Probe EX3DV4 | SN: 3503 | 25-Mar-19 (No. EX3-3503_Mar19) | Mar-20 |
| DAE4 | SN: 601 | 30-Apr-19 (No. DAE4-601_Apr19) | Apr-20 |

| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
|---|---|---|---|
| Power meter E4419B | SN: GB39512475 | 30-Oct-14 (in house check Feb-19) | In house check: Oct-20 |
| Power sensor HP 8481A | SN: US37292783 | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| Power sensor HP 8481A | SN: MY41092317 | 07-Oct-15 (in house check Oct-18) | In house check: Oct-20 |
| RF generator R&S SMT-06 | SN: 100972 | 15-Jun-15 (in house check Oct-18) | In house check: Oct-20 |
| Network Analyzer Agilent E8358A | SN: US41080477 | 31-Mar-14 (in house check Oct-18) | In house check: Oct-19 |

| | Name | Function | Signature |
|---|---|---|---|
| Calibrated by: | Jeton Kastrati | Laboratory Technician | |
| Approved by: | Katja Pokovic | Technical Manager | |

Issued: September 25, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

## Glossary:

| | |
|---|---|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

## Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Additional Documentation:

e) DASY4/5 System Handbook

## Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|---|---|---|
| **DASY Version** | DASY5 | V52.10.2 |
| **Extrapolation** | Advanced Extrapolation | |
| **Phantom** | Modular Flat Phantom V5.0 | |
| **Distance Dipole Center - TSL** | 10 mm | with Spacer |
| **Zoom Scan Resolution** | dx, dy = 4.0 mm, dz = 1.4 mm | Graded Ratio = 1.4 (Z direction) |
| **Frequency** | 5250 MHz ± 1 MHz<br>5600 MHz ± 1 MHz<br>5750 MHz ± 1 MHz | |

## Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

| | **Temperature** | **Permittivity** | **Conductivity** |
|---|---|---|---|
| **Nominal Head TSL parameters** | 22.0 °C | 35.9 | 4.71 mho/m |
| **Measured Head TSL parameters** | (22.0 ± 0.2) °C | 35.1 ± 6 % | 4.53 mho/m ± 6 % |
| **Head TSL temperature change during test** | < 0.5 °C | ---- | ---- |

## SAR result with Head TSL at 5250 MHz

| **SAR averaged over 1 $cm^3$ (1 g) of Head TSL** | Condition | |
|---|---|---|
| SAR measured | 100 mW input power | 8.09 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **80.5 W/kg ± 19.9 % (k=2)** |

| **SAR averaged over 10 $cm^3$ (10 g) of Head TSL** | condition | |
|---|---|---|
| SAR measured | 100 mW input power | 2.33 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **23.1 W/kg ± 19.5 % (k=2)** |

## Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

| | **Temperature** | **Permittivity** | **Conductivity** |
|---|---|---|---|
| **Nominal Head TSL parameters** | 22.0 °C | 35.5 | 5.07 mho/m |
| **Measured Head TSL parameters** | (22.0 ± 0.2) °C | 34.6 ± 6 % | 4.88 mho/m ± 6 % |
| **Head TSL temperature change during test** | < 0.5 °C | ---- | ---- |

## SAR result with Head TSL at 5600 MHz

| **SAR averaged over 1 $cm^3$ (1 g) of Head TSL** | Condition | |
|---|---|---|
| SAR measured | 100 mW input power | 8.40 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **83.4 W/kg ± 19.9 % (k=2)** |

| **SAR averaged over 10 $cm^3$ (10 g) of Head TSL** | condition | |
|---|---|---|
| SAR measured | 100 mW input power | 2.40 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **23.8 W/kg ± 19.5 % (k=2)** |

## Head TSL parameters at 5750 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|---|---|---|
| **Nominal Head TSL parameters** | 22.0 °C | 35.4 | 5.22 mho/m |
| **Measured Head TSL parameters** | (22.0 ± 0.2) °C | 34.4 ± 6 % | 5.03 mho/m ± 6 % |
| **Head TSL temperature change during test** | < 0.5 °C | ---- | ---- |

## SAR result with Head TSL at 5750 MHz

| **SAR averaged over 1 $cm^3$ (1 g) of Head TSL** | Condition | |
|---|---|---|
| SAR measured | 100 mW input power | 8.06 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **80.0 W/kg ± 19.9 % (k=2)** |

| **SAR averaged over 10 $cm^3$ (10 g) of Head TSL** | condition | |
|---|---|---|
| SAR measured | 100 mW input power | 2.30 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | **22.8 W/kg ± 19.5 % (k=2)** |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL at 5250 MHz

| | |
|---|---|
| Impedance, transformed to feed point | 51.7 Ω - 6.2 jΩ |
| Return Loss | - 24.0 dB |

### Antenna Parameters with Head TSL at 5600 MHz

| | |
|---|---|
| Impedance, transformed to feed point | 56.0 Ω - 2.7 jΩ |
| Return Loss | - 24.1 dB |

### Antenna Parameters with Head TSL at 5750 MHz

| | |
|---|---|
| Impedance, transformed to feed point | 56.7 Ω - 1.0 jΩ |
| Return Loss | - 23.9 dB |

### General Antenna Parameters and Design

| | |
|---|---|
| Electrical Delay (one direction) | 1.195 ns |

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

| | |
|---|---|
| Manufactured by | SPEAG |

## DASY5 Validation Report for Head TSL

Date: 24.09.2019

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1113**

Communication System: UID 0 - CW; Frequency: 5250 MHz, Frequency: 5600 MHz, Frequency: 5750 MHz
Medium parameters used: f = 5250 MHz; $\sigma$ = 4.53 S/m; $\varepsilon_r$ = 35.1; $\rho$ = 1000 kg/m$^3$ ,
Medium parameters used: f = 5600 MHz; $\sigma$ = 4.88 S/m; $\varepsilon_r$ = 34.6; $\rho$ = 1000 kg/m$^3$ ,
Medium parameters used: f = 5750 MHz; $\sigma$ = 5.03 S/m; $\varepsilon_r$ = 34.4; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.4, 5.4, 5.4) @ 5250 MHz, ConvF(4.95, 4.95, 4.95) @ 5600 MHz, ConvF(4.98, 4.98, 4.98) @ 5750 MHz; Calibrated: 25.03.2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2019
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.2(1504); SEMCAD X 14.6.12(7470)

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 78.54 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 27.9 W/kg
**SAR(1 g) = 8.09 W/kg; SAR(10 g) = 2.33 W/kg**
Maximum value of SAR (measured) = 18.1 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 78.00 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 31.1 W/kg
**SAR(1 g) = 8.40 W/kg; SAR(10 g) = 2.40 W/kg**
Maximum value of SAR (measured) = 19.4 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5750 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 75.13 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 31.8 W/kg
**SAR(1 g) = 8.06 W/kg; SAR(10 g) = 2.30 W/kg**
Maximum value of SAR (measured) = 19.0 W/kg

0 dB = 18.1 W/kg = 12.58 dBW/kg

## Impedance Measurement Plot for Head TSL



# D5GHzV2, Serial No. 1113 Extended Dipole Calibrations

Referring to KDB 865664 D01 v01r02, if dipoles are verified in return loss (<-20dB, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended.

| D5GHzV2 – serial no. 1113 | | | | | | |
|---|---|---|---|---|---|---|
| 5250 Head | | | | | | |
| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
| 2019.9.24 | -24.05 | | 51.71 | | -6.16 | |
| 2020.9.23 | -24.80 | -0.03 | 50.56 | 1.15 | -5.94 | -0.22 |

| D5GHzV2 – serial no. 1113 | | | | | | |
|---|---|---|---|---|---|---|
| 5600 Head | | | | | | |
| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
| 2019.9.24 | -24.09 | | 56.04 | | -2.71 | |
| 2020.9.23 | -23.95 | 0.01 | 57.70 | -1.66 | -2.85 | 0.14 |

| D5GHzV2 – serial no. 1113 | | | | | | |
|---|---|---|---|---|---|---|
| 5750 Head | | | | | | |
| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
| 2019.9.24 | -23.94 | | 56.70 | | -1.04 | |
| 2020.9.23 | -21.92 | 0.08 | 58.56 | -1.86 | -1.58 | 0.54 |

**<Justification of the extended calibration>**

The return loss is < -20dB, within 20% of prior calibration; the impedance is within 5 ohm of prior calibration. Therefore the verification result should support extended calibration.

## Dipole Verification Data> D5GHzV2 – serial no. 1113

### 5250MHz – Head




### 5600MHz – Head




### 5750MHz – Head



**Calibration Laboratory of**
Schmid & Partner
Engineering AG
**Zeughausstrasse 43, 8004 Zurich, Switzerland**

**S** Schweizerischer Kalibrierdienst
**C** Service suisse d'étalonnage
Servizio svizzero di taratura
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates**

**Accreditation No.: SCS 0108**

**Client** **Sporton**

**Certificate No: DAE4-1649_Feb21**

# CALIBRATION CERTIFICATE

| | |
|---|---|
| Object | DAE4 - SD 000 D04 BO - SN: 1649 |
| Calibration procedure(s) | QA CAL-06.v30<br>Calibration procedure for the data acquisition electronics (DAE) |
| Calibration date: | February 03, 2021 |

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|---|---|---|---|
| Keithley Multimeter Type 2001 | SN: 0810278 | 07-Sep-20 (No:28647) | Sep-21 |
| **Secondary Standards** | **ID #** | **Check Date (in house)** | **Scheduled Check** |
| Auto DAE Calibration Unit | SE UWS 053 AA 1001 | 07-Jan-21 (in house check) | In house check: Jan-22 |
| Calibrator Box V2.1 | SE UMS 006 AA 1002 | 07-Jan-21 (in house check) | In house check: Jan-22 |

| | Name | Function | Signature |
|---|---|---|---|
| Calibrated by: | Eric Hainfeld | Laboratory Technician | |
| Approved by: | Sven Kühn | Deputy Manager | i.V. |

Issued: February 3, 2021

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

## Glossary

| | |
|---|---|
| DAE | data acquisition electronics |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

## Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - *DC Voltage Measurement Linearity:* Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - *Common mode sensitivity:* Influence of a positive or negative common mode voltage on the differential measurement.
  - *Channel separation:* Influence of a voltage on the neighbor channels not subject to an input voltage.
  - *AD Converter Values with inputs shorted:* Values on the internal AD converter corresponding to zero input voltage
  - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
  - *Input Offset Current:* Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - *Input resistance:* Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - *Low Battery Alarm Voltage:* Typical value for information. Below this voltage, a battery alarm signal is generated.
  - *Power consumption:* Typical value for information. Supply currents in various operating modes.

## DC Voltage Measurement

A/D - Converter Resolution nominal

| | | | | |
|---|---|---|---|---|
| High Range: | 1LSB = | 6.1μV , | full range = | -100…+300 mV |
| Low Range: | 1LSB = | 61nV , | full range = | -1…….+3mV |

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---|---|---|---|
| **High Range** | 404.611 ± 0.02% (k=2) | 404.594 ± 0.02% (k=2) | 404.402 ± 0.02% (k=2) |
| **Low Range** | 3.98581 ± 1.50% (k=2) | 3.97757 ± 1.50% (k=2) | 3.97254 ± 1.50% (k=2) |

## Connector Angle

| | |
|---|---|
| **Connector Angle** to be used in DASY system | 98.5 ° ± 1 ° |

## Appendix (Additional assessments outside the scope of SCS0108)

### 1. DC Voltage Linearity

| High Range | | Reading (µV) | Difference (µV) | Error (%) |
|---|---|---|---|---|
| Channel X | + Input | 200031.53 | -1.43 | -0.00 |
| Channel X | + Input | 20005.23 | -0.19 | -0.00 |
| Channel X | - Input | -20004.73 | 1.29 | -0.01 |
| Channel Y | + Input | 200031.89 | -0.83 | -0.00 |
| Channel Y | + Input | 20002.89 | -2.62 | -0.01 |
| Channel Y | - Input | -20007.54 | -1.43 | 0.01 |
| Channel Z | + Input | 200033.67 | 0.44 | 0.00 |
| Channel Z | + Input | 20002.43 | -3.16 | -0.02 |
| Channel Z | - Input | -20006.81 | -0.96 | 0.00 |

| Low Range | | Reading (µV) | Difference (µV) | Error (%) |
|---|---|---|---|---|
| Channel X | + Input | 2001.30 | 0.62 | 0.03 |
| Channel X | + Input | 200.40 | -0.36 | -0.18 |
| Channel X | - Input | -199.04 | 0.24 | -0.12 |
| Channel Y | + Input | 2001.06 | 0.07 | 0.00 |
| Channel Y | + Input | 200.19 | -0.84 | -0.42 |
| Channel Y | - Input | -199.38 | -0.49 | 0.25 |
| Channel Z | + Input | 2001.07 | 0.16 | 0.01 |
| Channel Z | + Input | 200.26 | -0.70 | -0.35 |
| Channel Z | - Input | -198.99 | 0.06 | -0.03 |

### 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Common mode Input Voltage (mV) | High Range Average Reading (µV) | Low Range Average Reading (µV) |
|---|---|---|---|
| Channel X | 200 | 3.22 | 1.62 |
| | - 200 | -1.35 | -2.81 |
| Channel Y | 200 | -6.53 | -7.15 |
| | - 200 | 4.66 | 4.68 |
| Channel Z | 200 | -0.10 | -0.06 |
| | - 200 | -1.42 | -1.52 |

### 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Input Voltage (mV) | Channel X (µV) | Channel Y (µV) | Channel Z (µV) |
|---|---|---|---|---|
| Channel X | 200 | - | 0.24 | -3.74 |
| Channel Y | 200 | 5.97 | - | 2.81 |
| Channel Z | 200 | 9.32 | 4.37 | - |