


# FCC SAR Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.  
EQUIPMENT : Portable Tablet Computer  
BRAND NAME : lenovo  
MODEL NAME : YOGA Tablet 2-851F  
FCC ID : O57YT2851F  
STANDARD : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2003

We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



## **Table of Contents**

|                                                       |           |
|-------------------------------------------------------|-----------|
| <b>1. Statement of Compliance .....</b>               | <b>4</b>  |
| <b>2. Administration Data .....</b>                   | <b>5</b>  |
| <b>3. Guidance Standard .....</b>                     | <b>5</b>  |
| <b>4. Equipment Under Test (EUT) .....</b>            | <b>6</b>  |
| 4.1 General Information .....                         | 6         |
| 4.2 Maximum Tune-up Limit.....                        | 7         |
| <b>5. RF Exposure Limits .....</b>                    | <b>8</b>  |
| 5.1 Uncontrolled Environment.....                     | 8         |
| 5.2 Controlled Environment.....                       | 8         |
| <b>6. Specific Absorption Rate (SAR).....</b>         | <b>9</b>  |
| 6.1 Introduction .....                                | 9         |
| 6.2 SAR Definition.....                               | 9         |
| <b>7. System Description and Setup .....</b>          | <b>10</b> |
| <b>8. Measurement Procedures .....</b>                | <b>11</b> |
| 8.1 Spatial Peak SAR Evaluation.....                  | 11        |
| 8.2 Power Reference Measurement.....                  | 12        |
| 8.3 Area Scan .....                                   | 12        |
| 8.4 Zoom Scan.....                                    | 13        |
| 8.5 Volume Scan Procedures.....                       | 13        |
| 8.6 Power Drift Monitoring.....                       | 13        |
| <b>9. Test Equipment List .....</b>                   | <b>14</b> |
| <b>10. System Verification .....</b>                  | <b>15</b> |
| 10.1 Tissue Verification .....                        | 15        |
| 10.2 System Performance Check Results.....            | 16        |
| <b>11. RF Exposure Positions .....</b>                | <b>17</b> |
| 11.1 SAR Testing for Tablet .....                     | 17        |
| <b>12. Conducted RF Output Power (Unit: dBm).....</b> | <b>18</b> |
| <b>13. Antenna Location .....</b>                     | <b>25</b> |
| <b>14. SAR Test Results .....</b>                     | <b>27</b> |
| 14.1 Body SAR .....                                   | 27        |
| 14.2 Repeated SAR Measurement .....                   | 30        |
| <b>15. Simultaneous Transmission Analysis.....</b>    | <b>31</b> |
| <b>16. Uncertainty Assessment .....</b>               | <b>32</b> |
| <b>17. References .....</b>                           | <b>35</b> |
| <b>Appendix A. Plots of System Performance Check</b>  |           |
| <b>Appendix B. Plots of High SAR Measurement</b>      |           |
| <b>Appendix C. DASY Calibration Certificate</b>       |           |
| <b>Appendix D. Test Setup Photos</b>                  |           |

## Revision History

| REPORT NO.  | VERSION | DESCRIPTION             | ISSUED DATE   |
|-------------|---------|-------------------------|---------------|
| FA462003-03 | Rev. 01 | Initial issue of report | Aug. 16, 2014 |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |
|             |         |                         |               |

## **1. Statement of Compliance**

The maximum results of Specific Absorption Rate (SAR) found during testing for **Lenovo (Shanghai) Electronics Technology Co., Ltd., Portable Tablet Computer, YOGA Tablet 2-851F** are as follows.

| Equipment Class  | Frequency Band   | Operating Mode          | Highest SAR Summary          |                                      |
|------------------|------------------|-------------------------|------------------------------|--------------------------------------|
|                  |                  |                         | Body 1g SAR (W/kg) (0cm Gap) | Simultaneous Transmission SAR (W/kg) |
| DTS              | WLAN 2.4GHz Band | Data                    | 1.17                         |                                      |
| NII              | WLAN 5.2GHz Band | Data                    | 1.42                         |                                      |
|                  | WLAN 5.8GHz Band | Data                    | 1.50                         |                                      |
| DSS              | Bluetooth        | Data                    | <0.10                        |                                      |
| Date of Testing: |                  | 07/13/2014 ~ 07/21/2014 |                              |                                      |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

## **2. Administration Data**

| Testing Laboratory |                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------|
| Test Site          | SPORTON INTERNATIONAL (KUNSHAN) INC.                                                                             |
| Test Site Location | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.<br>TEL: +86-0512-5790-0158<br>FAX: +86-0512-5790-0958 |

| Applicant    |                                                                    |
|--------------|--------------------------------------------------------------------|
| Company Name | Lenovo (Shanghai) Electronics Technology Co., Ltd.                 |
| Address      | No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ, Shanghai, China |

| Manufacturer |                                                                          |
|--------------|--------------------------------------------------------------------------|
| Company Name | Lenovo PC HK Limited                                                     |
| Address      | 23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong |

| Factory 1    |                                                                                                                |
|--------------|----------------------------------------------------------------------------------------------------------------|
| Company Name | LENOVO MOBILE COMMUNICATION TECHNOLOGY CO LTD                                                                  |
| Address      | NO.999 QISHAN NORTH 2ND ROAD, INFORMATION & OPTOELECTRONICS PARK, TORCH HIGH TECH, XIAMEN FUJIAN 361009, CHINA |
| Factory 2    |                                                                                                                |
| Company Name | LENOVO MOBILE COMMUNICATION (WUHAN) CO LTD                                                                     |
| Address      | 19 GAOXIN 4TH RD EAST LAKE HIGH-TECH, ZONE WUHAN HUBEI 430205, CHINA                                           |

## **3. Guidance Standard**

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 248227 D01 SAR meas for 802 11abg v01r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r01

## **4. Equipment Under Test (EUT)**

### **4.1 General Information**

| Product Feature & Specification                                                                                                                                                                      |                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Equipment Name                                                                                                                                                                                       | Portable Tablet Computer                                                                                                                                  |
| Brand Name                                                                                                                                                                                           | lenovo                                                                                                                                                    |
| Model Name                                                                                                                                                                                           | YOGA Tablet 2-851F                                                                                                                                        |
| FCC ID                                                                                                                                                                                               | O57YT2851F                                                                                                                                                |
| Wireless Technology and Frequency Range                                                                                                                                                              | WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz<br>WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz<br>WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz |
| Mode                                                                                                                                                                                                 | • 802.11a/b/g/n HT20/HT40<br>• Bluetooth v3.0+EDR , Bluetooth v4.0 LE                                                                                     |
| HW Version                                                                                                                                                                                           | Lenovopad YOGA Tablet 2-851F                                                                                                                              |
| SW Version                                                                                                                                                                                           | Lenovo TAB2-W10-S100-001-140624-ES                                                                                                                        |
| EUT Stage                                                                                                                                                                                            | Production Unit                                                                                                                                           |
| <b>Remark:</b><br>1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.<br>2. Voice call is not supported. |                                                                                                                                                           |

## 4.2 Maximum Tune-up Limit

| Mode / Band                   | Average Power (dBm) |         |              |              |
|-------------------------------|---------------------|---------|--------------|--------------|
|                               | 802.11a             | 802.11g | 802.11n-HT20 | 802.11n-HT40 |
| WLAN 2.4 GHz Band Ant.0       |                     | 12      | 12           | 10           |
| WLAN 2.4 GHz Band Ant.1       |                     | 11      | 11.5         | 10           |
| WLAN 2.4 GHz Band Ant.0+1(0)  |                     |         | 10           | 5            |
| WLAN 2.4 GHz Band Ant.0+1(1)  |                     |         | 10           | 4.5          |
| WLAN 2.4 GHz Band Ant.0+1     |                     |         | 12.5         | 7.5          |
| WLAN 5.2 GHz Band Ant.0       | 9                   |         | 8.5          | 8.5          |
| WLAN 5.2 GHz Band Ant.1       | 9.5                 |         | 9            | 9            |
| WLAN 5.2 GHz Band Ant. 0+1(0) |                     |         | 6            | 6            |
| WLAN 5.2 GHz Band Ant. 0+1(1) |                     |         | 6            | 6            |
| WLAN 5.2 GHz Band Ant. 0+1    |                     |         | 9            | 9            |
| WLAN 5.8 GHz Band Ant.0       | 11                  |         | 10.5         | 10.5         |
| WLAN 5.8 GHz Band Ant.1       | 11                  |         | 10.5         | 10.5         |
| WLAN 5.8 GHz Band Ant. 0+1(0) |                     |         | 8            | 8            |
| WLAN 5.8 GHz Band Ant. 0+1(1) |                     |         | 8            | 7.5          |
| WLAN 5.8 GHz Band Ant. 0+1    |                     |         | 11           | 10.5         |

| Mode / Band             | Average Power (dBm) |      |       |
|-------------------------|---------------------|------|-------|
|                         | 802.11b             |      |       |
| Channel                 | CH 1                | CH 6 | CH 11 |
| WLAN 2.4 GHz Band Ant.0 | 16                  | 15.5 | 15.5  |
| WLAN 2.4 GHz Band Ant.1 | 14                  | 14   | 14    |

| Average Power (dBm) |         |          |
|---------------------|---------|----------|
| Mode / Band         | Channel | v3.0+EDR |
| Bluetooth           | CH 00   | 8.5      |
|                     | CH 39   | 10       |
|                     | CH 78   | 8.5      |

| Average Power (dBm) |            |
|---------------------|------------|
| Mode / Band         | BT v4.0 LE |
| Bluetooth           | 7.5        |

## **5. RF Exposure Limits**

### **5.1 Uncontrolled Environment**

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### **5.2 Controlled Environment**

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.4        | 8.0          | 20.0                           |

**Limits for General Population/Uncontrolled Exposure (W/kg)**

| Whole-Body | Partial-Body | Hands, Wrists, Feet and Ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **6. Specific Absorption Rate (SAR)**

### **6.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **6.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

## 7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## **8. Measurement Procedures**

The measurement procedures are as follows:

### **<Conducted power measurement>**

- (a) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (b) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### **<SAR measurement>**

- (a) Engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### **8.1 Spatial Peak SAR Evaluation**

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

## **8.2 Power Reference Measurement**

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

## **8.3 Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

|                                                                                                        | $\leq 3$ GHz                                                                                                                                                                                                                                                           | $> 3$ GHz                                              |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | $5 \pm 1$ mm                                                                                                                                                                                                                                                           | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm     |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                 |
| Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$                            | $\leq 2$ GHz: $\leq 15$ mm<br>$2 - 3$ GHz: $\leq 12$ mm                                                                                                                                                                                                                | $3 - 4$ GHz: $\leq 12$ mm<br>$4 - 6$ GHz: $\leq 10$ mm |
|                                                                                                        | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                        |

### 8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

|                                                                                                                                                                                                                                                                                                             |                                           |                                                                                             | $\leq 3$ GHz                                         | $> 3$ GHz                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------------------------------|
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$                                                                                                                                                                                                                      |                                           |                                                                                             | $\leq 2$ GHz: $\leq 8$ mm<br>2 – 3 GHz: $\leq 5$ mm* | 3 – 4 GHz: $\leq 5$ mm*<br>4 – 6 GHz: $\leq 4$ mm*                            |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                             | uniform grid: $\Delta z_{\text{Zoom}}(n)$ |                                                                                             | $\leq 5$ mm                                          | 3 – 4 GHz: $\leq 4$ mm<br>4 – 5 GHz: $\leq 3$ mm<br>5 – 6 GHz: $\leq 2$ mm    |
|                                                                                                                                                                                                                                                                                                             | graded grid                               | $\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4$ mm                                          | 3 – 4 GHz: $\leq 3$ mm<br>4 – 5 GHz: $\leq 2.5$ mm<br>5 – 6 GHz: $\leq 2$ mm  |
|                                                                                                                                                                                                                                                                                                             |                                           | $\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$         |                                                                               |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                                    | x, y, z                                   |                                                                                             | $\geq 30$ mm                                         | 3 – 4 GHz: $\geq 28$ mm<br>4 – 5 GHz: $\geq 25$ mm<br>5 – 6 GHz: $\geq 22$ mm |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.                                                                                                                                                           |                                           |                                                                                             |                                                      |                                                                               |
| * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                           |                                                                                             |                                                      |                                                                               |

### 8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

## 9. Test Equipment List

| Manufacturer  | Name of Equipment             | Type/Model    | Serial Number | Calibration   |               |
|---------------|-------------------------------|---------------|---------------|---------------|---------------|
|               |                               |               |               | Last Cal.     | Due Date      |
| SPEAG         | 2450MHz System Validation Kit | D2450V2       | 908           | Mar. 26, 2013 | Mar. 24, 2015 |
| SPEAG         | 2450MHz System Validation Kit | D2450V2       | 736           | Aug. 23, 2013 | Aug. 22, 2014 |
| SPEAG         | 5000MHz System Validation Kit | D5000V2       | 1006          | Sep. 23, 2013 | Sep. 22, 2014 |
| SPEAG         | Data Acquisition Electronics  | DAE4          | 1358          | Apr. 30, 2014 | Apr. 29, 2015 |
| SPEAG         | Data Acquisition Electronics  | DAE4          | 1210          | May 19, 2014  | May 18, 2015  |
| SPEAG         | Dosimetric E-Field Probe      | EX3DV4        | 3911          | Apr. 22, 2014 | Apr. 21, 2015 |
| SPEAG         | Dosimetric E-Field Probe      | EX3DV4        | 3857          | May 23, 2014  | May 22, 2015  |
| SPEAG         | ELI5 Phantom                  | QD OVA 002 AA | TP-1201       | NCR           | NCR           |
| SPEAG         | ELI4 Phantom                  | QD OVA 001 BB | TP-1079       | NCR           | NCR           |
| SPEAG         | Phone Positioner              | N/A           | N/A           | NCR           | NCR           |
| Agilent       | ENA Series Network Analyzer   | E5071C        | MY46111157    | May 04, 2014  | May 03, 2015  |
| Agilent       | Dielectric Probe Kit          | 85070E        | MY44300475    | NCR           | NCR           |
| Agilent       | Signal Generator              | N5181A        | MY50145381    | Jan. 04, 2014 | Jan. 03, 2015 |
| Anritsu       | Power Sensor                  | MA2411B       | 0917070       | Feb. 27, 2014 | Feb. 26, 2015 |
| Anritsu       | Power Meter                   | ML2495A       | 1005002       | Feb. 27, 2014 | Feb. 26, 2015 |
| R&S           | CBT BLUETOOTH TESTER          | CBT           | 100783        | Aug. 13, 2013 | Aug. 12, 2014 |
| R&S           | Spectrum Analyzer             | FSP7          | 101045        | Dec. 30, 2013 | Dec. 29, 2014 |
| Agilent       | Dual Directional Coupler      | 778D          | 50422         | Note 1        |               |
| Woken         | Attenuator                    | WK0602-XX     | N/A           | Note 1        |               |
| PE            | Attenuator                    | PE7005-10     | N/A           | Note 1        |               |
| PE            | Attenuator                    | PE7005- 3     | N/A           | Note 1        |               |
| AR            | Power Amplifier               | 5S1G4M2       | 0328767       | Note 1        |               |
| Mini-Circuits | Power Amplifier               | ZVE-3W        | 162601250     | Note 1        |               |
| Mini-Circuits | Power Amplifier               | ZHL-42W+      | 13440021344   | Note 1        |               |

**General Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. Referring to KDB 865664 D01v01r03, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole D2450V2, SN: 908 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

## **10. System Verification**

### **10.1 Tissue Verification**

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Frequency (MHz) | Water (%) | Sugar (%) | Cellulose (%) | Salt (%) | Preventol (%) | DGBE (%) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) |
|-----------------|-----------|-----------|---------------|----------|---------------|----------|---------------------------|-------------------------------|
| For Body        |           |           |               |          |               |          |                           |                               |
| 2450            | 68.6      | 0         | 0             | 0        | 0             | 31.4     | 1.95                      | 52.7                          |

Simulating Liquid for 5GHz, Manufactured by SPEAG

| Ingredients        | (% by weight) |
|--------------------|---------------|
| Water              | 64~78%        |
| Mineral oil        | 11~18%        |
| Emulsifiers        | 9~15%         |
| Additives and Salt | 2~3%          |

### **<Tissue Dielectric Parameter Check Results>**

| Frequency (MHz) | Tissue Type | Liquid Temp. (°C) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) | Conductivity Target ( $\sigma$ ) | Permittivity Target ( $\epsilon_r$ ) | Delta ( $\sigma$ ) (%) | Delta ( $\epsilon_r$ ) (%) | Limit (%) | Date      |
|-----------------|-------------|-------------------|---------------------------|-------------------------------|----------------------------------|--------------------------------------|------------------------|----------------------------|-----------|-----------|
| 2450            | Body        | 22.7              | 1.983                     | 51.159                        | 1.95                             | 52.70                                | 1.69                   | -2.92                      | ±5        | 2014.7.17 |
| 2450            | Body        | 22.4              | 1.942                     | 50.952                        | 1.95                             | 52.70                                | -0.41                  | -3.32                      | ±5        | 2014.7.21 |
| 5200            | Body        | 22.5              | 5.138                     | 47.493                        | 5.30                             | 49.00                                | -3.06                  | -3.08                      | ±5        | 2014.7.13 |
| 5800            | Body        | 22.6              | 6.127                     | 47.784                        | 6.00                             | 48.20                                | 2.12                   | -0.86                      | ±5        | 2014.7.15 |

## 10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

| Date      | Frequency (MHz) | Tissue Type | Input Power (mW) | Dipole S/N | Probe S/N | DAE S/N | Measured SAR (W/kg) | Targeted SAR (W/kg) | Normalized SAR (W/kg) | Deviation (%) |
|-----------|-----------------|-------------|------------------|------------|-----------|---------|---------------------|---------------------|-----------------------|---------------|
| 2014.7.17 | 2450            | Body        | 250              | 908        | 3911      | 1358    | 13.60               | 50.40               | 54.4                  | 7.94          |
| 2014.7.21 | 2450            | Body        | 250              | 736        | 3857      | 1210    | 12.70               | 51.30               | 50.8                  | -0.97         |
| 2014.7.13 | 5200            | Body        | 100              | 1006       | 3857      | 1210    | 7.23                | 71.50               | 72.3                  | 1.12          |
| 2014.7.15 | 5800            | Body        | 100              | 1006       | 3857      | 1210    | 7.23                | 72.30               | 72.3                  | 0.00          |




**Fig 8.3.1 System Performance Check Setup**



**Fig 8.3.2 Setup Photo**



## **11. RF Exposure Positions**

### **11.1 SAR Testing for Tablet**

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v05r02 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

## **12. Conducted RF Output Power (Unit: dBm)**

### **<WLAN Conducted Power>**

#### **General Note:**

1. Per KDB 248227, SAR for MIMO was measured with both transmitting simultaneously and was evaluated in dependently of SISO operation. For 2.4/5.2/5.8GHz MIMO, 802.11n was evaluated.
2. For SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
3. For IEEE802.11b/g SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were selected for SAR evaluation. 802.11g were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of 802.11b mode.
4. For IEEE802.11n, SAR testing can be conducted on channel with the highest output power when taking into consideration tune-up tolerance for same test configuration that was identified during SAR evaluations for IEEE802.11b/g (as applicable) provided bandwidth and test position are the same.
5. For IEEE802.11n with multiple channel BW configurations, highest channel BW configuration with highest output power limit shall be tested.
6. Testing of lower BW configurations is not required when the maximum average output of the default test channels in each lower BW configuration is less than 1/4dB higher than the default test channel in the highest BW configuration.

### **<2.4GHz WLAN Antenna 0>**

| WLAN 2.4GHz 802.11b Average Power (dBm) |                 |           |                     |         |        |
|-----------------------------------------|-----------------|-----------|---------------------|---------|--------|
| Power vs. Channel                       |                 |           | Power vs. Data Rate |         |        |
| Channel                                 | Frequency (MHz) | Data Rate | 2Mbps               | 5.5Mbps | 11Mbps |
|                                         |                 | 1Mbps     |                     |         |        |
| CH 1                                    | 2412            | 15.70     | 15.54               | 15.57   | 15.55  |
| CH 6                                    | 2437            | 14.98     |                     |         |        |
| CH 11                                   | 2462            | 14.89     |                     |         |        |

| WLAN 2.4GHz 802.11g Average Power (dBm) |                 |           |                     |        |        |        |        |        |        |
|-----------------------------------------|-----------------|-----------|---------------------|--------|--------|--------|--------|--------|--------|
| Power vs. Channel                       |                 |           | Power vs. Data Rate |        |        |        |        |        |        |
| Channel                                 | Frequency (MHz) | Data Rate | 9Mbps               | 12Mbps | 18Mbps | 24Mbps | 36Mbps | 48Mbps | 54Mbps |
|                                         |                 | 6Mbps     |                     |        |        |        |        |        |        |
| CH 1                                    | 2412            | 11.11     | 10.84               | 10.62  | 10.71  | 10.71  | 10.81  | 10.80  | 10.77  |
| CH 6                                    | 2437            | 10.47     |                     |        |        |        |        |        |        |
| CH 11                                   | 2462            | 10.23     |                     |        |        |        |        |        |        |

| WLAN 2.4GHz 802.11n-HT20 Average Power (dBm) |                 |           |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-----------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |           | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index | MCS1                | MCS2  | MCS3  | MCS4  | MCS5  | MCS6  | MCS7  |
|                                              |                 | MCS0      |                     |       |       |       |       |       |       |
| CH 1                                         | 2412            | 11.37     | 11.29               | 11.29 | 11.23 | 11.30 | 11.32 | 11.29 | 10.96 |
| CH 6                                         | 2437            | 11.21     |                     |       |       |       |       |       |       |
| CH 11                                        | 2462            | 11.23     |                     |       |       |       |       |       |       |

| WLAN 2.4GHz 802.11n-HT40 Average Power (dBm) |                 |           |                     |      |      |      |      |      |      |
|----------------------------------------------|-----------------|-----------|---------------------|------|------|------|------|------|------|
| Power vs. Channel                            |                 |           | Power vs. MCS Index |      |      |      |      |      |      |
| Channel                                      | Frequency (MHz) | MCS Index | MCS1                | MCS2 | MCS3 | MCS4 | MCS5 | MCS6 | MCS7 |
|                                              |                 | MCS0      |                     |      |      |      |      |      |      |
| CH 3                                         | 2422            | 8.82      | 9.30                | 9.25 | 9.14 | 9.26 | 9.30 | 9.32 | 8.99 |
| CH 6                                         | 2437            | 8.78      |                     |      |      |      |      |      |      |
| CH 9                                         | 2452            | 9.40      |                     |      |      |      |      |      |      |

**<2.4GHz WLAN Antenna 1>**

| WLAN 2.4GHz 802.11b Average Power (dBm) |                 |              |                     |         |        |
|-----------------------------------------|-----------------|--------------|---------------------|---------|--------|
| Power vs. Channel                       |                 |              | Power vs. Data Rate |         |        |
| Channel                                 | Frequency (MHz) | Data Rate    | 2Mbps               | 5.5Mbps | 11Mbps |
|                                         |                 | 1Mbps        |                     |         |        |
| CH 1                                    | 2412            | <b>13.47</b> | 13.45               | 13.44   | 13.46  |
| CH 6                                    | 2437            | 13.24        |                     |         |        |
| CH 11                                   | 2462            | 12.92        |                     |         |        |

| WLAN 2.4GHz 802.11g Average Power (dBm) |                 |              |                     |        |        |        |        |        |        |
|-----------------------------------------|-----------------|--------------|---------------------|--------|--------|--------|--------|--------|--------|
| Power vs. Channel                       |                 |              | Power vs. Data Rate |        |        |        |        |        |        |
| Channel                                 | Frequency (MHz) | Data Rate    | 9Mbps               | 12Mbps | 18Mbps | 24Mbps | 36Mbps | 48Mbps | 54Mbps |
|                                         |                 | 6Mbps        |                     |        |        |        |        |        |        |
| CH 1                                    | 2412            | <b>10.78</b> | 10.68               | 10.65  | 10.65  | 10.66  | 10.73  | 10.74  | 10.68  |
| CH 6                                    | 2437            | 10.45        |                     |        |        |        |        |        |        |
| CH 11                                   | 2462            | 10.37        |                     |        |        |        |        |        |        |

| WLAN 2.4GHz 802.11n-HT20 Average Power (dBm) |                 |              |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|--------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |              | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index    | MCS1                | MCS2  | MCS3  | MCS4  | MCS5  | MCS6  | MCS7  |
|                                              |                 | MCS0         |                     |       |       |       |       |       |       |
| CH 1                                         | 2412            | <b>11.19</b> | 11.03               | 10.98 | 10.94 | 10.94 | 10.91 | 10.87 | 10.84 |
| CH 6                                         | 2437            | 10.96        |                     |       |       |       |       |       |       |
| CH 11                                        | 2462            | 10.90        |                     |       |       |       |       |       |       |

| WLAN 2.4GHz 802.11n-HT40 Average Power (dBm) |                 |             |                     |      |      |      |      |      |      |
|----------------------------------------------|-----------------|-------------|---------------------|------|------|------|------|------|------|
| Power vs. Channel                            |                 |             | Power vs. MCS Index |      |      |      |      |      |      |
| Channel                                      | Frequency (MHz) | MCS Index   | MCS1                | MCS2 | MCS3 | MCS4 | MCS5 | MCS6 | MCS7 |
|                                              |                 | MCS0        |                     |      |      |      |      |      |      |
| CH 3                                         | 2422            | 9.27        | 9.80                | 9.69 | 9.58 | 9.84 | 9.70 | 9.67 | 9.66 |
| CH 6                                         | 2437            | 8.98        |                     |      |      |      |      |      |      |
| CH 9                                         | 2452            | <b>9.91</b> |                     |      |      |      |      |      |      |

**<2.4GHz WLAN Antenna 0+1(0)>**

| WLAN 2.4GHz 802.11n-HT20 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 1                                         | 2412            | 9.32              | 8.91                | 9.11  | 9.02  | 9.10  | 9.14  | 9.05  | 9.05  |
| CH 6                                         | 2437            | 9.12              |                     |       |       |       |       |       |       |
| CH 11                                        | 2462            | 9.14              |                     |       |       |       |       |       |       |

| WLAN 2.4GHz 802.11n-HT40 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 3                                         | 2422            | 4.20              | 2.54                | 4.58  | 2.33  | 1.81  | 2.60  | 2.23  | 2.14  |
| CH 6                                         | 2437            | 4.44              |                     |       |       |       |       |       |       |
| CH 9                                         | 2452            | 4.63              |                     |       |       |       |       |       |       |

**<2.4GHz WLAN Antenna 0+1(1)>**

| WLAN 2.4GHz 802.11n-HT20 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 1                                         | 2412            | 9.09              | 8.82                | 9.15  | 8.92  | 8.99  | 9.09  | 9.12  | 9.08  |
| CH 6                                         | 2437            | 8.96              |                     |       |       |       |       |       |       |
| CH 11                                        | 2462            | 9.04              |                     |       |       |       |       |       |       |

| WLAN 2.4GHz 802.11n-HT40 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 3                                         | 2422            | 4.00              | 4.20                | 4.23  | 4.07  | 3.90  | 4.03  | 3.78  | 3.54  |
| CH 6                                         | 2437            | 3.97              |                     |       |       |       |       |       |       |
| CH 9                                         | 2452            | 4.17              |                     |       |       |       |       |       |       |

**<2.4GHz WLAN Antenna 0+1>**

| WLAN 2.4GHz 802.11n-HT20 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 1                                         | 2412            | 12.21             | 11.88               | 12.14 | 11.98 | 12.06 | 12.12 | 12.09 | 12.08 |
| CH 6                                         | 2437            | 12.05             |                     |       |       |       |       |       |       |
| CH 11                                        | 2462            | 12.10             |                     |       |       |       |       |       |       |

| WLAN 2.4GHz 802.11n-HT40 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|----------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                            |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                      | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 3                                         | 2422            | 7.11              | 6.46                | 7.42  | 6.29  | 5.99  | 6.38  | 6.08  | 5.91  |
| CH 6                                         | 2437            | 7.22              |                     |       |       |       |       |       |       |
| CH 9                                         | 2452            | 7.42              |                     |       |       |       |       |       |       |

**<5GHz WLAN Antenna 0>**

| WLAN 5GHz 802.11a Average Power (dBm) |                 |                 |                     |        |        |        |        |        |        |
|---------------------------------------|-----------------|-----------------|---------------------|--------|--------|--------|--------|--------|--------|
| Power vs. Channel                     |                 |                 | Power vs. Data Rate |        |        |        |        |        |        |
| Channel                               | Frequency (MHz) | Data Rate 6Mbps | 9Mbps               | 12Mbps | 18Mbps | 24Mbps | 36Mbps | 48Mbps | 54Mbps |
| CH 36                                 | 5180            | 8.02            | 8.16                | 8.17   | 8.19   | 8.27   | 8.29   | 8.27   | 8.21   |
| CH 40                                 | 5200            | 7.97            |                     |        |        |        |        |        |        |
| CH 44                                 | 5220            | 8.25            |                     |        |        |        |        |        |        |
| CH 48                                 | 5240            | 8.62            |                     |        |        |        |        |        |        |
| CH 149                                | 5745            | 10.68           | 10.76               | 10.76  | 10.65  | 10.68  | 10.79  | 10.76  | 10.71  |
| CH 153                                | 5765            | 10.69           |                     |        |        |        |        |        |        |
| CH 157                                | 5785            | 10.70           |                     |        |        |        |        |        |        |
| CH 161                                | 5805            | 10.72           |                     |        |        |        |        |        |        |
| CH 165                                | 5825            | 10.81           |                     |        |        |        |        |        |        |

| WLAN 5GHz 802.11n-HT20 Average Power (dBm) |                 |                |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|----------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index MCS0 | MCS1                | MCS2  | MCS3  | MCS4  | MCS5  | MCS6  | MCS7  |
| CH 36                                      | 5180            | 7.79           | 7.91                | 7.81  | 7.74  | 7.86  | 8.00  | 7.90  | 7.90  |
| CH 40                                      | 5200            | 7.90           |                     |       |       |       |       |       |       |
| CH 44                                      | 5220            | 7.96           |                     |       |       |       |       |       |       |
| CH 48                                      | 5240            | 8.01           |                     |       |       |       |       |       |       |
| CH 149                                     | 5745            | 10.40          | 10.36               | 10.30 | 10.28 | 10.39 | 10.37 | 10.31 | 10.17 |
| CH 153                                     | 5765            | 10.32          |                     |       |       |       |       |       |       |
| CH 157                                     | 5785            | 10.29          |                     |       |       |       |       |       |       |
| CH 161                                     | 5805            | 10.37          |                     |       |       |       |       |       |       |
| CH 165                                     | 5825            | 10.30          |                     |       |       |       |       |       |       |

| WLAN 5GHz 802.11n-HT40 Average Power (dBm) |                 |                |                     |      |      |      |       |       |      |
|--------------------------------------------|-----------------|----------------|---------------------|------|------|------|-------|-------|------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |      |      |      |       |       |      |
| Channel                                    | Frequency (MHz) | MCS Index MCS0 | MCS1                | MCS2 | MCS3 | MCS4 | MCS5  | MCS6  | MCS7 |
| CH 38                                      | 5190            | 8.03           | 8.10                | 7.90 | 7.94 | 8.05 | 8.03  | 7.89  | 7.92 |
| CH 46                                      | 5230            | 8.25           |                     |      |      |      |       |       |      |
| CH 151                                     | 5755            | 9.91           | 10.06               | 9.99 | 9.95 | 9.99 | 10.11 | 10.16 | 9.93 |
| CH 159                                     | 5795            | 10.19          |                     |      |      |      |       |       |      |

**<5GHz WLAN Antenna 1>**

| WLAN 5GHz 802.11a Average Power (dBm) |                 |                 |                     |        |        |        |        |        |        |
|---------------------------------------|-----------------|-----------------|---------------------|--------|--------|--------|--------|--------|--------|
| Power vs. Channel                     |                 |                 | Power vs. Data Rate |        |        |        |        |        |        |
| Channel                               | Frequency (MHz) | Data Rate 6Mbps | 9Mbps               | 12Mbps | 18Mbps | 24Mbps | 36Mbps | 48Mbps | 54Mbps |
| CH 36                                 | 5180            | 8.66            | 9.05                | 8.86   | 8.71   | 8.84   | 9.05   | 9.09   | 8.62   |
| CH 40                                 | 5200            | 8.74            |                     |        |        |        |        |        |        |
| CH 44                                 | 5220            | 8.80            |                     |        |        |        |        |        |        |
| CH 48                                 | 5240            | 9.10            |                     |        |        |        |        |        |        |
| CH 149                                | 5745            | 10.52           | 10.73               | 10.56  | 10.55  | 10.63  | 10.66  | 10.61  | 10.49  |
| CH 153                                | 5765            | 10.61           |                     |        |        |        |        |        |        |
| CH 157                                | 5785            | 10.87           |                     |        |        |        |        |        |        |
| CH 161                                | 5805            | 10.52           |                     |        |        |        |        |        |        |
| CH 165                                | 5825            | 10.47           |                     |        |        |        |        |        |        |

| WLAN 5GHz 802.11n-HT20 Average Power (dBm) |                 |                |                     |      |      |      |      |      |      |
|--------------------------------------------|-----------------|----------------|---------------------|------|------|------|------|------|------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |      |      |      |      |      |      |
| Channel                                    | Frequency (MHz) | MCS Index MCS0 | MCS1                | MCS2 | MCS3 | MCS4 | MCS5 | MCS6 | MCS7 |
| CH 36                                      | 5180            | 8.15           | 8.12                | 8.20 | 8.18 | 8.33 | 8.43 | 8.31 | 8.04 |
| CH 40                                      | 5200            | 8.18           |                     |      |      |      |      |      |      |
| CH 44                                      | 5220            | 8.08           |                     |      |      |      |      |      |      |
| CH 48                                      | 5240            | 8.47           |                     |      |      |      |      |      |      |
| CH 149                                     | 5745            | 9.65           | 10.02               | 9.89 | 9.78 | 9.80 | 9.96 | 9.78 | 9.53 |
| CH 153                                     | 5765            | 9.71           |                     |      |      |      |      |      |      |
| CH 157                                     | 5785            | 10.18          |                     |      |      |      |      |      |      |
| CH 161                                     | 5805            | 9.56           |                     |      |      |      |      |      |      |
| CH 165                                     | 5825            | 9.54           |                     |      |      |      |      |      |      |

| WLAN 5GHz 802.11n-HT40 Average Power (dBm) |                 |                |                     |      |      |      |      |      |      |
|--------------------------------------------|-----------------|----------------|---------------------|------|------|------|------|------|------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |      |      |      |      |      |      |
| Channel                                    | Frequency (MHz) | MCS Index MCS0 | MCS1                | MCS2 | MCS3 | MCS4 | MCS5 | MCS6 | MCS7 |
| CH 38                                      | 5190            | 8.54           | 8.36                | 8.40 | 8.22 | 8.16 | 8.23 | 8.19 | 7.72 |
| CH 46                                      | 5230            | 8.42           |                     |      |      |      |      |      |      |
| CH 151                                     | 5755            | 10.08          | 9.91                | 9.79 | 9.75 | 9.85 | 9.96 | 9.84 | 9.72 |
| CH 159                                     | 5795            | 9.96           |                     |      |      |      |      |      |      |

**<5GHz WLAN Antenna 0+1(0)>**

| WLAN 5GHz 802.11n-HT20 Average Power (dBm) |                 |                |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|----------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                | Power vs. Data Rate |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | Data Rate MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 36                                      | 5180            | 5.00           | 5.09                | 4.96  | 5.01  | 5.20  | 5.21  | 5.23  | 5.13  |
| CH 40                                      | 5200            | 5.04           |                     |       |       |       |       |       |       |
| CH 44                                      | 5220            | 5.17           |                     |       |       |       |       |       |       |
| CH 48                                      | 5240            | <b>5.48</b>    |                     |       |       |       |       |       |       |
| CH 149                                     | 5745            | 7.73           | 7.82                | 7.76  | 7.54  | 7.77  | 7.79  | 7.80  | 7.64  |
| CH 153                                     | 5765            | 7.75           |                     |       |       |       |       |       |       |
| CH 157                                     | 5785            | 7.78           |                     |       |       |       |       |       |       |
| CH 161                                     | 5805            | 7.81           |                     |       |       |       |       |       |       |
| CH 165                                     | 5825            | <b>7.91</b>    |                     |       |       |       |       |       |       |

| WLAN 5GHz 802.11n-HT40 Average Power (dBm) |                 |                |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|----------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 38                                      | 5190            | <b>5.56</b>    | 5.20                | 4.89  | 4.80  | 4.92  | 4.84  | 4.88  | 4.73  |
| CH 46                                      | 5230            | 4.94           |                     |       |       |       |       |       |       |
| CH 151                                     | 5755            | 6.85           | 7.09                | 6.67  | 6.68  | 6.45  | 6.46  | 6.47  | 6.32  |
| CH 159                                     | 5795            | <b>7.40</b>    |                     |       |       |       |       |       |       |

**<5GHz WLAN Antenna 0+1(1)>**

| WLAN 5GHz 802.11n-HT20 Average Power (dBm) |                 |                |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|----------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 36                                      | 5180            | 5.28           | 5.34                | 5.19  | 5.15  | 5.35  | 5.31  | 5.39  | 5.16  |
| CH 40                                      | 5200            | 5.22           |                     |       |       |       |       |       |       |
| CH 44                                      | 5220            | 5.13           |                     |       |       |       |       |       |       |
| CH 48                                      | 5240            | <b>5.65</b>    |                     |       |       |       |       |       |       |
| CH 149                                     | 5745            | 7.11           | 6.55                | 6.67  | 6.43  | 6.52  | 6.45  | 6.76  | 6.32  |
| CH 153                                     | 5765            | 7.13           |                     |       |       |       |       |       |       |
| CH 157                                     | 5785            | 7.08           |                     |       |       |       |       |       |       |
| CH 161                                     | 5805            | 7.06           |                     |       |       |       |       |       |       |
| CH 165                                     | 5825            | <b>7.15</b>    |                     |       |       |       |       |       |       |

| WLAN 5GHz 802.11n-HT40 Average Power (dBm) |                 |                |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|----------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 38                                      | 5190            | <b>5.64</b>    | 5.10                | 5.03  | 5.05  | 5.12  | 5.13  | 5.12  | 5.03  |
| CH 46                                      | 5230            | 4.96           |                     |       |       |       |       |       |       |
| CH 151                                     | 5755            | 7.03           | 7.04                | 6.82  | 6.71  | 6.68  | 6.63  | 6.62  | 6.32  |
| CH 159                                     | 5795            | <b>7.21</b>    |                     |       |       |       |       |       |       |

**<5GHz WLAN Antenna 0+1>**

| WLAN 5GHz 802.11n-HT20 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 36                                      | 5180            | 8.15              | 8.23                | 8.08  | 8.09  | 8.29  | 8.28  | 8.32  | 8.15  |
| CH 40                                      | 5200            | 8.14              |                     |       |       |       |       |       |       |
| CH 44                                      | 5220            | 8.16              |                     |       |       |       |       |       |       |
| CH 48                                      | 5240            | <b>8.58</b>       |                     |       |       |       |       |       |       |
| CH 149                                     | 5745            | 10.44             | 10.24               | 10.26 | 10.03 | 10.20 | 10.19 | 10.32 | 10.04 |
| CH 153                                     | 5765            | 10.46             |                     |       |       |       |       |       |       |
| CH 157                                     | 5785            | 10.45             |                     |       |       |       |       |       |       |
| CH 161                                     | 5805            | 10.51             |                     |       |       |       |       |       |       |
| CH 165                                     | 5825            | <b>10.56</b>      |                     |       |       |       |       |       |       |

| WLAN 5GHz 802.11n-HT40 Average Power (dBm) |                 |                   |                     |       |       |       |       |       |       |
|--------------------------------------------|-----------------|-------------------|---------------------|-------|-------|-------|-------|-------|-------|
| Power vs. Channel                          |                 |                   | Power vs. MCS Index |       |       |       |       |       |       |
| Channel                                    | Frequency (MHz) | MCS Index<br>MCS8 | MCS9                | MCS10 | MCS11 | MCS12 | MCS13 | MCS14 | MCS15 |
| CH 38                                      | 5190            | <b>8.61</b>       | 8.16                | 7.97  | 7.94  | 8.03  | 8.00  | 8.01  | 7.89  |
| CH 46                                      | 5230            | 7.96              |                     |       |       |       |       |       |       |
| CH 151                                     | 5755            | 9.95              | 10.07               | 9.76  | 9.71  | 9.58  | 9.56  | 9.56  | 9.33  |
| CH 159                                     | 5795            | <b>10.32</b>      |                     |       |       |       |       |       |       |

**<Bluetooth Conducted Power>**

| Bluetooth Burst Average Power (dBm)_DH5 |                 |             |       |       |
|-----------------------------------------|-----------------|-------------|-------|-------|
| Channel                                 | Frequency (MHz) | Data Rate   |       |       |
|                                         |                 | 1Mbps       | 2Mbps | 3Mbps |
| CH 00                                   | 2402            | 7.05        | 5.33  | 5.32  |
| CH 39                                   | 2441            | <b>9.65</b> | 6.95  | 6.94  |
| CH 78                                   | 2480            | 7.90        | 4.65  | 4.63  |


  

| Channel | Frequency (MHz) | Burst Average power (dBm) |
|---------|-----------------|---------------------------|
|         |                 | BT v4.0, GFSK             |
| CH 00   | 2402            | 5.2                       |
| CH 19   | 2440            | <b>7.21</b>               |
| CH 39   | 2480            | 5.15                      |

**Note:**

1. The burst average power is the average power level during the "ON" burst of Bluetooth transmitter
2. Bluetooth SAR testing was performed at the data rate of 1Mbps and at DH5 due to highest duty factor which is theoretically maximum 83.3%.

### 13. Antenna Location



#### <Transmission configuration>

| Wireless Interface             | SISO Mode            |                      | MIMO Mode              |
|--------------------------------|----------------------|----------------------|------------------------|
|                                | Antenna 0<br><Tx/Rx> | Antenna 1<br><Tx/Rx> | Antenna 0+1<br><Tx/Rx> |
| WLAN 2.4GHz 802.11b/g          | yes                  | yes                  |                        |
| WLAN 2.4GHz 802.11n HT20/ HT40 | yes                  | yes                  | yes                    |
| WLAN 5GHz 802.11a              | yes                  | yes                  |                        |
| WLAN 5GHz 802.11n HT20/ HT40   | yes                  | yes                  | yes                    |
| Bluetooth                      | yes                  |                      |                        |

**General Note:**

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW".
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v05r02, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v05r02, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v05r02, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
  - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · ( f(MHz)/150)] mW, at 100 MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

**SAR test exclusion table distance is ≤ 50mm**

| Exposure Position | Wireless Interface           | 802.11b Ant.0 | 802.11b Ant.1 | 802.11a WLAN5.2G Ant.0 | 802.11a WLAN5.2G Ant.1 | 802.11a WLAN5.8G Ant.0 | 802.11a WLAN5.8G Ant.1 | Bluetooth |
|-------------------|------------------------------|---------------|---------------|------------------------|------------------------|------------------------|------------------------|-----------|
|                   | Tune-up Maximum power (dBm)  | 16            | 14            | 9                      | 9.5                    | 11                     | 11                     | 10        |
| Bottom Face       | Antenna to user (mm)         | 5.00          | 5.00          | 5.00                   | 5.00                   | 5.00                   | 5.00                   | 5.00      |
|                   | SAR exclusion threshold      | 13            | 8             | 4                      | 4                      | 6                      | 6                      | 3.4       |
|                   | SAR testing required?        | Yes           | Yes           | Yes                    | Yes                    | Yes                    | Yes                    | Yes       |
| Edge 1            | Antenna to user (mm)         |               | 12.00         |                        | 12.00                  |                        | 12.00                  |           |
|                   | SAR exclusion threshold      |               | 3             |                        | 2                      |                        | 3                      |           |
|                   | SAR testing required?        |               | No            |                        | No                     |                        | No                     |           |
| Edge 2            | Antenna to user (mm)         | 3.00          |               | 3.00                   |                        | 3.00                   |                        | 3.00      |
|                   | SAR exclusion threshold (mW) | 13            |               | 4                      |                        | 6                      |                        | 3.4       |
|                   | SAR testing required?        | Yes           |               | Yes                    |                        | Yes                    |                        | Yes       |
| Edge 3            | Antenna to user (mm)         | 44.00         |               | 44.00                  |                        | 44.00                  |                        | 44.00     |
|                   | SAR exclusion threshold (mW) | 1             |               | 0.4                    |                        | 1                      |                        | 0.4       |
|                   | SAR testing required?        | No            |               | No                     |                        | No                     |                        | No        |
| Edge 4            | Antenna to user (mm)         |               | 3.00          |                        | 3.00                   |                        | 3.00                   |           |
|                   | SAR exclusion threshold (mW) |               | 8             |                        | 4                      |                        | 6                      |           |
|                   | SAR testing required?        |               | Yes           |                        | Yes                    |                        | Yes                    |           |

**SAR test exclusion table distance is > 50mm**

| Exposure Position | Wireless Interface               | 802.11b Ant.0 | 802.11b Ant.1 | 802.11a WLAN5.2G Ant.0 | 802.11a WLAN5.2G Ant.1 | 802.11a WLAN5.8G Ant.0 | 802.11a WLAN5.8G Ant.1 | Bluetooth |
|-------------------|----------------------------------|---------------|---------------|------------------------|------------------------|------------------------|------------------------|-----------|
|                   | Tune-up Maximum power (dBm)      | 16            | 14            | 9                      | 9.5                    | 11                     | 11                     | 10        |
|                   | Tune-up Maximum rated power (mW) | 40            | 25            | 8                      | 9                      | 13                     | 13                     | 10        |
| Edge 1            | Antenna to user (mm)             | 82.00         |               | 82.00                  |                        | 82.00                  |                        | 82.00     |
|                   | SAR exclusion threshold          | 416           |               | 386                    |                        | 382                    |                        | 415       |
|                   | SAR testing required?            | No            |               | No                     |                        | No                     |                        | No        |
| Edge 2            | Antenna to user (mm)             |               | 198.50        |                        | 198.50                 |                        | 198.50                 |           |
|                   | SAR exclusion threshold (mW)     |               | 1581          |                        | 1551                   |                        | 1547                   |           |
|                   | SAR testing required?            |               | No            |                        | No                     |                        | No                     |           |
| Edge 3            | Antenna to user (mm)             |               | 111.00        |                        | 111.00                 |                        | 111.00                 |           |
|                   | SAR exclusion threshold (mW)     |               | 706           |                        | 676                    |                        | 672                    |           |
|                   | SAR testing required?            |               | No            |                        | No                     |                        | No                     |           |
| Edge 4            | Antenna to user (mm)             | 201.00        |               | 201.00                 |                        | 201.00                 |                        | 201.00    |
|                   | SAR exclusion threshold (mW)     | 1606          |               | 1576                   |                        | 1572                   |                        | 1605      |
|                   | SAR testing required?            | No            |               | No                     |                        | No                     |                        | No        |

## 14. SAR Test Results

### General Note:

1. Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
  - c. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
2. Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
  - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

### 14.1 Body SAR

#### <DTS WLAN SAR>

| Plot No.  | Band               | Mode                     | Test Position      | Gap (cm) | Antenna        | Ch.       | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|-----------|--------------------|--------------------------|--------------------|----------|----------------|-----------|-------------|---------------------|---------------------|----------------|--------------|---------------------------|------------------|------------------------|------------------------|
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Bottom Face        | 0        | Ant 0          | 1         | 2412        | 15.70               | 16.00               | 1.072          | 100          | 1.00                      | 0.01             | 1.050                  | 1.125                  |
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Edge 2             | 0        | Ant 0          | 1         | 2412        | 15.70               | 16.00               | 1.072          | 100          | 1.00                      | -0.01            | 0.672                  | 0.720                  |
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Bottom Face        | 0        | Ant 0          | 6         | 2437        | 14.98               | 15.50               | 1.127          | 100          | 1.00                      | 0.08             | 0.842                  | 0.949                  |
| <b>01</b> | <b>WLAN 2.4GHz</b> | <b>802.11b 1Mbps</b>     | <b>Bottom Face</b> | <b>0</b> | <b>Ant 0</b>   | <b>11</b> | <b>2462</b> | <b>14.89</b>        | <b>15.50</b>        | <b>1.151</b>   | <b>100</b>   | <b>1.00</b>               | <b>0.04</b>      | <b>1.020</b>           | <b>1.174</b>           |
|           | WLAN 2.4GHz        | 802.11n-HT40 MCS0        | Bottom Face        | 0        | Ant 0          | 9         | 2452        | 9.40                | 10.00               | 1.148          | 95.07        | 1.052                     | -0.02            | 0.259                  | 0.313                  |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS0        | Bottom Face        | 0        | Ant 0          | 1         | 2412        | 11.37               | 12.00               | 1.156          | 95.08        | 1.052                     | 0.06             | 0.426                  | 0.518                  |
| <b>02</b> | <b>WLAN 2.4GHz</b> | <b>802.11b 1Mbps</b>     | <b>Bottom Face</b> | <b>0</b> | <b>Ant 1</b>   | <b>1</b>  | <b>2412</b> | <b>13.47</b>        | <b>14.00</b>        | <b>1.130</b>   | <b>100</b>   | <b>1.00</b>               | <b>0.09</b>      | <b>0.440</b>           | <b>0.497</b>           |
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Edge 4             | 0        | Ant 1          | 1         | 2412        | 13.47               | 14.00               | 1.130          | 100          | 1.00                      | 0.08             | 0.154                  | 0.174                  |
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Bottom Face        | 0        | Ant 1          | 6         | 2437        | 13.24               | 14.00               | 1.191          | 100          | 1.00                      | -0.05            | 0.278                  | 0.331                  |
|           | WLAN 2.4GHz        | 802.11b 1Mbps            | Bottom Face        | 0        | Ant 1          | 11        | 2462        | 12.92               | 14.00               | 1.282          | 100          | 1.00                      | 0.07             | 0.236                  | 0.303                  |
|           | WLAN 2.4GHz        | 802.11n-HT40 MCS0        | Bottom Face        | 0        | Ant 1          | 9         | 2452        | 9.91                | 10.00               | 1.021          | 94.88        | 1.054                     | 0.04             | 0.156                  | 0.168                  |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS0        | Bottom Face        | 0        | Ant 1          | 1         | 2412        | 11.19               | 11.50               | 1.074          | 95.08        | 1.052                     | -0.01            | 0.329                  | 0.372                  |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS8        | Bottom Face        | 0        | Ant 0+1        | 1         | 2412        | 12.21               | 12.50               | 1.069          | 90.88        | 1.100                     | 0.04             | 0.266                  | 0.313                  |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS8        | Edge 2             | 0        | Ant 0+1        | 1         | 2412        | 12.21               | 12.50               | 1.069          | 90.88        | 1.100                     | -0.09            | 0.153                  | 0.180                  |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS8        | Edge4              | 0        | Ant 0+1        | 1         | 2412        | 12.21               | 12.50               | 1.069          | 90.88        | 1.100                     | -0.06            | 0.039                  | 0.046                  |
| <b>03</b> | <b>WLAN 2.4GHz</b> | <b>802.11n-HT20 MCS8</b> | <b>Bottom Face</b> | <b>0</b> | <b>Ant 0+1</b> | <b>6</b>  | <b>2437</b> | <b>12.05</b>        | <b>12.50</b>        | <b>1.109</b>   | <b>90.88</b> | <b>1.100</b>              | <b>0.07</b>      | <b>0.267</b>           | <b>0.326</b>           |
|           | WLAN 2.4GHz        | 802.11n-HT20 MCS8        | Bottom Face        | 0        | Ant 0+1        | 11        | 2462        | 12.10               | 12.50               | 1.096          | 90.88        | 1.100                     | -0.08            | 0.245                  | 0.296                  |
|           | WLAN 2.4GHz        | 802.11n-HT40 MCS8        | Bottom Face        | 0        | Ant 0+1        | 9         | 2452        | 7.42                | 7.50                | 1.019          | 90.63        | 1.103                     | 0.05             | 0.108                  | 0.121                  |



**<UNII WLAN SAR>**

| Plot No.  | Band               | Mode                     | Test Position | Gap (cm) | Antenna        | Ch.       | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|-----------|--------------------|--------------------------|---------------|----------|----------------|-----------|-------------|---------------------|---------------------|----------------|--------------|---------------------------|------------------|------------------------|------------------------|
|           | WLAN 5.2GHz        | 802.11a 6Mbps            | Bottom Face   | 0        | Ant.0          | 48        | 2412        | 8.62                | 9                   | 1.091          | 95.83        | 1.044                     | 0.05             | 0.520                  | 0.593                  |
|           | WLAN 5.2GHz        | 802.11a 6Mbps            | Edge2         | 0        | Ant.0          | 48        | 2412        | 8.62                | 9                   | 1.091          | 95.83        | 1.044                     | -0.1             | 0.877                  | 0.999                  |
| <b>04</b> | <b>WLAN 5.2GHz</b> | <b>802.11a 6Mbps</b>     | <b>Edge2</b>  | <b>0</b> | <b>Ant.0</b>   | <b>36</b> | <b>2437</b> | <b>8.02</b>         | <b>9</b>            | <b>1.253</b>   | <b>95.83</b> | <b>1.044</b>              | <b>-0.11</b>     | <b>1.000</b>           | <b>1.308</b>           |
|           | WLAN 5.2GHz        | 802.11n-HT40_MCS0        | Edge2         | 0        | Ant.0          | 46        | 2462        | 8.25                | 8.5                 | 1.059          | 95.13        | 1.051                     | -0.07            | 0.833                  | 0.927                  |
|           | WLAN 5.2GHz        | 802.11n-HT40_MCS0        | Edge2         | 0        | Ant.0          | 38        | 2412        | 8.03                | 8.5                 | 1.114          | 95.13        | 1.051                     | -0.03            | 0.957                  | 1.121                  |
|           | WLAN 5.2GHz        | 802.11a 6Mbps            | Bottom Face   | 0        | Ant.1          | 48        | 5240        | 9.1                 | 9.5                 | 1.096          | 95.48        | 1.047                     | -0.05            | 0.721                  | 0.828                  |
|           | WLAN 5.2GHz        | 802.11a 6Mbps            | Edge4         | 0        | Ant.1          | 48        | 5240        | 9.1                 | 9.5                 | 1.096          | 95.48        | 1.047                     | 0.1              | 0.891                  | 1.023                  |
|           | WLAN 5.2GHz        | 802.11a 6Mbps            | Bottom Face   | 0        | Ant.1          | 36        | 5180        | 8.66                | 9.5                 | 1.213          | 95.48        | 1.047                     | -0.15            | 0.777                  | 0.987                  |
| <b>05</b> | <b>WLAN 5.2GHz</b> | <b>802.11a 6Mbps</b>     | <b>Edge4</b>  | <b>0</b> | <b>Ant.1</b>   | <b>36</b> | <b>5180</b> | <b>8.66</b>         | <b>9.5</b>          | <b>1.213</b>   | <b>95.48</b> | <b>1.047</b>              | <b>-0.01</b>     | <b>1.120</b>           | <b>1.423</b>           |
|           | WLAN 5.2GHz        | 802.11n-HT40_MCS0        | Edge4         | 0        | Ant.1          | 38        | 5190        | 8.54                | 9                   | 1.112          | 94.7         | 1.056                     | 0.05             | 0.910                  | 1.068                  |
|           | WLAN 5.2GHz        | 802.11n-HT40_MCS0        | Edge4         | 0        | Ant.1          | 46        | 5230        | 8.42                | 9                   | 1.143          | 94.7         | 1.056                     | -0.03            | 0.844                  | 1.019                  |
|           | WLAN 5.2GHz        | 802.11n-HT20_MCS8        | Bottom Face   | 0        | Ant.0+1        | 48        | 5240        | 8.58                | 9                   | 1.102          | 90.98        | 1.099                     | 0.09             | 0.23                   | 0.278                  |
|           | WLAN 5.2GHz        | 802.11n-HT20_MCS8        | Edge2         | 0        | Ant.0+1        | 48        | 5240        | 8.58                | 9                   | 1.102          | 90.98        | 1.099                     | -0.08            | 0.413                  | 0.500                  |
|           | WLAN 5.2GHz        | 802.11n-HT20_MCS8        | Edge4         | 0        | Ant.0+1        | 48        | 5240        | 8.58                | 9                   | 1.102          | 90.98        | 1.099                     | 0.1              | 0.413                  | 0.500                  |
| <b>06</b> | <b>WLAN 5.2GHz</b> | <b>802.11n-HT20_MCS8</b> | <b>Edge4</b>  | <b>0</b> | <b>Ant.0+1</b> | <b>36</b> | <b>5180</b> | <b>8.15</b>         | <b>9</b>            | <b>1.216</b>   | <b>90.98</b> | <b>1.099</b>              | <b>-0.11</b>     | <b>0.452</b>           | <b>0.604</b>           |
|           | WLAN 5.2GHz        | 802.11n-HT40_MCS8        | Edge4         | 0        | Ant.0+1        | 38        | 5190        | 8.61                | 9                   | 1.094          | 90.13        | 1.110                     | -0.15            | 0.236                  | 0.287                  |



| Plot No.  | Band               | Mode                     | Test Position      | Gap (cm) | Antenna        | Ch.        | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|-----------|--------------------|--------------------------|--------------------|----------|----------------|------------|-------------|---------------------|---------------------|----------------|--------------|---------------------------|------------------|------------------------|------------------------|
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Bottom Face        | 0        | Ant.0          | 165        | 5825        | 10.81               | 11                  | 1.045          | 95.83        | 1.044                     | -0.05            | 0.179                  | 0.195                  |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Edge2              | 0        | Ant.0          | 165        | 5825        | 10.81               | 11                  | 1.045          | 95.83        | 1.044                     | -0.14            | 0.424                  | 0.462                  |
| <b>07</b> | <b>WLAN 5.8GHz</b> | <b>802.11n-HT40_MCS0</b> | <b>Edge2</b>       | <b>0</b> | <b>Ant.0</b>   | <b>159</b> | <b>5795</b> | <b>10.19</b>        | <b>10.5</b>         | <b>1.074</b>   | <b>95.13</b> | <b>1.051</b>              | <b>-0.09</b>     | <b>0.457</b>           | <b>0.516</b>           |
|           | WLAN 5.8GHz        | 802.11n-HT40_MCS0        | Edge2              | 0        | Ant.0          | 151        | 5755        | 9.91                | 10.5                | 1.146          | 95.13        | 1.051                     | -0.01            | 0.211                  | 0.254                  |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Bottom Face        | 0        | Ant.1          | 157        | 5785        | 10.87               | 11                  | 1.030          | 95.48        | 1.047                     | -0.1             | 1.150                  | 1.241                  |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Edge4              | 0        | Ant.1          | 157        | 5785        | 10.87               | 11                  | 1.030          | 95.48        | 1.047                     | 0.05             | 0.991                  | 1.069                  |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Bottom Face        | 0        | Ant.1          | 149        | 5745        | 10.52               | 11                  | 1.117          | 95.48        | 1.047                     | 0.1              | 1.160                  | 1.356                  |
| <b>08</b> | <b>WLAN 5.8GHz</b> | <b>802.11a 6Mbps</b>     | <b>Bottom Face</b> | <b>0</b> | <b>Ant.1</b>   | <b>165</b> | <b>5825</b> | <b>10.47</b>        | <b>11</b>           | <b>1.130</b>   | <b>95.48</b> | <b>1.047</b>              | <b>-0.06</b>     | <b>1.270</b>           | <b>1.502</b>           |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Edge4              | 0        | Ant.1          | 149        | 5745        | 10.52               | 11                  | 1.117          | 95.48        | 1.047                     | 0.14             | 1.020                  | 1.193                  |
|           | WLAN 5.8GHz        | 802.11a 6Mbps            | Edge4              | 0        | Ant.1          | 165        | 5825        | 10.47               | 11                  | 1.130          | 95.48        | 1.047                     | 0.15             | 1.010                  | 1.195                  |
|           | WLAN 5.8GHz        | 802.11n-HT40_MCS0        | Bottom Face        | 0        | Ant.1          | 151        | 5755        | 10.08               | 10.5                | 1.102          | 94.7         | 1.056                     | -0.06            | 0.859                  | 0.999                  |
|           | WLAN 5.8GHz        | 802.11n-HT40_MCS0        | Bottom Face        | 0        | Ant.1          | 159        | 5755        | 9.96                | 10.5                | 1.132          | 94.7         | 1.056                     | 0.08             | 0.904                  | 1.081                  |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Bottom Face        | 0        | Ant.0+1        | 165        | 5825        | 10.56               | 11                  | 1.107          | 90.98        | 1.099                     | -0.12            | 0.897                  | 1.091                  |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Edge2              | 0        | Ant.0+1        | 165        | 5825        | 10.56               | 11                  | 1.107          | 90.98        | 1.099                     | -0.06            | 0.304                  | 0.370                  |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Edge4              | 0        | Ant.0+1        | 165        | 5825        | 10.56               | 11                  | 1.107          | 90.98        | 1.099                     | 0.05             | 0.718                  | 0.873                  |
| <b>09</b> | <b>WLAN 5.8GHz</b> | <b>802.11n-HT20_MCS8</b> | <b>Bottom Face</b> | <b>0</b> | <b>Ant.0+1</b> | <b>149</b> | <b>5745</b> | <b>10.44</b>        | <b>11</b>           | <b>1.138</b>   | <b>90.98</b> | <b>1.099</b>              | <b>-0.04</b>     | <b>0.918</b>           | <b>1.148</b>           |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Bottom Face        | 0        | Ant.0+1        | 157        | 5785        | 10.45               | 11                  | 1.135          | 90.98        | 1.099                     | -0.09            | 0.892                  | 1.113                  |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Edge4              | 0        | Ant.0+1        | 149        | 5745        | 10.44               | 11                  | 1.138          | 90.98        | 1.099                     | 0.1              | 0.777                  | 0.971                  |
|           | WLAN 5.8GHz        | 802.11n-HT20_MCS8        | Edge4              | 0        | Ant.0+1        | 157        | 5785        | 10.45               | 11                  | 1.135          | 90.98        | 1.099                     | -0.01            | 0.741                  | 0.924                  |
|           | WLAN 5.8GHz        | 802.11n-HT40_MCS8        | Bottom Face        | 0        | Ant.0+1        | 159        | 5795        | 10.32               | 10.5                | 1.042          | 90.13        | 1.110                     | -0.07            | 0.612                  | 0.708                  |
|           | WLAN 5.8GHz        | 802.11n-HT40_MCS8        | Bottom Face        | 0        | Ant.0+1        | 151        | 5755        | 9.95                | 10.5                | 1.135          | 90.13        | 1.110                     | 0.1              | 0.570                  | 0.718                  |

**<Bluetooth SAR>**

| Plot No.  | Band             | Mode             | Test Position      | Gap (cm) | Ch.       | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Tune-up Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|-----------|------------------|------------------|--------------------|----------|-----------|-------------|---------------------|---------------------|------------------------|------------------|------------------------|------------------------|
|           | Bluetooth        | 1Mbps DH5        | Bottom Face        | 0        | 39        | 2441        | 9.65                | 10                  | 1.084                  | 0.01             | 0.00014                | <0.010                 |
|           | Bluetooth        | 1Mbps DH5        | Edge2              | 0        | 39        | 2441        | 9.65                | 10                  | 1.084                  | -0.03            | 4.42E-05               | <0.010                 |
|           | Bluetooth        | 1Mbps DH5        | Bottom Face        | 0        | 00        | 2402        | 7.05                | 8.5                 | 1.396                  | -0.05            | 0.000113               | <0.010                 |
| <b>10</b> | <b>Bluetooth</b> | <b>1Mbps DH5</b> | <b>Bottom Face</b> | <b>0</b> | <b>78</b> | <b>2480</b> | <b>7.9</b>          | <b>8.5</b>          | <b>1.148</b>           | <b>-0.05</b>     | <b>0.000165</b>        | <b>&lt;0.010</b>       |

### 14.2 Repeated SAR Measurement

| No. | Band        | Mode          | Test Position | Gap (cm) | Antenna | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Duty Cycle % | Duty Cycle Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Ratio | Reported 1g SAR (W/kg) |
|-----|-------------|---------------|---------------|----------|---------|-----|-------------|---------------------|---------------------|----------------|--------------|---------------------------|------------------|------------------------|-------|------------------------|
| 1st | WLAN 2.4GHz | 802.11b 1Mbps | Bottom Face   | 0        | Ant 0   | 1   | 2412        | 15.70               | 16.00               | 1.072          | -            | -                         | 0.01             | 1.05                   | 1     | 1.125                  |
| 2nd | WLAN 2.4GHz | 802.11b 1Mbps | Bottom Face   | 0        | Ant 0   | 1   | 2412        | 15.70               | 16.00               | 1.072          | -            | -                         | 0.08             | 1.03                   | 1.019 | 1.104                  |
| 1st | WLAN 5.2GHz | 802.11a 6Mbps | Edge4         | 0        | Ant.1   | 36  | 5180        | 8.66                | 9.5                 | 1.213          | 95.48        | 1.047                     | -0.01            | 1.12                   | 1     | 1.423                  |
| 2nd | WLAN 5.2GHz | 802.11a 6Mbps | Edge4         | 0        | Ant.1   | 36  | 5180        | 8.66                | 9.5                 | 1.213          | 95.48        | 1.047                     | -0.12            | 1.08                   | 1.036 | 1.372                  |
| 1st | WLAN 5.8GHz | 802.11a 6Mbps | Bottom Face   | 0        | Ant.1   | 165 | 5825        | 10.47               | 11                  | 1.130          | 95.48        | 1.047                     | -0.06            | 1.27                   | 1     | 1.502                  |
| 2nd | WLAN 5.8GHz | 802.11a 6Mbps | Bottom Face   | 0        | Ant.1   | 165 | 5825        | 10.47               | 11                  | 1.130          | 95.48        | 1.047                     | -0.04            | 1.23                   | 1.031 | 1.455                  |

**General Note:**

1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8\text{W/kg}$
2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45\text{W/kg}$ , only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

**15. Simultaneous Transmission Analysis**

| No. | Applicable Simultaneous Transmission Combination |
|-----|--------------------------------------------------|
| 1.  | None                                             |

**General Note:** WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.

**Test Engineer :** Fulu Hu

## **16. Uncertainty Assessment**

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

| <b>Uncertainty Distributions</b>   | <b>Normal</b> | <b>Rectangular</b> | <b>Triangular</b> | <b>U-Shape</b> |
|------------------------------------|---------------|--------------------|-------------------|----------------|
| Multi-plying Factor <sup>(a)</sup> | $1/k^{(b)}$   | $1/\sqrt{3}$       | $1/\sqrt{6}$      | $1/\sqrt{2}$   |

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $k$  is the coverage factor

**Table 14.1. Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Ci (10g) | Standard Uncertainty (1g) | Standard Uncertainty (10g) |
|--------------------------------------|------------------------|--------------------------|---------|---------|----------|---------------------------|----------------------------|
| <b>Measurement System</b>            |                        |                          |         |         |          |                           |                            |
| Probe Calibration                    | 6.0                    | Normal                   | 1       | 1       | 1        | ± 6.0 %                   | ± 6.0 %                    |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | 0.7      | ± 1.9 %                   | ± 1.9 %                    |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | 0.7      | ± 3.9 %                   | ± 3.9 %                    |
| Boundary Effects                     | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | 1        | ± 2.7 %                   | ± 2.7 %                    |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| Readout Electronics                  | 0.3                    | Normal                   | 1       | 1       | 1        | ± 0.3 %                   | ± 0.3 %                    |
| Response Time                        | 0.8                    | Rectangular              | √3      | 1       | 1        | ± 0.5 %                   | ± 0.5 %                    |
| Integration Time                     | 2.6                    | Rectangular              | √3      | 1       | 1        | ± 1.5 %                   | ± 1.5 %                    |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| Probe Positioner                     | 0.4                    | Rectangular              | √3      | 1       | 1        | ± 0.2 %                   | ± 0.2 %                    |
| Probe Positioning                    | 2.9                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| Max. SAR Eval.                       | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| <b>Test Sample Related</b>           |                        |                          |         |         |          |                           |                            |
| Device Positioning                   | 2.9                    | Normal                   | 1       | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| Device Holder                        | 3.6                    | Normal                   | 1       | 1       | 1        | ± 3.6 %                   | ± 3.6 %                    |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| <b>Phantom and Setup</b>             |                        |                          |         |         |          |                           |                            |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | 1        | ± 2.3 %                   | ± 2.3 %                    |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | 0.43     | ± 1.8 %                   | ± 1.2 %                    |
| Liquid Conductivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.64    | 0.43     | ± 1.6 %                   | ± 1.1 %                    |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | 0.49     | ± 1.7 %                   | ± 1.4 %                    |
| Liquid Permittivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.6     | 0.49     | ± 1.5 %                   | ± 1.2 %                    |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         |          | ± 11.0 %                  | ± 10.8 %                   |
| <b>Coverage Factor for 95 %</b>      |                        |                          |         |         |          | K=2                       |                            |
| <b>Expanded Uncertainty</b>          |                        |                          |         |         |          | ± 22.0 %                  | ± 21.5 %                   |

**Table 14.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz**

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Ci (10g) | Standard Uncertainty (1g) | Standard Uncertainty (10g) |
|--------------------------------------|------------------------|--------------------------|---------|---------|----------|---------------------------|----------------------------|
| <b>Measurement System</b>            |                        |                          |         |         |          |                           |                            |
| Probe Calibration                    | 6.55                   | Normal                   | 1       | 1       | 1        | ± 6.55 %                  | ± 6.55 %                   |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | 0.7      | ± 1.9 %                   | ± 1.9 %                    |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | 0.7      | ± 3.9 %                   | ± 3.9 %                    |
| Boundary Effects                     | 2.0                    | Rectangular              | √3      | 1       | 1        | ± 1.2 %                   | ± 1.2 %                    |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | 1        | ± 2.7 %                   | ± 2.7 %                    |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| Readout Electronics                  | 0.3                    | Normal                   | 1       | 1       | 1        | ± 0.3 %                   | ± 0.3 %                    |
| Response Time                        | 0.8                    | Rectangular              | √3      | 1       | 1        | ± 0.5 %                   | ± 0.5 %                    |
| Integration Time                     | 2.6                    | Rectangular              | √3      | 1       | 1        | ± 1.5 %                   | ± 1.5 %                    |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| Probe Positioner                     | 0.8                    | Rectangular              | √3      | 1       | 1        | ± 0.5 %                   | ± 0.5 %                    |
| Probe Positioning                    | 9.9                    | Rectangular              | √3      | 1       | 1        | ± 5.7 %                   | ± 5.7 %                    |
| Max. SAR Eval.                       | 4.0                    | Rectangular              | √3      | 1       | 1        | ± 2.3 %                   | ± 2.3 %                    |
| <b>Test Sample Related</b>           |                        |                          |         |         |          |                           |                            |
| Device Positioning                   | 2.9                    | Normal                   | 1       | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| Device Holder                        | 3.6                    | Normal                   | 1       | 1       | 1        | ± 3.6 %                   | ± 3.6 %                    |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| <b>Phantom and Setup</b>             |                        |                          |         |         |          |                           |                            |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | 1        | ± 2.3 %                   | ± 2.3 %                    |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | 0.43     | ± 1.8 %                   | ± 1.2 %                    |
| Liquid Conductivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.64    | 0.43     | ± 1.6 %                   | ± 1.1 %                    |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | 0.49     | ± 1.7 %                   | ± 1.4 %                    |
| Liquid Permittivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.6     | 0.49     | ± 1.5 %                   | ± 1.2 %                    |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         |          | ± 12.8 %                  | ± 12.6 %                   |
| <b>Coverage Factor for 95 %</b>      |                        |                          |         |         |          | K=2                       |                            |
| <b>Expanded Uncertainty</b>          |                        |                          |         |         |          | ± 25.6 %                  | ± 25.2 %                   |

**Table 14.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz**

## **17. References**

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [6] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [7] FCC KDB 616217 D04 v01r01, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", May 2013
- [8] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [9] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.



---

## ***Appendix A. Plots of System Performance Check***

The plots are shown as follows.

## System Check\_Body\_2450MHz\_140717

### DUT: D2450V2 - SN: 908

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_140717 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.983$  S/m;  $\epsilon_r = 51.159$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.32, 7.32, 7.32); Calibrated: 2014/4/22;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2014/4/30
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1201
- Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 20.4 W/kg



**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.996 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 27.4 W/kg

**SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.4 W/kg**

Maximum value of SAR (measured) = 20.6 W/kg



0 dB = 20.6 W/kg

**System Check\_Body\_2450MHz\_140721****DUT: D2450V2 - SN: 736**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_140721 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.942$  mho/m;  $\epsilon_r =$

$50.952$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.4 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3857; ConvF(7.14, 7.14, 7.14); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Pin=250mW/Area Scan (71x71x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 19.579 mW/g


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 85.745 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 26.075 W/kg

**SAR(1 g) = 12.7 mW/g; SAR(10 g) = 5.95 mW/g**

Maximum value of SAR (measured) = 19.395 mW/g



**System Check\_Body\_5200MHz\_140713****DUT: D5000V2 - SN:1006**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: MSL\_5000\_140713 Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.138$  mho/m;  $\epsilon_r =$

47.493;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.5 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3857; ConvF(4.54, 4.54, 4.54); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Pin=100mW/Area Scan (71x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 17.142 mW/g


**Pin=100mW/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 40.883 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 29.790 W/kg

**SAR(1 g) = 7.23 mW/g; SAR(10 g) = 2.04 mW/g**

Maximum value of SAR (measured) = 17.269 mW/g



0 dB = 17.270mW/g

**System Check\_Body\_5800MHz\_140715****DUT: D5000V2 - SN:1006**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: MSL\_5000\_140715 Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.127$  mho/m;  $\epsilon_r =$

47.784;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3857; ConvF(4.21, 4.21, 4.21); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Pin=100mW/Area Scan (71x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 17.982 mW/g


**Pin=100mW/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 36.905 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 32.729 W/kg

**SAR(1 g) = 7.23 mW/g; SAR(10 g) = 2.02 mW/g**

Maximum value of SAR (measured) = 17.733 mW/g



0 dB = 17.730mW/g



---

***Appendix B. Plots of High SAR Measurement***

The plots are shown as follows.

**01 WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch11\_Ant 0**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_140717 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2$  S/m;  $\epsilon_r = 51.115$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.32, 7.32, 7.32); Calibrated: 2014/4/22;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2014/4/30
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1201
- Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

**Ch11/Area Scan (91x71x1):** Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 1.37 W/kg


**Ch11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.271 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.24 W/kg

**SAR(1 g) = 1.020 W/kg; SAR(10 g) = 0.429 W/kg**

Maximum value of SAR (measured) = 1.67 W/kg



**02 WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch1\_Ant 1**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_140717 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.932$  S/m;  $\epsilon_r = 51.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.32, 7.32, 7.32); Calibrated: 2014/4/22;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2014/4/30
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1201
- Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

**Ch1/Area Scan (61x191x1):** Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.830 W/kg


**Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.609 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.161 W/kg**

Maximum value of SAR (measured) = 0.789 W/kg



**03 WLAN 2.4G\_802.11n-HT20\_Bottom Face\_0cm\_Ch6\_Ant 0+1**

Communication System: 802.11n; Frequency: 2437 MHz; Duty Cycle: 1:1.1

Medium: MSL\_2450\_140717 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.966$  S/m;  $\epsilon_r = 51.206$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3911; ConvF(7.32, 7.32, 7.32); Calibrated: 2014/4/22;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1358; Calibrated: 2014/4/30
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1201
- Measurement SW: DASY52, Version 52.8 (5); SEMCAD X Version 14.6.8 (7028)

**Ch6/Area Scan (91x201x1):** Interpolated grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.400 W/kg


**Ch6/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.685 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.576 W/kg

**SAR(1 g) = 0.267 W/kg; SAR(10 g) = 0.114 W/kg**

Maximum value of SAR (measured) = 0.397 W/kg



**#04\_WLAN 5G Band1\_802.11a\_6M\_Edge2 0cm\_Ch36\_Ant.0**

Communication System: WIFI (0); Frequency: 5180 MHz; Duty Cycle: 1:1.044

Medium: MSL\_5000\_140713 Medium parameters used:  $f = 5180$  MHz;  $\sigma = 5.104$  mho/m;  $\epsilon_r =$

47.493;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.54, 4.54, 4.54); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch36/Area Scan (61x181x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.111 mW/g


**Ch36/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 12.324 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 3.587 W/kg

**SAR(1 g) = 1.000 mW/g; SAR(10 g) = 0.267 mW/g**

Maximum value of SAR (measured) = 2.156 mW/g



**#05\_WLAN 5G Band1\_802.11a\_6M\_Edge4 0cm\_Ch36\_Ant.1**

Communication System: WIFI (0); Frequency: 5180 MHz; Duty Cycle: 1:1.047

Medium: MSL\_5000\_140713 Medium parameters used:  $f = 5180$  MHz;  $\sigma = 5.104$  mho/m;  $\epsilon_r =$

47.493;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.54, 4.54, 4.54); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch36/Area Scan (61x181x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.830 mW/g


**Ch36/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0.994 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.939 W/kg

**SAR(1 g) = 1.120 mW/g; SAR(10 g) = 0.304 mW/g**

Maximum value of SAR (measured) = 2.559 mW/g



**#06\_WLAN 5G Band1\_802.11n-HT20\_MCS0\_Edge4 0cm\_Ch36\_Ant.0+1**

Communication System: WIFI (0); Frequency: 5180 MHz; Duty Cycle: 1:1.099

Medium: MSL\_5000\_140713 Medium parameters used:  $f = 5180$  MHz;  $\sigma = 5.104$  mho/m;  $\epsilon_r =$

47.493;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.54, 4.54, 4.54); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch36/Area Scan (61x181x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.198 mW/g


**Ch36/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0.700 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.630 W/kg

**SAR(1 g) = 0.452 mW/g; SAR(10 g) = 0.117 mW/g**

Maximum value of SAR (measured) = 1.083 mW/g



**#07\_WLAN 5G Band4\_802.11n-HT40\_MCS0\_Edge2 0cm\_Ch159\_Ant.0**

Communication System: WIFI (0); Frequency: 5795 MHz; Duty Cycle: 1:1.051

Medium: MSL\_5000\_140715 Medium parameters used:  $f = 5795$  MHz;  $\sigma = 5.987$  mho/m;  $\epsilon_r =$

46.542;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.21, 4.21, 4.21); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch159/Area Scan (61x181x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.170 mW/g


**Ch159/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 8.490 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.500 W/kg

**SAR(1 g) = 0.457 mW/g; SAR(10 g) = 0.123 mW/g**

Maximum value of SAR (measured) = 1.054 mW/g



**#08\_WLAN 5G Band4\_802.11a\_6M\_Bottom Face 0cm\_Ch165\_Ant.1**

Communication System: WIFI (0); Frequency: 5825 MHz; Duty Cycle: 1:1.047

Medium: MSL\_5000\_140715 Medium parameters used:  $f = 5825$  MHz;  $\sigma = 6.054$  mho/m;  $\epsilon_r =$

46.462;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.21, 4.21, 4.21); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch165/Area Scan (131x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.925 mW/g


**Ch165/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0.927 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 4.206 W/kg

**SAR(1 g) = 1.270 mW/g; SAR(10 g) = 0.369 mW/g**

Maximum value of SAR (measured) = 2.770 mW/g



**#09\_WLAN 5G Band4\_802.11n-HT20\_MCS0\_Bottom Face 0cm\_Ch149\_Ant.0+1**

Communication System: WIFI (0); Frequency: 5745 MHz; Duty Cycle: 1:1.099

Medium: MSL\_5000\_140715 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 5.936$  mho/m;  $\epsilon_r =$

46.728;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(4.21, 4.21, 4.21); Calibrated: 2014.05.23
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch149/Area Scan (141x261x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.068 mW/g


**Ch149/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.572 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.979 W/kg

**SAR(1 g) = 0.918 mW/g; SAR(10 g) = 0.269 mW/g**

Maximum value of SAR (measured) = 2.017 mW/g



**#10\_BT\_DH5\_Bottom Face 0cm\_Ch78**

Communication System: Bluetooth (0); Frequency: 2480 MHz; Duty Cycle: 1:1.2

Medium: MSL\_2450\_140721 Medium parameters used:  $f = 2480$  MHz;  $\sigma = 1.982$  mho/m;  $\epsilon_r =$

50.808;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.14, 7.14, 7.14); Calibrated: 2014.05.23
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2014.05.19
- Phantom: SAM3; Type: SAM; Serial: TP-1079
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.4.5 (3634)

**Ch78/Area Scan (81x51x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.00915 mW/g


**Ch78/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.669 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.011 W/kg

**SAR(1 g) = 0.000165 mW/g; SAR(10 g) = 1.72e-005 mW/g**

Maximum value of SAR (measured) = 0.00603 mW/g



0 dB = 0.006mW/g