



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	KODEN ELECTRONICS CO., LTD.
	5278 UENOHARA UENOHARA-SHI YAMANASHI JAPAN 409-0112
FCC ID	O5VRB805
IC	8477A-RB805
MODEL NUMBER	RB805
PRODUCT DESCRIPTION	X BAND MARINE RADAR
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Christian Pawlak

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Christian Pawlak

Engineering Project Manager

Date: 01/26/2017

Applicant: KODEN ELECTRONICS CO., LTD.

FCC ID: O5VRB805

IC: 8477A-RB805

Report: V:\K\KODEN_O5V\1246AUT16\1246AUT16RF EXP MPE.DOCX

RF Exposure Requirements

General information

Device type: X BAND MARINE RADAR

Devices that operate under Part 80, 90 of this chapter are subject to RF exposure evaluation prior to equipment authorization or use.

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

Applicant: KODEN ELECTRONICS CO., LTD.

FCC ID: O5VRB805

IC: 8477A-RB805

Report: V:\K\KODEN_O5V\1246AUT16\1246AUT16RF EXP MPE.DOCX

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	4000	W	<i>equals</i>	Max Power	4000000	mW
Duty Cycle	0.05	%	<i>equals</i>	Duty Factor	0.0005	numeric
Antenna Gain	24	dBi	<i>equals</i>	Gain numeric	251.1886	numeric
Coax Loss	0	dB		Gain - Coax Loss	251.1886	numeric
Power Density	1	mW/cm ²				
Frequency	9440	MHz				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency range	Power den	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	6.3
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	200 cm	2.00 m
------------------------------------	---------------	---------------

Minimum Separation in Inches 78.65828 Inches

Applicant: KODEN ELECTRONICS CO., LTD.

FCC ID: O5VRB805

IC: 8477A-RB805

Report: V:\K\KODEN_O5V\1246AUT16\1246AUT16RF EXP MPE.DOCX