

Rescan Test Data on August 30, 2001, for Fundamental Frequency, 3 meters

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Subpart C	
Frequency MHz	Ampl. dBmV/m	Comments	Angle Degree	Height Meter	Polar H/ V	Antenna dBmV/m	Cable dB	Amp. dB	Corr. Ampl. dBmV/m	Limit dBmV/m	Margin dB
902.12	92.9	Base, Low Channel (QP)	180	1.5	V	24.8	3.0	30.0	90.7	94.0	-3.3
902.12	91.4	Base, Low Channel (QP)	225	1.3	H	24.8	3.0	30.0	89.2	94.0	-4.8
902.69	92.8	Base, Middle Channel (QP)	160	1.5	V	24.8	3.0	30.0	90.6	94.0	-3.4
902.69	91.6	Base, Middle Channel (QP)	250	1.4	H	24.8	3.0	30.0	89.4	94.0	-4.6
903.29	92.8	Base, High Channel (QP)	275	1.2	V	24.8	3.0	30.0	90.6	94.0	-3.4
903.29	91.2	Base, High Channel (QP)	180	1.5	H	24.8	3.0	30.0	89.0	94.0	-5.0
926.12	91.3	Handset, Low Channel(QP)	90	1.5	V	24.7	4.4	30.0	90.4	94.0	-3.6
926.12	92.3	Handset, Low Channel(QP)	90	1.3	H	24.7	4.4	30.0	91.4	94.0	-2.6
926.69	90.0	Handset, Middle Channel(QP)	0	1.2	V	24.7	4.4	30.0	89.1	94.0	-4.9
926.69	92.7	Handset, Middle Channel(QP)	180	1.6	H	24.7	4.4	30.0	91.8	94.0	-2.2
927.29	93.7	Handset, High Channel(QP)	0	1.3	V	24.7	4.4	30.0	92.8	94.0	-1.2
927.29	91.9	Handset, High Channel(QP)	180	1.4	H	24.7	4.4	30.0	91.0	94.0	-3.0