



FCC TEST REPORT

REPORT NO.: RF911217R02A

MODEL NO.: WM606-B

RECEIVED: Dec. 17, 2002

TESTED: Dec. 12 ~ Dec. 22, 2002

APPLICANT: BROMAX COMMUNICATIONS, INC.

ADDRESS: No. 20, Kuang Fu Road, Hsin Chu Industrial
Park, Hu Kou, Hsin Chu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan,
R.O.C.

This test report consists of 74 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP	11
4.1.6	EUT OPERATING CONDITIONS	12
4.1.7	TEST RESULTS	13
4.2	RADIATED EMISSION MEASUREMENT	19
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	19
4.2.2	TEST INSTRUMENTS	20
4.2.3	TEST PROCEDURES	21
4.2.4	DEVIATION FROM TEST STANDARD	21
4.2.5	TEST SETUP	22
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	TEST RESULTS --- (with 2dBi antenna gain)	23
4.2.8	TEST RESULTS --- (with 5dBi antenna gain)	25
4.2.9	TEST RESULTS (A) --- (with 2dBi antenna gain)	27
4.2.10	TEST RESULTS (A) --- (with 5dBi antenna gain)	30
4.2.11	TEST RESULTS (B) --- (with 2dBi antenna gain)	33
4.2.12	TEST RESULTS (B) --- (with 5dBi antenna gain)	36
4.3	6dB BANDWIDTH MEASUREMENT	39
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	39
4.3.2	TEST INSTRUMENTS	39
4.3.3	TEST PROCEDURE	40
4.3.4	DEVIATION FROM TEST STANDARD	40
4.3.5	TEST SETUP	40



4.3.6	EUT OPERATING CONDITIONS.....	40
4.3.7	TEST RESULTS (A).....	41
4.3.8	TEST RESULTS (B).....	45
4.4	MAXIMUM PEAK OUTPUT POWER.....	49
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	49
4.4.2	TEST INSTRUMENTS.....	49
4.4.3	TEST PROCEDURES.....	50
4.4.4	DEVIATION FROM TEST STANDARD.....	50
4.4.5	TEST SETUP.....	50
4.4.6	EUT OPERATING CONDITIONS.....	50
4.4.7	TEST RESULTS (A).....	51
4.4.8	TEST RESULTS (B).....	51
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	52
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	52
4.5.2	TEST INSTRUMENTS.....	52
4.5.3	TEST PROCEDURE.....	53
4.5.4	DEVIATION FROM TEST STANDARD.....	53
4.5.5	TEST SETUP.....	53
4.5.6	EUT OPERATING CONDITIONS.....	53
4.5.7	TEST RESULTS (A).....	54
4.5.8	TEST RESULTS (B).....	58
4.6	BAND EDGES MEASUREMENT.....	62
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	62
4.6.2	TEST INSTRUMENTS.....	62
4.6.3	TEST PROCEDURE.....	62
4.6.4	DEVIATION FROM TEST STANDARD.....	62
4.6.5	EUT OPERATING CONDITION.....	63
4.6.6	TEST RESULTS (A).....	63
4.6.7	TEST RESULTS (B).....	66
4.7	ANTENNA REQUIREMENT.....	69
4.7.1	STANDARD APPLICABLE.....	69
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	69
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	70
6	INFORMATION ON THE TESTING LABORATORIES.....	74



1 CERTIFICATION

PRODUCT : 54M WLAN MiniPCI Module
MODEL NO. : WM606-B
BRAND : BroMax
APPLICANT : BROMAX COMMUNICATIONS, INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Dec. 12 ~ Dec. 22, 2002, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY: Rennie Wang, **DATE:** December 25, 2002
Rennie Wang

APPROVED BY: Alan Lane, **DATE:** December 25, 2002
Dr. Alan Lane
Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -14.24dBuV at 0.17MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.00dBuV at 116.5 MHz & 2484.00 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	54M WLAN MiniPCI Module
MODEL NO.	WM606-B
POWER SUPPLY	3.3VDC from host equipment
MODULATION TYPE	BPSK, QPSK, CCK, 16QAM, 64QAM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	1/2/5.5/6/9/11/12/18/24/36/48/54Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
BANDWIDTH OF EACH CHANNEL	22MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	17.24dBm
ANTENNA TYPE	Dipole Antenna
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. This report is issued as a supplementary report to the original report with no. RF911217R02. And the model in this report is identical to the original application model.
2. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
3. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
4. There are three antennas provided to this EUT. Please refer to the following for details:

Item	Antenna type	Internal Connector	External Connector	Antenna Gain (dBi)
1	Dipole	UFL	Reversed TNC	2
2	Dipole	UFL	Reversed SMC	5
3	Dipole	UFL	Reversed TNC	5

Note: For item 1 and 3, the worst case, were chosen for final test.

5. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate, 11Mbps with CCK technique and 54Mbps with OFDM technique, the worst case, were chosen for final test.
4. For "Radiated Emission Measurement" test, antenna gain with 2dBi and 5dBi which mentioned on NOTE 3 of section 3.1, were chosen for final test.
5. Test result A is for 802.11b(DSSS) and test result B is for 802.11g(OFDM).

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 54M WLAN MiniPCI Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED
2	MODEM	ACEEX	1414	980020569	IFAXDM1414
3	NOTEBOOK PC	DELL	PPX	99125	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
2	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
3	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 12, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	Jul. 23, 2003
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 30, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Nov. 29, 2003
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Nov. 29, 2003
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	Jul. 23, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	Jul. 23, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*”: These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Open Site No. 5.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

The diagram illustrates a test setup for electromagnetic compatibility. On the left, a box labeled 'EUT' (Equipment Under Test) is positioned on a stand. A vertical dimension line indicates a distance of 40 cm from the 'Vertical Reference Ground Plane' (a vertical wall) to the EUT. Below the EUT, a box labeled 'LISN' (Line Impedance Stabilization Network) is connected to the EUT. A horizontal dimension line indicates a distance of 80 cm from the 'Horizontal Reference Ground Plane' (a horizontal line) to the LISN. The LISN is connected to a 'Test Receiver' on the right, which is also on a stand. The Test Receiver is connected to the 'Horizontal Reference Ground Plane' via a cable. The entire setup is connected to a 'Bonded to Horizontal Ground Plane' (a horizontal line at the bottom). A dashed line points to the 'Vertical Reference Ground Plane'.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

Issued: December 25, 2002



4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer and the printer prints them on paper.


4.1.7 TEST RESULTS

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	50.64	-	50.74	-	64.98	54.98	-14.24	-
2	0.224	0.10	42.85	-	42.95	-	62.66	52.66	-19.71	-
3	0.283	0.10	39.87	-	39.97	-	60.73	50.73	-20.76	-
4	0.849	0.17	18.57	-	18.74	-	56.00	46.00	-37.26	-
5	12.520	0.70	25.11	-	25.81	-	60.00	50.00	-34.19	-
6	18.109	0.99	27.79	-	28.78	-	60.00	50.00	-31.22	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.171	0.10	50.22	-	50.32	-	64.92	54.92	-14.60	-
2	0.174	0.10	44.34	-	44.44	-	64.76	54.76	-20.32	-
3	0.369	0.10	10.66	-	10.76	-	58.53	48.53	-47.77	-
4	3.617	0.28	28.81	-	29.09	-	56.00	46.00	-26.91	-
5	12.050	0.44	24.40	-	24.84	-	60.00	50.00	-35.16	-
6	21.750	0.77	25.28	-	26.05	-	60.00	50.00	-33.95	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.36	-	49.46	-	64.98	54.98	-15.52	-
2	0.228	0.10	43.36	-	43.46	-	62.52	52.52	-19.06	-
3	0.283	0.10	37.86	-	37.96	-	60.73	50.73	-22.77	-
4	3.570	0.36	24.51	-	24.87	-	56.00	46.00	-31.13	-
5	12.473	0.70	23.29	-	23.99	-	60.00	50.00	-36.01	-
6	19.555	1.07	28.29	-	29.36	-	60.00	50.00	-30.64	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.57	-	49.67	-	64.98	54.98	-15.31	-
2	0.228	0.10	41.99	-	42.09	-	62.52	52.52	-20.43	-
3	0.287	0.10	33.63	-	33.73	-	60.62	50.62	-26.89	-
4	3.570	0.28	28.99	-	29.27	-	56.00	46.00	-26.73	-
5	13.723	0.47	24.17	-	24.64	-	60.00	50.00	-35.36	-
6	19.270	0.76	28.68	-	29.44	-	60.00	50.00	-30.56	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.172	0.10	48.77	-	48.87	-	64.85	54.85	-15.98	-
2	0.228	0.10	42.79	-	42.89	-	62.52	52.52	-19.63	-
3	0.283	0.10	38.71	-	38.81	-	60.73	50.73	-21.92	-
4	3.863	0.39	28.77	-	29.16	-	56.00	46.00	-26.84	-
5	14.285	0.77	16.50	-	17.27	-	60.00	50.00	-42.73	-
6	19.266	1.06	25.71	-	26.77	-	60.00	50.00	-33.23	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60%RH, 1005 hPa	TESTED BY: Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	49.05	-	49.15	-	64.98	54.98	-15.83	-
2	0.224	0.10	38.69	-	38.79	-	62.66	52.66	-23.87	-
3	0.283	0.10	37.21	-	37.31	-	60.73	50.73	-23.42	-
4	4.031	0.30	27.64	-	27.94	-	56.00	46.00	-28.06	-
5	11.461	0.43	21.69	-	22.12	-	60.00	50.00	-37.88	-
6	17.656	0.66	26.74	-	27.40	-	60.00	50.00	-32.60	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Apr. 29, 2003
* HP Preamplifier	8449B	3008A01201	Dec. 01, 2003
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHAFFNER Tunable Dipole Antenna SCHWARZBECK Tunable Dipole Antenna	VHBA 9123 UHA 9105	459 977	Nov. 22, 2003
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 09, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA
Site Registration No.	FCC: 90422 Canada IC: IC 3789 VCCI: R-1039		

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 5.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS --- (with 2dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	18 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.00	31.7 QP	40.00	-8.30	1.50 H	5	22.50	9.20
2	120.00	20.6 QP	43.50	-22.90	1.74 H	124	5.30	15.30
3	160.00	31.3 QP	43.50	-12.20	1.37 H	88	18.40	12.90
4	240.00	32.2 QP	46.00	-13.80	1.65 H	62	14.80	17.40
5	280.00	25.5 QP	46.00	-20.50	1.60 H	206	6.00	19.50
6	320.00	30.2 QP	46.00	-15.80	1.34 H	191	9.70	20.50
7	420.00	32.9 QP	46.00	-13.10	1.00 H	146	9.60	23.30

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	18 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.00	22.6 QP	40.00	-17.40	1.26 V	129	13.40	9.20
2	120.00	40.7 QP	43.50	-2.80	1.18 V	347	25.40	15.30
3	160.00	36.5 QP	43.50	-7.00	1.31 V	187	23.60	12.90
4	200.00	38.2 QP	43.50	-5.30	1.28 V	39	25.00	13.20
5	240.00	32.3 QP	46.00	-13.70	1.77 V	79	14.90	17.40
6	280.00	26.6 QP	46.00	-19.40	1.54 V	161	7.10	19.50
7	420.00	28.7 QP	46.00	-17.30	1.23 V	318	5.40	23.30
8	719.99	23.5 QP	46.00	-22.50	1.40 V	81	-5.10	28.60

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

4.2.8 TEST RESULTS --- (with 5dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.00	35.0 QP	40.00	-5.00	1.53 H	210	25.80	9.20
2	83.71	36.1 QP	40.00	-3.90	1.41 H	225	26.10	10.00
3	91.70	32.0 QP	43.50	-11.50	1.29 H	73	20.30	11.70
4	95.00	35.2 QP	43.50	-8.30	1.31 H	162	22.70	12.50
5	116.50	41.5 QP	43.50	-2.00	1.62 H	191	26.50	15.00
6	120.00	38.0 QP	43.50	-5.50	1.49 H	241	22.70	15.30
7	146.60	41.0 QP	43.50	-2.50	1.62 H	191	27.10	13.90
8	163.20	37.5 QP	43.50	-6.00	1.46 H	156	24.60	12.90
9	184.50	36.0 QP	43.50	-7.50	1.23 H	227	23.20	12.80
10	200.00	35.0 QP	43.50	-8.50	1.35 H	136	21.80	13.20
11	216.20	39.0 QP	46.00	-7.00	1.54 H	98	24.10	14.90
12	335.50	38.4 QP	46.00	-7.60	1.22 H	47	17.40	21.00
13	440.00	31.0 QP	46.00	-15.00	1.08 H	15	7.40	23.60
14	480.00	31.5 QP	46.00	-14.50	1.05 H	305	6.90	24.60
15	640.00	33.7 QP	46.00	-12.30	1.45 H	232	6.00	27.70
16	720.00	31.2 QP	46.00	-14.80	1.12 H	236	2.60	28.60

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 60 % RH, 1050 hPa	TESTED BY: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	112.00	32.0 QP	43.50	-11.50	1.42 V	123	17.40	14.60
2	120.00	39.0 QP	43.50	-4.50	1.04 V	114	23.70	15.30
3	129.00	33.0 QP	43.50	-10.50	1.25 V	141	18.10	14.90
4	160.00	33.2 QP	43.50	-10.30	1.58 V	117	20.30	12.90
5	200.00	29.0 QP	43.50	-14.50	1.31 V	45	15.80	13.20
6	240.00	27.6 QP	46.00	-18.40	1.48 V	108	10.20	17.40
7	362.00	35.3 QP	46.00	-10.70	1.39 V	117	13.50	21.80
8	440.00	29.4 QP	46.00	-16.60	1.35 V	171	5.80	23.60
9	533.50	33.4 QP	46.00	-12.60	1.06 V	145	7.90	25.50
10	640.00	33.9 QP	46.00	-12.10	1.25 V	171	6.20	27.70
11	720.00	33.8 QP	46.00	-12.20	1.39 V	185	5.20	28.60
12	960.00	34.0 QP	46.00	-12.00	1.28 V	104	2.30	31.70

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

4.2.9 TEST RESULTS (A) ---(with 2dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	37.8 PK	74.00	-36.20	1.32 H	220	10.30	27.40
2	2390.00	53.4 PK	74.00	-20.60	1.00 H	5	23.90	29.50
2	2390.00	42.7 AV	54.00	-11.30	1.00 H	5	13.20	27.40
3	*2412.00	100.0 PK			1.30 H	3	70.30	29.70
3	*2412.00	89.4 AV			1.30 H	3	59.70	29.00
4	3216.00	48.2 PK	74.00	-25.80	1.37 H	44	15.80	32.40
5	4824.00	45.5 PK	74.00	-28.50	1.27 H	268	10.10	35.40
6	9648.00	53.6 PK	74.00	-20.40	1.50 H	325	9.80	43.80
6	9648.00	43.6 AV	54.00	-10.40	1.50 H	325	-0.30	29.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	36.0 PK	74.00	-38.00	1.35 V	45	8.50	27.40
2	2390.00	61.6 PK	74.00	-12.40	1.30 V	1	32.10	29.50
2	2390.00	51.8 AV	54.00	-2.20	1.30 V	1	22.30	27.40
3	*2412.00	107.2 PK			1.26 V	1	77.50	29.70
3	*2412.00	99.8 AV			1.26 V	1	70.10	29.70
4	3126.00	52.9 PK	74.00	-21.10	1.17 V	358	20.80	32.20
4	3126.00	51.1 AV	54.00	-2.90	1.17 V	358	19.00	29.70
5	4824.00	53.4 PK	74.00	-20.60	1.64 V	257	18.00	35.40
5	4824.00	46.3 AV	54.00	-7.70	1.64 V	257	10.90	32.20
6	9648.00	52.3 PK	74.00	-21.70	1.15 V	42	8.40	43.80
6	9648.00	41.4 AV	54.00	-12.60	1.15 V	42	-2.50	35.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. " * " : Fundamental frequency.
 6. The other emission levels were very low against the limit.

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.30	37.0 PK	74.00	-37.00	1.28 H	213	9.60	27.40
2	2390.00	45.0 PK	74.00	-29.00	1.43 H	243	15.50	29.50
3	*2437.00	99.4 PK			1.15 H	268	69.50	29.90
3	*2437.00	88.5 AV			1.15 H	268	58.60	29.90
4	3249.00	47.6 PK	74.00	-26.40	1.32 H	50	15.20	32.40
5	4874.00	44.6 PK	74.00	-29.40	1.34 H	279	9.10	35.50
6	9748.00	55.8 PK	74.00	-18.20	1.48 H	272	12.00	43.80
6	9748.00	44.6 AV	54.00	-9.40	1.48 H	272	0.80	29.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.30	35.8 PK	74.00	-38.20	1.24 V	36	8.40	27.40
2	2390.00	51.8 PK	74.00	-22.20	1.39 V	2	22.30	29.50
2	2390.00	36.9 AV	54.00	-17.10	1.39 V	2	7.40	27.40
3	*2437.00	107.0 PK			1.33 V	15	77.10	29.90
3	*2437.00	99.3 AV			1.33 V	15	69.40	29.90
4	3249.00	51.9 PK	74.00	-22.10	1.09 V	353	19.50	32.40
4	3249.00	50.3 AV	54.00	-3.70	1.09 V	353	17.90	29.90
5	4874.00	52.9 PK	74.00	-21.10	1.58 V	240	17.40	35.50
5	4874.00	45.8 AV	54.00	-8.20	1.58 V	240	10.30	32.40
6	9748.00	53.7 PK	74.00	-20.30	1.06 V	50	9.90	43.80
6	9748.00	42.6 AV	54.00	-11.40	1.06 V	50	-1.20	35.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	36.4 PK	74.00	-37.60	1.42 H	234	9.00	27.40
2	*2462.00	99.9 PK			1.11 H	286	69.80	30.10
2	*2462.00	89.2 AV			1.11 H	286	59.10	30.10
3	2484.00	57.1 PK	74.00	-16.90	1.06 H	4	26.90	30.30
3	2484.00	46.6 AV	54.00	-7.40	1.06 H	4	16.40	30.10
4	3282.00	47.4 PK	74.00	-26.60	1.33 H	66	14.90	32.50
5	4924.00	45.1 PK	74.00	-28.90	1.36 H	276	9.50	35.60
6	9848.00	53.0 PK	74.00	-21.00	1.58 H	345	9.20	43.80
6	9848.00	41.5 AV	54.00	-12.50	1.58 H	345	-2.30	30.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.0 PK			1.28 V	10	76.90	30.10
1	*2462.00	99.2 AV			1.28 V	10	69.10	30.10
2	2484.00	62.9 PK	74.00	-11.10	1.42 V	37	32.70	30.30
2	2484.00	52.0 AV	54.00	-2.00	1.42 V	37	21.80	30.10
3	3282.00	52.9 PK	74.00	-21.10	1.00 V	124	20.40	32.50
3	3282.00	51.5 AV	54.00	-2.50	1.00 V	124	19.00	30.30
4	4924.00	54.8 PK	74.00	-19.20	1.74 V	268	19.20	35.60
4	4924.00	45.9 AV	54.00	-8.10	1.74 V	268	10.30	32.50
5	9848.00	41.7 PK	74.00	-32.30	1.07 V	30	-2.10	43.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

4.2.10 TEST RESULTS (A) ---(with 5dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	39.0 PK	74.00	-35.00	1.22 H	254	11.50	27.40
2	2387.00	47.6 PK	74.00	-26.40	1.24 H	45	18.10	29.50
3	*2412.00	90.2 AV			1.20 H	270	60.50	29.70
3	*2412.00	100.9 PK			1.20 H	270	71.20	29.70
4	3216.00	47.3 PK	74.00	-26.70	1.04 H	341	14.90	32.40
5	4824.00	44.9 PK	74.00	-29.10	1.35 H	48	9.50	35.40
6	7233.00	52.6 PK	74.00	-21.40	1.27 H	248	10.90	41.60
6	7233.00	45.6 AV	54.00	-8.40	1.27 H	248	3.90	29.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	39.0 PK	74.00	-35.00	1.30 V	224	11.50	27.40
2	2387.00	55.0 PK	74.00	-19.00	1.17 V	143	25.50	29.50
2	2387.00	43.7 AV	54.00	-10.30	1.17 V	143	14.20	27.40
3	*2412.00	108.5 PK			1.29 V	5	78.80	29.70
3	*2412.00	99.9 AV			1.29 V	5	70.20	29.70
4	3216.00	51.1 PK	74.00	-22.90	1.00 V	138	18.70	32.40
4	3216.00	47.6 AV	54.00	-6.40	1.00 V	138	15.20	29.70
5	4824.00	55.6 PK	74.00	-18.40	1.34 V	241	20.20	35.40
5	4824.00	48.6 AV	54.00	-5.40	1.34 V	241	13.20	32.40
6	7233.00	56.6 PK	74.00	-17.40	1.34 V	89	14.90	41.60
6	7233.00	49.2 AV	54.00	-4.80	1.34 V	89	7.60	35.40
7	9648.00	53.5 PK	74.00	-20.50	1.18 V	11	9.60	43.80
7	9648.00	44.5 AV	54.00	-9.50	1.18 V	11	0.60	41.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	40.2 PK	74.00	-33.80	1.17 H	24	12.80	27.40
2	*2437.00	100.2 PK			1.26 H	264	70.30	29.90
2	*2437.00	89.3 AV			1.26 H	264	59.40	29.90
3	3249.80	45.3 PK	74.00	-28.70	1.41 H	207	12.90	32.40
4	4874.00	44.7 PK	74.00	-29.30	1.14 H	52	9.20	35.50
5	7311.00	57.0 PK	74.00	-17.00	1.72 H	13	15.10	41.90
5	7311.00	47.8 AV	54.00	-6.20	1.72 H	13	5.90	29.90
6	9745.00	54.4 PK	74.00	-19.60	1.19 H	34	10.60	43.80
6	9745.00	47.3 AV	54.00	-6.70	1.19 H	34	3.50	32.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	41.1 PK	74.00	-32.90	1.32 V	27	13.70	27.40
2	*2437.00	108.0 PK			1.36 V	2	78.10	29.90
2	*2437.00	99.5 AV			1.36 V	2	69.60	29.90
3	3249.80	49.7 PK	74.00	-24.30	1.50 V	290	17.30	32.40
4	4874.00	49.2 PK	74.00	-24.80	1.42 V	127	13.70	35.50
5	7311.00	62.8 PK	74.00	-11.20	1.32 V	93	20.90	41.90
5	7311.00	50.6 AV	54.00	-3.40	1.32 V	93	8.70	29.90
6	9745.00	53.6 PK	74.00	-20.40	1.28 V	163	9.80	43.80
6	9745.00	45.9 AV	54.00	-8.10	1.28 V	163	2.10	32.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.



EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	39.4 PK	74.00	-34.60	1.44 H	167	12.00	27.40
2	*2462.00	100.5 PK			1.10 H	296	70.40	30.10
2	*2462.00	90.3 AV			1.10 H	296	60.20	30.10
3	2499.00	44.7 PK	74.00	-29.30	1.61 H	17	14.30	30.40
4	3282.50	44.8 PK	74.00	-29.20	1.82 H	206	12.30	32.50
5	4924.00	46.0 PK	74.00	-28.00	1.42 H	355	10.40	35.60
6	7386.00	54.1 PK	74.00	-19.90	1.28 H	225	11.90	42.20
6	7386.00	45.1 AV	54.00	-8.90	1.28 H	225	2.90	30.10
7	9848.00	53.6 PK	74.00	-20.40	1.60 H	271	9.80	43.80
7	9848.00	47.1 AV	54.00	-6.90	1.60 H	271	3.30	30.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	40.8 PK	74.00	-33.20	1.07 V	138	13.40	27.40
2	*2462.00	108.3 PK			1.32 V	16	78.20	30.10
2	*2462.00	100.2 AV			1.32 V	16	70.10	30.10
3	2499.00	54.7 PK	74.00	-19.30	1.07 V	276	24.30	30.40
3	2499.00	39.3 AV	54.00	-14.70	1.07 V	276	8.90	30.10
4	3283.00	48.2 PK	74.00	-25.80	1.10 V	39	15.70	32.50
5	4924.00	50.8 PK	74.00	-23.20	1.48 V	45	15.20	35.60
5	4924.00	44.8 AV	54.00	-9.20	1.48 V	45	9.20	30.40
6	7386.00	60.1 PK	74.00	-13.90	1.42 V	185	17.90	42.20
6	7386.00	49.1 AV	54.00	-4.90	1.42 V	185	6.90	32.50
7	9847.00	52.8 PK	74.00	-21.20	1.30 V	213	9.00	43.80
7	9847.00	45.6 AV	54.00	-8.40	1.30 V	213	1.80	35.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

4.2.11 TEST RESULTS (B) --- (with 2dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	36.4 PK	74.00	-37.60	1.32 H	96	8.90	27.40
2	2390.00	60.3 PK	74.00	-13.70	1.16 H	278	30.80	29.50
2	2390.00	44.0 AV	54.00	-10.00	1.16 H	278	14.50	27.40
3	*2412.00	97.6 PK			1.45 H	12	67.90	29.70
3	*2412.00	88.2 AV			1.45 H	12	58.50	29.00
4	3216.00	43.7 PK	74.00	-30.30	1.55 H	296	11.40	32.40
5	9648.00	55.0 PK	74.00	-19.00	1.15 H	50	11.20	43.80
5	9648.00	44.3 AV	54.00	-9.70	1.15 H	50	0.40	29.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	36.8 PK	74.00	-37.20	1.23 V	313	9.30	27.40
2	2386.00	67.9 PK	74.00	-6.10	1.15 V	16	38.40	29.50
2	2386.00	51.6 AV	54.00	-2.40	1.15 V	16	22.10	27.40
3	*2412.00	107.5 PK			1.25 V	50	77.80	29.70
3	*2412.00	99.6 AV			1.25 V	50	69.90	29.70
4	3216.00	52.6 PK	74.00	-21.40	1.21 V	9	20.20	32.40
4	3216.00	45.8 AV	54.00	-8.20	1.21 V	9	13.40	29.70
5	4824.00	51.5 PK	74.00	-22.50	1.61 V	271	16.10	35.40
5	4824.00	45.0 AV	54.00	-9.00	1.61 V	271	9.60	32.40
6	9648.00	57.9 PK	74.00	-16.10	1.56 V	61	14.00	43.80
6	9648.00	48.4 AV	54.00	-5.60	1.56 V	61	4.50	35.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.



EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.40	39.9 PK	74.00	-34.10	1.42 H	85	12.50	27.40
2	2390.00	47.5 PK	74.00	-26.50	1.24 H	282	18.00	29.50
3	*2437.00	98.7 PK			1.25 H	299	68.80	29.90
3	*2437.00	89.1 AV			1.25 H	299	59.20	29.90
4	3249.30	42.1 PK	74.00	-31.90	1.72 H	278	9.70	32.40
5	9748.00	55.7 PK	74.00	-18.30	1.08 H	78	11.90	43.80
5	9748.00	45.2 AV	54.00	-8.80	1.08 H	78	1.40	29.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.40	36.3 PK	74.00	-37.70	1.34 V	294	8.90	27.40
2	2390.00	53.9 PK	74.00	-20.10	1.19 V	7	24.40	29.50
2	2390.00	36.9 AV	54.00	-17.10	1.19 V	7	7.40	27.40
3	*2437.00	106.8 PK			1.22 V	284	76.90	29.90
3	*2437.00	98.1 AV			1.22 V	284	68.20	29.90
4	3249.30	53.7 PK	74.00	-20.30	1.18 V	16	21.30	32.40
4	3249.30	46.5 AV	54.00	-7.50	1.18 V	16	14.10	29.90
5	4874.00	49.8 PK	74.00	-24.20	1.48 V	262	14.30	35.50
6	9748.00	59.0 PK	74.00	-15.00	1.48 V	49	15.20	43.80
6	9748.00	49.5 AV	54.00	-4.50	1.48 V	49	5.70	32.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.



EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	37.5 PK	74.00	-36.50	1.39 H	85	10.10	27.40
2	*2462.00	98.2 PK			1.26 H	287	68.10	30.10
2	*2462.00	88.5 AV			1.26 H	287	58.40	30.10
3	2484.00	61.7 PK	74.00	-12.30	1.20 H	270	31.40	30.30
3	2484.00	45.9 AV	54.00	-8.10	1.20 H	270	15.60	30.10
4	9848.00	53.8 PK	74.00	-20.20	1.10 H	63	10.00	43.80
4	9848.00	42.9 AV	54.00	-11.10	1.10 H	63	-0.90	30.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	37.3 PK	74.00	-36.70	1.25 V	330	9.90	27.40
2	*2462.00	105.9 PK			1.18 V	13	75.80	30.10
2	*2462.00	98.2 AV			1.18 V	13	68.10	30.10
3	2484.00	71.3 PK	74.00	-2.70	1.12 V	10	41.10	30.30
3	2484.00	51.7 AV	54.00	-2.30	1.12 V	10	21.50	30.10
4	3282.60	53.1 PK	74.00	-20.90	1.32 V	92	20.60	32.50
4	3282.60	46.7 AV	54.00	-7.30	1.32 V	92	14.20	30.30
5	4924.00	52.2 PK	74.00	-21.80	1.54 V	275	16.60	35.60
5	4924.00	46.0 AV	54.00	-8.00	1.54 V	275	10.40	32.50
6	9848.00	56.6 PK	74.00	-17.40	1.47 V	57	12.80	43.80
6	9848.00	47.3 AV	54.00	-6.70	1.47 V	57	3.50	35.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

4.2.12 TEST RESULTS (B) ---(with 5dBi antenna gain)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	39.0 PK	74.00	-35.00	1.28 H	193	11.60	27.40
2	2384.00	52.4 PK	74.00	-21.60	1.25 H	218	22.90	29.50
2	2384.00	41.4 AV	54.00	-12.60	1.25 H	218	11.90	27.40
3	*2412.00	99.2 PK			1.14 H	279	69.50	29.70
3	*2412.00	89.8 AV			1.14 H	279	60.10	29.00
4	3216.00	43.8 PK	74.00	-30.20	1.67 H	241	11.40	32.40
5	4824.00	47.6 PK	74.00	-26.40	1.26 H	335	12.20	35.40
6	7237.00	56.2 PK	74.00	-17.80	1.62 H	39	14.50	41.60
6	7237.00	45.3 AV	54.00	-8.70	1.62 H	39	3.60	29.70
7	9648.00	54.2 PK	74.00	-19.80	1.10 H	310	10.30	43.80
7	9648.00	44.5 AV	54.00	-9.50	1.10 H	310	0.60	32.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	41.1 PK	74.00	-32.90	1.52 V	164	13.70	27.40
2	2386.00	56.4 PK	74.00	-17.60	1.66 V	58	26.90	29.50
2	2386.00	42.4 AV	54.00	-11.60	1.66 V	58	12.90	27.40
3	*2412.00	108.5 PK			1.28 V	2	78.80	29.70
3	*2412.00	100.6 AV			1.28 V	2	70.90	29.70
4	3216.00	47.6 PK	74.00	-26.40	1.58 V	145	15.20	32.40
5	4824.00	47.8 PK	74.00	-26.20	1.33 V	94	12.40	35.40
6	7236.00	59.4 PK	74.00	-14.60	1.65 V	271	17.70	41.60
6	7236.00	45.6 AV	54.00	-8.40	1.65 V	271	3.90	29.70
7	9651.00	53.0 PK	74.00	-21.00	1.17 V	145	9.10	43.80
7	9651.00	42.5 AV	54.00	-11.50	1.17 V	145	-1.40	32.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	38.4 PK	74.00	-35.60	1.27 H	138	11.00	27.40
2	*2437.00	100.0 PK			1.15 H	280	70.10	29.90
2	*2437.00	90.1 AV			1.15 H	280	60.20	29.90
3	3249.00	43.3 PK	74.00	-30.70	1.52 H	127	10.90	32.40
4	4874.00	46.9 PK	74.00	-27.10	1.32 H	27	11.40	35.50
5	7311.00	53.8 PK	74.00	-20.20	1.61 H	48	11.90	41.90
5	7311.00	41.8 AV	54.00	-12.20	1.61 H	48	-0.10	29.90
6	9747.00	53.4 PK	74.00	-20.60	1.28 H	150	9.60	43.80
6	9747.00	44.1 AV	54.00	-9.90	1.28 H	150	0.30	32.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	40.5 PK	74.00	-33.50	1.42 V	103	13.10	27.40
2	*2437.00	107.9 PK			1.20 V	2	78.00	29.90
2	*2437.00	99.5 AV			1.20 V	2	69.60	29.90
3	3249.00	46.3 PK	74.00	-27.70	1.56 V	324	13.90	32.40
4	4874.00	49.5 PK	74.00	-24.50	1.08 V	103	14.00	35.50
5	7311.00	63.9 PK	74.00	-10.10	1.58 V	285	22.00	41.90
5	7311.00	48.0 AV	54.00	-6.00	1.58 V	285	6.10	29.90
6	9748.00	57.6 PK	74.00	-16.40	1.52 V	328	13.80	43.80
6	9748.00	45.8 AV	54.00	-8.20	1.52 V	328	2.00	32.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.



EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22 deg. C, 60 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	39.2 PK	74.00	-34.80	1.35 H	234	11.80	27.40
2	*2462.00	99.0 PK			1.20 H	288	68.90	30.10
2	*2462.00	89.2 AV			1.20 H	288	59.10	30.10
3	2491.00	44.6 PK	74.00	-29.40	1.31 H	271	14.30	30.30
4	3288.00	41.6 PK	74.00	-32.40	1.43 H	23	9.10	32.50
5	4924.00	45.5 PK	74.00	-28.50	1.29 H	261	9.90	35.60
6	7379.00	56.0 PK	74.00	-18.00	1.55 H	20	13.90	42.20
6	7379.00	47.0 AV	54.00	-7.00	1.55 H	20	4.90	30.10
7	9848.00	55.6 PK	74.00	-18.40	1.25 H	327	11.80	43.80
7	9848.00	48.4 AV	54.00	-5.60	1.25 H	327	4.60	30.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	40.0 PK	74.00	-34.00	1.24 V	127	12.60	27.40
2	*2462.00	106.8 PK			1.36 V	1	76.70	30.10
2	*2462.00	99.0 AV			1.36 V	1	68.90	30.10
3	2497.00	55.4 PK	74.00	-18.60	1.00 V	234	25.10	30.40
3	2497.00	40.2 AV	54.00	-13.80	1.00 V	234	9.90	30.10
4	3282.00	46.2 PK	74.00	-27.80	2.00 V	142	13.70	32.50
5	4924.00	51.2 PK	74.00	-22.80	1.38 V	142	15.60	35.60
5	4924.00	43.8 AV	54.00	-10.20	1.38 V	142	8.20	30.40
6	7385.00	64.1 PK	74.00	-9.90	1.25 V	96	21.90	42.20
6	7385.00	46.1 AV	54.00	-7.90	1.25 V	96	3.90	32.50
7	9842.00	58.4 PK	74.00	-15.60	1.10 V	230	14.60	43.80
7	9842.00	45.8 AV	54.00	-8.20	1.10 V	230	2.00	35.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.
 6. The other emission levels were very low against the limit.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS (A)


EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.50	0.5	PASS
6	2437	11.14	0.5	PASS
11	2462	11.46	0.5	PASS


CH1



CH6



CH11




4.3.8 TEST RESULTS (B)


EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.51	0.5	PASS
6	2437	16.39	0.5	PASS
11	2462	16.31	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
POWER METER	E4416A	GB41291118	Jul. 30, 2003
PEAK POWER SENSOR	E9327A	US40440722	Jul. 30, 2003

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS (A)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.21	30	PASS
6	2437	16.45	30	PASS
11	2462	16.83	30	PASS

4.4.8 TEST RESULTS (B)

EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	17.24	30	PASS
6	2437	16.50	30	PASS
11	2462	16.40	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS


Same as 4.3.6

4.5.7 TEST RESULTS (A)


EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-4.83	8	PASS
6	2437	-4.16	8	PASS
11	2462	-3.99	8	PASS


CH1



CH6



CH11




4.5.8 TEST RESULTS (B)


EUT	54M WLAN MiniPCI Module	MODEL	WM606-B
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24 deg. C, 64%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-10.52	8	PASS
6	2437	-10.76	8	PASS
11	2462	-10.69	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6


4.6.6 TEST RESULTS (A)

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE1: The band edge emission plot on the following first page shows 47.15dB delta between carrier maximum power and local maximum emission in restrict band (2.3879GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.10 (page 30) is 99.9dBuV/m, so the maximum field strength in restrict band is $99.9 - 47.15 = 52.75$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second page shows 48.38dB delta between carrier maximum power and local maximum emission in restrict band (2.4856GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.10 (page 32) is 100.2dBuV/m, so the maximum field strength in restrict band is $100.2 - 48.38 = 51.82$ dBuV/m which is under 54 dBuV/m limit.









4.6.7 TEST RESULTS (B)

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE1: The band edge emission plot on the following first page shows 48.31dB delta between carrier maximum power and local maximum emission in restrict band (2.3200GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.12 (page 36) is 100.6dBuV/m, so the maximum field strength in restrict band is $100.6 - 48.31 = 52.29$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second page shows 46.25dB delta between carrier maximum power and local maximum emission in restrict band (2.4843GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.12 (page 38) is 99.00dBuV/m, so the maximum field strength in restrict band is $99.0 - 46.25 = 52.75$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with UFL antenna connector. The maximum Gain of this antenna is 5dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST





RADIATED EMISSION TEST







6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.