

APPENDIX L: ADDITIONAL INFORMATION

Radiated Test Data - OATS 1 Mode: Digital/Receiver Limit/Distance: FCC B/3M

Temperature: 50°F					Humidity: 91%				
Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
38.600	Qp	V	180	1.0	42.4	-16.9	25.5	40.0	-14.5
57.790	Qp	H	145	1.0	36.7	-22.7	14.0	40.0	-26.0
76.980	Qp	V	180	1.0	44.3	-23.2	21.1	40.0	-18.9
96.170	Qp	V	45	1.0	43.7	-19.1	24.6	43.5	-18.9
115.360	Qp	V	145	1.0	41.3	-16.6	24.7	43.5	-18.8
153.740	Qp	V	180	1.0	37.6	-17.9	19.7	43.5	-23.8
345.622	Qp	V	25	1.0	35.2	-13.8	21.4	46.0	-24.6
518.332	Qp	V	45	1.0	35.8	-9.6	26.2	46.0	-19.8
556.730	Qp	H	45	1.0	33.9	-8.1	25.8	46.0	-20.2
633.472	Qp	V	145	1.0	34.8	-7.4	27.4	46.0	-18.6
786.992	Qp	V	45	1.0	33.8	-5.7	28.1	46.0	-17.9

TEST PERSONNEL:

Signature:



Test Date:

May 18, 2003

Typed/Printed
Name:

Rachid Sehb

Position:

Test Engineer