

Testing Laboratory
3787

RADIO TEST REPORT

FCC ID : O6ZA21KW
Equipment : AT&T TV™ Device and Remote Control
Brand Name : AT&T
Model Name : A21KW-500
Applicant : Humax Co., Ltd.
HUMAX BLDG., 2, Yeongmun-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do South Korea 17040
Manufacturer : Humax Co., Ltd.
HUMAX BLDG., 2, Yeongmun-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do South Korea 17040
Standard : 47 CFR FCC Part 15.247

The product was received on Oct. 19, 2020, and testing was started from Jan. 19, 2021 and completed on Mar. 10, 2021. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Cliff Chang

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Information.....	5
1.2 Applicable Standards	7
1.3 Testing Location Information	7
1.4 Measurement Uncertainty	7
2 Test Configuration of EUT	8
2.1 Test Channel Mode	8
2.2 The Worst Case Measurement Configuration.....	9
2.3 EUT Operation during Test	10
2.4 Accessories	10
2.5 Support Equipment.....	10
2.6 Test Setup Diagram	11
3 Transmitter Test Result	13
3.1 AC Power-line Conducted Emissions	13
3.2 DTS Bandwidth	15
3.3 Maximum Conducted Output Power	16
3.4 Power Spectral Density	19
3.5 Emissions in Non-restricted Frequency Bands	21
3.6 Emissions in Restricted Frequency Bands.....	22
4 Test Equipment and Calibration Data	26
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of DTS Bandwidth	
Appendix C. Test Results of Maximum Conducted Output Power	
Appendix D. Test Results of Power Spectral Density	
Appendix E. Test Results of Emissions in Non-restricted Frequency Bands	
Appendix F. Test Results of Emissions in Restricted Frequency Bands	
Appendix G. Test Photos	
Photographs of EUT v01	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A10_6 Ver1.3



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Wendy Pan



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ♦ Bluetooth LE uses a GFSK modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Antenna Gain (dBi)					Bluetooth
						WLAN 2.4GHz	WLAN5GHz				
							Band 1	Band 2	Band 3	Band 4	
1	2	Galtronics	DB1	PCB	I-PEX	2.366	3.786	3.786	4.028	4.041	-
2	1	Galtronics	DB2	PCB	I-PEX	2.987	3.513	3.624	4.484	4.875	-
3	1	Galtronics	BT	Printed	I-PEX	-	-	-	-	-	2.867

Correlated Antenna Gain (dBi)				
WLAN 2.4GHz	WLAN5GHz			
	Band 1	Band 2	Band 3	Band 4
4.72	5.2	5.45	5.9	5.9

Note: The above information was declared by manufacturer.

For WLAN 2.4GHz function:

For IEEE 802.11b/g/n/ax mode (2TX/2RX):

Ant.1 and Ant.2 can be used as transmitting/receiving antenna.

Ant.1 and Ant.2 could transmit/receive simultaneously.

For WLAN 5GHz function:

For IEEE 802.11a/n/ac/ax mode (2TX/2RX):

Ant.1 and Ant.2 can be used as transmitting/receiving antenna.

Ant.1 and Ant.2 could transmit/receive simultaneously.

For Bluetooth (1TX/1RX):

Only Ant.3 can be used as transmitting/receiving antenna.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-LE(1Mbps)	0.85	0.71	2.124m	1k

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	From Power Adapter		
Function	☒ Point-to-multipoint	☐ Point-to-point	
Test Software Version	PUTTY.exe_Release0.62		
Support Mode	☒	LE 1M PHY: 1 Mb/s	
	☐	LE Coded PHY (S=2): 500 Kb/s	
	☐	LE Coded PHY (S=8): 125 Kb/s	
	☐	LE 2M PHY: 2 Mb/s	

Note: The above information was declared by manufacturer.

1.1.5 EUT Function

The EUT supports AP Router in WLAN 2.4GHz, WLAN 5GHz Band 1/ Band 4 and supports Client without radar detection in WLAN 5GHz Band 2 / Band 3 function.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ FCC KDB 558074 D01 v05r02
- ♦ FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) TEL: 886-3-656-9065 FAX: 886-3-656-9085 Test site Designation No. TW3787 with FCC. Conformity Assessment Body Identifier (CABID) TW3787 with ISED.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted	TH02-CB	Jeff Wu	21.2-21.8 / 62-65	Jan. 20, 2021
Radiated<1G	03CH06-CB	Eason Chen	20.3-21.5 / 56-58	Mar. 09, 2021
Radiated>1G	03CH02-CB	Eason Chen	20.4-21.4 / 55-57	Jan. 19, 2021
AC Conduction	CO02-CB	Wei Li	21~23 / 54~57	Mar. 10, 2021

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Conducted Emission	2.4 dB	Confidence levels of 95%
Output Power Measurement	1.5 dB	Confidence levels of 95%
Power Density Measurement	2.4 dB	Confidence levels of 95%
Bandwidth Measurement	2%	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	Power Setting
BT-LE(1Mbps)	-
2402MHz	Default
2440MHz	Default
2480MHz	Default

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	CTX - BT
2	CTX - WLAN 2.4GHz
3	CTX - WLAN 5GHz
For operating mode 3 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
1	CTX - BT
2	CTX - WLAN 2.4GHz
3	CTX - WLAN 5GHz
For operating mode 2 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX



The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	Bluetooth+WLAN 2.4GHz
2	Bluetooth+WLAN 5GHz
Refer to Sporton Test Report No.: FA001903 for Co-location RF Exposure Evaluation.	

Note: The EUT can only be used at Z axis position.

2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

2.4 Accessories

Accessories				
No.	Equipment Name	Brand Name	Model Name	Rating
1	Adapter	AT&T	EPS18R1B-16	INPUT: 120V~0.5A Max 60Hz OUTPUT: 12V, 15A 18W
Other				
Remote Controller*1				

2.5 Support Equipment

For AC Conduction:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Ethernet NB	DELL	E6430	N/A
B	Flash disk3.0	Transcend	639205 7755	N/A


For Radiated:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Ethernet NB	DELL	E4300	N/A
B	Flash disk	Silicon Power	I-Series	N/A


For RF Conducted:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	Power cable	No	1.8m
3	USB cable	Yes	0.15m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



1.1.1. Measurement Results Calculation

The measured Level is calculated using:

- Corrected Reading: LISN Factor (LISN) + Attenuator (AT/AUX) + Cable Loss (CL) + Read Level (Raw) = Level
- Margin = -Limit + Level

3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
For the emission bandwidth shall be measured using one of the options below:
☒ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
☐ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
☐ Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	▪ Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
☐	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
Maximum Conducted Output Power	
[duty cycle ≥ 98% or external video / power trigger]	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
☐	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
☒	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
▪ Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪ Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).	
☒	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD. [duty cycle $\geq 98\%$ or external video / power trigger]
▪ For conducted measurement.	
▪ If The EUT supports multiple transmit chains using options given below:	
☐	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
☐	Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
☐	Option 3: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].	
Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
For the transmitter unwanted emissions shall be measured using following options below:	
	Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
☐	Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$).
☐	Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
☒	Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$).
☐	Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
☐	Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
☒	Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
For the transmitter band-edge emissions shall be measured using following options below:	
	Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Dec. 04, 2020	Dec. 03, 2021	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 20, 2020	Nov. 19, 2021	Conduction (CO02-CB)
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.4GHz	Mar. 03, 2021	Mar. 02, 2022	Conduction (CO02-CB)
COND Cable	Woken	Cable	2	0.15MHz ~ 30MHz	Oct. 20, 2020	Oct. 19, 2021	Conduction (CO02-CB)
Pulse Limiter	Schwarzbeck	VTSD 9561F-N	00378	9kHz ~ 30MHz	Mar. 19, 2020	Mar. 18, 2021	Conduction (CO02-CB)
Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conduction (CO02-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Apr. 13, 2020	Apr. 12, 2021	Radiation (03CH06-CB)
3m Semi Anechoic Chamber NSA	TDK	SAC-3M	03CH06-CB	30 MHz ~ 1 GHz	Aug. 10, 2020	Aug. 09, 2021	Radiation (03CH06-CB)
Bilog Antenna with 6 dB attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37878 & AT-N0606	20MHz ~ 2GHz	Aug. 02, 2020	Aug. 01, 2021	Radiation (03CH06-CB)
Pre-Amplifier	Agilent	310N	187290	0.1MHz ~ 1GHz	Nov. 05, 2020	Nov. 04, 2021	Radiation (03CH06-CB)
Spectrum analyzer	R&S	FSP40	100080	9kHz~40GHz	Dec. 15, 2020	Dec. 14, 2021	Radiation (03CH06-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 13, 2020	May 12, 2021	Radiation (03CH06-CB)
RF Cable-low	Woken	RG402	Low Cable-05+24	30MHz~1GHz	Oct. 05, 2020	Oct. 04, 2021	Radiation (03CH06-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH06-CB)
3m Semi Anechoic Chamber VSWR	RIKEN	SAC-3M	03CH02-CB	1GHz ~18GHz 3m	Mar. 28, 2020	Mar. 27, 2021	Radiation (03CH02-CB)
Horn Antenna	EMCO	3115	9610-4976	1GHz ~ 18GHz	Apr. 21, 2020	Apr. 20, 2021	Radiation (03CH02-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2020	Jul. 20, 2021	Radiation (03CH02-CB)
Pre-Amplifier	Agilent	83017A	MY39501305	1GHz ~ 26.5GHz	Jul. 13, 2020	Jul. 12, 2021	Radiation (03CH02-CB)
Pre-Amplifier	MITEQ	TTA1840-35-H G	1864479	18GHz ~ 40GHz	Jul. 08, 2020	Jul. 07, 2021	Radiation (03CH02-CB)
Spectrum analyzer	R&S	FSU	100015	9kHz~26GHz	Oct. 15, 2020	Oct. 14, 2021	Radiation (03CH02-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Oct. 05, 2020	Oct. 04, 2021	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Oct. 05, 2020	Oct. 04, 2021	Radiation (03CH02-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 16, 2020	Jul. 15, 2021	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 16, 2020	Jul. 15, 2021	Radiation (03CH02-CB)
Spectrum analyzer	R&S	FSV40	101027	9kHz~40GHz	Jul. 27, 2020	Jul. 26, 2021	Conducted (TH02-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Sep. 17, 2020	Sep. 16, 2021	Conducted (TH02-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Sep. 17, 2020	Sep. 16, 2021	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-01	1 GHz – 18 GHz	Oct. 05, 2020	Oct. 04, 2021	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-02	1 GHz – 18 GHz	Oct. 05, 2020	Oct. 04, 2021	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-03	1 GHz – 18 GHz	Oct. 05, 2020	Oct. 04, 2021	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-04	1 GHz – 18 GHz	Oct. 05, 2020	Oct. 04, 2021	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-05	1 GHz – 18 GHz	Oct. 05, 2020	Oct. 04, 2021	Conducted (TH02-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conducted (TH02-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.



Conducted Emissions at Powerline


Appendix A

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 3	Pass	AV	488.323k	42.78	46.19	-3.41	Line

Mode 3


10/03/2021



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	249k	43.49	61.79	-18.30	10.29	Line	-	33.20	0.07	0.07	10.15			
AV	249k	25.95	51.79	-25.84	10.29	Line	-	15.66	0.07	0.07	10.15			
QP	488.323k	44.71	56.19	-11.48	10.24	Line	-	34.47	0.08	0.06	10.10			
AV	488.323k	42.78	46.19	-3.41	10.24	Line	"Worst"	32.54	0.08	0.06	10.10			
QP	510k	42.92	56.00	-13.08	10.25	Line	-	32.67	0.08	0.07	10.10			
AV	510k	39.33	46.00	-6.67	10.25	Line	-	29.08	0.08	0.07	10.10			
QP	964.5k	32.86	56.00	-23.14	10.28	Line	-	22.58	0.09	0.08	10.11			
AV	964.5k	23.00	46.00	-23.00	10.28	Line	-	12.72	0.09	0.08	10.11			
QP	1.518M	30.30	56.00	-25.70	10.31	Line	-	19.99	0.10	0.09	10.12			
AV	1.518M	21.26	46.00	-24.74	10.31	Line	-	10.95	0.10	0.09	10.12			
QP	10.712M	32.59	60.00	-27.41	10.68	Line	-	21.91	0.28	0.23	10.17			
AV	10.712M	25.53	50.00	-24.47	10.68	Line	-	14.85	0.28	0.23	10.17			

Mode 3

10/03/2021



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)			
QP	483.539k	42.85	56.29	-13.44	10.22	Neutral	-	32.63	0.06	0.06	10.10			
AV	483.539k	40.74	46.29	-5.55	10.22	Neutral	"Worst"	30.52	0.06	0.06	10.10			
QP	505.5k	39.63	56.00	-16.37	10.24	Neutral	-	29.39	0.07	0.07	10.10			
AV	505.5k	31.73	46.00	-14.27	10.24	Neutral	-	21.49	0.07	0.07	10.10			
QP	1.109M	31.86	56.00	-24.14	10.27	Neutral	-	21.59	0.08	0.08	10.11			
AV	1.109M	23.42	46.00	-22.58	10.27	Neutral	-	13.15	0.08	0.08	10.11			
QP	1.361M	29.21	56.00	-26.79	10.29	Neutral	-	18.92	0.08	0.09	10.12			
AV	1.361M	20.22	46.00	-25.78	10.29	Neutral	-	9.93	0.08	0.09	10.12			
QP	2.153M	26.69	56.00	-29.31	10.32	Neutral	-	16.37	0.09	0.10	10.13			
AV	2.153M	17.70	46.00	-28.30	10.32	Neutral	-	7.38	0.09	0.10	10.13			
QP	10.761M	29.92	60.00	-30.08	10.63	Neutral	-	19.29	0.23	0.23	10.17			
AV	10.761M	23.09	50.00	-26.91	10.63	Neutral	-	12.46	0.23	0.23	10.17			

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	665k	1.053M	1M05F1D	658.75k	1.052M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	661.25k	1.052M
2440MHz	Pass	500k	658.75k	1.053M
2480MHz	Pass	500k	665k	1.053M


Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE(1Mbps)
2402MHz
EBW

20/01/2021


BT-LE(1Mbps)
2440MHz
EBW


20/01/2021



BT-LE(1Mbps)

2480MHz

20/01/2021





Summary

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	12.24	0.01675



Average Power-DTS

Appendix C

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.867	12.09	30.00
2440MHz	Pass	2.867	12.24	30.00
2480MHz	Pass	2.867	12.23	30.00

DG = Directional Gain; **Port X** = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-5.45

RBW=3 kHz.

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.867	-5.45	8.00
2440MHz	Pass	2.867	-6.03	8.00
2480MHz	Pass	2.867	-5.64	8.00

DG = Directional Gain; RBW=3 kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

BT-LE(1Mbps)

PSD

2402MHz

20/01/2021




Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-5.45	-5.45	-5.45

BT-LE(1Mbps)

PSD

2440MHz

20/01/2021




Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-6.03	-6.03	-6.03

BT-LE(1Mbps)

PSD

2480MHz

20/01/2021



Sum	PD	Port 1
(dBm/Hz)	(dBm/Hz)	(dBm/Hz)
-5.64	-5.64	-5.64



Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.44025G	11.13	-18.87	860.14M	-54.00	2.39997G	-46.59	2.4G	-49.81	2.49499G	-52.68	3.20089G	-43.32	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LTE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.44025G	11.13	-18.87	860.14M	-54.00	2.39997G	-46.59	2.4G	-49.81	2.49499G	-52.68	3.20089G	-43.32	1
2440MHz	Pass	2.44025G	11.13	-18.87	2.10241G	-53.32	2.39553G	-53.02	2.4G	-56.32	2.48455G	-53.51	3.25151G	-43.51	1
2480MHz	Pass	2.44025G	11.13	-18.87	1.65326G	-51.99	2.39556G	-53.74	2.4835G	-54.66	2.4964G	-52.10	3.30494G	-44.33	1



BT-LE(1Mbps)

2402MHz

CSE NdB

20/01/2021

Port1



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44025G	11.13	-18.87	860.14M	-54.00	2.39997G	-46.59	2.4G	-49.81	2.49499G	-52.68	3.20089G	-43.32	1



BT-LE(1Mbps)

2440MHz

CSE NdB

20/01/2021

Port1



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44025G	11.13	-18.87	2.10241G	-53.32	2.39553G	-53.02	2.4G	-56.32	2.48455G	-53.51	3.25151G	-43.51	1



BT-LE(1Mbps)

2480MHz

CSE NdB

20/01/2021

Port 1



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44025G	11.13	-18.87	1.65326G	-51.99	2.39556G	-53.74	2.4835G	-54.66	2.4964G	-52.10	3.30494G	-44.33	1



Radiated Emissions below 1GHz


Appendix F.1

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 2	Pass	QP	239.52M	42.94	46.00	-3.06	Horizontal

Mode 2


09/03/2021



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	30M	32.49	40.00	-7.51	-7.58	3	Vertical	20	1.00	-	40.07	23.79	1.00	32.37
PK	39.7M	30.26	40.00	-9.74	-12.79	3	Vertical	262	3.00	-	43.05	18.49	1.09	32.37
PK	109.54M	31.22	43.50	-12.28	-12.54	3	Vertical	189	1.25	-	43.76	17.87	1.90	32.31
PK	235.64M	39.33	46.00	-6.67	-12.69	3	Vertical	223	1.00	"Worst"	52.02	16.71	2.81	32.21
PK	242.43M	39.00	46.00	-7.00	-11.91	3	Vertical	240	1.00	-	50.91	17.44	2.85	32.20
PK	699.3M	38.89	46.00	-7.11	-1.43	3	Vertical	227	1.00	-	40.32	25.46	5.10	31.99

Mode 2

09/03/2021



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	30M	31.82	40.00	-8.18	-7.58	3	Horizontal	314	1.50	-	39.40	23.79	1.00	32.37
PK	39.7M	35.15	40.00	-4.85	-12.79	3	Horizontal	309	1.25	-	47.94	18.49	1.09	32.37
PK	237.58M	42.43	46.00	-3.57	-12.44	3	Horizontal	299	1.25	-	54.87	16.93	2.83	32.20
QP	239.52M	42.94	46.00	-3.06	-12.20	3	Horizontal	281	1.00	"Worst"	55.14	17.16	2.84	32.20
PK	331.67M	29.34	46.00	-16.66	-9.06	3	Horizontal	233	1.00	-	38.40	19.72	3.35	32.13
PK	915.61M	35.75	46.00	-10.25	1.46	3	Horizontal	303	2.00	-	34.29	26.67	5.96	31.17




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.4835G	47.96	54.00	-6.04	3	Horizontal	315	1.34	-

BT-LE(1Mbps)

2402MHz_TX

19/01/2021




EUT Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.381G	58.64	74.00	-15.36	27.93	3	Vertical	238	1.64	-	28.30	2.41	-
AV	2.3875G	46.71	54.00	-7.29	16.00	3	Vertical	238	1.64	-	28.30	2.41	-
PK	2.4021G	101.01	Inf	-Inf	70.31	3	Vertical	238	1.64	-	28.30	2.40	-
AV	2.402G	99.37	Inf	-Inf	68.67	3	Vertical	238	1.64	-	28.30	2.40	-

BT-LE(1Mbps)

2402MHz_TX

19/01/2021




EUT Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3788G	58.72	74.00	-15.28	28.01	3	Horizontal	290	2.22	-	28.30	2.41	-
AV	2.3862G	46.69	54.00	-7.31	15.98	3	Horizontal	290	2.22	-	28.30	2.41	-
PK	2.4021G	108.13	Inf	-Inf	77.43	3	Horizontal	290	2.22	-	28.30	2.40	-
AV	2.4021G	106.46	Inf	-Inf	75.76	3	Horizontal	290	2.22	-	28.30	2.40	-

BT-LE(1Mbps)

19/01/2021

2402MHz_TX




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80349G	48.86	74.00	-25.14	43.12	3	Vertical	360	2.71	-	32.81	4.70	31.77
AV	4.80408G	39.12	54.00	-14.88	33.37	3	Vertical	360	2.71	-	32.82	4.70	31.77

BT-LE(1Mbps)

2402MHz_TX

19/01/2021




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80354G	46.30	74.00	-27.70	40.56	3	Horizontal	16	2.57	-	32.81	4.70	31.77
AV	4.80425G	34.13	54.00	-19.87	28.38	3	Horizontal	16	2.57	-	32.82	4.70	31.77

BT-LE(1Mbps)

2440MHz_TX

19/01/2021




EUT Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.388G	58.90	74.00	-15.10	28.19	3	Vertical	243	1.63	-	28.30	2.41	-
AV	2.3856G	46.64	54.00	-7.36	15.93	3	Vertical	243	1.63	-	28.30	2.41	-
PK	2.4396G	99.17	Inf	-Inf	68.37	3	Vertical	243	1.63	-	28.38	2.42	-
AV	2.44G	97.60	Inf	-Inf	66.80	3	Vertical	243	1.63	-	28.38	2.42	-
PK	2.4984G	59.15	74.00	-14.85	28.11	3	Vertical	243	1.63	-	28.59	2.45	-
AV	2.49G	47.09	54.00	-6.91	16.09	3	Vertical	243	1.63	-	28.56	2.44	-

BT-LE(1Mbps)

2440MHz_TX

19/01/2021




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.36G	58.48	74.00	-15.52	27.76	3	Horizontal	317	1.24	-	28.30	2.42	-
AV	2.3832G	46.72	54.00	-7.28	16.01	3	Horizontal	317	1.24	-	28.30	2.41	-
PK	2.4396G	107.06	Inf	-Inf	76.26	3	Horizontal	317	1.24	-	28.38	2.42	-
AV	2.44G	105.42	Inf	-Inf	74.62	3	Horizontal	317	1.24	-	28.38	2.42	-
PK	2.4936G	58.85	74.00	-15.15	27.83	3	Horizontal	317	1.24	-	28.57	2.45	-
AV	2.4848G	47.12	54.00	-6.88	16.14	3	Horizontal	317	1.24	-	28.54	2.44	-

BT-LE(1Mbps)

2440MHz_TX

19/01/2021




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.88042G	47.23	74.00	-26.77	41.21	3	Vertical	347	2.52	-	33.12	4.70	31.80
AV	4.87998G	36.64	54.00	-17.36	30.62	3	Vertical	347	2.52	-	33.12	4.70	31.80
PK	7.31916G	50.50	74.00	-23.50	40.73	3	Vertical	88	1.05	-	36.44	5.76	32.43
AV	7.32058G	38.78	54.00	-15.22	29.01	3	Vertical	88	1.05	-	36.44	5.76	32.43

BT-LE(1Mbps)

2440MHz_TX

19/01/2021




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.88084G	45.22	74.00	-28.78	39.20	3	Horizontal	15	1.12	-	33.12	4.70	31.80
AV	4.88022G	31.54	54.00	-22.46	25.52	3	Horizontal	15	1.12	-	33.12	4.70	31.80
PK	7.32068G	52.43	74.00	-21.57	42.66	3	Horizontal	315	1.15	-	36.44	5.76	32.43
AV	7.31945G	41.83	54.00	-12.17	32.06	3	Horizontal	315	1.15	-	36.44	5.76	32.43

BT-LE(1Mbps)

2480MHz_TX

19/01/2021




EUT Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4802G	102.04	Inf	-Inf	71.08	3	Vertical	222	2.48	-	28.52	2.44	-
AV	2.48G	100.53	Inf	-Inf	69.57	3	Vertical	222	2.48	-	28.52	2.44	-
PK	2.4851G	59.42	74.00	-14.58	28.44	3	Vertical	222	2.48	-	28.54	2.44	-
AV	2.4836G	47.34	54.00	-6.66	16.37	3	Vertical	222	2.48	-	28.53	2.44	-

BT-LE(1Mbps)

2480MHz_TX

19/01/2021




EUT Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4801G	106.79	Inf	-Inf	75.83	3	Horizontal	315	1.34	-	28.52	2.44	-
AV	2.4801G	105.21	Inf	-Inf	74.25	3	Horizontal	315	1.34	-	28.52	2.44	-
PK	2.4869G	59.36	74.00	-14.64	28.37	3	Horizontal	315	1.34	-	28.55	2.44	-
AV	2.4835G	47.96	54.00	-6.04	16.99	3	Horizontal	315	1.34	-	28.53	2.44	-

BT-LE(1Mbps)

2480MHz_TX

19/01/2021




EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.95965G	45.74	74.00	-28.26	39.65	3	Vertical	0	1.06	-	33.22	4.70	31.83
AV	4.95986G	33.89	54.00	-20.11	27.80	3	Vertical	0	1.06	-	33.22	4.70	31.83

BT-LE(1Mbps)

2480MHz_TX

19/01/2021



EUT_Z_1TX
Setting Default
02-B-B-2

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.95915G	44.21	74.00	-29.79	38.12	3	Horizontal	26	2.27	-	33.22	4.70	31.83
AV	4.96G	31.28	54.00	-22.72	25.19	3	Horizontal	26	2.27	-	33.22	4.70	31.83