# FCC Co-Location Test Report

| | | |
|---|---|---|
| **FCC ID** | : | **O6ZHXQX1AP0S** |
| **Equipment** | : | **8-Channel LoRa Module** |
| **Model No.** | : | **HXQX1AP0S** |
| **Brand Name** | : | **machineQ** |
| **Applicant** | : | **Humax Co., Ltd.** |
| **Address** | : | **HUMAX BLDG., 2, HUMAX BLDG., 2, Yeongmun-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, South Korea, 17040** |
| **Standard** | : | **47 CFR FCC Part 15.247** |
| **Received Date** | : | **Mar. 05, 2019** |
| **Tested Date** | : | **Mar. 08, 2019** |

**We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.**

**Reviewed by:**

**Along Chen / Assistant Manager**

**Approved by:**

**Gary Chang / Manager**

Testing Laboratory 2732

# Table of Contents


**1 GENERAL DESCRIPTION ..... 5**

1.1 Information ..... 5
1.2 The Equipment List ..... 7
1.3 Test Standards ..... 8
1.4 Deviation from Test Standard and Measurement Procedure ..... 8
1.5 Measurement Uncertainty ..... 8

**2 TEST CONFIGURATION ..... 9**

2.1 Testing Condition ..... 9
2.2 The Worst Test Modes and Channel Details ..... 9

**3 TRANSMITTER TEST RESULTS ..... 10**

3.1 Unwanted Emissions into Restricted Frequency Bands ..... 10

**4 TEST LABORATORY INFORMATION ..... 44**

# Release Record

| Report No. | Version | Description | Issued Date |
|---|---|---|---|
| FR782401-11CO | Rev. 01 | Initial issue | Mar. 26, 2019 |

# Summary of Test Results

| FCC Rules | Test Items | Measured | Result |
|---|---|---|---|
| 15.247(d)<br>15.209 | Radiated Emissions | [dBuV/m at 3m]: 108.49MHz<br>42.11 (Margin -1.39dB) - QP | Pass |

| **Declaration of Conformity:** |
|---|
| The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. |
| **Comments and Explanations:** |
| The declared values of gain for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of the gain. |

# 1 General Description

## 1.1 Information

This report is prepared for FCC class II change.
This report is issued as a supplementary report to original ICC report no. FR782401-08CO. The difference is concerned with following item of host host listed on FR782401-08CO:

- ✧ Modification of PCB and components of non-RF section for ESD, Ethernet Port Surge and LED circuit Improvement and GPIO circuit.
- ✧ Remove matching circuit and replace by band pass filter on Lora external antenna area
- ✧ Lora External antenna connector location is moved out 3.15 mm
- ✧ Modification of SIM card detection circuit
- ✧ Remove an adapter(Brand name: PHIHONG, Model name: PSAC24A-120L6)

radiated emission tests had been re-tested and only its data was presented in the following sections.

### 1.1.1 Specification of the Equipment under Test (EUT)

| | |
|---|---|
| **Operating Frequency** | 902 MHz ~ 928 MHz |
| **Modulaton Type** | CSS |

### 1.1.2 Information of Host

| | |
|---|---|
| **Brand Name** | machineQ |
| **Product name** | 8-Channel LoRa Gateway |
| **Model name** | HXQX1AP0S |
| **Certified module (installed in the system)** | FCC ID: XMR201605EC25A |

### 1.1.2.1 Antenna of Host

**For LoRa**

| Ant. No. | Brand | Type | Gain (dBi) | Connector | Remark |
|---|---|---|---|---|---|
| 1 | LoRa antenna (External) | Dipole | 0.96 | SMA | --- |
| 2 | LoRa antenna (Internal) | Monopole | -1.65 | UFL | --- |

**For LTE / WCDMA**

| Ant. No. | Type | Connector | Gain (dBi) | Operating Band |
|---|---|---|---|---|
| 1 | PIFA | UFL | 4.49 | LTE Band 2 / WCDMA Band II |
| | | | 3.59 | LTE Band 4 / WCDMA Band IV |
| | | | 2.05 | LTE Band 12 / WCDMA Band V |

## 1.2 The Equipment List

| Test Item | Radiated Emission | | | | |
|---|---|---|---|---|---|
| **Test Site** | 966 chamber 3 / (03CH03-WS) | | | | |
| **Tested Date** | Mar. 08, 2019 | | | | |
| **Instrument** | **Manufacturer** | **Model No.** | **Serial No.** | **Calibration Date** | **Calibration Until** |
| Spectrum Analyzer | R&S | FSV40 | 101499 | Jan. 07, 2019 | Jan. 06, 2020 |
| Receiver | R&S | ESR3 | 101658 | Dec. 11, 2018 | Dec. 10, 2019 |
| Bilog Antenna | SCHWARZBECK | VULB9168 | VULB9168-685 | Apr. 19, 2018 | Apr. 18, 2019 |
| Horn Antenna 1G-18G | SCHWARZBECK | BBHA 9120 D | BBHA 9120 D 1206 | Jan. 07, 2019 | Jan. 06, 2020 |
| Horn Antenna 18G-40G | SCHWARZBECK | BBHA 9170 | BBHA 9170517 | Nov. 15, 2018 | Nov. 14, 2019 |
| Loop Antenna | R&S | HFH2-Z2 | 100330 | Nov. 09, 2018 | Nov. 08, 2019 |
| Loop Antenna Cable | KOAX KABEL | 101354-BW | 101354-BW | Oct. 08, 2018 | Oct. 07, 2019 |
| Preamplifier | EMC | EMC02325 | 980187 | Aug. 24, 2018 | Aug. 23, 2019 |
| Preamplifier | Agilent | 83017A | MY53270014 | Aug. 09, 2018 | Aug. 08, 2019 |
| Preamplifier | EMC | EMC184045B | 980192 | Aug. 09, 2018 | Aug. 08, 2019 |
| RF cable-3M | HUBER+SUHNER | SUCOFLEX104 | MY22620/4 | Oct. 01, 2018 | Sep. 30, 2019 |
| RF cable-8M | EMC | EMC104-SM-SM-8000 | 181107 | Oct. 01, 2018 | Sep. 30, 2019 |
| RF cable-1M | HUBER+SUHNER | SUCOFLEX104 | MY22624/4 | Oct. 01, 2018 | Sep. 30, 2019 |
| LF cable-0.8M | EMC | EMC8D-NM-NM-800 | EMC8D-NM-NM-800-001 | Oct. 01, 2018 | Sep. 30, 2019 |
| LF cable-3M | EMC | EMC8D-NM-NM-3000 | 131103 | Oct. 01, 2018 | Sep. 30, 2019 |
| LF cable-13M | EMC | EMC8D-NM-NM-13000 | 131104 | Oct. 01, 2018 | Sep. 30, 2019 |
| Measurement Software | AUDIX | e3 | 6.120210g | NA | NA |
| Note: Calibration Interval of instruments listed above is one year. | | | | | |

## 1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247
47 CFR FCC Part 15.407
ANSI C63.10-2013
FCC KDB 558074 D01 15.247 Meas Guidance v05r01
FCC KDB 662911 D01 Multiple Transmitter Output v02r01

## 1.4 Deviation from Test Standard and Measurement Procedure

None

## 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

| Measurement Uncertainty | |
|---|---|
| **Parameters** | **Uncertainty** |
| Radiated emission ≤ 1GHz | ±3.96 dB |
| Radiated emission > 1GHz | ±4.51 dB |

# 2 Test Configuration

## 2.1 Testing Condition

| Test Item | Test Site | Ambient Condition | Tested By |
|---|---|---|---|
| Radiated Emissions | 03CH03-WS | 21°C / 66% | Roger Lu |

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

## 2.2 The Worst Test Modes and Channel Details

| Test item | Test Mode | Test mode |
|---|---|---|
| Radiated Emissions | WCDMA Band V + LoRa 923.3MHz | 1, 2 |
| | LTE Band 2 + LoRa 923.3MHz | |
| | LTE Band 4 + LoRa 923.3MHz | |
| | LTE Band 12 + LoRa 923.3MHz | |

Note:
1. Test configuration are listed as listed as follows:
   Test mode 1: Lora / external antenna
   Test mode 2: Lora / Internal antenna

# 3 Transmitter Test Results

## 3.1 Unwanted Emissions into Restricted Frequency Bands

### 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

| Restricted Band Emissions Limit | | | |
|---|---|---|---|
| **Frequency Range (MHz)** | **Field Strength (uV/m)** | **Field Strength (dBuV/m)** | **Measure Distance (m)** |
| 0.009~0.490 | 2400/F(kHz) | 48.5 - 13.8 | 300 |
| 0.490~1.705 | 24000/F(kHz) | 33.8 - 23 | 30 |
| 1.705~30.0 | 30 | 29 | 30 |
| 30~88 | 100 | 40 | 3 |
| 88~216 | 150 | 43.5 | 3 |
| 216~960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

**Note 1:**
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit
**Note 2:**
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.1.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.1.3 Test Setup

**Radiated Emissions below 1 GHz**




**Radiated Emissions above 1 GHz**



## *Configuration 1: external antenna*

### 3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.62 | 35.86 | 43.50 | -7.64 | 48.47 | -12.61 | Peak | --- | --- |
| 2 | 138.58 | 37.21 | 43.50 | -6.29 | 46.10 | -8.89 | Peak | --- | --- |
| 3 | 148.21 | 38.04 | 43.50 | -5.46 | 46.44 | -8.40 | Peak | --- | --- |
| 4 | 228.80 | 29.35 | 46.00 | -16.65 | 39.67 | -10.32 | Peak | --- | --- |
| 5 | 249.60 | 26.27 | 46.00 | -19.73 | 35.55 | -9.28 | Peak | --- | --- |
| 6 | 959.20 | 37.99 | 46.00 | -8.01 | 32.06 | 5.93 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.44 | 37.62 | 40.00 | -2.38 | 46.27 | -8.65 | QP | 100 | 238 |
| 2 | 49.51 | 35.36 | 40.00 | -4.64 | 43.25 | -7.89 | QP | 100 | 35 |
| 3 | 97.82 | 40.51 | 43.50 | -2.99 | 54.27 | -13.76 | QP | 100 | 301 |
| 4 | 108.49 | 42.02 | 43.50 | -1.48 | 54.13 | -12.11 | QP | 100 | 316 |
| 5 | 226.40 | 32.29 | 46.00 | -13.71 | 42.79 | -10.50 | Peak | --- | --- |
| 6 | 953.60 | 39.95 | 46.00 | -6.05 | 34.09 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 49.22 | 33.56 | 40.00 | -6.44 | 41.46 | -7.90 | Peak | --- | --- |
| 2 | 157.53 | 35.42 | 43.50 | -8.08 | 43.74 | -8.32 | Peak | --- | --- |
| 3 | 249.60 | 31.55 | 46.00 | -14.45 | 40.83 | -9.28 | Peak | --- | --- |
| 4 | 341.53 | 30.57 | 46.00 | -15.43 | 37.13 | -6.56 | Peak | --- | --- |
| 5 | 357.51 | 30.66 | 46.00 | -15.34 | 36.78 | -6.12 | Peak | --- | --- |
| 6 | 959.53 | 38.21 | 46.00 | -7.79 | 32.27 | 5.94 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.55 | 37.62 | 40.00 | -2.38 | 46.26 | -8.64 | QP | 100 | 235 |
| 2 | 49.62 | 35.36 | 40.00 | -4.64 | 43.25 | -7.89 | QP | 100 | 41 |
| 3 | 97.00 | 40.37 | 43.50 | -3.13 | 54.18 | -13.81 | QP | 100 | 300 |
| 4 | 226.40 | 32.29 | 46.00 | -13.71 | 42.79 | -10.50 | Peak | --- | --- |
| 5 | 249.62 | 29.44 | 46.00 | -16.56 | 38.72 | -9.28 | Peak | --- | --- |
| 6 | 953.60 | 39.95 | 46.00 | -6.05 | 34.09 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 49.43 | 33.62 | 40.00 | -6.38 | 41.51 | -7.89 | Peak | --- | --- |
| 2 | 157.63 | 35.96 | 43.50 | -7.54 | 44.28 | -8.32 | Peak | --- | --- |
| 3 | 249.55 | 31.27 | 46.00 | -14.73 | 40.55 | -9.28 | Peak | --- | --- |
| 4 | 341.21 | 30.72 | 46.00 | -15.28 | 37.28 | -6.56 | Peak | --- | --- |
| 5 | 357.43 | 30.45 | 46.00 | -15.55 | 36.57 | -6.12 | Peak | --- | --- |
| 6 | 959.62 | 38.77 | 46.00 | -7.23 | 32.83 | 5.94 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.41 | 37.62 | 40.00 | -2.38 | 46.27 | -8.65 | QP | 100 | 231 |
| 2 | 49.62 | 35.41 | 40.00 | -4.59 | 43.30 | -7.89 | QP | 100 | 38 |
| 3 | 97.23 | 40.44 | 43.50 | -3.06 | 54.23 | -13.79 | QP | 100 | 298 |
| 4 | 226.31 | 33.12 | 46.00 | -12.88 | 43.63 | -10.51 | Peak | --- | --- |
| 5 | 249.60 | 29.85 | 46.00 | -16.15 | 39.13 | -9.28 | Peak | --- | --- |
| 6 | 953.75 | 40.12 | 46.00 | -5.88 | 34.26 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| Test Mode | LTE Band 12 + LoRa 923.3MHz |
|---|---|
| Polarization | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.44 | 35.75 | 43.50 | -7.75 | 48.40 | -12.65 | Peak | --- | --- |
| 2 | 138.51 | 37.45 | 43.50 | -6.05 | 46.35 | -8.90 | Peak | --- | --- |
| 3 | 148.53 | 38.61 | 43.50 | -4.89 | 47.00 | -8.39 | Peak | --- | --- |
| 4 | 228.73 | 29.62 | 46.00 | -16.38 | 39.95 | -10.33 | Peak | --- | --- |
| 5 | 249.60 | 27.11 | 46.00 | -18.89 | 36.39 | -9.28 | Peak | --- | --- |
| 6 | 959.20 | 38.12 | 46.00 | -7.88 | 32.19 | 5.93 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.63 | 37.55 | 40.00 | -2.45 | 46.18 | -8.63 | QP | 100 | 237 |
| 2 | 49.62 | 35.16 | 40.00 | -4.84 | 43.05 | -7.89 | QP | 100 | 42 |
| 3 | 97.48 | 40.31 | 43.50 | -3.19 | 54.09 | -13.78 | QP | 100 | 308 |
| 4 | 108.49 | 42.11 | 43.50 | -1.39 | 54.22 | -12.11 | QP | 100 | 316 |
| 5 | 226.37 | 33.15 | 46.00 | -12.85 | 43.65 | -10.50 | Peak | --- | --- |
| 6 | 953.85 | 40.12 | 46.00 | -5.88 | 34.26 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1000.10 | 39.24 | 54.00 | -14.76 | 47.69 | -8.45 | Average | 100 | 50 |
| 2 | 1000.10 | 51.86 | 74.00 | -22.14 | 60.31 | -8.45 | Peak | 100 | 50 |
| 3 | 1769.90 | 26.26 | 54.00 | -27.74 | 30.85 | -4.59 | Average | 100 | 179 |
| 4 | 1769.90 | 38.61 | 74.00 | -35.39 | 43.20 | -4.59 | Peak | 100 | 179 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| Test Mode | WCDMA Band V + LoRa 923.3MHz |
|---|---|
| Polarization | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1000.10 | 39.25 | 54.00 | -14.75 | 47.70 | -8.45 | Average | 100 | 100 |
| 2 | 1000.10 | 51.84 | 74.00 | -22.16 | 60.29 | -8.45 | Peak | 100 | 100 |
| 3 | 1769.90 | 25.75 | 54.00 | -28.25 | 30.34 | -4.59 | Average | 100 | 222 |
| 4 | 1769.90 | 38.02 | 74.00 | -35.98 | 42.61 | -4.59 | Peak | 100 | 222 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2831.80 | 27.16 | 54.00 | -26.84 | 27.05 | 0.11 | Average | 350 | 265 |
| 2 | 2831.80 | 39.66 | 74.00 | -34.34 | 39.55 | 0.11 | Peak | 350 | 265 |
| 3 | 3755.10 | 27.86 | 54.00 | -26.14 | 25.59 | 2.27 | Average | 100 | 179 |
| 4 | 3755.10 | 40.67 | 74.00 | -33.33 | 38.40 | 2.27 | Peak | 100 | 179 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2831.80 | 27.55 | 54.00 | -26.45 | 27.44 | 0.11 | Average | 195 | 251 |
| 2 | 2831.80 | 39.76 | 74.00 | -34.24 | 39.65 | 0.11 | Peak | 195 | 251 |
| 3 | 3755.10 | 28.31 | 54.00 | -25.69 | 26.04 | 2.27 | Average | 100 | 68 |
| 4 | 3755.10 | 40.95 | 74.00 | -33.05 | 38.68 | 2.27 | Peak | 100 | 68 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2677.60 | 26.11 | 54.00 | -27.89 | 26.70 | -0.59 | Average | 100 | 215 |
| 2 | 2677.60 | 39.24 | 74.00 | -34.76 | 39.83 | -0.59 | Peak | 100 | 215 |
| 3 | 3600.90 | 28.43 | 54.00 | -25.57 | 26.64 | 1.79 | Average | 100 | 318 |
| 4 | 3600.90 | 41.25 | 74.00 | -32.75 | 39.46 | 1.79 | Peak | 100 | 318 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2677.60 | 26.93 | 54.00 | -27.07 | 27.52 | -0.59 | Average | 155 | 18 |
| 2 | 2677.60 | 39.55 | 74.00 | -34.45 | 40.14 | -0.59 | Peak | 155 | 18 |
| 3 | 3600.90 | 28.43 | 54.00 | -25.57 | 26.64 | 1.79 | Average | 100 | 143 |
| 4 | 3600.90 | 41.28 | 74.00 | -32.72 | 39.49 | 1.79 | Peak | 100 | 143 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1134.70 | 39.55 | 54.00 | -14.45 | 46.82 | -7.27 | Average | 100 | 61 |
| 2 | 1134.70 | 53.43 | 74.00 | -20.57 | 60.70 | -7.27 | Peak | 100 | 61 |
| 3 | 1635.20 | 26.55 | 54.00 | -27.45 | 31.47 | -4.92 | Average | 100 | 92 |
| 4 | 1635.20 | 38.91 | 74.00 | -35.09 | 43.83 | -4.92 | Peak | 100 | 92 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1134.70 | 39.67 | 54.00 | -14.33 | 46.94 | -7.27 | Average | 100 | 76 |
| 2 | 1134.70 | 52.98 | 74.00 | -21.02 | 60.25 | -7.27 | Peak | 100 | 76 |
| 3 | 1635.20 | 29.75 | 54.00 | -24.25 | 34.67 | -4.92 | Average | 100 | 255 |
| 4 | 1635.20 | 40.77 | 74.00 | -33.23 | 45.69 | -4.92 | Peak | 100 | 255 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## *Configuration 2: internal antenna*

### 3.1.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.59 | 35.85 | 43.50 | -7.65 | 48.47 | -12.62 | Peak | --- | --- |
| 2 | 138.55 | 37.49 | 43.50 | -6.01 | 46.39 | -8.90 | Peak | --- | --- |
| 3 | 148.45 | 38.02 | 43.50 | -5.48 | 46.41 | -8.39 | Peak | --- | --- |
| 4 | 218.40 | 28.72 | 46.00 | -17.28 | 39.69 | -10.97 | Peak | --- | --- |
| 5 | 231.20 | 31.01 | 46.00 | -14.99 | 41.17 | -10.16 | Peak | --- | --- |
| 6 | 959.20 | 37.54 | 46.00 | -8.46 | 31.61 | 5.93 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.52 | 37.49 | 40.00 | -2.51 | 46.13 | -8.64 | QP | 100 | 242 |
| 2 | 49.52 | 35.46 | 40.00 | -4.54 | 43.35 | -7.89 | QP | 100 | 35 |
| 3 | 98.02 | 40.42 | 43.50 | -3.08 | 54.16 | -13.74 | QP | 100 | 303 |
| 4 | 108.49 | 42.00 | 43.50 | -1.50 | 54.11 | -12.11 | QP | 100 | 315 |
| 5 | 226.40 | 29.88 | 46.00 | -16.12 | 40.38 | -10.50 | Peak | --- | --- |
| 6 | 953.60 | 38.02 | 46.00 | -7.98 | 32.16 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.42 | 35.61 | 43.50 | -7.89 | 48.26 | -12.65 | Peak | --- | --- |
| 2 | 138.31 | 37.63 | 43.50 | -5.87 | 46.55 | -8.92 | Peak | --- | --- |
| 3 | 148.68 | 38.42 | 43.50 | -5.08 | 46.80 | -8.38 | Peak | --- | --- |
| 4 | 218.25 | 29.12 | 46.00 | -16.88 | 40.10 | -10.98 | Peak | --- | --- |
| 5 | 231.55 | 31.55 | 46.00 | -14.45 | 41.68 | -10.13 | Peak | --- | --- |
| 6 | 959.15 | 38.13 | 46.00 | -7.87 | 32.20 | 5.93 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.37 | 37.62 | 40.00 | -2.38 | 46.27 | -8.65 | QP | 100 | 240 |
| 2 | 49.31 | 35.63 | 40.00 | -4.37 | 43.53 | -7.90 | QP | 100 | 38 |
| 3 | 97.68 | 40.42 | 43.50 | -3.08 | 54.18 | -13.76 | QP | 100 | 295 |
| 4 | 226.72 | 30.12 | 46.00 | -15.88 | 40.60 | -10.48 | Peak | --- | --- |
| 5 | 249.56 | 29.75 | 46.00 | -16.25 | 39.03 | -9.28 | QP | 100 | 315 |
| 6 | 953.85 | 38.88 | 46.00 | -7.12 | 33.02 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.31 | 35.78 | 43.50 | -7.72 | 48.45 | -12.67 | Peak | --- | --- |
| 2 | 138.45 | 37.55 | 43.50 | -5.95 | 46.46 | -8.91 | Peak | --- | --- |
| 3 | 148.53 | 38.62 | 43.50 | -4.88 | 47.01 | -8.39 | Peak | --- | --- |
| 4 | 218.41 | 29.66 | 46.00 | -16.34 | 40.63 | -10.97 | Peak | --- | --- |
| 5 | 231.43 | 31.63 | 46.00 | -14.37 | 41.77 | -10.14 | Peak | --- | --- |
| 6 | 959.27 | 38.44 | 46.00 | -7.56 | 32.51 | 5.93 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.45 | 37.68 | 40.00 | -2.32 | 46.33 | -8.65 | QP | 100 | 238 |
| 2 | 49.52 | 35.68 | 40.00 | -4.32 | 43.57 | -7.89 | QP | 100 | 41 |
| 3 | 97.55 | 40.31 | 43.50 | -3.19 | 54.08 | -13.77 | QP | 100 | 292 |
| 4 | 226.68 | 30.44 | 46.00 | -15.56 | 40.92 | -10.48 | Peak | --- | --- |
| 5 | 249.38 | 29.75 | 46.00 | -16.25 | 39.03 | -9.28 | QP | 100 | 318 |
| 6 | 953.75 | 38.75 | 46.00 | -7.25 | 32.89 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 105.21 | 35.71 | 43.50 | -7.79 | 48.39 | -12.68 | Peak | --- | --- |
| 2 | 138.46 | 37.62 | 43.50 | -5.88 | 46.52 | -8.90 | Peak | --- | --- |
| 3 | 148.41 | 38.16 | 43.50 | -5.34 | 46.55 | -8.39 | Peak | --- | --- |
| 4 | 218.22 | 28.83 | 46.00 | -17.17 | 39.81 | -10.98 | Peak | --- | --- |
| 5 | 231.43 | 31.63 | 46.00 | -14.37 | 41.77 | -10.14 | Peak | --- | --- |
| 6 | 959.53 | 37.85 | 46.00 | -8.15 | 31.91 | 5.94 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 38.43 | 37.62 | 40.00 | -2.38 | 46.27 | -8.65 | QP | 100 | 240 |
| 2 | 49.44 | 35.12 | 40.00 | -4.88 | 43.01 | -7.89 | QP | 100 | 33 |
| 3 | 98.41 | 40.16 | 43.50 | -3.34 | 53.87 | -13.71 | QP | 100 | 295 |
| 4 | 108.35 | 42.03 | 43.50 | -1.47 | 54.16 | -12.13 | QP | 100 | 311 |
| 5 | 226.12 | 29.76 | 46.00 | -16.24 | 40.28 | -10.52 | Peak | --- | --- |
| 6 | 953.96 | 38.75 | 46.00 | -7.25 | 32.89 | 5.86 | Peak | --- | --- |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1000.10 | 39.27 | 54.00 | -14.73 | 47.72 | -8.45 | Average | 100 | 100 |
| 2 | 1000.10 | 51.86 | 74.00 | -22.14 | 60.31 | -8.45 | Peak | 100 | 100 |
| 3 | 1769.90 | 26.52 | 54.00 | -27.48 | 31.11 | -4.59 | Average | 100 | 178 |
| 4 | 1769.90 | 38.81 | 74.00 | -35.19 | 43.40 | -4.59 | Peak | 100 | 178 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | WCDMA Band V + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1000.10 | 39.29 | 54.00 | -14.71 | 47.74 | -8.45 | Average | 100 | 20 |
| 2 | 1000.10 | 51.77 | 74.00 | -22.23 | 60.22 | -8.45 | Peak | 100 | 20 |
| 3 | 1769.90 | 26.93 | 54.00 | -27.07 | 31.52 | -4.59 | Average | 111 | 281 |
| 4 | 1769.90 | 39.04 | 74.00 | -34.96 | 43.63 | -4.59 | Peak | 111 | 281 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2831.80 | 26.78 | 54.00 | -27.22 | 26.67 | 0.11 | Average | 100 | 299 |
| 2 | 2831.80 | 40.01 | 74.00 | -33.99 | 39.90 | 0.11 | Peak | 100 | 299 |
| 3 | 3755.10 | 27.96 | 54.00 | -26.04 | 25.69 | 2.27 | Average | 100 | 235 |
| 4 | 3755.10 | 40.35 | 74.00 | -33.65 | 38.08 | 2.27 | Peak | 100 | 235 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 2 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2831.80 | 26.68 | 54.00 | -27.32 | 26.57 | 0.11 | Average | 100 | 53 |
| 2 | 2831.80 | 40.11 | 74.00 | -33.89 | 40.00 | 0.11 | Peak | 100 | 53 |
| 3 | 3755.10 | 28.15 | 54.00 | -25.85 | 25.88 | 2.27 | Average | 100 | 151 |
| 4 | 3755.10 | 40.37 | 74.00 | -33.63 | 38.10 | 2.27 | Peak | 100 | 151 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2677.60 | 26.53 | 54.00 | -27.47 | 27.12 | -0.59 | Average | 100 | 255 |
| 2 | 2677.60 | 39.44 | 74.00 | -34.56 | 40.03 | -0.59 | Peak | 100 | 255 |
| 3 | 3600.90 | 28.15 | 54.00 | -25.85 | 26.36 | 1.79 | Average | 100 | 298 |
| 4 | 3600.90 | 42.76 | 74.00 | -31.24 | 40.97 | 1.79 | Peak | 100 | 298 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 4 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2677.60 | 26.57 | 54.00 | -27.43 | 27.16 | -0.59 | Average | 100 | 44 |
| 2 | 2677.60 | 39.75 | 74.00 | -34.25 | 40.34 | -0.59 | Peak | 100 | 44 |
| 3 | 3600.90 | 28.16 | 54.00 | -25.84 | 26.37 | 1.79 | Average | 100 | 151 |
| 4 | 3600.90 | 40.23 | 74.00 | -33.77 | 38.44 | 1.79 | Peak | 100 | 151 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Horizontal |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1134.70 | 39.56 | 54.00 | -14.44 | 46.83 | -7.27 | Average | 262 | 85 |
| 2 | 1134.70 | 52.88 | 74.00 | -21.12 | 60.15 | -7.27 | Peak | 262 | 85 |
| 3 | 1635.20 | 25.37 | 54.00 | -28.63 | 30.29 | -4.92 | Average | 135 | 311 |
| 4 | 1635.20 | 37.43 | 74.00 | -36.57 | 42.35 | -4.92 | Peak | 135 | 311 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

| | |
|---|---|
| **Test Mode** | LTE Band 12 + LoRa 923.3MHz |
| **Polarization** | Vertical |




| | Freq. MHz | Emission level dBuV/m | Limit dBuV/m | Margin dB | SA reading dBuV | Factor dB | Remark | ANT High cm | Turn Table deg |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 1134.70 | 39.45 | 54.00 | -14.55 | 46.72 | -7.27 | Average | 100 | 61 |
| 2 | 1134.70 | 52.37 | 74.00 | -21.63 | 59.64 | -7.27 | Peak | 100 | 61 |
| 3 | 1635.20 | 26.43 | 54.00 | -27.57 | 31.35 | -4.92 | Average | 265 | 251 |
| 4 | 1635.20 | 37.96 | 74.00 | -36.04 | 42.88 | -4.92 | Peak | 269 | 251 |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

| **Linkou** | **Kwei Shan** | **Kwei Shan Site II** |
|---|---|---|
| Tel: 886-2-2601-1640 | Tel: 886-3-271-8666 | Tel: 886-3-271-8640 |
| No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C. | No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C. | No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.. |

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

**═END═**