

A. DEVICE UNDER TEST

The device is a VHF Handheld Transceiver operating under Part 90 of the FCC rules. The transmit frequency range of operation is 150.050 MHz. to 174.050 MHz.

B. MEASUREMENT PROCEDURE:

TRANSMITTER SECTION CABINET RADIATED EMISSIONS

Transmitter cabinet radiation field strength measurements were conducted according to the procedures set forth in ANSI C63.4 (1992). The device under test was terminated with a 50 ohm dummy load and placed on a rotating turntable 0.8 meters high, centered at 3 meters distant from the measurement antenna. The device was placed in the center of the turntable and tested in three major planes as shown in the photographs

The device is powered by an internal 7.5V, NiCad rechargeable battery. The test was conducted with a fresh battery. A spare battery pack was on hand and was used after the first battery dropped to 85% capacity. For the purposes of testing, the device was locked in a constant transmit mode by holding the transmit key depressed with a rubber band. Testing was conducted at the low, mid and high ends of the operational range.

The device was scanned from 30MHz. to 2GHz. and all emissions were noted. In this case, the only emissions detected were those harmonically related to the fundamental transmit frequency.

RECEIVER SECTION RADIATED EMISSIONS

Receiver radiation measurements were conducted according to the procedures set forth in ANSI C63.4 (1992). The device under test was placed on the center of turntable and terminated with the antenna supplied by the manufacturer. Testing was conducted with the device positioned in three major planes. The sample was tested the low, mid and high ends of its range. The squelch control was adjusted to allow sound from the speaker and the volume control was set to approximately one quarter rotation.

The device was scanned from 30MHz. to 2GHz. and all emissions were noted. In this case, the only emissions detected were those harmonically related to the fundamental frequency of the first local oscillator. The manufacturer's specifications indicated a second local oscillator running

at 33.845 MHz., common to all channels. The fourth harmonic (135.380MHz.) of this oscillator was discernable at the antenna terminal (-68.22dBm.) when connected directly to the spectrum analyzer. However, none of the signals related to the second local oscillator were detectable under open field conditions.

MEASUREMENTS

The field strength measurements were taken using an HP8596E spectrum analyzer, an EMC0 3120 dipole set, an EMC0 3115 double ridge guide horn antenna and an Avantek UJ210 preamp.

At each detected frequency of emission, the device was measured by rotating the turntable and adjusting the antenna height over a range of 1 to 4 meters to obtain the maximum output level. This procedure was performed with both horizontal and vertical antenna polarizations with the device placed in the positions shown in the photographs. The peak reading for each frequency was captured and recorded in the second column on the data sheet.

C. FACILITY

Radiated emissions testing for this device was conducted by Control Design & Testing, Inc. and performed on the Hyak Laboratories 3 meter open area test site located in Spotsylvania, VA.

RADIATED EMISSIONS			FCC ID:			page 1 of 6					
client			ADRAD Communications			model			project 0752		
device						handheld transceiver			Test date 16-Nov-2000		
CFR			test antenna Dipoles/DRG Horn						temp. 7C		
Transmitter Radiated Emissions											
Frequency Radiated MHz.		Peak Reading dBm		Ant Factor dB		Test Antenna Polarity		Field Intensity uV/m @ 3m		FCC Limit uV/m @ 3m	
device tuned to 150.050 MHz. 50 ohm dummy load termination											
300.100		-82.01		25.6		H		338		4,500	
450.150		-90.10		26.8		V		153		4,500	
600.200		-83.86		30.4		H		475		4,500	
750.250		-101.28		31.8		H		75		4,500	
900.300		-97.46		36.7		V		205		4,500	
1050.350		-89.31		25.1		V		138		4,500	
1200.400		-88.26		25.6		H		165		4,500	
1350.450		-85.09		26.3		V		257		4,500	
1500.500		-86.84		26.9		V		225		4,500	

RADIATED EMISSIONS			FCC ID:			page 2 of 6		
client		ADRAD Communications			model		project 0752	
device handheld transceiver					Test date		16-Nov-2000	
CFR		test antenna Dipoles/DRG Horn					temp. 7C	
Transmitter Radiated Emissions								
Frequency Radiated MHz.	Peak Reading dBm	Ant Factor dB	Test Antenna Polarity	Field Intensity uV/m @ 3m		FCC Limit uV/m @ 3m		
device tuned to 168.950 MHz. 50 ohm dummy load termination								
337.900	-81.29	25.8	H	376		4,500		
506.850	-89.27	27.5	H	183		4,500		
675.800	-97.10	31.2	H	114		4,500		
844.750	-105.03	33.0	V	56		4,500		
1013.700	-94.93	24.9	V	71		4,500		
1182.650	-81.39	25.5	V	359		4,500		
1351.600	-86.80	26.3	V	211		4,500		
1520.550	-88.17	27.0	V	196		4,500		
1689.500	-91.37	27.7	V	147		4,500		

RADIATED EMISSIONS			FCC ID:			page 3 of 6		
client		ADRAD Communications			model		project 0752	
device		handheld transceiver				Test date		17-Nov-2000
CFR		test antenna Dipoles/DRG Horn					temp. 12C	
Transmitter Radiated Emissions								
Frequency Radiated MHz.	Peak Reading dBm	Ant Factor dB	Test Antenna Polarity	Field Intensity uV/m @ 3m			FCC Limit uV/m @ 3m	
device tuned to 174.050 MHz. 50 ohm dummy load termination								
348.100	-81.77	25.9	H	360			4,500	
522.150	-86.43	27.6	H	256			4,500	
696.200	-90.51	31.3	V	245			4,500	
870.250	-104.48	33.6	V	64			4,500	
1044.300	-93.58	25.0	V	83			4,500	
1218.350	-88.07	25.6	V	168			4,500	
1392.400	-85.39	26.4	V	251			4,500	
1566.450	-89.80	27.3	H	168			4,500	
1740.500	-90.84	28.2	V	165			4,500	

[illegible]

RADIATED EMISSIONS		FCC ID:		page 5 of 6		
client ADRAD Communications			model		project 0752	
device handheld transceiver				Test date 16-Nov-2000		
CFR		test antenna Dipoles			temp. 7C	
Receiver Section Radiated Emissions						
Frequency Radiated MHz.	Peak Reading dBm	Ant Factor dB	Test Antenna Polarity	Field Intensity uV/m @ 3m		FCC Limit uV/m @ 3m
device tuned to 168.950 MHz. supplied antenna attached						
147.550	-97.60	15.7	V	18		150
295.100	-119.72	25.4	H	4		200
442.650	-119.68	26.5	V	5		200
590.200	-124.34	28.2	H	3		200
737.750	-128.05*	31.7	H	3		200
*noise floor = 131.02						

[illegible]



Receiver Testing, Vertical Plane



Receiver Testing, Horizontal, sides



Receiver Testing, Horizontal, Front/Rear



Transmitter Testing, Horizontal, Sides



Transmitter Testing, Vertical



Transmitter Testing, Horizontal, Front/Back