



FCC ID: 07VMA191820
IC: 5928A-MA191820

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : MONITOR AUDIO LTD.
Unit 2, 24 Brook Road, Rayleigh, Essex SS6 7XJ England

Manufacturer : MONITOR AUDIO LTD.
Unit 2, 24 Brook Road, Rayleigh, Essex SS6 7XJ England

Equipment : Amplifier

Type/Model : Airstream S200

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

R is chosen to be 20cm, the gain of antenna $G = 3.00\text{dBi} = 1.995$

As we can see from the test reports 131200990SHA-001:

The maximum output power for Wi-Fi = $21.24\text{dBm} = 133.04\text{mW}$

The MPE of Wi-Fi = $PG / (4\pi R^2) = 133.04 * 1.995 / (4 * 3.14 * 20 * 20) = 0.05 \text{ W/cm}^2$

As we can see from the test reports 131200990SHA-002:

The maximum output power for Bluetooth = $2.81\text{dBm} = 1.910\text{mW}$

$S = PG / (4\pi R^2) = 1.910 * 1.995 / (4 * 3.14 * 20 * 20) = 0.00076\text{mW/cm}^2$

For the device can support simultaneous transmission, according to 447498 D01 General RF Exposure Guidance v05r01,

The sum of the MPE ratios = $0.05 / 1.0 + 0.00076 / 1.0 = 0.05$

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Date of issue: Feb 14, 2014

Prepared by:

Jesse Xu (*Project Engineer*)

Reviewed by:

Daniel Zhao (*Reviewer*)



FCC ID: O7VMA191820
IC: 5928A-MA191820

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.
To ensure compliance, operations at closer than this distance is not recommended.