

CERTIFICATE OF COMPLIANCE **IC RSS-102 SAR EVALUATION**

Test Lab:

CELLTECH RESEARCH INC.
Testing and Engineering Lab
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250 - 860-3130
Fax: 250 - 860-3110
Toll Free: 1-877-545-6287
e-mail: celltech@globuswireless.com
web site: www.globuswireless.com

Applicant Information:


TRISQUARE COMMUNICATIONS INC.
1420 NW Vivion Rd., Suite 113
Kansas City, MO 64118
Attn: Mr. Barry Vonada
Tel: (816) 505-3575
Fax: (816) 505-3579

FCC ID:	O9GFRS440
Model(s):	FRS 400 / FRS 420
EUT Type:	Portable FRS PTT Radio Transceiver
Modulation:	FM
Tx Frequency Range:	462.5625 - 467.7125 MHz
Max. RF Output Power:	0.49 Watts
No. of Channels:	14
IC Rule Part(s):	RSS-102

This wireless mobile and/or portable device has been shown to be compliant for localized Specific Absorption Rate (SAR) for uncontrolled environment / general exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1999.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Celltech Research Inc. certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



Shawn McMillen
General Manager
Celltech Research Inc.



TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	DESCRIPTION OF EUT.....	1
3.0	SAR MEASUREMENT SYSTEM	2
4.0	MEASUREMENT SUMMARY.....	3-4
5.0	SAR LIMITS.....	5
6.0	DETAILS OF SAR EVALUATION.....	5
7.0	EVALUATION PROCEDURES.....	6
8.0	SYSTEM VALIDATION.....	6
9.0	SIMULATED EQUIVALENT TISSUES.....	7
10.0	TISSUE PARAMETERS.....	7
11.0	SYSTEM SPECIFICATIONS.....	8
12.0	TEST EQUIPMENT LIST.....	9
13.0	MEASUREMENT UNCERTAINTIES.....	10
14.0	REFERENCES.....	11
	APPENDIX A - SAR MEASUREMENT DATA.....	12
	APPENDIX B - DIPOLE VALIDATION.....	13
	APPENDIX C - PROBE CALIBRATION.....	14
	APPENDIX D - TEST SETUP PHOTOGRAPHS.....	15

1.0 INTRODUCTION

This measurement report shows compliance of the TRISQUARE COMMUNICATIONS INC. Model: Uniden FRS 400 / FRS 420 Portable FRS Radio Transceiver FCC ID: O9GFRS440 with the regulations and procedures specified in RSS-102 of Industry Canada for mobile and portable devices. The test procedures, as described in American National Standards Institute C95.1-1992 (1), FCC OET Bulletin 65-1997 were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION of Equipment Under Test (EUT)

Rule Part(s)	IC RSS-102	Modulation	FM
		No. of Channels	14
EUT Type	Portable FRS Radio Transceiver	Tx Frequency Range (MHz)	462.5625 - 467.7125
FCC ID	O9GFRS440	Max. RF Output Power	0.49 Watts
Model No.(s)	Uniden FRS 400/FRS 420	Antenna Type	Integral
Serial No.	Pre-production	Power Supply	1.5V AA Alkaline Battery (x3)



Front of EUT



Left Side of EUT



Right Side of EUT



Rear of EUT

3.0 SAR MEASUREMENT SYSTEM

Celltech Research SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the generic twin phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY3 SAR Measurement System

4.0 MEASUREMENT SUMMARY

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the EUT are reported in Appendix A.

Face-Held SAR Measurements

Frequency (MHz)	Channel	Mode	Output Power	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
462.5625	Low	Unmod.	Max.	Fixed	4.0	0.179	0.0895 (50% duty cycle)
467.7125	High	Unmod.	Max.	Fixed	4.0	0.159	0.0795 (50% duty cycle)
Mixture Type: Brain Dielectric Constant: 48.9 Conductivity: 0.61			ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population BRAIN: 1.6 W/kg (averaged over 1 gram)				

Notes: 1. The SAR values found were below the maximum limit of 1.6 w/kg. The highest SAR value found was 0.0895 w/kg (50% duty cycle).



Face SAR at 4.0cm


Body-Worn & Hand SAR Measurements

Frequency (MHz)	Channel	Mode	Output Power	Antenna Position	Separation Distance (cm)	Test Position	SAR (w/kg)	
462.5625	Low	Unmod.	Max.	Fixed	0.0	Front of EUT	1.31	0.655 (50% duty cycle)
467.7125	High	Unmod.	Max.	Fixed	0.0	Front of EUT	1.12	0.560 (50% duty cycle)
462.5625	Low	Unmod.	Max.	Fixed	0.0	Rear of EUT	0.796	0.398 (50% duty cycle)
467.7125	High	Unmod.	Max.	Fixed	0.0	Rear of EUT	0.779	0.390 (50% duty cycle)
462.5625*	Low	Unmod.	Max.	Fixed	0.0	Rear of EUT	0.545	0.273 (50% duty cycle)
467.7125*	High	Unmod.	Max.	Fixed	0.0	Rear of EUT	0.529	0.265 (50% duty cycle)
Mixture Type: Muscle Dielectric Constant: 57.5 Conductivity: 0.84			ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population BODY: 1.6 W/kg (averaged over 1 gram) *HAND: 4.0 W/kg (averaged over 10 grams)					

Notes: 1. The SAR values found were below the maximum limit of 1.6 w/kg. The highest SAR value found for body SAR was 0.655 w/kg (50% duty cycle). The highest SAR value found for hand SAR was 0.273 w/kg (50% duty cycle).
2. The EUT was tested for body-worn SAR in two configurations, with the front side of the EUT and the rear side of the EUT touching the planar phantom.



Body SAR - Front of EUT



Body SAR - Rear of EUT



Hand SAR

5.0 SAR SAFETY LIMITS

EXPOSURE LIMITS (General populations/Uncontrolled Exposure Environment)	SAR (W/Kg)
Spatial Average (averaged over the whole body)	0.08
Spatial Peak (averaged over any 1g of tissue)	1.60
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.00

Notes: 1. The SAR safety limits specified in the table above apply to devices operated in the General Population / Uncontrolled Exposure environment.
2. Uncontrolled environments are defined as locations where there is exposure of individuals who have no knowledge or control of their exposure.

6.0 DETAILS OF SAR EVALUATION

The TRISQUARE COMMUNICATIONS INC. Model: Uniden FRS 400 / FRS 420 Portable FRS Radio Transceiver FCC ID: O9GFRS440 was found to be compliant for localized Specific Absorption Rate (SAR) based on the following test provisions and conditions:

- 1) The EUT was tested in a face-held configuration with the device placed parallel to and at a nominal distance of 40mm from the outer surface of the planar phantom.
- 2) The EUT was tested in a body-worn configuration with the front of the device touching the outer surface of the planar phantom.
- 3) The EUT was tested in a body-worn configuration with the rear of the device touching the outer surface of the planar phantom.
- 4) The EUT was tested in a hand-held configuration with the rear of the device touching the outer surface of the planar phantom.
- 5) The EUT was evaluated for SAR at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimize drift.
- 6) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- 7) The location of the maximum spatial SAR distribution (Hot Spot) was determined relative to the device. This location was then related to a phantom that possesses human like facial attributes. For this particular device the hot spot occurred in the LCD area, which relates to the nose area on the phantom.
- 8) The EUT was tested with fully charged batteries.

7.0 EVALUATION PROCEDURES

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a. (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices worn about the ear during normal operation, both the left and right ear positions were evaluated at the center frequency of the band at maximum power. The side, which produced the greatest SAR, determined which side of the phantom would be used for the entire evaluation. FCC OET Bulletin 65 Supplement C dictated the test position of the device relative to the phantom.
(ii) For face-held and body-worn devices, or devices which can be operated within 20cm of the body, the planar section of the phantom was used. The type of device being evaluated dictated the distance of the EUT to the outer surface of the planar phantom.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. A 5x5x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

8.0 SYSTEM VALIDATION

Prior to the assessment, the system was verified in the planar region of the phantom. For devices operating below 1GHz, an 835MHz dipole or 900MHz was used, depending on the operating frequency of the EUT. For devices operating above 1GHz, an 1800MHz dipole was used. A forward power of 250mW was applied to the dipole and system was verified to a tolerance of $\pm 3\%$. Following the validation, the fluid remained or was changed depending on the particular part of the body being evaluated. The applicable verifications are as follows (see Appendix B for validation test plot):

Dipole Validation Kit	Target SAR 1g (w/kg)	Measured SAR 1g (w/kg)
D835V2	2.06	2.04

9.0 SIMULATED TISSUES

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

INGREDIENT	MIXTURE		
	450MHz Brain %	835MHz Brain % (Validation)	450MHz Muscle %
Water	42.0	40.1	50.0
Sugar	56.0	58.1	48.2
Salt	1.7	0.7	1.6
HEC	0.1	1.0	0.1
Bactericide	0.2	0.1	0.1

10.0 TISSUE PARAMETERS

The dielectric parameters of the fluids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer. The dielectric parameters of the fluid are as follows:

Equivalent Tissue (450MHz)	Dielectric Constant ϵ_r	Conductivity s (mho/m)	ρ (Kg/m ³)
Brain	48.9 $\pm$ 5%	0.61 $\pm$ 10%	1000
Brain (835MHz Validation)	44.2 $\pm$ 5%	0.80 $\pm$ 10%	1000
Muscle	57.5 $\pm$ 5%	0.84 $\pm$ 10%	1000

11.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium III
Clock Speed: 450 MHz
Operating System: Windows NT
Data Card: DASY3 PC-Board

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY3 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

PC Interface Card

Function: 24 bit (64 MHz) DSP for real time processing
Link to DAE3
16 bit A/D converter for surface detection system
serial link to robot
direct emergency stop output for robot

E-Field Probe

Model: ET3DV6
Serial No.: 1387
Construction: Triangular core fiber optic detection system
Frequency: 10 MHz to 6 GHz
Linearity: ± 0.2 dB (30 MHz to 3 GHz)

Phantom

Phantom: Generic Twin
Shell Material: Fiberglass
Thickness: 2.0 $\pm$ 0.1 mm

12.0 TEST EQUIPMENT LIST

SAR MEASUREMENT SYSTEM		
<u>EQUIPMENT</u>	<u>S/N #</u>	<u>CAL. DATE</u>
DASY3 System -Robot -ET3DV6 E-Field Probe -DAE -835MHz Validation Dipole -900MHz Validation Dipole -1800MHz Validation Dipole -Generic Twin Phantom V3.0	599396-01 1387 383 411 054 247 N/A	N/A Sept 1999 Sept 1999 Aug 1999 Aug 1999 Aug 1999 N/A
85070C Dielectric Probe Kit	N/A	N/A
Gigatronics 8652A Power Meter -Power Sensor 80701A -Power Sensor 80701A	1835272 1833535 1833542	Oct 1999 Oct 1999 Oct 1999
E4408B Spectrum Analyzer	US39240170	Nov 1999
8594E Spectrum Analyzer	3543A02721	Mar 2000
8753E Network Analyzer	US38433013	Nov 1999
8648D Signal Generator	3847A00611	N/A
5S1G4 Amplifier Research Power Amplifier	26235	N/A

13.0 MEASUREMENT UNCERTAINTIES

Uncertainty Description	Error	Distribution	Weight	Standard Deviation	Offset
Probe Uncertainty					
Axial isotropy	± 0.2 dB	U-Shaped	0.5	± 2.4 %	
Spherical isotropy	± 0.4 dB	U-Shaped	0.5	± 4.8 %	
Isotropy from gradient	± 0.5 dB	U-Shaped	0	$\pm$	
Spatial resolution	± 0.5 %	Normal	1	± 0.5 %	
Linearity error	± 0.2 dB	Rectangle	1	± 2.7 %	
Calibration error	± 3.3 %	Normal	1	± 3.3 %	
SAR Evaluation Uncertainty					
Data acquisition error	± 1 %	Rectangle	1	± 0.6 %	
ELF and RF disturbances	± 0.25 %	Normal	1	± 0.25 %	
Conductivity assessment	± 10 %	Rectangle	1	± 5.8 %	
Spatial Peak SAR Evaluation Uncertainty					
Extrapolated boundary effect	± 3 %	Normal	1	± 3 %	± 5 %
Probe positioning error	± 0.1 mm	Normal	1	± 1 %	
Integrated and cube orientation	± 3 %	Normal	1	± 3 %	
Cube Shape inaccuracies	± 2 %	Rectangle	1	± 1.2 %	
Device positioning	± 6 %	Normal	1	± 6 %	
Combined Uncertainties				± 11.7 %	± 5 %

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, the estimated measurement uncertainties in SAR are less than 15-25 %.

According to ANSI/IEEE C95.3, the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2 dB can be expected.

According to CENELEC, typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.

14.0 REFERENCES

- (1) ANSI, *ANSI/IEEE C95.1: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 Ghz*, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992;
- (2) Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997;
- (3) Thomas Schmid, Oliver Egger, and Neils Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, Vol. 44, pp. 105 – 113, January, 1996.
- (4) Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with know precision”, *IEICE Transactions of Communications*, vol. E80-B, no. 5, pp. 645 – 652, May 1997.

APPENDIX A - SAR MEASUREMENT DATA

Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Brain: $S = 0.61$ mho/m $\epsilon_r = 48.9$ $\rho = 1.00$ g/cm³

Coarse: $Dx = 20.0$, $Dy = 20.0$, $Dz = 10.0$

Cube 4x4x7

SAR (1g): 0.179 mW/g, SAR (10g): 0.137 mW/g

Face SAR at 4.0 cm Separation


Uniden Model: FRS400/420

Unmodulated Carrier

Low Channel [462.5625MHz]

Conducted Power - Max

Date Tested: March 12, 2001



Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Brain: $S = 0.61$ mho/m $\epsilon_r = 48.9$ $\rho = 1.00$ g/cm³

Coarse: $Dx = 20.0$, $Dy = 20.0$, $Dz = 10.0$

Cube 4x4x7

SAR (1g): 0.159 mW/g, SAR (10g): 0.121 mW/g

Face SAR at 4.0 cm Separation


Uniden Model: FRS400/420

Unmodulated Carrier

High Channel [467.7125MHz]

Conducted Power - Max

Date Tested: March. 12, 2001



Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Muscle: $s = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 1.31 mW/g, SAR (10g): 0.889 mW/g

Body SAR with Belt Hook (Front of EUT Touching Phantom)


Uniden Model: FRS400/420

Unmodulated Carrier

Low Channel [462.5625MHz]

Conducted Power - Max

Date Tested: March 12, 2001



Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Muscle: $s = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 1.12 mW/g, SAR (10g): 0.764 mW/g

Body SAR with Belt Hook (Front of EUT Touching Phantom)


Uniden Model: FRS400/420

Unmodulated Carrier

High Channel [467.7125MHz]

Conducted Power - Max

Date Tested: March 12, 2001



Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (270°,270°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Muscle: $s = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.796 mW/g, SAR (10g): 0.545 mW/g

Body SAR with Belt Hook (Rear of EUT Touching Phantom)


Uniden Model: FRS400/420

Unmodulated Carrier

Low Channel [462.5625MHz]

Conducted Power - Max

Date Tested: March 12, 2001



Trisquare Communications Inc. FCC ID: O9GFRS440

Generic Twin Phantom; Flat Section; Position: (270°,270°);
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0;
450MHz Muscle: $s = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.779 mW/g, SAR (10g): 0.529 mW/g

Body SAR with Belt Hook (Rear of EUT Touching Phantom)


Uniden Model: FRS400/420

Unmodulated Carrier

High Channel [467.7125MHz]

Conducted Power - Max

Date Tested: March 12, 2001




APPENDIX B - DIPOLE VALIDATION

Dipole 835 MHz

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;
Brain 835 MHz: $\sigma = 0.80$ mho/m $\epsilon_r = 44.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.04 mW/g, SAR (10g): 1.34 mW/g

Validation Date: March 12, 2001



Validation Dipole D835V2 SN:411, $d = 15\text{mm}$

Frequency: 835 MHz; Antenna Input Power: 250 [mW]


Generic Twin Phantom; Flat Section; Grid Spacing: $D_x = 20.0$, $D_y = 20.0$, $D_z = 10.0$

Probe: ET3DV5 - SN1342/DAE3; ConvF(5.75,5.75,5.75); Brain 835 MHz: $\sigma = 0.80$ mho/m $\epsilon_r = 44.2$ $\rho = 1.00$ g/cm³

Cubes (2): Peak: 3.07 mW/g ± 0.05 dB, SAR (1g): 2.06 mW/g ± 0.05 dB, SAR (10g): 1.38 mW/g ± 0.05 dB, (Worst-case extrapolation)

Penetration depth: 13.6 (12.7, 14.8) [mm]

Powerdrift: -0.00 dB



APPENDIX C - PROBE CALIBRATION

Probe ET3DV6

SN:1387

Manufactured:	September 21, 1999
Last calibration:	September 22, 1999

Calibrated for System DASY3

DASY3 - Parameters of Probe: ET3DV6 SN:1387

Sensitivity in Free Space

Diode Compression

NormX	1.55 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	98 mV
NormY	1.65 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	98 mV
NormZ	1.64 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	98 mV


Sensitivity in Tissue Simulating Liquid


Brain	450 MHz	$\epsilon_r = 48 \pm 5\%$	$s = 0.50 \pm 10\% \text{ mho/m}$
ConvF X	6.76 extrapolated	Boundary effect:	
ConvF Y	6.76 extrapolated	Alpha	0.30
ConvF Z	6.76 extrapolated	Depth	2.52
Brain	900 MHz	$\epsilon_r = 42.5 \pm 5\%$	$s = 0.86 \pm 10\% \text{ mho/m}$
ConvF X	6.34 $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	6.34 $\pm 7\%$ (k=2)	Alpha	0.47
ConvF Z	6.34 $\pm 7\%$ (k=2)	Depth	2.25
Brain	1500 MHz	$\epsilon_r = 41 \pm 5\%$	$s = 1.32 \pm 10\% \text{ mho/m}$
ConvF X	5.78 interpolated	Boundary effect:	
ConvF Y	5.78 interpolated	Alpha	0.69
ConvF Z	5.78 interpolated	Depth	1.88
Brain	1800 MHz	$\epsilon_r = 41 \pm 5\%$	$s = 1.69 \pm 10\% \text{ mho/m}$
ConvF X	5.50 $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	5.50 $\pm 7\%$ (k=2)	Alpha	0.81
ConvF Z	5.50 $\pm 7\%$ (k=2)	Depth	1.70

Sensor Offset


Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	1.6 $\pm$ 0.2	mm

Receiving Pattern (f) , q = 0°








Isotropy Error (f), q = 0°




Frequency Response of E-Field
(TEM-Cell:ifi110, Waveguide R22, R26)




Dynamic Range f(SAR_{brain})
(TEM-Cell:ifi110)



Conversion Factor Assessment





Receiving Pattern (f) (in brain tissue, z = 5 mm)



APPENDIX D - TEST SETUP PHOTOGRAPHS


FACE-HELD SAR TEST SETUP PHOTOGRAPHS
4.0cm Separation Distance



BODY-WORN SAR TEST SETUP PHOTOGRAPHS
0.0cm Separation Distance with Belt-Hook
Rear of EUT



Front of EUT



HAND-HELD SAR TEST SETUP PHOTOGRAPHS
0.0cm Separation Distance

