



RF EXPOSURE REPORT

For

Quanzhou Chierda Electronic Telecom Co., Ltd.

No.8,Zi'an Road,Jiangnan High-tech Industrial Zone Licheng District, Quanzhou Fujian, China

FCC ID: OA8-M520D


Report Type: Original Report	Product Name: AMATEUR RADIO
Report Number:	2507Z03677E-RF-04
Report Date:	2026-06-13
Reviewed By:	Ash Lin 
Approved By:	Miles Chen 
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue Science and Technology Innovation Park, Torch High Tech Zone Xiamen, People's Republic of China Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
TEST EQUIPMENT LIST	5
FCC§15.247 (i), §1.1307(b)(1) & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
APPLICABLE STANDARD	6
CALCULATED FORMULARY:.....	6
MPE TEST PROCEDURE	6
BLOCK DIAGRAM OF TEST SETUP	7
TEST DATA	7
EUT PHOTOGRAPHS	11

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2507Z03677E-RF-04	R1V1	2026-06-13	Initial Release

GENERAL INFORMATION**Product Description for Equipment under Test (EUT)**

Applicant:	Quanzhou Chierda Electronic Telecom Co., Ltd.
Product Name:	AMATEUR RADIO
Tested Model:	M520D
Multiple Model(s):	AR-7800
Trade Mark:	Chierda, ABBREE
Power Supply:	DC 13.8V from DC Source
EUT Received Status:	Good
<i>Note:</i> 1. The Maximum Antenna Gain was declared by manufacturer. 2. The difference between tested model and series model are model name and color, please refer to declaration letter for more detail. 3. The EUT supplied by the applicant was received on 2025-11-04.	

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on the Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Broadband Field Meter	narda	NBM-550	E-0696	2024/9/13	2027/9/12
E-Field probe	narda	EF 0391	D-1748	2024/9/13	2027/9/12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307(b)(1) & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to FCC §1.1307(b)(1) & §2.1091, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Limits for Maximum Permissible Exposure (MPE)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz;

* = Plane-wave equivalent power density.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;


R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{\text{limit},i}} \leq 1$$

MPE Test Procedure

1. Place the EUT's antenna was vertical polarization on the table.
2. The EUT was set to transmit at the frequency at maximum RF power.
3. The Distance between the test probe and the investigated EUT's antenna equal to the distance be specified as safety distance in the user manual.
4. Power density measurements were taken at different heights of the probe from the ground (0.8 to 2.8 meters) while rotating versus azimuth (from 0° to 360°) the antenna.
5. Adjusted the distance between the test probe and the tested antenna to the real safe distance, R_{real} , such that the measured highest power density in the "worst case" position was the same or slightly less than the test limit.
6. The measurement results of final measurements conducted at the chosen azimuth and different heights of the probe above the ground.

Block Diagram of Test Setup**Test Data**

Test Mode:	Transmitting	Test Engineer:	Lucas Lin
Test Date:	2026-6-8~2026-6-9	Test Result:	Pass

Environment Conditions:					
Temperature: (°C)	22.4~23.3	Relative Humidity: (%)	51~56	ATM Pressure: (kPa)	100.1~100.2

Please refer to below table and plots:

For 147.9875MHz

Measuring Probe Height (cm)	Power Density(mW/cm ²)
	40cm
80	0.065
100	0.078
150	0.355
160	0.372
170	0.364
180	0.351
190	0.275
200	0.204
250	0.233
280	0.082

Test Result Summary:

Maximum Power Density (mW/cm ²)	0.372
Measured Conducted Output Power (W)	12.2
Maximum Rated Power Including Tolerance (W)	13
Scaled Maximum Power Density(50% duty Cycle) (mW/cm ²)	0.186
Limit (mW/cm ²)	0.200
Safety Distance (cm)	40
Result	Compliant

Note:

1. The maximum measured conducted output power in the 144~148 MHz band is 40.85 dBm (12.2W) at 147.9875 MHz.
2. Operating duty cycle 50% is declared by manufacturer and showed on the user manual.

For 449.9875MHz

Measuring Probe Height (cm)	Power Density(mW/cm ²)
	40cm
80	0.058
100	0.077
150	0.356
160	0.366
170	0.354
180	0.333
190	0.245
200	0.178
250	0.231
280	0.089

Test Result Summary:

Maximum Power Density (mW/cm ²)	0.366
Measured Conducted Output Power (W)	8.7
Maximum Rated Power Including Tolerance (W)	10
Scaled Maximum Power Density(50% duty Cycle) (mW/cm ²)	0.183
Limit (mW/cm ²)	0.280
Safety Distance (cm)	40
Result	Compliant

Note:

1. The maximum measured conducted output power in the 420~450 MHz band is 39.41 dBm (8.7W) at 449.9875 MHz.
2. Operating duty cycle 50% is declared by manufacturer and showed on the user manual.

For Bluetooth/BLE:

Mode	Frequency (MHz)	★Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	-0.9	0.81	-2.5	0.56	20	0.0001	1
BT	2402-2480	-0.9	0.81	-6.5	0.22	20	<0.0001	1

Result: Compliant.

The Stand-alone Maximum Permissible Exposure was compliant at the distance more than 20cm.

BT/BLE can't transmit simultaneously.

For Simultaneous transmission:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$= S_{VHF}/S_{limit-VHF} + S_{BT}/S_{limit-BT}$$

$$= 0.186/0.2 + 0.0001/1.0$$

$$= 0.93 \leq 1$$

Result: The device meet FCC MPE at 40 cm distance for General Population/Uncontrolled use.

EUT PHOTOGRAPHS

Please refer to the attachment 2507Z03677E-EM-EXP EUT EXTERNAL PHOTOGRAPHS and 2507Z03677E-EM-INP EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2507Z03677E-RF-TSP-03 SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

******* END OF REPORT *******