

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
CERTIFICATION TO FCC PART 15 REQUIREMENTS**

for

INTENTIONAL RADIATOR

315 MHz SKI FINDER ALARM TRANSMITTER

MODEL NO: MFSKITX2

FCC ID NO: OAVSKI315TX

REPORT NO: 00E8929

ISSUE DATE: SEPTEMBER 19, 2000

Prepared for

**ALTRUSTY ENTERPRISE CO., LTD.
4th FLOOR, NO. 3, ALLEY 16, LANE 235,
BAU CHIAU ROAD, HSIN-TIEN CITY, TAIPEI ,
TAIWAN, R. O. C.**

Prepared by

COMPLIANCE ENGINEERING SERVICES, INC.

d.b.a.

COMPLIANCE CERTIFICATION SERVICES

**1366 BORDEAUX DRIVE
SUNNYVALE, CA 94089, USA**

TEL: (408) 752-8166

FAX: (408) 752-8168



TABLE OF CONTENTS	PAGE
1. VERIFICATION OF COMPLIANCE.....	1
2. Product Description.....	2
3. Test Facility.....	2
4. Measurement Standards	2
5. Test Methodology	2
6. Measurement Equipment Used	2
7. POWERLINE RFI LIMIT	3
8. RADIATED EMISSION LIMITS	3
9. SYSTEM TEST CONFIGURATION.....	4
10. Test Procedure.....	5
11. Equipment Modifications.....	6
12. TEST RESULT	7
12.1 Maximum Modulation Percentage (M%)	7
12.2 The Emissions Bandwidth.....	7

TEST DATA

- Maximum Modulation Percentage Plot
- Emission Bandwidth Plot
- Radiated Emission Worksheet for Peak Measurement
- Radiated Emission Worksheet for Average Measurement

1. VERIFICATION OF COMPLIANCE

COMPANY NAME: ALTRUSTY ENTERPRISE CO., LTD.
4th FLOOR, NO. 3, ALLEY 16, LANE 235,
BAU CHIAU ROAD, HSIN-TIEN CITY, TAIPEI,
TAIWAN, R. O. C.

CONTACT PERSON: ERIC WANG / GENERAL MANAGER

TELEPHONE NO.: 02-8665-6969

EUT DESCRIPTION: 315 MHz SKI FINDER ALARM TRANSMITTER

MODEL NAME/NUMBER: MFSKITX2

FCC ID: OAVSKI315TX

DATE TESTED: AUGUST 28, 2000 ~ SEPTEMBER 14, 2000

REPORT NUMBER: 00E8929

TYPE OF EQUIPMENT	SECURITY EQUIPMENT (INTENTIONAL RADIATOR)
EQUIPMENT TYPE	315 MHz SKI FINDER ALARM TRANSMITTER
MEASUREMENT PROCEDURE	ANSI C63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15

The above equipment was tested by Compliance Certification Services for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties. **Warning** : This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification will constitute fraud and shall nullify the document.



RICK YEO / EMC MANAGER
COMPLIANCE ENGINEERING SERVICES, INC.

PAGE NO: 1

COMPLIANCE ENGINEERING SERVICES, INC.
1366 BORDEAUX DRIVE, SUNNYVALE, CA 94089, USA

CCS DOCUMENT NO: CCSUP4020B
TEL: (408) 752-8166 FAX: (408) 752-8168

This report shall not be reproduced except in full, without the written approval of CCS. This document may be altered or revised by Compliance Certification Services personnel only, and shall be noted in the revision section of the document.

2. Product Description

Fundamental Frequency	315 MHz
Power Source	12V Battery
Transmitting Time	Periodic $\leq$ 5 seconds
Associated Receiver	FCC DoC

3. Test Facility

The 3/10/30 meter open area test site and conducted measurement facility used to collect the radiated data is located at 561F Monterey Road, Morgan Hill, California, U.S.A. A detailed description of the test facility was submitted to the Commission on May 27, 1994.

4. Measurement Standards

The site is constructed and calibrated in conformance with the requirements of ANSI C63.4/1992.

5. Test Methodology

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 KHz, up to at least the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. (CFR 47 Section 15.33)

6. Measurement Equipment Used

Manufacturer	Model Number	Description	Cal Due Date
H.P.	8566B	Spectrum Analyzer (100Hz – 22GHz)	12/00
H.P.	8595EM	Spectrum Analyzer (9KHz – 6.5GHz)	01/01
EMCO	3115	Antenna (1-18GHz)	09/01
EMCO	3142	Antenna (30-2000MHz)	06/01
T.E.C.	PA-102	Amplifier(30-2000MHz)	05/01
MITEQ	NSP2600-44	Amplifier(1-26GHz)	12/00

7. POWERLINE RFI LIMIT

CONNECTED TO AC POWER LINE	SECTION 15.207
CARRIER CURRENT SYSTEM IN THE FREQUENCY RANGE OF 450 kHz TO 30 MHz	SECTION 15.205 AND SECTION 15.209, 15.221, 15.223, 15.225 OR 15.227, AS APPROPRIATE.
BATTERY POWER	NO REQUIRED.

8. RADIATED EMISSION LIMITS

GENERAL REQUIREMENTS	SECTION 15.209
RESTRICTED BANDS OF OPERATION	SECTION 15.205
PERIODIC OPERATION IN THE BAND 40.66 -40.70 MHz AND ABOVE 70 MHz.	SECTION 15.231

9. SYSTEM TEST CONFIGURATION

Use a block of foam and combined it with EUT wrapping rubber band around it. This way it can test X.Y, and Z axis. To activate continuous transmission, place a small plastic block between rubber band and EUT push button.



10. Test Procedure

Radiated Emissions, 15.231(4)(b)




Fig. 1

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 3-meters from the EUT.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.


Test set-up for measurements above 1GHz

FIG. 2

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 1-meters from the EUT. The EUT antenna was mounted vertically as per normal installation.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.

11. Equipment Modifications

To achieve compliance to FCC Section 15.231 technical limits, the following change(s) were made during compliance testing:

NONE

12. TEST RESULT

Powerline RFI Class B	Eut	Radiated Emission Limits	Eut
SECTION 15.207		SECTION 15.209	X
SECTION 15.205, 15.209, 15.221, 15.223, x 15.225 OR 15.227		SECTION 15.205	
BATTERY POWER	X	SECTION 15.231 (b)	X
		SECTION 15.231 (e)	

12.1 Maximum Modulation Percentage (M%)

CALCULATION:

Average Reading = Peak Reading (dBuV/m)+ 20log (Duty Cycle)

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT. We measured:

WHERE 1 Period =31.325 mS
 Long pulse =0.45 mS
 Short pulse = 0.15 mS
 No of Long pulse = 15
 No of Short pulse = 14

$$\text{Duty Cycle} = (N1L1+N2L2+\dots+Nn-1Ln-1+NnLn)/100 \text{ or } T$$

$$\text{Duty Cycle} = ((15 \times 0.45) + (14 \times 0.15)) / 31.325 = 0.2825 = 28.25\% \text{ or } -10.98\text{dB}$$
12.2 The Emissions Bandwidth

The bandwidth of the emissions were investigated per 15.231(c)

Center Frequency	Measured	Limits
315 MHz	442.2 kHz < (refer to plot)	315X0.25%=787.5 kHz

14:30:39 AUG 30, 2000

MKR 31.325 msec

REF 100.0 dB μ V AT 10 dB


-.02 dB

PEAK

LOG

10

dB/



WA SB

SC FS

CORR

CENTER 315.000 MHz

RES BW 120 kHz

SPAN 0 Hz

SWP 70.0 msec

VBW 300 kHz

14: 35: 39 AUG 30, 2000

MKR 24.525 msec

REF 100.0 dB μ V AT 10 dB


.00 dB

PEAK

LOG

10

dB/



WA SB
SC FS
CORR

CENTER 315.000 MHz

RES BW 120 KHz

VBW 300 KHz

#SWP 30.0 msec

SPAN 0 Hz

14:39:49 AUG 30, 2000

MKR 450.00 μ sec

REF 100.0 dB μ V AT 10 dB


.10 dB

PEAK

LOG

10

dB/



WA SB

SC FS

CORR

CENTER 315.000 MHz

RES BW 120 kHz

VBW 300 kHz

#SWP 15.0 msec

SPAN 0 Hz

14: 43: 06 AUG 30, 2000

MKR 150.00 μ sec

REF 100.0 dB μ V AT 10 dB


.21 dB

PEAK

LOG

10

dB/



WA SB
SC FS
CORR

CENTER 315.000 MHz

RES BW 120 kHz

VBW 300 kHz


#SWP 15.0 msec

SPAN 0 Hz



Date 28.Aug.'00 Time 10:58:00
Ref.Lvl Delta
100.00 dBμV -0.18 dB
442.2 kHz

Res.Bw 120 kHz [imp]
TG.Lvl Off
CF.Stp 200.000 kHz
Vid.Bw 300 kHz
RF.Att 10 dB
Unit [dBμV]



Start 313.966666 MHz Stop 315.966666 MHz
Span 2 MHz Sweep 100 ms
Center 314.966666 MHz

N dB down level 20.0 dB
DELTA MARK 442.2 kHz

[illegible]



FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

1366 BORDEAUX DRIVE, SUNNYVALE, CA 94089
PHONE: (408) 752-8166 FAX: (408) 752-8168

Project #: 00E8929
Report #: 8929D2
Date & Time: 9/14/00 22:44
Test Engr: Vince Chiang

Company: ALTRUSTY ENTERPRISE CO.,LTD.
EUT Description: MFSKITX2 (Alam TX /315 MHZ)
Test Configuration : EUT ONLY
Type of Test: FCC CLASS B
Mode of Operation: NORMAL MODE

☒ D Site

☐ E Site

6 W orst

Descendin

Freq.	Reading	AF	Closs	Pre-amp	Dist	Level	Limit	Margin	Pol	Az	Height	Mark
(MHz)	(dBuV)	(dB)	(dB)	(dB)	dB	(dBuV/m)	FCC_B	(dB)	(H/V)	(Deg)	(Meter)	(P/Q/A)
1260	57.50	25.2	2.8	43.29	-9.5	32.62	74.0	-41.38	1mV	0	1.2	P
1260	46.00	25.2	2.8	43.29	-9.5	21.12	54.0	-32.88	1mV	0	1.2	A
1575	60.04	25.5	3.1	43.13	-9.5	36.00	74.0	-38.00	1mV	0	1.2	P
1575	49.18	25.5	3.1	43.13	-9.5	25.14	54.0	-28.86	1mV	0	1.2	A
1260	50.31	25.2	2.8	43.29	-9.5	25.43	74.0	-48.57	1mH	270	1.2	P
1260	38.03	25.2	2.8	43.29	-9.5	13.15	54.0	-40.85	1mH	270	1.2	A
1575	53.65	25.5	3.1	43.13	-9.5	29.61	74.0	-44.39	1mH	270	1.2	P
1575	39.91	25.5	3.1	43.13	-9.5	15.87	54.0	-38.13	1mH	270	1.2	A

No other emissions were found within 20dB under the limits upto 3.2GHz.

Total data #: 8
V.2d

Peak: RBW=VBW=1MHz
Average: RBW=1MHz, VBW=10Hz

Distance = $20\log(1/3) = -9.5\text{dB}$