

Date:1999-01-25
No.: HM1618/504

TEST REPORT

Page 1 of 5

APPLICANT: (CODE :018842)

SUNNY-TECH ELECTRONIC CO., LTD.

18/F, Po Shau Centre, 115 How Ming Street, Kwun Tong, Kowloon, Hong Kong.

DATE OF SAMPLES RECEIVED: 1998-11-28

DATE OF TESTING: 1998-11-29 & 1999-01-18

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: PLL DIGITAL RADIO RECEIVER

Manufacturer: SUNNY-TECH ELECTRONIC CO., LTD.

Band Combination: AM/FM/AIR

Model Number: MR-318A

Brand Name: N/A

Rating: 3.0Vd.c. ("AA" size battery × 2) / with DC jack

Origin: China

The product tested with AC-DC adaptor Brand Name: WINSTAR, model no. NA-1535, input AC117/230V 50/60Hz 34W Output DC 3-15V 1500mA max.

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiators.

RESULT/ REMARK: Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED after modification by customer with the requirement for the relevant clauses of Federal Communication Commission Rules for Radio Receivers.

TEST EQUIPMENT AUDIT: Please see Appendix A

Law Man Kit
Testing Engineer

Kitty Choy
Verify by

Patrick Wong
Patrick Wong
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication

Date: 1999-01-25
No.: HM1618/504

TEST REPORT

Page 2 of 5

TEST SUMMARY

(A) **Measurement of Radiated Emissions**
(On FM & AIR BAND)

Result -- Satisfactory

Data -- See the attached data

(B) **Measurement of Line-Conducted Voltage**
(On FM & AIR BAND)

Result -- Satisfactory

Data : (The spectrum was checked from 450KHz to 30KHz. All emissions were too low to be measurable and they were all more than 20dB below the permitted limit.)

Date: 1999-01-25
No.: HM1618/504

TEST REPORT

Page 3 of 5

FM BAND RADIO RECEIVER

(A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109

TEST CONDITION : FM Broadcast Receiver

TEST DATE : 1999.01.18

Freq. to which tuned	Freq. of the emission	Polarity	Meter Reading (including Antenna Factor) at 3m	Field Strength (at 3m)	FCC Limit @
MHz	MHz		dB(μ V/m)	μ V/m	μ V/m
88.3	99.0	Horizontal	28.9	27.9	150
98.3	109.0	Horizontal	31.6	38.0	150
108.3	119.0	Horizontal	32.9	44.2	150

=====SUMMARY=====

All data is within limits

=====

Broad-band Antennas were used

=====

Remark: IF = 10.70 MHz

Date: 1999-01-25
No.: HM1618/504

TEST REPORT

Page 4 of 5

AIR BAND RECEIVER

(A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109

TEST CONDITION : AIR BAND RECEIVER (Build in Antenna)

TEST DATE : 1999-01-18

Freq. to which tuned MHz	Freq. of the emission MHz	Polarity	Meter Reading (including Antenna Factor) at 3m dB(μ V/m)	Field Strength (at 3m) μ V/m	FCC Limit @ μ V/m
108.0	118.7	Horizontal	33.8	49.0	150
	237.4	Horizontal	33.6	47.9	200
124.0	134.7	Horizontal	34.4	52.5	150
	269.4	Horizontal	39.0	89.1	200
140.0	150.7	Horizontal	33.9	49.5	150
	301.4	Horizontal	39.8	97.7	200

=====SUMMARY=====

All data is within limits

=====

Broad-band Antennas were used

=====

Remark : I.F. = 10.7MHz

Date: 1999-01-25

TEST REPORT

Page 5 of 5

No.: HM1618/504

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 15.109 of the FCC rules.

(2) Distance between the EUT and measuring antenna:

3 meters.

(3) Measuring instrumentations:

CISPR Quasi-peak type field strength meter (25MHz - 1000MHz) 6 dB bandwidth set at 120KHz.

(4) Measuring antenna:

Broad band antenna for the frequency range 25 - 1000 MHz, connected with 10 meters coaxial cable. Cable loss of the coaxial cable included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarization.

(5) Frequency range scanned:

The frequency range from 25 MHz to 1000 MHz had been searched. Readings of the highest emissions relating to the limit were reported as above.

(6) Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

(7) Measuring Procedure:

In accordance with the relevant sections of ANSI C63.4:1992.

(8) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 200MHz = $\pm 3.7\text{dB}$, 300MHz to 1000MHz = $3.0\text{dB}/-2.7\text{dB}$.

NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

(1) LISN (Line Impedance Stabilization Network) used :

50 μH LISN in accordance with Section of ANSI C63.4:1992.

(2) Measurement Instrumentations:

CISPR quasi-peak type radio noise meter (9 KHz - 30 MHz), 6 dB bandwidth set at 9 KHz for measurement between 150 KHz & 30MHz.

(3) Frequency range scanned :

The frequency range form 450 KHz to 30 MHz had been searched. Reading of the highest emissions relating to the limit were reported as above.

(4) Configuration of EUT

Connection of equipment and operation conditions were same as those in the Radiation measurement.

(5) Measurement procedure :

In accordance with the relevant sections of ANSI C63.4:1992 "FCC Methods of measurement of "Radio Noise Emissions from Computing Devices".

(6) Measuring Uncertainty:

The calculated uncertainty for conducted power-line measurement is = $\pm 2.3\text{dB}$.

Remark : Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

End of Document