

FCC RF Exposure

EUT Description: **8 INCH BLUETOOTH SPEAKER 3 ASST**

Model No.: **KV936235MUCC & 348283**

FCC ID: **OD7-KV936235MUCC**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max power of channel, including tune - up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$] ≤ 3.0 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result=P/D* $\sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

frequency	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
2.402	2.17	2 ± 1	3/2.0	5	0.621	3.0	Pass
2.441	1.95	1 ± 1	2/1.6	5	0.494	3.0	Pass
2.480	1.57	1 ± 1	2/1.6	5	0.498	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HK1905060999-E, antenna gain=0dBi							

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.315 which is ≤ 3 , SAR testing is not required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$]

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm