
Application Note : Telink TLSR826XDK48 User Guide

AN-18080300-E1

Ver 1.0.0

2018/8/13

Brief:

This document is the user guide for Telink TLSR826XDK48 board.



TELINK SEMICONDUCTOR

Published by
Telink Semiconductor

Bldg 3, 1500 Zuchongzhi Rd,
Zhangjiang Hi-Tech Park, Shanghai, China

© Telink Semiconductor
All Right Reserved

Legal Disclaimer

Telink Semiconductor reserves the right to make changes without further notice to any products herein to improve reliability, function or design. Telink Semiconductor disclaims any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Telink Semiconductor does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling Telink Semiconductor products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Telink Semiconductor for any damages arising or resulting from such use or sale.

Information:

For further information on the technology, product and business term, please contact Telink Semiconductor Company (www.telink-semi.com).

For sales or technical support, please send email to the address of:

telinkcnsales@telink-semi.com

telinkcnsupport@telink-semi.com

Revision History

Version	Major Changes	Date	Author
1.0.0	Initial release	2018/8	HZF, Cynthia

Table of contents

1	Brief.....	4
1.1	EVK Function	4
2	EVK Pin Description	7
3	Pin Connection Guide	10
3.1	Supply power for TLSR826XDK48	10
3.2	Download Firmware into TLSR826XDK48	11
3.3	Measure power-saving mode current for TLSR826XDK48	12
3.4	Test RF signal for TLSR826XDK48	13
3.5	Test GPIOs for TLSR826XDK48	14
4	Appendix.....	15

Table of figures

Figure 1	TLSR826XDK48 silkscreen	5
Figure 2	TLSR826XDK48 photo	6
Figure 3	Connection chart to supply power	10
Figure 4	Connection chart to download FW	11
Figure 5	Connection chart to test sleep current	12
Figure 6	Connection chart to test RF signal.....	13
Figure 7	Schematic of TLSR826XDK48	16

Table of tables


Table 1	EVK pin description.....	7
---------	--------------------------	---


1 Brief

This document presents guide on how to use Telink TLSR826XDK48 board, and applies to all engineers who want to develop Bluetooth Low Energy (BLE) applications based on TLSR8267 / TLSR8269 / TLSR8646 / TLSR8261 / TLSR8262 / TLSR8287.

1.1 EVK Function

Telink TLSR826XDK48 board can be used for SDK development. Firmware can be directly downloaded to the TLSR826XDK48 board to be up and running.








Figure 2 TLSR826XDK48 photo

For schematic of TLSR826XDK48 board, please refer to Appendix or the PDF document “C1T80A30_V2_0A”.

2 EVK Pin Description

Table 1 EVK pin description

J1 USB Host	
1	Connected to VBUS
2	Connected to TL_IO via 1K resistor
3	TL_SWM
4	GND
S1	GND
S2	GND
J7 mini USB interface (Power supply and debug)	
1	VBUS
2	TL_DM
3	TL_DP
4~9	GND
J2	
1~2	VBUS
J3	
1	NC
2	TL_SWM
3	GND
4	VBUS
5	TL_SWS
6	TL_DVDD
J4	
	RF Connector
J5	
1~2	VBUS/5V
J9	
1~2	Connected to TL_DVDD and 3V3
J10	
1	TL_32K01/C2
2	TL_32K02/C3
J11	
1~2	TL_DVDD/TL_IO
J17	
1	TL_3V3DUT
2	GND
3	TL_SWM
J18 & J21	
1	TL_A6
2	TL_CN/P2N/A5

3	TL_CK/A4
4	TL_DI/A3
5	TL_DO/P0N/A2
6	TL_P2/D7
J19	
1	NC
2	5V
3	TL_RST
4	3V3
5	5V
6	GND
7	GND
8	NC
J20 & J29	
1	TL_I2CCK/C1
2	TL_I2CDI/C0
3	NC
4	GND
5	TL_CK/B7
6	DO
7	DI
8	TL_CN/B4
9	TL_D2
10	TL_D1
J22 & J31	
1	TL_D0
2	TL_C7
3	AmicBias/C6
4	AmicSP/C5
5	AmicSN/C4
6	TL_B1
7	UTX
8	URX
J23	
1~2	TL_DM/E2
J24	
1~2	TL_DP/E3
J25	
1	GND
2	TL_IO
3	TL_Row1
4	TL_Row0

5	TL_Col1
6	TL_Col0
J28	
1	TL_DDI/A0
2	TL_DCK/A1
3	TL_D3
4	TL_D4
5	TL_P0/D5
6	TL_P1/D6
J32	
1	3V3
2	5V
3	GND
4	GND
J33	
1	TL_UTX/B2
2	UTX
3	TL_URX/B3
J34	
1	TL_URX/B3
2	URX
3	TL_UTX/B2
J35	
1	TL_DO/B5
2	DO
3	TL_DI/B6
J36	
1	TL_DI/B6
2	DI
3	TL_DO/B5

3 Pin Connection Guide

3.1 Supply power for TLSR826XDK48

There are two connection methods to supply power for Telink TLSR826XDK48 board.

Method 1:

Make sure three jumper caps are connected on J9, J23 and J24 of TLSR826XDK48.

Connect J7 (miniUSB interface) with PC USB via an USB cable.

Method 2:

Connect PIN3 and PIN6 of J3 with GND and 3.3V of a burning EVK, respectively.




Figure 3 Connection chart to supply power

3.2 Download Firmware into TLSR826XDK48

There are two connection methods to download firmware into Telink TLSR826XDK48 board.

1. Method 1: Connect via USB

Make sure three jumper caps are connected on J9, J23 and J24 of TLSR826XDK48.

Connect J7 (miniUSB interface) with the USB interface of a burning EVK via an USB cable. The miniUSB interface of the burning EVK is connected with PC USB via an USB cable.

2. Method 2: Connect via Swire

Connect PIN3, PIN5 and PIN6 of J3 with GND, SWM and 3.3V of a burning EVK, respectively.




Figure 4 Connection chart to download FW

3.3 Measure power-saving mode current for TLSR826XDK48

To measure current consumption of Telink TLSR826XDK48 board in deep sleep or suspend mode, please follow the connection steps below:

- 1) Follow the steps in section 3.1 to download firmware into the TLSR826XDK48.
- 2) Power off the TLSR826XDK48.
- 3) Remove the jumper cap from J9 of TLSR826XDK48, as shown in Figure 5.
- 4) Connect anode (+) and cathode (-) of an amperemeter with anode (+) of 3.3V power supply and PIN6 of J3, respectively.
- 5) Connect cathode (-) of the 3.3V power supply with PIN3 of J3.




Figure 5 Connection chart to test sleep current

3.4 Test RF signal for TLSR826XDK48

Make sure three jumper caps are connected on J9, J23 and J24 of TLSR826XDK48.

Connect PIN3, PIN5 and PIN6 of J3 with GND, SWM and 3.3V of a burning EVK, respectively.

To test RF signal for Telink TLSR826XDK48 board, the J4 should be connected with a spectrum analyzer via a RF cable (supplied by Telink).




Figure 6 Connection chart to test RF signal

3.5 Test GPIOs for TLSR826XDK48

Since all GPIOs of Telink TLSR826XDK48 board are already connected to corresponding pins of headers including J10, J21, J25, J28, J29, J31, J33, J34, J35 and J36 (please refer to Table 1 or the schematic), user can directly test GPIO signals on header pins.

FCC STATEMENT

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1) this device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try correct the interference by one or more of the following measures:

- Reorient the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into and outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.