FCC PART 15 SUBPART C MEASURMENT AND TEST REPORT

For

Harmonic International Ltd

Room 1201-02, C-Bons International Centre, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

E.U.T.: Hidden Radio Wireless Speaker

Model Name: HS002

Brand Name: HIDDEN

FCC ID: OGWHS002

Report Number: NTC1503044F

Test Date(s): March 10, 2015 to April 17, 2015

Report Date(s): April 17, 2015

Prepared by

Dongguan Nore Testing Center Co., Ltd.

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District,Dongguan City, Guangdong, China

Tel: +86-769-22022444 Fax: +86-769-22022799

Prepared By	Approved & Authorized Signer
Rose Hu / Engineer	Sunm Lv / Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan Nore Testing Center Co., Ltd. The test results referenced from this report are relevant only to the sample tested.

Table of Contents

1. GENERAL INFORMATION 4

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST 4
1.2 RELATED SUBMITTAL(S) / GRANT (S) 4
1.3 TEST METHODOLOGY 5
1.4 EQUIPMENT MODIFICATIONS 5
1.5 SUPPORT DEVICE 5
1.6 TEST FACILITY AND LOCATION 6
1.7 SUMMARY OF TEST RESULTS 6

2. SYSTEM TEST CONFIGURATION 7

2.1 EUT CONFIGURATION 7
2.2 SPECIAL ACCESSORIES 7
2.3 DESCRIPTION OF TEST MODES 7
2.4 EUT EXERCISE 7

3. CONDUCTED EMISSIONS TEST 8

3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 8
3.2 TEST CONDITION 8
3.3 MEASUREMENT RESULTS 8

4. RADIATED EMISSION TEST 11

4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 11
4.2 MEASUREMENT PROCEDURE 12
4.3 LIMIT 12
4.4 MEASUREMENT RESULTS 14

5. CHANNEL SEPARATION TEST 16

5.1 MEASUREMENT PROCEDURE 16
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16
5.3 MEASUREMENT RESULTS 16

6. 20DB BANDWIDTH 22

6.1 MEASUREMENT PROCEDURE 22
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 22
6.3 MEASUREMENT RESULTS 22

7. HOPPING CHANNEL NUMBER 23

7.1 MEASUREMENT PROCEDURE 28
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 28
7.3 MEASUREMENT RESULTS 28

8. TIME OF OCCUPANCY (DWELL TIME) 30

8.1 MEASUREMENT PROCEDURE 30
8.2 MEASUREMENT RESULTS 30

9. MAXIMUM PEAK OUTPUT POWER 30

9.1 MEASUREMENT PROCEDURE 36
9.2 MEASUREMENT RESULTS 36

10. BAND EDGE 36

10.1 MEASUREMENT PROCEDURE 42
10.2 LIMIT 42
10.3 MEASUREMENT RESULTS 42

11. ANTENNA APPLICATION 42

11.1 ANTENNA REQUIREMENT 49
11.2 MEASUREMENT RESULTS 49

12. CONDUCTED SPURIOUS EMISSIONS 50

12.1 MEASUREMENT PROCEDURE 50
12.2. MEASUREMENT RESULTS 50

13. TEST EQUIPMENT LIST 57

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a BT speaker, it's powered by DC 7.4V Li-Polymer battery or DC 5V come from USB Port. For more details features, please refer to User's Manual.

Manufacturer	:	Harmonic International Ltd
Address	:	Room 1201-02, C-Bons International Centre, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	:	Dongguan Homania Electronic Products Co., Ltd
Address	:	Chung Kou Manage Area, Shijie Town, Dongguan City, Guangdong, China
Power Supply	:	DC5V 1000mA from external USB port, DC7.4V 1500mAh rechargeable Li-Polymer battery
Model name	:	HS002
Hardware version	:	PCB-2 V2.5
Software version	:	001
Serial number	:	N/A

For BT function
BT Version:
BLE(V4.0) and backward compatible 3.0HS, 2.1+EDR version.
We prepare version BLE(V4.0) and 2.1+EDR for RF test.

Item	BT2.1+EDR	BLE(V4.0)
Frequency	2402-2480MHz	2402-2480MHz
Modulation	GFSK, π/4-DQPSK, 8DPSK	GFSK
Number of Channel	79	40
Channel space	1MHz	2MHz
Antenna Type	PCB antenna	PCB antenna
Antenna Gain	-0.61 dBi (declared by manufacturer)	-0.61 dBi (declared by manufacturer)

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **OGWHS002** filing to comply with Section 15.247 of the FCC Part 15 (2014), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2014) and DA 00-705. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

PC	:	Manufacturer: IBM Corporation M/N: R50e S/N: L3-HZNGO P/N: 1834KDC
Adapter	:	Manufacturer: IBM Corporation M/N: 08K8210 Input: AC100-240V 50/60Hz 0.5-1.0A Output: DC 16V 4.5A

1.6 Test Facility and Location

Listed by FCC, August 02, 2011
The Certificate Registration Number is 665078.
Listed by Industry Canada, July 01, 2011
The Certificate Registration Number is 9743A.

Dongguan NTC Co., Ltd.
(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China
(Full Name: Building D, Gaosheng Science & Technology Park, Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Hopping Channel Number	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.207 (a)	AC Power Conducted Emission	Compliant
§15.247(d),§15.209, §15.205	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant
§15.247(d)	Conducted Spurious Emission	Compliant

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing, and all packets DH1, DH3 and DH5 mode in all modulation type GFSK, π/4-DQPSK, 8DPSK were tested.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: Charging + BT Mode

3.3 Measurement Results

Please refer to following plots.

Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: Http://www.ntc-c.com

Site: Conduction

Test Time: 2015-3-16 10:36:38



Report No.: HS002
Test Standard: FCC PART 15B_Class B_QP
Test item: Conducted Emission
Phase: L1
Applicant: Harmonic International Ltd.
Temp.( )/Hum.(%): 24(C) / 53 %
Product: Hidden Radio Wireless Speaker
Power Rating: AC 120V/60Hz
Model No.: HS002
Test Engineer: Jason

Test Mode: Charging+BT Mode
Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	10.80	32.94	43.74	65.99	-22.25	QP	P	
2	0.1500	10.80	28.11	38.91	55.99	-17.08	AVG	P	
3	0.1660	10.80	29.10	39.90	65.15	-25.25	QP	P	
4	0.1660	10.80	24.51	35.31	55.15	-19.84	AVG	P	
5	0.2420	10.80	26.68	37.48	62.02	-24.54	QP	P	
6	0.2420	10.80	22.24	33.04	52.02	-18.98	AVG	P	
7	0.6380	10.80	18.69	29.49	56.00	-26.51	QP	P	
8	0.6380	10.80	12.02	22.82	46.00	-23.18	AVG	P	
9	1.1220	10.80	18.89	29.69	56.00	-26.31	QP	P	
10	1.1220	10.80	10.61	21.41	46.00	-24.59	AVG	P	
11	13.2380	10.80	31.98	42.78	60.00	-17.22	QP	P	
12	13.2380	10.80	21.21	32.01	50.00	-17.99	AVG	P	

Note: Level=Reading+Factor.
Margin=Limit-Level.

Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: Http://www.ntc-c.com

Site: Conduction

Test Time: 2015-3-16 10:40:03



Report No.: HS002
Test Standard: FCC PART 15B_Class B_QP
Test item: Conducted Emission
Phase: N
Applicant: Harmonic International Ltd.
Temp.( )/Hum.(%): 24(C) / 53 %
Product: Hidden Radio Wireless Speaker
Power Rating: AC 120V/60Hz
Model No.: HS002
Test Engineer: Jason

Test Mode: Charging+BT Mode
Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	10.80	32.51	43.31	65.99	-22.68	QP	P	
2	0.1500	10.80	28.01	38.81	55.99	-17.18	AVG	P	
3	0.2420	10.80	26.64	37.44	62.02	-24.58	QP	P	
4	0.2420	10.80	22.03	32.83	52.02	-19.19	AVG	P	
5	0.6340	10.80	18.73	29.53	56.00	-26.47	QP	P	
6	0.6340	10.80	11.38	22.18	46.00	-23.82	AVG	P	
7	1.1180	10.80	20.14	30.94	56.00	-25.06	QP	P	
8	1.1180	10.80	9.21	20.01	46.00	-25.99	AVG	P	
9	1.2100	10.80	19.91	30.71	56.00	-25.29	QP	P	
10	1.2100	10.80	7.68	18.48	46.00	-27.52	AVG	P	
11	13.2620	10.80	32.09	42.89	60.00	-17.11	QP	P	
12	13.2620	10.80	21.63	32.43	50.00	-17.57	AVG	P	

Note: Level=Reading+Factor.
Margin=Limit-Level.

4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz





4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.

4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209) μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark：(1) Emission level (dB)μV = 20 log Emission level μV/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

4.4 Measurement Results

Operation Mode:	TX (the worst case GFSK, Lowest channel)		
Frequency Range:	9KHz~1GHz	Temperature :	23 ℃
Test Result:	PASS	Humidity :	50 %
Measured Distance:	3m	Test By:	Sance
Test Date :	March 29, 2015		

Freq. (MHz)	Ant.Pol. H/V	Reading Level (dBuV)	Factor (dB/m)	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Note
55.2199	V	34.82	-13.72	21.10	40.00	-18.90	QP
146.4000	V	44.78	-18.58	26.20	43.50	-17.30	QP
208.4798	V	43.78	-16.28	27.50	43.50	-16.00	QP
360.7699	V	39.73	-11.13	28.60	46.00	-17.40	QP
442.2500	V	39.54	-11.04	28.50	46.00	-17.50	QP

179.3797	H	40.98	-14.18	26.80	43.50	-16.70	QP
201.6896	H	41.50	-13.40	28.10	43.50	-15.40	QP
294.8100	H	38.81	-10.61	28.20	46.00	-17.80	QP
362.7099	H	39.05	-9.15	29.90	46.00	-16.10	QP

Other emissions are lower than 10dB below the allowable limit.

Note:
(1) Emission Level= Reading Level + Factor
(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(3) Measurement uncertainty : ±3.4dB
(4) Loop antenna used for the emission below 30MHz.
(5) Data of measurement within this frequency range shown " ---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.

Modulation:	GFSK (the worst case)		
Frequency Range:	1-25GHz	Test Date :	January 26, 2015
Test Result:	PASS	Temperature :	20 ℃
Measured Distance:	3m	Humidity :	50 %
Test By:	Sance		

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
4804	V	38.02	28.37	14.63	52.65	43.00	74.00	54.00	-21.35	-11.00
7206	V	39.29	27.95	20.68	59.97	48.63	74.00	54.00	-14.03	-5.37

4804	H	37.92	28.66	14.63	52.55	43.29	74.00	54.00	-21.45	-10.71
7206	H	36.96	27.93	20.68	57.64	48.61	74.00	54.00	-16.36	-5.39

Operation Mode: TX Mode (Mid)										
4882	V	42.57	32.39	14.97	57.54	47.36	74.00	54.00	-16.46	-6.64
7323	V	29.18	21.16	20.91	50.09	42.07	74.00	54.00	-23.91	-11.93

4882	H	39.03	27.29	14.97	54.00	42.26	74.00	54.00	-20.00	-11.74
7323	H	33.33	21.10	20.91	54.24	42.01	74.00	54.00	-19.76	-11.99

Operation Mode: TX Mode (High)										
4960	V	36.70	27.56	15.30	52.00	42.86	74.00	54.00	-22.00	-11.14
7440	V	36.58	27.49	21.16	57.74	48.65	74.00	54.00	-16.26	-5.35

4960	H	36.70	27.72	15.30	52.00	43.02	74.00	54.00	-22.00	-10.98
7440	H	37.84	27.45	21.16	59.00	48.61	74.00	54.00	-15.00	-5.39

Note:
(1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level + Factor
(3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(4) Data of measurement within this frequency range shown " ---" in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
(5) Measurement uncertainty : ±3.7dB.
(6) Horn antenna used for the emission over 1000MHz.

5. Channel Separation test

5.1 Measurement Procedure

Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable, and using the MARKER and Max-Hold function to record the separation of two adjacent channels.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Results

Modulation:	GFSK, π/4-DQPSK, 8DPSK		
RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	March 27, 2015
Temperature :	24 ℃	Humidity :	50 %
Test Result:	PASS		

Channel number	Channel frequency (MHz)	Separation Read Value (KHz)	Separation Limit (KHz)
GFSK			
Lowest	2402	1002	>596
Middle	2441	1002	>596
Highest	2480	1002	>592
π/4-DQPSK			
Lowest	2402	1002	>844
Middle	2441	1002	>860
Highest	2480	1002	>864
8DPSK			
Lowest	2402	1002	>860
Middle	2441	1002	>848
Highest	2480	1002	>860

GFSK Lowest Channel



Date: 27.MAR.2015 15:04:50

GFSK Middle Channel



Date: 27.MAR.2015 15:05:53

GFSK Highest Channel



Date: 27.MAR.2015 15:06:32

π/4-DQPSK Lowest Channel



Date: 27.MAR.2015 15:08:33

π/4-DQPSK Middle Channel



Date: 27.MAR.2015 15:10:12

π/4-DQPSK Highest Channel



Date: 27.MAR.2015 15:11:21

8DPSK Lowest Channel



Date: 27.MAR.2015 15:12:47

8DPSK Middle Channel



Date: 27.MAR.2015 15:14:19

8DPSK Highest Channel



Date: 27.MAR.2015 15:15:09

6. 20dB Bandwidth

6.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Results

Refer to attached data chart.

Modulation:	GFSK, π/4-DQPSK, 8DPSK		
RBW:	30KHz	VBW:	100KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	March 27, 2015
Temperature :	24 ℃	Humidity :	50 %
Test Result:	PASS		

Channel frequency (MHz)	20dB Down BW(kHz)
GFSK	
2402	894
2441	894
2480	888
π/4-DQPSK	
2402	1266
2441	1290
2480	1296
8DPSK	
2402	1290
2441	1272
2480	1290

GFSK Lowest Channel



Date: 27.MAR.2015 14:57:20

GFSK Middle Channel



Date: 27.MAR.2015 14:57:44

GFSK Highest Channel



Date: 27.MAR.2015 14:58:06

π/4-DQPSK Lowest Channel



Date: 27.MAR.2015 14:59:15

π/4-DQPSK Middle Channel



Date: 27.MAR.2015 14:59:41

π/4-DQPSK Highest Channel



Date: 27.MAR.2015 15:00:08

8DPSK Lowest Channel



Date: 27.MAR.2015 15:00:53

8DPSK Middle Channel



Date: 27.MAR.2015 15:01:21

8DPSK Highest Channel



Date: 27.MAR.2015 15:01:46

7. Hopping Channel Number

7.1 Measurement Procedure

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, and the spectrum analyzer set to MAX HOLD readings were taken for 3-5 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Results

Modulation	GFSK, π/4-DQPSK, 8DPSK		
RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	March 27, 2015
Temperature :	24 ℃	Humidity :	50 %
Test Result:	PASS		

Hopping Channel Frequency Range	Number of Hopping Channels	Limit
2402-2480	79	≥15

The worst case: GFSK

GFSK



Date: 26.MAR.2015 19:12:16

8. Time of Occupancy (Dwell Time)

8.1 Measurement Procedure

Average Channel Occupancy Time, FCC Ref:15.247(a)(1)(iii):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.
The spectrum analyzer center frequency was set to one of the known hopping channels. The Sweep was set to 10 ms, the SPAN was set to Zero SPAN. The time duration of the transmissions so captured was measured with the Marker Delta function

8.2 Measurement Results

The maximum number of hopping channels in 31.6s (0.4s/Channel x 79 Channel)

Refer to attached data chart.

Modulation :	GFSK, π/4-DQPSK, 8DPSK		
RBW :	1MHz	VBW :	3MHz
Spectrum Detector:	PK	Test By:	Sance
Test Date :	March 27, 2015	Temperature :	24℃
Test Result:	PASS	Humidity :	50 %

Packet	Frequency (MHz)	Result (msec)	Limit (msec)
GFSK			
DH1	2441	0.415 (ms)*(1600/(2*79))*31.6=132.8	400
DH3	2441	1.670 (ms)*(1600/(4*79))*31.6=267.2	400
DH5	2441	2.925 (ms)*(1600/(6*79))*31.6=312.0	400
π/4-DQPSK			
2-DH1	2441	0.410 (ms)*(1600/(2*79))*31.6=131.2	400
2-DH3	2441	1.690 (ms)*(1600/(4*79))*31.6=270.2	400
2-DH5	2441	2.925 (ms)*(1600/(6*79))*31.6=312.0	400
8DPSK			
3-DH1	2441	0.405 (ms)*(1600/(2*79))*31.6=129.6	400
3-DH3	2441	1.690 (ms)*(1600/(4*79))*31.6=270.2	400
3-DH5	2441	2.940 (ms)*(1600/(6*79))*31.6=313.6	400

GFSK DH1



Date: 26.MAR.2015 13:59:25

GFSK DH3



Date: 26.MAR.2015 14:00:08

GFSK DH5



Date: 26.MAR.2015 18:00:20

π/4-DQPSK 2-DH1



Date: 26.MAR.2015 18:01:30

π/4-DQPSK 2-DH3



Date: 26.MAR.2015 18:02:07

π/4-DQPSK 2-DH5



Date: 26.MAR.2015 18:03:04

8DPSK 3-DH1



Date: 26.MAR.2015 18:03:58

8DPSK 3-DH3



Date: 26.MAR.2015 18:04:45

8DPSK 3-DH5



Date: 26.MAR.2015 18:05:37

9. MAXIMUM PEAK OUTPUT POWER

9.1 Measurement Procedure

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm. Cable loss was considered during this measurement.

9.2 Measurement Results

Refer to attached data chart.

Modulation :	GFSK, π/4-DQPSK, 8DPSK		
RBW :	3MHz	VBW :	3MHz
Spectrum Detector:	PK	Test Date :	March 27, 2015
Test By:	Sance	Temperature :	24 ℃
Test Result:	PASS	Humidity :	50 %

Channel Frequency (MHz)	Cable Loss dB	Peak Power output(mW)	Peak Power output(dBm)	Peak Power Limit(dBm)	Pass/Fail
GFSK					
2402.00	1.5	0.21	-6.81	21	PASS
2441.00	1.5	0.28	-5.53	21	PASS
2480.00	1.5	0.32	-4.94	21	PASS
π/4-DQPSK					
2402.00	1.5	0.18	-7.52	21	PASS
2441.00	1.5	0.23	-6.41	21	PASS
2480.00	1.5	0.27	-5.75	21	PASS
8DPSK					
2402.00	1.5	0.17	-7.70	21	PASS
2441.00	1.5	0.21	-6.70	21	PASS
2480.00	1.5	0.29	-5.35	21	PASS

GFSK Lowest Channel



Date: 26.MAR.2015 10:07:44

GFSK Middle Channel



Date: 26.MAR.2015 10:08:09

GFSK Highest Channel



Date: 26.MAR.2015 10:08:34

π/4-DQPSK Lowest Channel



Date: 26.MAR.2015 10:09:35

π/4-DQPSK Middle Channel



Date: 26.MAR.2015 10:10:17

π/4-DQPSK Highest Channel



Date: 26.MAR.2015 10:10:56

8DPSK Lowest Channel



Date: 26.MAR.2015 10:11:44

8DPSK Middle Channel



Date: 26.MAR.2015 10:12:20

8DPSK Highest Channel



Date: 26.MAR.2015 10:12:42

10. Band Edge

10.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to100KHz, and the video bandwidth set to 300KHz.

10.2 Limit

15.247(d)In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

10.3 Measurement Results

Please see below test table and plots.
For Radiated Emission
The worst case: GFSK

Hopping-on mode

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
2399.990	H	42.86	32.56	8.09	50.95	40.65	74.00	54.00	-23.05	-13.35
2399.990	V	41.41	30.26	8.09	49.50	38.35	74.00	54.00	-24.50	-15.65
2483.660	H	40.64	27.04	8.36	49.00	35.40	74.00	54.00	-25.00	-18.60
2483.660	V	40.90	28.90	8.36	49.26	37.26	74.00	54.00	-24.74	-16.74

Note: (1) Emission Level= Reading Level + Factor
(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(3) Horn antenna used for the emission over 1000MHz.

For RF Conducted

GFSK Lowest Channel



Date: 27.MAR.2015 15:20:54



Date: 27.MAR.2015 15:22:32

GFSK Highest Channel



Date: 27.MAR.2015 15:30:25



Date: 27.MAR.2015 15:32:54

π/4-DQPSK Lowest Channel



Date: 27.MAR.2015 15:26:53



Date: 27.MAR.2015 15:28:50

π/4-DQPSK Highest Channel



Date: 27.MAR.2015 15:34:18



Date: 27.MAR.2015 15:36:24

8DPSK Lowest Channel



Date: 27.MAR.2015 15:43:34



Date: 27.MAR.2015 15:45:14

8DPSK Highest Channel



Date: 27.MAR.2015 15:46:20



Date: 27.MAR.2015 15:48:37

11. Antenna Application

11.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

11.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is -0.61dBi. So, the antenna is consider meet the requirement.

12. Conducted Spurious Emissions

12.1 Measurement Procedure

Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. All spurious emission and up tp the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband.

12.2. Measurement Results

Please refer to following plots, the worst case (GFSk) was shown.

Lowest Channel



Date: 27.MAR.2015 22:33:42







Note: Sweep points=8001pts

Middle Channel



Date: 27.MAR.2015 22:33:16







Note: Sweep points=8001pts

Highest Channel



Date: 27.MAR.2015 22:33:29







Note: Sweep points=8001pts

13. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 24, 2014	Nov. 23, 2015
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 27, 2014	Nov. 26, 2015
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Mar. 07, 2015	Mar. 06, 2016
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 08, 2014	Nov. 07, 2015
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.24, 2014	Oct.23, 2015
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 06, 2014	Nov. 05, 2015
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.11, 2014	Oct.10, 2015
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Sep. 02, 2014	Sep. 01, 2015
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 04, 2014	Nov. 03, 2015
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 08, 2014	Nov. 07, 2015
Temporary antenna connector	TESCOM	SS402	N/A	1G-18GHz	N/A	N/A

---End---