Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

FCC 15.247& RSS-247
2.4 GHz Test Report

for

AAEON Technology Inc.

5F, No. 135, Lane 235, PaoChiao Rd., Hsin-TienDist, New Taipei City, 231, Taiwan, R.O.C.

Product Name	**:**	**IOTAS Connect 3**
Model Name	**:**	**(1)ITS-GW01-A10-C001** **(2)ITS-GW01-A10-C002**
Brand		**IOTAS**
FCC ID	**:**	**OHB-A010001**
IC	**:**	**23644-A010001**

Prepared by:	**:**	**AUDIX Technology Corporation,** **EMC Department**

Testing Laboratory
1724

TESTING
NVLAP LAB CODE 200077-0

The test report is based on a single evaluation of one sample of the above-mentioned products. It does notimply an assessment of the whole production and does not permit the use of the test lab logo.
The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

TABLE OF CONTENTS

Description Page

TEST REPORT 4
1. REVISION RECORD OF TEST REPORT 5
2. SUMMARY OF TEST RESULTS 6
3. GENERAL INFORMATION 7
3.1. Description of Application 7
3.2. Description of EUT 8
3.3. Reference Test Guidance 8
3.4. Antenna Information 9
3.5. EUT Specifications Assessed in Current Report 9
3.6. Description of Key Components 10
3.7. Test Configuration 11
3.8. Output Power Setting 12
3.9. Tested Supporting System List 12
3.10. Setup Configuration 12
3.11. Operating Condition of EUT 12
3.12. Description of Test Facility 13
3.13. Measurement Uncertainty 14
4. MEASUREMENT EQUIPMENTLIST 16
4.1. Conducted Emission Measurement 16
4.2. Radiated Emission Measurement 17
4.3. RF Conducted Measurement 17
5. CONDUCTED EMISSION 18
5.1. Block Diagram of Test Setup 18
5.2. Conducted Emission Limit 18
5.3. Test Procedure 18
5.4. Test Results 19
6. RADIATED EMISSION 20
6.1. Block Diagram of Test Setup 20
6.2. Radiated Emission Limits 22
6.3. Test Procedure 23
6.4. Measurement Result Explanation 24
6.5. Test Results 24
7. 20dB/OCCUPIED BANDWIDTH 25
7.1. Block Diagram of Test Setup 25
7.2. Specification Limits 25
7.3. Test Procedure 25
7.4. Test Results 25
8. CARRIER FREQUENCY SEPARATION 26
8.1. Block Diagram of Test Setup 26
8.2. Specification Limits 26
8.3. Test Procedure 26
8.4. Test Results 26
9. TIME OF OCCUPANCY 27
9.1. Block Diagram of Test Setup 27

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

9.2. Specification Limits....27
9.3. Test Procedure....27
9.4. Test Results....27
10. NUMBER OF HOPPING CHANNELS....28
10.1. Block Diagram of Test Setup....28
10.2. Specification Limits....28
10.3. Test Procedure....28
10.4. Test Results....28
11. MAXIMUM PEAK OUTPUT POWER....29
11.1. Block Diagram of Test Setup....29
11.2. Specification Limits....29
11.3. Test Procedure....29
11.4. Test Results....29
12. EMISSION LIMITATIONS....30
12.1. Block Diagram of Test Setup....30
12.2. Specification Limits....30
12.3. Test Procedure....30
12.4. Test Results....30
13. DEVIATION TO TEST SPECIFICATIONS....31

APPENDIX A TEST DATA AND PLOTS
APPENDIX B TESTPHOTOGRAPHS

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

TEST REPORT

Applicant	:	AAEON Technology Inc.
Manufacturer	:	AAEON Technology Inc.
EUT Description		
(1) Product	:	IOTAS Connect 3
(2) Model	:	(1)ITS-GW01-A10-C001 (2)ITS-GW01-A10-C002
(3) Brand	:	IOTAS
(4) Power Supply	:	DC 5V, 3A

Applicable Standards:

Title 47CFRFCC Part 15 Subpart C
RSS-Gen (Issue 5), April2018
RSS-247 (Issue 2), February 2017
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.
Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2021. 04. 09

Reviewed by: Annie Yu (Annie Yu/Administrator)

Approved by: Johnny Hsueh (Johnny Hsueh/Section Manager)

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Date	Revision Summary	Report Number
0	2021. 04. 09	Original Report	EM-F210206

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	**PASS**
15.247(d)/15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	**PASS**
15.247(a)(1)	RSS-247 §5.1(2)	20dB/Occupied Bandwidth	**PASS**
15.247(a)(1)	RSS-247 §5.1(2)	Carrier Frequency Separation	**PASS**
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Time of Occupancy	**PASS**
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Number of Hopping Channels	**PASS**
15.247(b)(1)	RSS-247 §5.1(2)	Maximum Peak Output Power	**PASS**
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	**PASS**
15.203	---	Antenna Requirement	**Compliance**
Note: The uncertainties value is not used in determining the result.			

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3. GENERAL INFORMATION

3.1. Description of Application

<table>
<tr><td>Applicant</td><td>AAEON Technology Inc.
5F, No. 135, Lane 235, PaoChiao Rd., Hsin-TienDist, New Taipei City, 231, Taiwan, R.O.C.</td></tr>
<tr><td>Manufacturer</td><td>AAEON Technology Inc.
5F, No. 135, Lane 235, PaoChiao Rd., Hsin-TienDist, New Taipei City, 231, Taiwan, R.O.C.</td></tr>
<tr><td>Product</td><td>IOTAS Connect 3</td></tr>
<tr><td>Brand</td><td>IOTAS</td></tr>
<tr><td>Model</td><td>(1)ITS-GW01-A10-C001 (2)ITS-GW01-A10-C002
The difference between models is as following, and the difference has no influence on RF function. The modelITS-GW01-A10-C002 was tested in this report.
<table>
<tr><td>Model / Difference</td><td>ITS-GW01-A10-C001</td><td>ITS-GW01-A10-C002</td></tr>
<tr><td>LTE Module</td><td>Without</td><td>With</td></tr>
</table></td></tr>
</table>

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.2. Description of EUT

Test Model	ITS-GW01-A10-C002
Serial Number	N/A
Power Rating	DC 5V, 3A
RF Features	WLAN:802.11 a/b/g/n/ac Bluetooth: BT and BLE ZigBee Z-Wave
Transmit Type	WLAN: 1T1R Bluetooth: 1T1R ZigBee: 1T1R Z-Wave: 1T1R
Sample Status	Mass production
Test Sample	Sample No. 02 / Test Item: AC Conduction, RSE, Conducted / Firmware: N/A
Date of Receipt	2021. 03. 09
Date of Test	2021. 03. 22 ~ 29
Interface Ports of EUT	• One LAN Port • One USB Port • One DC Input Port
Accessories Supplied	• AC Adapter

3.3. Reference Test Guidance

None

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.4. Antenna Information

WLAN/ZigBee/BT Antenna				
Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain(dBi)
RFA-DB1-AP609-70-100	Aristotle	PIFA	2400-2500	2.39
			5150-5875	4.06

Z-Wave Antenna				
Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain(dBi)
RFA-ZW-AP856-100-R2	Aristotle	PIFA	868-928	0.3

3.5. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
Bluetooth	2402-2480	79	FHSS (GFSK, π/4 DQPSK, 8-DPSK)	1/2/3

Channel List							
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.6. Description of Key Components

Item	Supplier	Model / Type	Character
CPU (Socket: BGA1170)	Intel	N2807	1.58GHz
Storage (SSD)	Kingston	EMMC16G-TB28	eMMC flash 16GB
Memory (RAM)	NANYA	NT5CC256M16EP-EK	4GB DDR3
WLAN/BT Combo Card	AMPAK	AP6255	---
Antenna	Aristotle	RFA-DB1-AP609-70-100	Wi-Fi/BT/ZigBee/antenna
Z-Wave Chip	Silicon Labs	ZGM130S	---
Antenna	Aristotle	RFA-ZW-AP856-100-R2	Z-Wave antenna
ZigBee Chip	Silicon Labs	EFR32MG1B232	---
Antenna	Aristotle	RFA-DB1-AP609-70-100	Wi-Fi/BT/ZigBee/antenna
LTE Module (Option)	Quectel	EC25-AFX	FCC ID: XMR201909EC25AFX IC: 10224A-2019EC25AFX
Antenna	Aristotle	RFA-LTE-T42-U-M62-1	LTE antenna
AC Adapter (Wall-mount, 2C)	SUNNY COMPUTER TECHNOLOGY CO., LTD	SYS1639-1505-W2 (P/N: G401163915009)	I/P: 100-240Vac, 50-60Hz, 1.0A O/P: 5Vdc, 3A 15W MAX
	DC Cable: Unshielded, Detachable, 1.4m		

Remark: For more detailed features description, please refer to the manufacturer's specifications or the user manual.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.7. Test Configuration

Mode	Duty Cycle (x)	T (ms)	Duty Cycle Correction Factor (dB)
BT	N/A	2.900	N/A

AC Conduction	
Test Case	Normal operation

Item		Modulation	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge Note 1 & 2	GFSK	1Mbps	00/78
		8-DPSK	3Mbps	00/78
	Radiated Spurious Emission Note1	GFSK	1Mbps	00/39/78
Conducted Test Case	20dB/Occupied Bandwidth	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Carrier Frequency Separation	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Time of Occupancy	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Number of Hopping Channels	GFSK	1Mbps	39
		8-DPSK	3Mbps	39
	Maximum Peak Output Power	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Band Edges	GFSK	1Mbps	00/78
		8-DPSK	3Mbps	00/78
	Spurious Emission	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78

Note 1:■Mobile Device

☐Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow:☐ Lie☐ Side☐ Stand

Note 2: We performed testing of the highest and lowest data rate.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.8. Output Power Setting

Centre Frequency (MHz)	Power Setting	
	GFSK	8-DPSK
2402	Default	Default
2441	Default	Default
2480	Default	Default

3.9. Tested Supporting System List

3.9.1. Support Peripheral Unit

No.	Product	Brand	Model No.	Serial No.	Approval
1.	Notebook Computer	hp	TPN-Q189	5CD8175992	Contains FCC ID: PD93168NG Contains IC: 1000M-3168NG

3.9.2. Cable Lists

No.	Cable Description Of The Above Support Units
1.	LAN Cable: Unshielded, Detachable, 1.0m Adapter: hp, M/N PPP-012C-S DC Cord：Shielded, Undetachable, 1.8m,Bonded a ferrite core AC Power Cord：Unshielded, Detachable, 1.0m

3.10.Setup Configuration

3.10.1. EUTConfiguration for Power Line & Radiated Emission

3.10.2. EUT Configuration for RF Conducted Test Items



3.11.Operating Condition of EUT

Test program “putty” is used for enabling EUT BTfunction under continues transmitting and choosing data rate/ channel.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.12.Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 491, Zhongfu Rd., Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 ISED CAB Identifier Number under APEC TEL MRA by NCC is TW1724 (1) No.8 Shielded Room (2) No.1 3m Semi Anechoic Chamber (3) Fully Anechoic Chamber

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

3.13.Measurement Uncertainty

Test Items/Facilities			Frequency Range	Uncertainty
Conduction Test			9kHz-150kHz	±3.7dB
			150kHz-30MHz	±3.4dB
Radiation Test	☒	No.1 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.8dB
			200MHz-1000MHz, 3m, Horizontal	±4.1dB
			30MHz-200MHz, 3m, Vertical	±4.5dB
			200MHz-1000MHz, 3m, Vertical	±4.5dB
			1GHz-6GHz, 3m	±4.7dB
			6GHz-18GHz, 3m	±4.1dB
	☐	No.3 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
			200MHz-1000MHz, 3m, Horizontal	±4.2dB
			30MHz-200MHz, 3m, Vertical	±4.3dB
			200MHz-1000MHz, 3m, Vertical	±4.5dB
	☐	No.4 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.1dB
			200MHz-1000MHz, 3m, Horizontal	±4.5dB
			30MHz-200MHz, 3m, Vertical	±4.4dB
			200MHz-1000MHz, 3m, Vertical	±4.8dB
			1GHz-6GHz, 3m	±5.0dB
			6GHz-18GHz, 3m	±4.7dB
	☐	No.5 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.2dB
			200MHz-1000MHz, 3m, Horizontal	±4.3dB
			30MHz-200MHz, 3m, Vertical	±4.3dB
			200MHz-1000MHz, 3m, Vertical	±4.7dB
			1GHz-6GHz, 3m	±4.8dB
			6GHz-18GHz, 3m	±4.5dB
	☒	Fully Anechoic Chamber	30MHz~1000MHz	±4.6dB
			1GHz~18GHz	±5.4dB
			18GHz~40GHz	±3.52dB
			40GHz~260GHz	±3.56dB

Remark：Uncertainty = $ku_c(y)$

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Item	Uncertainty
20dB Bandwidth	±0.2kHz
99% Occupied Bandwidth	±0.38%
Carrier Frequency Separation	±0.2kHz
Time of Occupancy	±0.03sec
Maximum peak Output power	± 0.52dB
Conducted Emission Limitations	± 0.13dB

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

4. MEASUREMENT EQUIPMENTLIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESR3	101774	2021. 02. 02	1 Year
2.	A.M.N.	R&S	ENV432	101567	2020. 04. 20	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2020. 12. 10	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	100354	2021. 01. 04	1 Year
5.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.8 S/R	2020. 04. 17	1 Year
6.	Coaxial Cable	Yeida	RG/58AU	CE-08	2020. 09. 19	1 Year
7.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2020. 04. 29	1 Year
2.	Spectrum Analyzer	Agilent	N9030A-526	MY53310269	2021. 01. 14	1 Year
3.	Test Receiver	R&S	ESCS30	100039	2020. 06. 05	1 Year
4.	Amplifier	HP	8447D	2944A07178	2020. 04. 29	1 Year
5.	Microwave Amplifier	Keysight	83051A	MY53010042	2020. 08. 05	1 Year
6.	Microwave Amplifier	Agilent	8449B	3008A02678	2021. 02. 27	1 Year
7.	Loop Antenna	R&S	HFH2-Z2	891847/27	2019. 12. 26	2 Years
8.	Bilog Antenna	TESEQ	CBL6112D	33821	2021. 01. 15	1 Year
9.	Horn Antenna	ETS-Lindgren	3117	00135902	2021. 03. 19	1 Year
10.	Horn Antenna	COM-POWER	AH-840	101092	2020 .05. 08	1 Year
11.	2.4GHz Notch Filter	K&L Microwave	7NSL10-2441.5/E130.5-O/O	1	2020 .07. 24	1 Year
12.	3GHz Notch Filter	Microwave	H3G018G1	484796	2020. 08. 20	1 Year
13.	Coaxial Cable	MIYAZAKI	5D2W	CLAMP-01	2020.09.19	1 Year
14.	Coaxial Cable	MIYAZAKI	5D2W	RE-11	2021. 01. 29	1 Year
15.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 104	RE-29	2020. 09. 19	1 Year
16.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 102	RE-30	2020. 09. 19	1 Year
17.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2020. 04. 17	1 Year
18.	Digital Thermo-Hygro Meter	EVERY DAY	E-512	RF-02	2020. 04. 17	1 Year
19.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.
20.	Test Software	Audix	e3	V6.110601	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9020B-544	MY57120357	2021. 01. 06	1 Year
2.	Digital Thermo-Hygro Meter	Shenzhen Datronn Electronics	KT-905	RF	2020. 04. 17	1 Year

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.10

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dBμV	56 ~ 46 dBμV
500kHz ~ 5MHz	56 dBμV	46 dBμV
5MHz ~ 30MHz	60 dBμV	50 dBμV

Remark1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.
2.: The lower limit applies to the band edges.

5.3. Test Procedure

5.3.1. To set up the EUT as indicated in ANSI C63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.

5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).

5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)

5.3.4. Checking frequency range from 150kHz to 30 MHz and record the emission which does not have 20 dB below limit.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

5.4. Test Results

Please refer to Appendix A.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

6. RADIATED EMISSION

6.1. Block Diagram of Test Setup

6.1.1. Block Diagram of EUT

Indicated as section 3.10

6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000MHz



This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

6.1.4. Setup Diagram for above 1GHz

Fully Anechoic Chamber



Semi Anechoic Chamber



This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance(m)	Limits	
		dBμV/m	μV/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark：(1) dBμV/m = 20 log (μV/m)
(2) The tighter limit applies to the edge between two frequency bands.
(3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
(4) Fundamental and emission fall within operation band are exempted from this section.
(5) Pursuant to ANSI C63.10: 6.6.4.3,if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

6.3. Test Procedure

Frequency Range 9kHz~30MHz:
The EUT setup on the turntable which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level.
In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013regulation.

(1) RBW = 9kHz with peak and average detector.
(2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:
The EUT setup on the turn table which has 80cm (for 30-1000MHz) and 1.5m (for above 1GHz) height to the ground.The turn table rotated 360 degrees and antenna varied from 1 m to 4 m (for 30-1000MHz) and from 1m to 3m (for above 1GHz at fully Anechoic Chamber)orfrom 1 m to 4 m (for above 1GHz at Semi Anechoic Chamber) to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013regulation.

Frequency below 1GHz:
Spectrum Analyzer is used for pre-testing with following setting:
(1)RBW = 120KHz
(2)VBW ≥ 3 x RBW.
(3)Detector = Peak.
(4)Sweep time = auto.
(5)Trace mode = max hold.
(6)Allow sweeps to continue until the trace stabilizes.
Note 1: When peak-detected value is lower than limit that the measurement using theQ.P. detector is not required, otherwise using Q.P. for final measurement.
Note 2: When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Frequency above 1GHz to 10th harmonic(up to 25 GHz):
Peak Detector:
(1)RBW = 1MHz
(2)VBW ≥ 3 x RBW.
(3)Detector = Peak.
(4)Sweep time = auto.
(5)Trace mode = max hold.
(6)Allow sweeps to continue until the trace stabilizes.
Note: When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Average Detector:

■**Option 1:**

(1)RBW = 1MHz
(2)VBW ≥ 1/ T.
(3)Detector = Peak.
(4)Sweep time = auto.
(5)Trace mode = max hold.
(6)Allow sweeps to continue until the trace stabilizes.

☐**Option 2:**

Average Emission Level= Peak Emission Level+ D.C.C.F.

6.4. Measurement Result Explanation

■Peak Emission Level=Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)

■Average Emission Level l=Antenna Factor + Cable Loss +Meter Reading (including Preamp factor if test used)

☐Average Emission Level= Peak Emission Level+ DCCF
Duty Cycle Correction Factor (DCCF)= 20log(TX_{on}/TX_{on+off}) presented in section 3.6

☐ERP= Peak Emission Level-95.2dB-2.14dB

6.5. Test Results

Please refer to Appendix A.

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

7. 20dB/OCCUPIED BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.3. Test Procedure

Following measurement procedure is reference toANSI C63.10:2013:

For 20dB Bandwidth

(1) Set Span range 2~5 times the OBW
(2) Set VBW≥3xRBW.
(3) Detector = Peak.
(4) Trace mode = Max hold.
(5) Sweep = Auto couple.
(6) Allow the trace to stabilize.
(7) Setting channel bandwidth function x dB to -20 dB to record the final bandwidth.

For 99% Occupied Bandwidth

(8) Set Span range 1.5~5 times the OBW
(9) Set RBW close to1% to 5% of OBW.
(10) Set VBW≥3xRBW.
(11) Detector = Peak.
(12) Trace mode = Max hold
(13) Sweep = Auto couple.
(14) Allow the trace to stabilize.

7.4. Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

8. CARRIER FREQUENCY SEPARATION

8.1. Block Diagram of Test Setup



8.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output no greater than 125mW.

8.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

(1) Span = Wide enough to capture the peaks of two adjacent channels
(2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
(3) VBW≥ RBW
(4) Sweep = Auto
(5) Detector function = Peak
(6) Trace = Max hold
(7) Allow the trace to stabilize.

8.4. Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

9. TIME OF OCCUPANCY

9.1. Block Diagram of Test Setup



9.2. Specification Limits

Frequency hopping systems in the 2400-2483.5MHz shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by number of hopping channels employed.

9.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

(1) Span: Zero span, centered on a hopping channel.
(2) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1/T, where T is the expected dwell time per channel.
(3) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
(4) Detector function = Peak
(5) Trace = Max hold

9.4. Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

10. NUMBER OF HOPPING CHANNELS

10.1. Block Diagram of Test Setup



10.2. Specification Limits

Frequency hopping systems which use fewer than 20 hopping frequencies may employ intelligent hopping techniques to avoid interference to other transmissions. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels.

10.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

(1) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
(2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
(3) VBW ≥ RBW
(4) Sweep = Auto
(5) Detector function = Peak
(6) Trace = m=Max hold
(7) Allow the trace to stabilize.

10.4. Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

11.MAXIMUM PEAK OUTPUT POWER

11.1.Block Diagram of Test Setup



11.2.Specification Limits

The Limits of maximum Peak Output Power for frequency hopping systems in 2400-2483.5MHz is: 0.125Watt. (21dBm)

11.3.Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

(a) Use the following spectrum analyzer settings

(1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
(2) RBW > 20 dB bandwidth of the emission being measured.
(3) VBW ≥ RBW
(4) Sweep:Auto
(5) Detector function: Peak
(6) Trace:Max hold

(b) Allow trace to stabilize.

(c) Use the marker-to-peak function to set the marker to the peak of the emission.

11.4.Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

12. EMISSION LIMITATIONS

12.1. Block Diagram of Test Setup



12.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, that the required attenuation shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a)/RSS-Gen Section 8.9table 4is not required. In addition, radiated emissions which fall in restricted bands, asdefined in Section 15.205(a)/RSS-Gen Section 8.10 table 6,, must also comply withthe radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 (See Section 15.205(c)).

12.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

(1) Set span wide enough to capture the peak level of the in-band emission and all spurious emissions; up to 10th harmonic.
(2) RBW = 100 kHz
(3) VBW ≥ RBW
(4) Sweep = Auto
(5) Detector function = Peak
(6) Trace = Max hold

12.4. Test Results

Please refer to Appendix A

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

13.DEVIATION TO TEST SPECIFICATIONS

【NONE】

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS

(Model: (1)ITS-GW01-A10-C001 (2)ITS-GW01-A10-C002)

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

TABLE OF CONTENTS

A.1 CONDUCTED EMISSION 2
A.2 RADIATED EMISSION 4
A.2.1 Emissions within Restricted Frequency Bands 4
A.2.2 Emissions outside the frequency band: 13
A.2.3 Emissions in Non-restricted Frequency Bands: 14
A.3 20dB BANDWIDTH 15
A.3.1 20dB Bandwidth Result 15
A.3.2 Measurement Plots 16
A.4 CARRIER FREQUENCY SEPARATION 17
A.5 TIME OF OCCUPANCY 19
A.5.1 Time of Occupancy 19
A.6 NUMBER OF HOPPING CHANNELS 29
A.7 MAXIMUM PEAK OUTPUT POWER 30
A.7.1 Maximum Peak Output Power 30
A.7.2 Measurement Plots 31
A.8 EMISSION LIMITATIONS MEASUREMENT 32
A.8.1 Band Edge 32
A.8.2 Spurious Emission 33

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.1 CONDUCTED EMISSION

Test Date	2021/03/29	Temp./Hum.	24°C/74%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu



Site No. : No.8 Shielded Room
Instrument 1 : Receiver ESR3(774)
Instrument 2 : ENV432 (567)(A)|CE-08|ESH3-Z2 (354)
Limit : FCC PART 15C
Environment : 24°C / 74%
EUT Model : ITS-GW01-A10-C002
Test Mode : Operating

Data No. : 2
Phase : NEUTRAL
Engineer : Chucky Chiu
Test Rating : 120Vac/60Hz

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.172	10.20	0.03	9.85	1.81	21.89	54.86	32.97	Average
2	0.172	10.20	0.03	9.85	16.84	36.92	64.86	27.94	QP
3	0.216	10.20	0.03	9.85	13.11	33.19	52.96	19.77	Average
4	0.216	10.20	0.03	9.85	27.20	47.28	62.96	15.68	QP
5	0.327	10.20	0.03	9.85	6.28	26.36	49.53	23.17	Average
6	0.327	10.20	0.03	9.85	19.56	39.64	59.53	19.89	QP
7	0.440	10.20	0.03	9.85	0.43	20.51	47.07	26.56	Average
8	0.440	10.20	0.03	9.85	11.70	31.78	57.07	25.29	QP
9	0.567	10.20	0.03	9.85	-2.48	17.60	46.00	28.40	Average
10	0.567	10.20	0.03	9.85	6.68	26.76	56.00	29.24	QP
11	8.822	10.46	0.13	9.88	4.15	24.62	50.00	25.38	Average
12	8.822	10.46	0.13	9.88	9.84	30.31	60.00	29.69	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2021/03/29	Temp./Hum.	24°C/74%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Chucky Chiu



Site No. : No.8 Shielded Room
Instrument 1 : Receiver ESR3(774)
Instrument 2 : EMV432 (567)(A)|CE-08|ESH3-Z2 (354)
Limit : FCC PART 15C
Environment : 24°C / 74%
EUT Model : ITS-GW01-A10-C002
Test Mode : Operating

Data No. : 1
Phase : LINE
Engineer : Chucky Chiu
Test Rating : 120Vac/60Hz

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.178	10.20	0.03	9.85	7.19	27.27	54.59	27.32	Average
2	0.178	10.20	0.03	9.85	18.78	38.86	64.59	25.73	QP
3	0.215	10.20	0.03	9.85	10.73	30.81	53.01	22.20	Average
4	0.215	10.20	0.03	9.85	27.23	47.31	63.01	15.70	QP
5	0.308	10.20	0.03	9.85	7.35	27.43	50.02	22.59	Average
6	0.308	10.20	0.03	9.85	21.44	41.52	60.02	18.50	QP
7	0.431	10.20	0.03	9.85	3.70	23.78	47.24	23.46	Average
8	0.431	10.20	0.03	9.85	13.19	33.27	57.24	23.97	QP
9	0.552	10.20	0.03	9.85	6.36	26.44	46.00	19.56	Average
10	0.552	10.20	0.03	9.85	12.11	32.19	56.00	23.81	QP
11	9.451	10.38	0.14	9.88	7.12	27.52	50.00	22.48	Average
12	9.451	10.38	0.14	9.88	14.29	34.69	60.00	25.31	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.2 RADIATED EMISSION

Test Date	2021/03/26 ~ 29	Temp./Hum.	21 ~ 25℃/69 ~ 70%
Test Voltage	AC 120V 60Hz (Via AC Adapter)	Tested By	Sean Wang

A.2.1 Emissions within Restricted Frequency Bands

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1GHz

Mode	GFSK	Frequency	TX 2402MHz

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
31.940	18.03	1.26	28.14	33.55	24.70	40.00	15.30	Peak
150.280	10.56	3.06	27.83	43.81	29.60	43.50	13.90	Peak
500.450	17.28	6.93	29.21	40.05	35.05	46.00	10.95	Peak
700.270	18.84	7.62	29.33	41.70	38.83	46.00	7.17	Peak
900.090	20.39	8.72	28.86	40.48	40.73	46.00	5.27	Peak
965.080	21.01	9.01	28.66	35.29	36.65	54.00	17.35	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
37.760	14.73	1.43	28.13	47.52	35.55	40.00	4.45	Peak
150.280	10.56	3.06	27.83	45.31	31.10	43.50	12.40	Peak
500.450	17.28	6.93	29.21	42.33	37.33	46.00	8.67	Peak
700.270	18.84	7.62	29.33	40.32	37.45	46.00	8.55	Peak
900.090	20.39	8.72	28.86	37.41	37.66	46.00	8.34	Peak
996.120	21.29	9.14	28.59	35.02	36.86	54.00	17.14	Peak

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.1.3 Frequency Above 1 GHz to 10th harmonics

Band Edge:

Mode	GFSK	Frequency	TX 2402MHz



Antenna at Horizontal Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.400	32.44	7.95	34.53	48.75	54.61	74.00	19.39	Peak
	2390.000	32.44	7.95	34.54	46.04	51.89	74.00	22.11	Peak
@	2401.800	32.50	7.95	34.54	86.55	92.46	---	---	Peak



Antenna at Horizontal Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.400	32.44	7.95	34.53	35.04	40.90	54.00	13.10	Average
	2390.000	32.44	7.95	34.54	34.73	40.58	54.00	13.42	Average
@	2402.000	32.50	7.95	34.54	86.38	92.29	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2402MHz



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.800	32.44	7.95	34.53	47.38	53.24	74.00	20.76	Peak
	2390.000	32.44	7.95	34.54	45.35	51.20	74.00	22.80	Peak
@	2402.100	32.50	7.95	34.54	85.91	91.82	---	---	Peak



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.800	32.44	7.95	34.53	43.37	49.23	54.00	4.77	Average
	2390.000	32.44	7.95	34.54	34.78	40.63	54.00	13.37	Average
@	2402.000	32.50	7.95	34.54	85.64	91.55	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2480MHz



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	93.33	98.88	---	---	Peak
2483.500	32.14	7.99	34.55	46.58	52.16	74.00	21.84	Peak
2702.500	32.40	8.10	34.60	47.23	53.13	74.00	20.87	Peak



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	93.07	98.62	---	---	Average
2483.500	32.14	7.99	34.55	35.52	41.10	54.00	12.90	Average
2672.000	32.29	8.08	34.60	35.95	41.72	54.00	12.28	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2480MHz



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	94.89	100.44	---	---	Peak
2483.500	32.14	7.99	34.55	47.85	53.43	74.00	20.57	Peak
2484.000	32.14	7.99	34.55	47.88	53.46	74.00	20.54	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	94.63	100.18	---	---	Average
2483.500	32.14	7.99	34.55	36.27	41.85	54.00	12.15	Average
2554.500	32.30	8.03	34.57	35.81	41.57	54.00	12.43	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2402MHz



Antenna at Horizontal Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2349.100	32.24	7.93	34.53	48.73	54.37	74.00	19.63	Peak
	2390.000	32.44	7.95	34.54	46.16	52.01	74.00	21.99	Peak
@	2401.900	32.50	7.95	34.54	81.03	86.94	---	---	Peak



Antenna at Horizontal Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.400	32.44	7.95	34.53	35.58	41.44	54.00	12.56	Average
	2390.000	32.44	7.95	34.54	35.15	41.00	54.00	13.00	Average
@	2402.100	32.50	7.95	34.54	77.54	83.45	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2402MHz



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2355.800	32.30	7.93	34.53	47.54	53.24	74.00	20.76	Peak
	2390.000	32.44	7.95	34.54	45.61	51.46	74.00	22.54	Peak
@	2402.100	32.50	7.95	34.54	79.95	85.86	---	---	Peak



Antenna at Vertical Polarization

	Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
	2388.800	32.44	7.95	34.53	38.45	44.31	54.00	9.69	Average
	2390.000	32.44	7.95	34.54	34.84	40.69	54.00	13.31	Average
@	2402.100	32.50	7.95	34.54	78.00	83.91	---	---	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2480MHz



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	86.56	92.11	---	---	Peak
2483.500	32.14	7.99	34.55	45.35	50.93	74.00	23.07	Peak
2714.000	32.40	8.10	34.60	48.52	54.42	74.00	19.58	Peak



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	83.49	89.04	---	---	Average
2483.500	32.14	7.99	34.55	35.26	40.84	54.00	13.16	Average
2925.500	32.90	8.19	34.65	35.48	41.92	54.00	12.08	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2480MHz



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	88.65	94.20	---	---	Peak
2483.500	32.14	7.99	34.55	46.31	51.89	74.00	22.11	Peak
2922.500	32.90	8.19	34.64	47.61	54.06	74.00	19.94	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2480.000	32.11	7.99	34.55	85.31	90.86	---	---	Average
2483.500	32.14	7.99	34.55	34.90	40.48	54.00	13.52	Average
2779.500	32.53	8.13	34.62	35.88	41.92	54.00	12.08	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.2 Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Mode	GFSK	Frequency	TX 2402MHz

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4804.000	34.10	10.49	34.44	31.84	41.99	54.00	12.01	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4804.000	34.10	10.49	34.44	31.57	41.72	54.00	12.28	Peak

Mode	GFSK	Frequency	TX 2441MHz

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4882.000	34.03	10.54	34.43	31.91	42.05	54.00	11.95	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4882.000	34.03	10.54	34.43	31.63	41.77	54.00	12.23	Peak

Mode	GFSK	Frequency	TX 2480MHz

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4960.000	34.10	10.60	34.41	31.47	41.76	54.00	12.24	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Gain (dB)	Read Level (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
4960.000	34.10	10.60	34.41	32.23	42.52	54.00	11.48	Peak

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.3 Emissions in Non-restricted Frequency Bands:

All emission levels below the FCC 15.209(a)/RSS-Gen Section 8.9 table 4 general radiated emissions limits is not required.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.3 20dB BANDWIDTH

Test Date	2021/03/23	Temp./Hum.	17℃/63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.3.1 20dB Bandwidth Result

Mode	Centre Frequency (MHz)	20dB Bandwidth (MHz)	99%Occupied Bandwidth (MHz) (Reference only)	2/3 (20dB Bandwidth)
GFSK	2402	0.9211	0.90956	0.614
	2441	0.9219	0.91191	0.615
	2480	0.9215	0.90985	0.614
8-DPSK	2402	1.275	1.2333	0.850
	2441	1.274	1.2354	0.849
	2480	1.289	1.2349	0.859

Remark: The maximum two-thirds of the 20dB bandwidth is the limit for carrier frequency separation presented.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.3.2 Measurement Plots

GFSK	8-DPSK
	
	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.4 CARRIER FREQUENCY SEPARATION

Test Date	2021/03/23	Temp./Hum.	17℃/63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

GFSK	
2402MHz	2441MHz adjacent channel of left carrier frequency
	
2441MHz adjacent channel of right carrier frequency	2480MHz
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

8-DPSK	
2402MHz	2441MHz adjacent channel of left carrier frequency
	
2441MHz adjacent channel of right carrier frequency	2480MHz
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.5 TIME OF OCCUPANCY

Test Date	2021/03/23	Temp./Hum.	17℃/63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.5.1 Time of Occupancy

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2402	DH1	10	0.380	120.080	<400
		DH3	5	1.640	259.120	<400
		DH5	2	2.890	182.648	<400

Observation Period:
79 channels* **0.4** seconds= **31.6** seconds

DH1 Mode
For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.380** ms= **120.080** ms (<400ms)

DH3 Mode
For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.640** ms= **259.120** ms (<400ms)

DH5 Mode
For each second of **2** transmission appearance,the longest time of occupancy is
2 transmission* **31.6** seconds* **2.890** ms= **182.648** ms (<400ms)

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2440	DH1	10	0.380	120.080	<400
		DH3	5	1.640	259.120	<400
		DH5	2	2.880	182.016	<400

Observation Period:
79 channels* **0.4** seconds= **31.6** seconds

DH1 Mode
For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.380** ms= **120.080** ms (<400ms)

DH3 Mode
For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.640** ms= **259.120** ms (<400ms)

DH5 Mode
For each second of **2** transmission appearance,the longest time of occupancy is
2 transmission* **31.6** seconds* **2.880** ms= **182.016** ms (<400ms)

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2480	DH1	10	0.380	120.080	<400
		DH3	5	1.630	257.540	<400
		DH5	2	2.890	182.648	<400

Observation Period:

79 channels* **0.4** seconds= **31.6** seconds

DH1 Mode

For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.380** ms= **120.080** ms (<400ms)

DH3 Mode

For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.630** ms= **257.540** ms (<400ms)

DH5 Mode

For each second of **2** transmission appearance,the longest time of occupancy is
2 transmission* **31.6** seconds* **2.890** ms= **182.648** ms (<400ms)

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

- Measurement Plots

GFSK	
2402MHz	
DH1	
	
DH3	
	
DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

GFSK	
2441MHz	
DH1	
	
DH3	
	
DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

GFSK	
2480MHz	
DH1	
	
DH3	
	
DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2402	3DH1	10	0.390	123.240	<400
		3DH3	5	1.640	259.120	<400
		3DH5	3	2.900	274.920	<400

Observation Period:

79 channels* **0.4** seconds= **31.6** seconds

3DH1 Mode

For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.390** ms= **123.240** ms (<400ms)

3DH3 Mode

For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.640** ms= **259.120** ms (<400ms)

3DH5 Mode

For each second of **3** transmission appearance,the longest time of occupancy is
3 transmission* **31.6** seconds* **2.900** ms= **274.920** ms (<400ms)

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2441	3DH1	10	0.390	123.240	<400
		3DH3	5	1.640	259.120	<400
		3DH5	3	2.890	273.972	<400

Observation Period:

79 channels* **0.4** seconds= **31.6** seconds

3DH1 Mode

For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.390** ms= **123.240** ms (<400ms)

3DH3 Mode

For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.640** ms= **259.120** ms (<400ms)

3DH5 Mode

For each second of **3** transmission appearance,the longest time of occupancy is
3 transmission* **31.6** seconds* **2.890** ms= **273.972** ms (<400ms)

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2480	3DH1	10	0.390	123.240	<400
		3DH3	5	1.640	259.120	<400
		3DH5	3	2.890	273.972	<400

Observation Period:

79 channels* **0.4** seconds= **31.6** seconds

3DH1 Mode

For each second of **10** transmission appearance,the longest time of occupancy is
10 transmission* **31.6** seconds* **0.390** ms= **123.240** ms (<400ms)

3DH3 Mode

For each second of **5** transmission appearance,the longest time of occupancy is
5 transmission* **31.6** seconds* **1.640** ms= **259.120** ms (<400ms)

3DH5 Mode

For each second of **3** transmission appearance,the longest time of occupancy is
3 transmission* **31.6** seconds* **2.890** ms= **273.972** ms (<400ms)

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

- Measurement Plots

8-DPSK	
2402MHz	
3DH1	
	
3DH3	
	
3DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

8-DPSK	
2441MHz	
3DH1	
	
3DH3	
	
3DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

8-DPSK	
2480MHz	
3DH1	
	
3DH3	
	
3DH5	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.6 NUMBER OF HOPPING CHANNELS

Test Date	2021/03/23	Temp./Hum.	17℃/63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

Mode: GFSK	Mode: 8-DPSK
	
The number hopping channel is 79.	The number hopping channel is 79.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan
Tel: +886 2 26099301
Fax: +886 2 26099303

A.7 MAXIMUM PEAK OUTPUT POWER

Test Date	2021/03/22 ~ 23	Temp./Hum.	17 ~ 18℃/59 ~ 63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.7.1 Maximum Peak Output Power

Mode	Centre Frequency (MHz)	Maximum Peak Output Power		Limit
		dBm	W	
GFSK	2402	5.68	0.004	21dBm (0.125W)
	2441	4.58	0.003	
	2480	3.58	0.002	
8-DPSK	2402	0.05	0.001	
	2441	-1.20	0.001	
	2480	-0.47	0.001	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.7.2 Measurement Plots

GFSK	8-DPSK
	
	
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.8 EMISSION LIMITATIONS MEASUREMENT

Test Date	2021/03/22 ~ 23	Temp./Hum.	17 ~ 18℃/59 ~ 63%
Cable Loss	1.67dB	Tested By	Sean Wang
Test Voltage	AC 120V 60Hz (Via AC Adapter)		

A.8.1 Band Edge

GFSK	
Single Channel	
Low channel	High channel
	

8-DPSK	
Single Channel	
Low channel	High channel
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.8.2 Spurious Emission

GFSK	
2402MHz	2441MHz
30MHz –8GHz	30MHz –8GHz
	
8GHz –15GHz	8GHz –15GHz
	
15GHz – 25GHz	15GHz – 25GHz
	

Note: All results have been included cable loss.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

GFSK	8-DPSK
2480MHz	2402MHz
30MHz –8GHz	30MHz –8GHz
	
8GHz –15GHz	8GHz –15GHz
	
15GHz – 25GHz	15GHz – 25GHz
	

Note: All results have been included cable loss.

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

8-DPSK	
2441MHz	2480MHz
30MHz –8GHz	30MHz –8GHz
	
8GHz –15GHz	8GHz –15GHz
	
15GHz – 25GHz	15GHz – 25GHz
	

This test report may be reproduced in full only. The document may only be updated by Audix Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

Audix Technology Corp.
No. 491, Zhongfu Rd., Linkou Dist.,
New Taipei City244,Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX B

TEST PHOTOGRAPHS

(Model:(1)ITS-GW01-A10-C001 (2)ITS-GW01-A10-C002)

This test report may be reproduced in full only. The documentmay only be updated by Audix TechnologyCorp. personnel. AnychangeswillbenotedintheDocumentHistorysectionofthereport.