




FCC Part 15.247

TEST REPORT

For

AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist, New Taipei City, 231, Taiwan, R.O.C.

Report Type	Original Report
FCC Identity:	FCC ID: OHBRICO3399
Brand Name	 an ASUS assoc. co.
Product Name	RISC Single Board Computer
Model Name	RICO-3399
Series Model Name:	RICO-3399-xxx-xxxx (x-Where x may be any combination of alphanumeric characters or "-" or blank.)
Report Number	RLK201110001-00C
Report Date	2021/04/22
Reviewed By	Zeus Chen 
Prepared By: Bay Area Compliance Laboratories Corp.(Linkou Laboratory) No. 6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.) Tel: +886 (3)3961072; Fax: +886 (3) 3961027 www.bacl.com.tw	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

Revision History

Revision	Report Number	Issue Date	Description
1.0	RLK201110001-00C	2021/04/22	Original Report

TABLE OF CONTENTS

1	GENERAL INFORMATION	5
1.1	PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2	OPERATION CONDITION OF EUT	5
1.3	OBJECTIVE AND TEST METHODOLOGY	6
1.4	MEASUREMENT UNCERTAINTY	6
1.5	ENVIRONMENTAL CONDITIONS AND TEST DATE	6
1.6	TEST FACILITY	6
2	SYSTEM TEST CONFIGURATION.....	7
2.1	DESCRIPTION OF TEST CONFIGURATION	7
2.2	SUPPORT EQUIPMENT LIST AND DETAILS	7
2.3	BLOCK DIAGRAM OF TEST SETUP	8
3	SUMMARY OF TEST RESULTS	9
4	FCC§15.247(I), §1.1307, § 2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
4.1	APPLICABLE STANDARD.....	10
4.2	RF EXPOSURE EVALUATION RESULT	10
5	FCC §15.203 – ANTENNA REQUIREMENTS.....	11
5.1	APPLICABLE STANDARD.....	11
5.2	ANTENNA LIST AND DETAILS	11
6	FCC §15.207 - AC LINE CONDUCTED EMISSIONS	12
6.1	APPLICABLE STANDARD.....	12
6.2	EUT SETUP AND TEST PROCEDURE	12
6.3	TEST EQUIPMENT LIST AND DETAILS.....	13
6.4	TEST DATA AND TEST PLOT.....	13
7	FCC §15.209, §15.205, §15.247(D) – SPURIOUS EMISSIONS	14
7.1	APPLICABLE STANDARD.....	14
7.2	EUT SETUP AND TEST PROCEDURE	16
7.3	TEST EQUIPMENT LIST AND DETAILS.....	17
7.4	RADIATED EMISSION TEST PLOT AND DATA	18
8	FCC §15.247(A)(1) – 20 DB EMISSION BANDWIDTH.....	25
8.1	APPLICABLE STANDARD.....	25
8.2	TEST PROCEDURE	25
8.3	TEST EQUIPMENT LIST AND DETAILS.....	25
8.4	TEST RESULTS	26
9	FCC §15.247(A)(1) – CHANNEL SEPARATION TEST	28
9.1	APPLICABLE STANDARD.....	28
9.2	TEST PROCEDURE	28
9.3	TEST EQUIPMENT LIST AND DETAILS.....	28
9.4	TEST RESULTS	29
10	FCC §15.247(A)(1)(III) – TIME OF OCCUPANCY (DWEELL TIME)	31
10.1	APPLICABLE STANDARD.....	31
10.2	TEST PROCEDURE	31
10.3	TEST EQUIPMENT LIST AND DETAILS.....	32
10.4	TEST RESULTS	32
11	FCC §15.247(A)(1)(III) –QUANTITY OF HOPPING CHANNEL TEST	34
11.1	APPLICABLE STANDARD.....	34
11.2	TEST PROCEDURE	34
11.3	TEST EQUIPMENT LIST AND DETAILS.....	34
11.4	TEST RESULTS	35
12	FCC §15.247(B)(1) – MAXIMUM OUTPUT POWER.....	36
12.1	APPLICABLE STANDARD.....	36

12.2	TEST PROCEDURE	36
12.3	TEST EQUIPMENT LIST AND DETAILS.....	36
12.4	TEST RESULTS	37
13	FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	38
13.1	APPLICABLE STANDARD.....	38
13.2	TEST PROCEDURE	38
13.3	TEST EQUIPMENT LIST AND DETAILS.....	38
13.4	TEST RESULTS	39

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Application	AAEON Technology Inc. 5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist, New Taipei City, 231, Taiwan, R.O.C.
Manufacturer	AAEON Technology Inc. 5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist, New Taipei City, 231, Taiwan, R.O.C.
Brand Name	
Product (Equipment)	RISC Single Board Computer
Model Name	RICO-3399
Serial Model	RICO-3399-xxx-xxxx (x-Where x may be any combination of alphanumeric characters or "-" or blank.)
Model Discrepancy	Marketing purpose
Frequency Range	2402 - 2480 MHz
Number of Channels	79 Channels
Output Power	BR-1Mbps: 4.09 dBm (0.0026W) EDR-2Mbps: 1.24 dBm (0.0013W) EDR-3Mbps: 1.47 dBm (0.0014W)
Modulation Type	BR-1Mbps: GFSK EDR-2Mbps: $\pi/4$ -DQPSK EDR-3Mbps: 8DPSK
Related Submittal(s)/Grant(s)	FCC Part 15.247 DTS with FCC ID: OHBRICO3399
Received Date	Dec. 30, 2020
Date of Test	Jan. 27, 2021 - Mar. 25, 2021

Note: All measurement and test data in this report was gathered from production sample serial number: 201110001. Assigned by Bay Area Compliance Laboratories Corp. (Linkou Laboratory)

1.2 Operation Condition of EUT

Power Operation (Voltage Range)	☐ AC 120V/60Hz ☐ Adapter ☐ By Power Cord
	☒ DC Type ☐ DC Power Supply ☐ Battery ☐ External from USB Cable ☒ External DC Adapter (Not For Sale)
	☒ Host System

1.3 Objective and Test Methodology

The Objective of this Test Report was to document the compliance of the AAEON Technology Inc. Appliance (Model(s): RICO-3399, RICO-3399-xxx-xxxx (x-Where x may be any combination of alphanumeric characters or "-" or blank.)) to the requirements of the following Standards:

- Part 2, Subpart J, Part 15, Subparts A and C, section 15.247 of the Federal Communication Commission's rules.
- ANSI C63.10-2013 of the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.4 Measurement Uncertainty

Parameter	Expanded Measurement uncertainty
RF output power	± 1.488 dB
Occupied Channel Bandwidth	± 453.927 Hz
RF Conducted Emission test	± 2.77 dB
AC Power Line Conducted Emission	± 2.66 dB
Radiated Below 1G	± 3.78 dB
Radiated Above 1G	± 4.29 dB

The test results with statement of conformity, the decision rules are based on the specifications and standards. The test results will not take the measurement uncertainty into account.

1.5 Environmental Conditions and Test Date

Test Site	Test Date	Temperature (°C)	Relative Humidity (%)	Test Engineer
Conduction (Con-01)	Jan. 27, 2021 – Mar. 16, 2021	23.4-25.5	54-55	Brian Chang
Radiated (966A)	Feb. 08, 2021 – Mar. 25, 2021	16.2-17.9	61-68	Leo Cheng
Conducted (TH-02)	Feb. 17, 2021 – Mar. 17, 2021	23.2	55-57	Brian Chang

1.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Linkou Laboratory) to collect test data is located on

☒ No.6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.).

Bay Area Compliance Laboratories Corp. (Linkou Laboratory) Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3546) by Mutual Recognition Agreement (MRA). The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database. The FCC Registration No.: 0027578244. Designation No.: TW3546. The Test Firm Registration No.: 181430.

2 System Test Configuration

2.1 Description of Test Configuration

The system was configured for testing in testing mode which was provided by manufacturer.

No special accessory, No modification was made to the EUT and No special equipment used during test.

For BT (BR/EDR), there are totally 79 channels.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441
1	2403	--	--
2	2404	--	--
3	2405	76	2478
--	--	77	2479
38	2440	78	2480

For BR/EDR: Channel 0, 39 and 78 were tested.

The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the peak power across all data rates bandwidths, and modulations.


Radiated below 1G were tested worst output power.

Worst Case of Power Setting				
EUT Exercise Software		Ampak RFTTestTool		
Configuration	N _{TX}	Low CH	Mid CH	High CH
BR-1Mbps mode	1	Default	Default	Default
EDR-2Mbps mode	1	Default	Default	Default
EDR-3Mbps mode	1	Default	Default	Default

2.2 Support Equipment List and Details

No.	Description	Manufacturer	Model Number
A	Notebook	DELL	E6410
B	Monitor	DELL	U2412M
C	Keyboard	ASUS	AW211
D	Mouse	ASUS	MOBTU0A
E	Modem	iEager	TY5600

2.3 Block Diagram of Test Setup



3 Summary of Test Results

FCC Rules	Description of Test	Result
§15.247(i), §1.1310, §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance

4 FCC§15.247(i), §1.1307, § 2.1091 – Maximum Permissible Exposure (MPE)

4.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary: Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with: $\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$

4.2 RF Exposure Evaluation Result

MPE Evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi 2.4G	2412-2462	2.38	1.7298	28.00	630.9573	20	0.2172	1.0
BLE-1Mbps	2402-2480	2.38	1.7298	4.00	2.5119	20	0.0009	1.0
BR/EDR	2402-2480	2.38	1.7298	5.00	3.1623	20	0.0011	1.0

Note: Wi-Fi and BT can't simultaneously.

Result: MPE evaluation of transmission meet the requirement of standard.

5 FCC §15.203 – Antenna Requirements

5.1 Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna does not exceed 6dBi

5.2 Antenna List and Details

Brand	Model	Antenna Type	Antenna Gain	Result
ARiSTOTLE	RFA-02-C2M2-U-M70	Dipole Antenna	2.38 dBi	Compliance

Note: The EUT has an external dedicated antennas arrangement and the connector type is RP-SMA Male, fulfill the requirement of this section.

6 FCC §15.207 - AC Line Conducted Emissions

6.1 Applicable Standard


According to FCC §15.207,

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 2}
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency. Note 2: A linear average detector is required

6.2 EUT Setup and Test Procedure



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits. The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations

Frequency Range	Receiver RBW
150 kHz - 30 MHz	9 kHz


During the conducted emission test, the adapter was connected to the outlet of the LISN. Maximizing procedure was performed on the six (6) highest emissions of the EUT. All data was recorded in the Quasi-peak and average detection mode.

6.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
AC Line Conduction Room (CON-01)					
Two-Line V-Network	Rohde & Schwarz	ENV216	100010	2020/09/14	2021/09/13
Pulse Limiter	SCHWARZBECK	VSTD 9561-F	00432	2020/09/11	2021/09/10
ESR EMI Test Receiver	Rohde & Schwarz	ESR3	102430	2020/05/07	2021/05/06
RF Cable	EMCI	EMCCFD300-BM-BM-8000	180526	2020/08/18	2021/08/17
Software	Audix	e3 v9	E3LK-03	N.C.R	N.C.R

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

6.4 Test Data and Test Plot



Note:

Level = Read Level + Factor

Over Limit (Margin) = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

7 FCC §15.209, §15.205, §15.247(d) – Spurious Emissions

7.1 Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function.

Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1MHz.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	13.36-13.41	399.9-410	4.5-5.15
0.495-0.505	16.42-16.423	608-614	5.35-5.46
2.1735-2.1905	16.69475-16.69525	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6


As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.2 EUT Setup and Test Procedure



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.209 and FCC 15.247 Limits.

The system was investigated from 30 MHz to 26.5 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10.

Frequency Range	RBW	VBW	Duty cycle	Measurement Detector method
30-1000 MHz	120 kHz	/	-	QP
Above 1 GHz	1 MHz	3 MHz	-	PK
	1 MHz	10 Hz	>98%	PK
	1 MHz	1/T	<98%	PK

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations. All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.


7.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Radiation 3M Room (966B)					
Active Loop	EMCO	6502	0001-3322	2020/03/16	2021/03/15
Active Loop	EMCO	6502	0001-3322	2021/03/16	2022/03/15
Bilog Antenna/6 dB Attenuator	SUNOL SCIENCES & EMEC /EMCI	JB3/N-6-06	A111513/AT-N0668	2020/03/19	2021/03/18
Bilog Antenna/6 dB Attenuator	SUNOL SCIENCES & EMEC /EMCI	JB3/N-6-06	A111513/AT-N0668	2021/03/30	2022/03/29
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Horn Antenna	ETS-Lindgren	3115	00109141	2020/07/15	2021/07/14
Horn Antenna	ETS-Lindgren	3160-09	00123852	2020/07/07	2021/07/06
Preamplifier	A.H. Systems	PAM-1840VH	174	2020/03/25	2021/03/24
Preamplifier	A.H. Systems	PAM-1840VH	174	2021/03/22	2022/03/21
Preamplifier	A.H. Systems	PAM-0118	478	2020/05/05	2021/05/04
Microflex Cable (1m)	EMCI	EMC102-KM-KM-1000	180524	2020/08/06	2021/08/05
Microflex Cable (2m)	EMCI	EMC106-SM-SM-2000	180516	2020/08/06	2021/08/05
Microflex Cable (8m)	UTIFLEX	UFA210A-1-3149-300300	MFR 64639 232490-002	2020/08/06	2021/08/05
Turn Table	Chaintek	T-200-S-1	003501	N.C.R	N.C.R
Antenna Tower	Chaintek	MBD-400-1	003504	N.C.R	N.C.R
Controller	Chaintek	3000-1	003507	N.C.R	N.C.R
Software	Audix	e3 v9	E3LK-01	N.C.R	N.C.R
Conducted Room (TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

7.4 Radiated Emission Test Plot and Data

Below 1G (30 MHz-1 GHz) (Pre-scan with three orthogonal axis, and worse case as Z axis)



Note:

Level = Read Level + Factor, Over Limit = Level – Limit,

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain


Spurious emissions more than 20 dB below the limit were not reported

Above 1G (1 GHz-26.5 GHz)

BR-1Mbps Low CH Horizontal							BR-1Mbps Low CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2353.300	38.44	54.00	-15.56	43.98	-5.54	Average	2372.800	38.55	54.00	-15.45	44.04	-5.49	Average
2353.300	53.42	74.00	-20.58	58.96	-5.54	Peak	2372.800	53.31	74.00	-20.69	58.80	-5.49	Peak
2401.900	79.41			84.84	-5.43	Average	2402.200	88.98			94.41	-5.43	Average
2401.900	90.78			96.21	-5.43	Peak	2402.200	102.74			108.17	-5.43	Peak
4804.000	31.75	54.00	-22.25	30.21	1.54	Average	4804.000	33.07	54.00	-20.93	31.53	1.54	Average
4804.000	44.74	74.00	-29.26	43.20	1.54	Peak	4804.000	46.15	74.00	-27.85	44.61	1.54	Peak
7206.000	36.59	54.00	-17.41	28.64	7.95	Average	7206.000	39.27	54.00	-14.73	31.32	7.95	Average
7206.000	49.79	74.00	-24.21	41.84	7.95	Peak	7206.000	52.60	74.00	-21.40	44.65	7.95	Peak
BR-1Mbps Middle CH Horizontal							BR-1Mbps Middle CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2329.602	38.41	54.00	-15.59	43.97	-5.56	Average	2367.596	38.51	54.00	-15.49	44.02	-5.51	Average
2329.602	53.27	74.00	-20.73	58.83	-5.56	Peak	2367.596	52.47	74.00	-21.53	57.98	-5.51	Peak
2440.922	78.38			83.76	-5.38	Average	2441.164	88.35			93.73	-5.38	Average
2440.922	89.47			94.85	-5.38	Peak	2441.164	101.91			107.29	-5.38	Peak
2513.280	38.95	54.00	-15.05	44.27	-5.32	Average	2498.518	39.01	54.00	-14.99	44.37	-5.36	Average
2513.280	53.62	74.00	-20.38	58.94	-5.32	Peak	2498.518	53.79	74.00	-20.21	59.15	-5.36	Peak
4882.000	32.05	54.00	-21.95	30.40	1.65	Average	4882.000	33.98	54.00	-20.02	32.33	1.65	Average
4882.000	45.33	74.00	-28.67	43.68	1.65	Peak	4882.000	45.94	74.00	-28.06	44.29	1.65	Peak
7323.000	35.31	54.00	-18.69	27.94	7.37	Average	7323.000	37.52	54.00	-16.48	30.15	7.37	Average
7323.000	49.49	74.00	-24.51	42.12	7.37	Peak	7323.000	50.41	74.00	-23.59	43.04	7.37	Peak
BR-1Mbps High CH Horizontal							BR-1Mbps High CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2480.086	71.84			77.21	-5.37	Average	2480.168	87.94			93.31	-5.37	Average
2480.086	89.00			94.37	-5.37	Peak	2480.168	101.41			106.78	-5.37	Peak
2546.588	39.24	54.00	-14.76	44.43	-5.19	Average	2543.390	39.30	54.00	-14.70	44.51	-5.21	Average
2546.588	54.37	74.00	-19.63	59.56	-5.19	Peak	2543.390	53.99	74.00	-20.01	59.20	-5.21	Peak
4960.000	34.37	54.00	-19.63	32.60	1.77	Average	4960.000	39.16	54.00	-14.84	37.39	1.77	Average
4960.000	46.49	74.00	-27.51	44.72	1.77	Peak	4960.000	47.98	74.00	-26.02	46.21	1.77	Peak
7440.000	35.65	54.00	-18.35	27.99	7.66	Average	7440.000	37.28	54.00	-16.72	29.62	7.66	Average
7440.000	48.69	74.00	-25.31	41.03	7.66	Peak	7440.000	50.06	74.00	-23.94	42.40	7.66	Peak

EDR-2Mbps Low CH Horizontal							EDR-2Mbps Low CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2385.800	38.50	54.00	-15.50	43.96	-5.46	Average	2312.200	38.53	54.00	-15.47	44.10	-5.57	Average
2385.800	53.27	74.00	-20.73	58.73	-5.46	Peak	2312.200	53.56	74.00	-20.44	59.13	-5.57	Peak
2401.900	73.63			79.06	-5.43	Average	2402.200	83.51			88.94	-5.43	Average
2401.900	86.76			92.19	-5.43	Peak	2402.200	99.07			104.50	-5.43	Peak
4804.000	31.30	54.00	-22.70	29.76	1.54	Average	4804.000	31.28	54.00	-22.72	29.74	1.54	Average
4804.000	44.95	74.00	-29.05	43.41	1.54	Peak	4804.000	45.18	74.00	-28.82	43.64	1.54	Peak
7206.000	35.87	54.00	-18.13	27.92	7.95	Average	7206.000	35.83	54.00	-18.17	27.88	7.95	Average
7206.000	49.03	74.00	-24.97	41.08	7.95	Peak	7206.000	49.87	74.00	-24.13	41.92	7.95	Peak
EDR-2Mbps Middle CH Horizontal							EDR-2Mbps Middle CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2320.890	38.44	54.00	-15.56	44.00	-5.56	Average	2342.186	39.35	54.00	-14.65	44.90	-5.55	Average
2320.890	53.15	74.00	-20.85	58.71	-5.56	Peak	2342.186	52.98	74.00	-21.02	58.53	-5.55	Peak
2441.164	73.39			78.77	-5.38	Average	2440.922	82.53			87.91	-5.38	Average
2441.164	86.30			91.68	-5.38	Peak	2440.922	97.69			103.07	-5.38	Peak
2515.942	39.07	54.00	-14.93	44.37	-5.30	Average	2486.176	39.00	54.00	-15.00	44.36	-5.36	Average
2515.942	53.93	74.00	-20.07	59.23	-5.30	Peak	2486.176	53.43	74.00	-20.57	58.79	-5.36	Peak
4882.000	31.50	54.00	-22.50	29.85	1.65	Average	4882.000	31.65	54.00	-22.35	30.00	1.65	Average
4882.000	46.70	74.00	-27.30	45.05	1.65	Peak	4882.000	45.26	74.00	-28.74	43.61	1.65	Peak
7323.000	35.22	54.00	-18.78	27.85	7.37	Average	7323.000	35.25	54.00	-18.75	27.88	7.37	Average
7323.000	49.75	74.00	-24.25	42.38	7.37	Peak	7323.000	49.04	74.00	-24.96	41.67	7.37	Peak
EDR-2Mbps High CH Horizontal							EDR-2Mbps High CH Vertical						
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	
2479.758	72.57			77.94	-5.37	Average	2480.168	82.02			87.39	-5.37	Average
2479.758	85.31			90.68	-5.37	Peak	2480.168	97.12			102.49	-5.37	Peak
2532.894	39.22	54.00	-14.78	44.46	-5.24	Average	2517.478	39.12	54.00	-14.88	44.41	-5.29	Average
2532.894	54.10	74.00	-19.90	59.34	-5.24	Peak	2517.478	53.85	74.00	-20.15	59.14	-5.29	Peak
4960.000	31.68	54.00	-22.32	29.91	1.77	Average	4960.000	32.30	54.00	-21.70	30.53	1.77	Average
4960.000	44.72	74.00	-29.28	42.95	1.77	Peak	4960.000	45.42	74.00	-28.58	43.65	1.77	Peak
7440.000	35.80	54.00	-18.20	28.14	7.66	Average	7440.000	35.58	54.00	-18.42	27.92	7.66	Average
7440.000	49.56	74.00	-24.44	41.90	7.66	Peak	7440.000	49.64	74.00	-24.36	41.98	7.66	Peak

EDR-3Mbps Low CH Horizontal								EDR-3Mbps Low CH Vertical							
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark		Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		
2387.000	38.64	54.00	-15.36	44.10	-5.46	Average		2371.500	38.48	54.00	-15.52	43.97	-5.49	Average	
2387.000	53.90	74.00	-20.10	59.36	-5.46	Peak		2371.500	53.17	74.00	-20.83	58.66	-5.49	Peak	
2402.100	73.67			79.10	-5.43	Average		2402.000	83.04			88.47	-5.43	Average	
2402.100	87.00			92.43	-5.43	Peak		2402.000	98.80			104.23	-5.43	Peak	
4804.000	31.30	54.00	-22.70	29.76	1.54	Average		4804.000	31.29	54.00	-22.71	29.75	1.54	Average	
4804.000	45.70	74.00	-28.30	44.16	1.54	Peak		4804.000	44.55	74.00	-29.45	43.01	1.54	Peak	
7206.000	34.95	54.00	-19.05	27.00	7.95	Average		7206.000	35.99	54.00	-18.01	28.04	7.95	Average	
7206.000	48.90	74.00	-25.10	40.95	7.95	Peak		7206.000	49.06	74.00	-24.94	41.11	7.95	Peak	
EDR-3Mbps Middle CH Horizontal								EDR-3Mbps Middle CH Vertical							
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark		Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		
2360.820	38.58	54.00	-15.42	44.10	-5.52	Average		2353.802	38.43	54.00	-15.57	43.97	-5.54	Average	
2360.820	52.29	74.00	-21.71	57.81	-5.52	Peak		2353.802	52.40	74.00	-21.60	57.94	-5.54	Peak	
2440.922	72.95			78.33	-5.38	Average		2441.164	82.94			88.32	-5.38	Average	
2440.922	86.00			91.38	-5.38	Peak		2441.164	98.54			103.92	-5.38	Peak	
2496.582	39.04	54.00	-14.96	44.40	-5.36	Average		2491.742	39.02	54.00	-14.98	44.38	-5.36	Average	
2496.582	52.95	74.00	-21.05	58.31	-5.36	Peak		2491.742	52.97	74.00	-21.03	58.33	-5.36	Peak	
4882.000	31.42	54.00	-22.58	29.77	1.65	Average		4882.000	31.58	54.00	-22.42	29.93	1.65	Average	
4882.000	46.41	74.00	-27.59	44.76	1.65	Peak		4882.000	45.37	74.00	-28.63	43.72	1.65	Peak	
7323.000	35.14	54.00	-18.86	27.77	7.37	Average		7323.000	35.27	54.00	-18.73	27.90	7.37	Average	
7323.000	48.70	74.00	-25.30	41.33	7.37	Peak		7323.000	48.58	74.00	-25.42	41.21	7.37	Peak	
EDR-3Mbps High CH Horizontal								EDR-3Mbps High CH Horizontal							
Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark		Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		
2480.004	72.04			77.41	-5.37	Average		2480.004	81.94			87.31	-5.37	Average	
2480.004	84.89			90.26	-5.37	Peak		2480.004	97.34			102.71	-5.37	Peak	
2497.224	39.05	54.00	-14.95	44.41	-5.36	Average		2503.456	39.11	54.00	-14.89	44.46	-5.35	Average	
2497.224	53.39	74.00	-20.61	58.75	-5.36	Peak		2503.456	53.98	74.00	-20.02	59.33	-5.35	Peak	
4960.000	31.97	54.00	-22.03	30.20	1.77	Average		4960.000	33.18	54.00	-20.82	31.41	1.77	Average	
4960.000	45.85	74.00	-28.15	44.08	1.77	Peak		4960.000	45.88	74.00	-28.12	44.11	1.77	Peak	
7440.000	35.90	54.00	-18.10	28.24	7.66	Average		7440.000	36.08	54.00	-17.92	28.42	7.66	Average	
7440.000	49.50	74.00	-24.50	41.84	7.66	Peak		7440.000	50.73	74.00	-23.27	43.07	7.66	Peak	

Above 1G (1 GHz-26.5 GHz): The worst mode BR-1Mbps Low CH.

Note:

Level = Read Level + Factor, Over Limit = Level – Limit,


Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported


Conducted Spurious Emissions:

Configuration	Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
BR-1Mbps	Low	2402	48.90	≥ 20	Compliance
	Middle	2441	49.55	≥ 20	Compliance
	High	2480	47.89	≥ 20	Compliance
EDR-2Mbps	Low	2402	43.36	≥ 20	Compliance
	Middle	2441	42.58	≥ 20	Compliance
	High	2480	42.05	≥ 20	Compliance
EDR-3Mbps	Low	2402	43.43	≥ 20	Compliance
	Middle	2441	41.65	≥ 20	Compliance
	High	2480	39.88	≥ 20	Compliance


BR-1Mbps Low CH




BR-1Mbps Middle CH



BR-1Mbps High CH




EDR-2Mbps Low CH




Date: 17_MAR_2021 14:09:57

EDR-2Mbps Middle CH




Date: 17_MAR_2021 14:12:55

EDR-2Mbps High CH




Date: 17_MAR_2021 14:15:23

EDR-3Mbps Low CH




Date: 17_MAR_2021 15:13:01

EDR-3Mbps Middle CH



Date: 17_MAR_2021 15:17:21

EDR-3Mbps High CH



Date: 17_MAR_2021 15:18:57

8 FCC §15.247(a)(1) – 20 dB Emission Bandwidth

8.1 Applicable Standard

According to FCC §15.247(a) (1) the maximum 20 dB bandwidth of the hopping channel shall be presented.

8.2 Test Procedure

- (1) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- (2) Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- (3) Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- (4) Repeat above procedures until all frequencies measured were complete.

8.3 Test Equipment List and Details


Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

8.4 Test Results


Configuration	Channel	Frequency (MHz)	20 dB Bandwidth (MHz))
BR-1Mbps	Low	2402	1.03
	Middle	2441	1.04
	High	2480	1.04
EDR-2Mbps	Low	2402	1.36
	Middle	2441	1.36
	High	2480	1.36
EDR-3Mbps	Low	2402	1.33
	Middle	2441	1.33
	High	2480	1.33

BR-1Mbps Low CH




Date: 17_MAR_2021 12:14:22

BR-1Mbps Middle CH




Date: 17_MAR_2021 12:16:00

BR-1Mbps High CH




Date: 17_MAR_2021 12:19:05

EDR-2Mbps Low CH




Date: 17_MAR_2021 14:09:13

EDR-2Mbps Middle CH




Date: 17_MAR_2021 14:13:49

EDR-2Mbps High CH




Date: 17_MAR_2021 14:14:38

EDR-3Mbps Low CH




Date: 17_MAR_2021 15:15:17

EDR-3Mbps Middle CH



Date: 17_MAR_2021 15:16:51

EDR-3Mbps High CH



Date: 17_MAR_2021 15:18:13

9 FCC §15.247(a)(1) – Channel Separation Test

9.1 Applicable Standard

According to FCC §15.247(a) (1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

9.2 Test Procedure

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\approx$ 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel. Video (or Average) Bandwidth (VBW) $\geq$ RBW. Sweep = auto

Detector function = peak Trace = max hold

9.3 Test Equipment List and Details


Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).


9.4 Test Results

Configuration	Channel	Frequency (MHz)	20 dBc BW (MHz)	Channel Separation (MHz)	Limit (MHz)
BR-1Mbps	Low	2402	1.03	1.00	0.690
	Middle	2441	1.04	1.00	0.693
	High	2480	1.04	1.00	0.693
EDR-2Mbps	Low	2402	1.36	1.00	0.904
	Middle	2441	1.36	1.00	0.904
	High	2480	1.36	1.00	0.904
EDR-3Mbps	Low	2402	1.33	1.00	0.887
	Middle	2441	1.33	1.00	0.890
	High	2480	1.33	1.00	0.887


* Limit is >two-thirds of the 20 dB bandwidth




EDR-2Mbps Low CH




EDR-2Mbps Middle CH




EDR-2Mbps High CH




EDR-3Mbps Low CH



EDR-3Mbps Middle CH



EDR-3Mbps High CH



10 FCC §15.247(a)(1)(iii) – Time of Occupancy (Dwell Time)

10.1 Applicable Standard

According to FCC §15.247(a)(1)(iii),

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel

RBW $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel

Sweep = as necessary to capture the entire dwell time per hopping channel Detector function = peak

Trace = max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements.

Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer) x (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

10.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

10.4 Test Results


Modulation Mode	Pulse Time per Hop (ms)	Number of Pulse in [0.4 x N sec]	Dwell Time in [0.4 x N sec] (s)	Dwell Time Limits (s)
BR-1Mbps	2.99	107	0.319	0.4
EDR-2Mbps	2.99	107	0.319	0.4
EDR-3Mbps	2.99	107	0.319	0.4

Note1: Number of Pulse in [0.4 x N sec] = $1600/79/6 \times (0.4 \times 79)$.

Note2: Dwell Time in [0.4 x N sec] = $(\text{Pulse Time} \times \text{Number of Pulse in [0.4 x N sec]})/1000$.


Note3: Bluetooth ACL packets can be 1, 3, or 5 time slots. The DH1 packet can cover a single time slot. The DH3 packet can cover up to 3 time slots. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms.

DH5




Date: 17_MAR_2021 11:47:47

2-DH5



Date: 17_MAR_2021 11:51:11

3-DH5



Date: 17_MAR_2021 11:58:52

-

-

11 FCC §15.247(a)(1)(iii) –Quantity of hopping channel Test

11.1 Applicable Standard

According to FCC §15.247(a)(1)(iii),

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Test Procedure

Span = the frequency band of operation.

RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller VBW ≥ RBW.

Sweep = auto. Detector function = peak Trace = max hold.


11.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

11.4 Test Results

Mode	Frequency Range (MHz)	Number of Hopping Channel	Limit (CH)	Result
BR-1Mbps	2402-2480	79	>15	Compliance
EDR-2Mbps	2402-2480	79	>15	Compliance
EDR-3Mbps	2402-2480	79	>15	Compliance



12 FCC §15.247(b)(1) – Maximum Output Power

12.1 Applicable Standard

According to FCC §15.247(b) (1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

12.2 Test Procedure

Place the EUT on a bench and set it in transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Power sensor.

12.3 Test Equipment List and Details

Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
USB Wideband Power Sensor	Agilent	U2021XA	MY56120026	2020/09/14	2021/09/13
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

12.4 Test Results

Configuration	Channel	Frequency (MHz)	Maximum Peak Output Power		Limit (dBm)	Result
			(dBm)	(W)		
BR-1Mbps	Low	2402	4.09	0.0026	21	Compliance
	Middle	2441	3.41	0.0022	21	Compliance
	High	2480	2.82	0.0019	21	Compliance
EDR-2Mbps	Low	2402	1.24	0.0013	21	Compliance
	Middle	2441	0.78	0.0012	21	Compliance
	High	2480	-0.35	0.0009	21	Compliance
EDR-3Mbps	Low	2402	1.47	0.0014	21	Compliance
	Middle	2441	1.12	0.0013	21	Compliance
	High	2480	-0.04	0.0010	21	Compliance

13 FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge

13.1 Applicable Standard

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c)

13.2 Test Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.

RBW = 100 kHz VBW = 300 kHz.

Sweep = coupled. Detector function = peak Trace = max hold.

13.3 Test Equipment List and Details


Description	Manufacture	Model	Serial No.	Cal. Date.	Cal. Due.
Conducted Room(TH-02)					
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101434	2020/05/07	2021/05/06
Cable	MTJ	MT40S	620620-MT40S-100	Each Use	-

***Statement of Traceability:** The testing equipment's listed above have finished the calibration by Electronics Testing Center, Taiwan (ETC) or other laboratories which were accredited by TAF or equivalent organizations. The calibration result could be traceable to the International System of Units (SI).

13.4 Test Results


Configuration	Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
BR-1Mbps	Low	2402	57.88	≥ 20	Compliance
	High	2480	55.90	≥ 20	Compliance
BR-1Mbps Hopping	Low	2402	57.83	≥ 20	Compliance
	High	2480	56.21	≥ 20	Compliance
EDR-2Mbps	Low	2402	41.48	≥ 20	Compliance
	High	2480	50.96	≥ 20	Compliance
EDR-2Mbps Hopping	Low	2402	52.09	≥ 20	Compliance
	High	2480	49.89	≥ 20	Compliance
EDR-3Mbps	Low	2402	52.54	≥ 20	Compliance
	High	2480	51.22	≥ 20	Compliance
EDR-3Mbps Hopping	Low	2402	51.66	≥ 20	Compliance
	High	2480	49.83	≥ 20	Compliance

BR-1Mbps Left Side




Date: 17_MAR_2021 12:14:52

BR-1Mbps Right Side




Date: 17_MAR_2021 12:19:20

BR-1Mbps Hopping Left Side




Date: 17_MAR_2021 12:31:59

BR-1Mbps Hopping Right Side




Date: 17_MAR_2021 12:34:48

EDR-2Mbps Left Side




Date: 17_MAR_2021 14:09:42

EDR-2Mbps Right Side




Date: 17_MAR_2021 14:16:37

EDR-2Mbps Hopping Left Side




Date: 17_MAR_2021 14:25:12

EDR-2Mbps Hopping Right Side




Date: 17_MAR_2021 14:30:05

EDR-3Mbps Left Side




Date: 17_MAR_2021 15:35:46

EDR-3Mbps Right Side




Date: 17_MAR_2021 15:38:42

EDR-3Mbps Hopping Left Side



Date: 17_MAR_2021 15:45:10

EDR-3Mbps Hopping Right Side



Date: 17_MAR_2021 15:48:22

----- END OF REPORT -----